

Package ‘Laterality’

July 2, 2014

Type Package

Title Functions to calculate common laterality statistics in primatology.

Version 0.9.2

Date 2013-07-07

Author Borel A., Pouydebat E., Reghem E.

Maintainer Antony Borel <antony.borel@gmail.com>

Description Laterality package calculates Handedness index (HI) and z-score. It gives also absolute HI and mean HI at the individual and group level. The corresponding graphs can also be plotted. Some functions based on the ade4 package perform correspondence analysis (package ade4 is needed).

License GPL (>= 2.0)

LazyLoad yes

Depends ade4

NeedsCompilation no

Repository CRAN

Date/Publication 2013-07-08 07:22:53

R topics documented:

Laterality-package	2
HImeanact	4
HImeanactabs	6
HImeanind	8
HImeanindabs	10
HIndiv	12
HIndivabs	14
later	16

lateradata	18
laterAFCM	18
laterdata	20
laterhist	21
lvisAFCM	23
visAFCM	26

Index	28
--------------	-----------

Laterality-package *Laterality*

Description

This package permits to calculate handedness index (HI) and z-score for each individual for each task performed. It plots histograms of the different type of grasp (Left, right, bimanual...) for each kind of activity but also of the Handedness Index of each individual for each activity. The mean Handedness Index and the absolute HI and absolute mean HI can also be calculated. Finally some functions (based on ade4-package functions) calculates disjunctive table, Burt table and contributions for MCA and then plots multiple correspondence analysis graphs.

Details

Package:	Laterality
Type:	Package
Version:	0.9.1
Date:	2012-12-05
License:	GPL (>=2.0)
LazyLoad:	yes

This package is particularly useful to calculate and plot the different indexes (HI, z-score, mean HI, absolute HI) commonly used in laterality studies of non-human primates.

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

References

Chessel D., Dufour A.-B. and Dray S., with contributions from Jombart T., Lobry J.R., Ollier S., Pavoine S. and Thioulouse J. Package ade4: Analysis of Ecological Data : Exploratory and Euclidean methods in Environmental sciences.

Hopkins W.D.(1999) On the Other Hand: Statistical Issues in the Assessment and Interpretation of Hand Preference Data in Nonhuman Primates. *International Journal of Primatology* 20(6):851-866.

See Also

[ade4](#) the multiple correspondence analysis functions are based on ade4 package.

Examples

```
### later function ###
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
later(Data, catch ="Food", indiv="Indiv", hand="Hand",
RightHand="R", LeftHand="L", savetable = FALSE)
## or
later(Data)

## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
later(Data, catch ="Act", indiv="Individual", hand="HandPref",
RightHand="Right", LeftHand="Left", savetable = FALSE)

### HIndiv function ###
## With arguments corresponding to the default ones:
str(laterdata)
Data<-laterdata
HIndiv(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", legendlocation=FALSE, legend.text=TRUE)
## or
HIndiv(Data, legendlocation=FALSE, legend.text=TRUE)

## With arguments different from the default ones:
str(lateradata)
Data<-lateradata
HIndiv(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left", legendlocation=FALSE, legend.text=TRUE)

### HImeanact function ###
## With arguments corresponding to the default ones:
str(laterdata)
Data<-laterdata
HImeanact(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L")
## or
HImeanact(Data)

## With arguments different from the default ones:
str(lateradata)
Data<-lateradata
HImeanact(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left")
```

HImeanact	<i>HImeanact: this function calculates the mean Handedness Index for each activity.</i>
-----------	---

Description

The HImeanact function calculate the mean Handedness Index for each task performed and plots the corresponding histogram. The results can be saved in a .csv file.

Usage

```
HImeanact(data, catch = "Food", hand = "Hand", indiv = "Indiv",
  RightHand = "R", LeftHand = "L", col = 2:(length(levels
  (data[[catch]])) + 1), ylab = "Mean handedness index",
  main = "Hand preference regarding to the performed task",
  legend.text = FALSE, beside = TRUE, ylim = c(-1, 1), names.arg=levels(data[[catch]]),
  legendlocation = FALSE, standarderror=TRUE, cex = 1, pt.cex = 2, pch = 15,
  horiz = FALSE, savetable = FALSE, file = "HImeanPerAct.csv")
```

Arguments

data	The object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand), the individuals (indiv) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCatched", write catch = "ObjectCatched".
hand	The name/header of the column concerning the hand used (by default "Hand").
indiv	The name/header of the column concerning the individuals (by default "Indiv").
RightHand	The code used in the database (and particularly in the "hand" variable) for "RightHand". If "RightHand" is coded as "Right" write RightHand = "Right" (by default "R").
LeftHand	The code used in the database (and particularly in the "hand" variable) for "Left-Hand". If "LeftHand" is coded as "Left" write LeftHand = "Left" (by default "L").
col	A list of color for the bars of the histogram. By default it will automatically find the number of colors you need but it's using the 8 colors of the default palette of R. If you need more don't forget to select another palette or to name the color you want to add.
ylab	A title for the y axis.
main	The main title of the graph.
legend.text	If legend.text = TRUE, the legend will be automatically placed on the graph. If legend.text = FALSE, no legend will appear except if legendlocation = TRUE.

beside	If FALSE, the columns of height are portrayed as stacked bars, and if TRUE the columns are portrayed as juxtaposed bars.
ylim	The minimum and maximum value of the y axis. For example ylim = c(0,500). By default (ylim = NULL) the values are automatically selected.
names.arg	Plot the name of the arguments under each bar of the barplot. If names.args=FALSE, one should choose to turn to TRUE legend.text or legendlocation.
legendlocation	If TRUE you will have to click where you want to place the legend after the plot is done.
standarderror	If standarderror=TRUE standard error bars will be plotted for each bar of the barplot.
cex	A numeric giving the size of the legend characters.
pt.cex	A numeric giving the size of the legend points.
pch	This can either be a single character or an integer code for one of a set of graphics symbols. This will be applied to the legend. (By default pch = 15 which is square).
horiz	If horiz = TRUE, the legend will be displayed horizontally (by default). If horiz = FALSE, the legend will be displayed vertically.
savetable	This arguments permits to save directly the results of the function in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be "," for the decimal point and a ";" for the separator. (by default savetable = FALSE)
file	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "HImeanPerAct.csv")

Details

The mean HI is calculated from the HI of each task performs by each individual.

Value

The function returns results of class "data.frame".

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
HImeanact(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", legendlocation=FALSE)
## or
HImeanact(Data)
```

```
## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
HImeanact(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left")
```

HImeanactabs

HImeanactabs: this function calculates the absolute mean Handedness Index for each activity.

Description

The HImeanactabs function calculate the absolute mean Handedness Index for each task performed and plots the corresponding histogram. The results can be saved in a .csv file.

Usage

```
HImeanactabs(data, catch = "Food", hand = "Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", col = 2:(length(levels
(data[[catch]])) + 1), ylab = "Mean handedness index",
main = "Hand preference regarding to the performed task",
legend.text = FALSE, beside = TRUE, ylim = c(-1, 1), names.arg=levels(data[[catch]]),
legendlocation = FALSE, standarderror=TRUE, cex = 1, pt.cex = 2, pch = 15,
horiz = FALSE, savetable = FALSE, file = "HImeanPerActabs.csv")
```

Arguments

data	The object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand), the individuals (indiv) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCatched", write catch = "ObjectCatched".
hand	The name/header of the column concerning the hand used (by default "Hand").
indiv	The name/header of the column concerning the individuals (by default "Indiv").
RightHand	The code used in the database (and particularly in the "hand" variable) for "RightHand". If "RightHand" is coded as "Right" write RightHand = "Right" (by default "R").
LeftHand	The code used in the database (and particularly in the "hand" variable) for "LeftHand". If "LeftHand" is coded as "Left" write LeftHand = "Left" (by default "L").
col	A list of color for the bars of the histogram. By default it will automatically find the number of colors you need but it's using the 8 colors of the default palette of R. If you need more don't forget to select another palette or to name the color you want to add.

ylab	A title for the y axis.
main	The main title of the graph.
legend.text	If legend.text = TRUE, the legend will be automatically placed on the graph. If legend.text = FALSE, no legend will appear except if legendlocation = TRUE.
beside	If FALSE, the columns of height are portrayed as stacked bars, and if TRUE the columns are portrayed as juxtaposed bars.
ylim	The minimum and maximum value of the y axis. For example ylim = c(0,500). By default (ylim = NULL) the values are automatically selected.
names.arg	Plot the name of the arguments under each bar of the barplot. If names.args=FALSE, one should choose to turn to TRUE legend.text or legendlocation.
legendlocation	If TRUE you will have to click where you want to place the legend after the plot is done.
standarderror	If standarderror=TRUE standard error bars will be plotted for each bar of the barplot.
cex	A numeric giving the size of the legend characters.
pt.cex	A numeric giving the size of the legend points.
pch	This can either be a single character or an integer code for one of a set of graphics symbols. This will be applied to the legend. (By default pch = 15 which is square).
horiz	If horiz = TRUE, the legend will be displayed horizontally (by default). If horiz = FALSE, the legend will be displayed vertically.
savetable	This arguments permits to save directly the results of the function in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be "," for the decimal point and a ";" for the separator. (by default savetable = FALSE)
file	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "HImeanPerActabs.csv")

Value

The function returns results of class "data.frame".

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
HImeanactabs(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L")
## or
HImeanactabs(Data)
```

```
## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
HImeanactabs(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left")
```

HImeanind	<i>HImeanind: this function calculates the mean Handedness Index of each individual.</i>
-----------	--

Description

The HImeanind function calculate the mean Handedness Index of each individual and plots the corresponding histogram. The results can be saved in a .csv file.

Usage

```
HImeanind(data, catch = "Food", hand = "Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", col = 2:((length(levels
(data[[indiv]]))) + 1), ylab = "Mean handedness index",
main = "Hand preference regarding to the individuals",
legend.text = FALSE, beside = TRUE, ylim = c(-1, 1), names.arg=levels(data[[indiv]]),
legendlocation = FALSE, standarderror=TRUE, cex = 1, pt.cex = 2, pch = 15,
horiz = FALSE, savetable = FALSE, file = "HImeanPerIndiv.csv")
```

Arguments

data	The object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand), the individuals (indiv) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCaught", write catch = "ObjectCaught".
hand	The name/header of the column concerning the hand used (by default "Hand").
indiv	The name/header of the column concerning the individuals (by default "Indiv").
RightHand	The code used in the database (and particularly in the "hand" variable) for "RightHand". If "RightHand" is coded as "Right" write RightHand = "Right" (by default "R").
LeftHand	The code used in the database (and particularly in the "hand" variable) for "Left-Hand". If "LeftHand" is coded as "Left" write LeftHand = "Left" (by default "L").
col	A list of color for the bars of the histogram. By default it will automatically find the number of colors you need but it's using the 8 colors of the default palette of R. If you need more don't forget to select another palette or to name the color you want to add.

ylab	A title for the y axis.
main	The main title of the graph.
legend.text	If legend.text = TRUE, the legend will be automatically placed on the graph. If legend.text = FALSE, no legend will appear except if legendlocation = TRUE.
beside	If FALSE, the columns of height are portrayed as stacked bars, and if TRUE the columns are portrayed as juxtaposed bars.
ylim	The minimum and maximum value of the y axis. For example ylim = c(0,500). By default (ylim = NULL) the values are automatically selected.
names.arg	Plot the name of the arguments under each bar of the barplot. If names.args=FALSE, one should choose to turn to TRUE legend.text or legendlocation.
legendlocation	If TRUE you will have to click where you want to place the legend after the plot is done.
standarderror	If standarderror=TRUE standard error bars will be plotted for each bar of the barplot.
cex	A numeric giving the size of the legend characters.
pt.cex	A numeric giving the size of the legend points.
pch	This can either be a single character or an integer code for one of a set of graphics symbols. This will be applied to the legend. (By default pch = 15 which is square).
horiz	If horiz = TRUE, the legend will be displayed horizontally. If horiz = FALSE (by default), the legend will be displayed vertically.
savetable	This arguments permits to save directly the results of the function in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be "," for the decimal point and a ";" for the separator. (by default savetable = FALSE)
file	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "HImeanPerIndiv.csv")

Details

The mean HI is calculated from the HI of each individual for each task performed.

Value

The function returns results of class "data.frame".

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
```

```

HImeanind(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", horiz = FALSE)
## or
HImeanind(Data, horiz = FALSE)

## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
HImeanind(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left", horiz = FALSE)

```

HImeanindabs	<i>HImeanindabs: this function calculates the absolute mean Handedness Index of each individual.</i>
--------------	--

Description

The HImeanindabs function calculate the absolute mean Handedness Index of each individual and plots the corresponding histogram. The results can be saved in a .csv file.

Usage

```

HImeanindabs(data, catch = "Food", hand = "Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", col = 2:(length(levels
(data[[indiv]])) + 1), ylab = "Mean handedness index",
main = "Hand preference regarding to the individuals",
legend.text = FALSE, beside = TRUE, ylim = c(-1, 1), names.arg=levels(data[[indiv]]),
legendlocation = FALSE, standarderror=TRUE, cex = 1, pt.cex = 2, pch = 15,
horiz = FALSE, savetable = FALSE, file = "HImeanIndivabs.csv")

```

Arguments

data	The object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand), the individuals (indiv) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCaught", write catch = "ObjectCaught".
hand	The name/header of the column concerning the hand used (by default "Hand").
indiv	The name/header of the column concerning the individuals (by default "Indiv").
RightHand	The code used in the database (and particularly in the "hand" variable) for "RightHand". If "RightHand" is coded as "Right" write RightHand = "Right" (by default "R").
LeftHand	The code used in the database (and particularly in the "hand" variable) for "LeftHand". If "LeftHand" is coded as "Left" write LeftHand = "Left" (by default "L").

col	A list of color for the bars of the histogram. By default it will automatically find the number of colors you need but it's using the 8 colors of the default palette of R. If you need more don't forget to select another palette or to name the color you want to add.
ylab	A title for the y axis.
main	The main title of the graph.
legend.text	If legend.text = TRUE, the legend will be automatically placed on the graph. If legend.text = FALSE, no legend will appear except if legendlocation = TRUE.
beside	If FALSE, the columns of height are portrayed as stacked bars, and if TRUE the columns are portrayed as juxtaposed bars.
ylim	The minimum and maximum value of the y axis. For example ylim = c(0,500). By default (ylim = NULL) the values are automatically selected.
names.arg	Plot the name of the arguments under each bar of the barplot. If names.args=FALSE, one should choose to turn to TRUE legend.text or legendlocation.
legendlocation	If TRUE you will have to click where you want to place the legend after the plot is done.
standarderror	If standarderror=TRUE standard error bars will be plotted for each bar of the barplot.
cex	A numeric giving the size of the legend characters.
pt.cex	A numeric giving the size of the legend points.
pch	This can either be a single character or an integer code for one of a set of graphics symbols. This will be applied to the legend. (By default pch = 15 which is square).
horiz	If horiz = TRUE, the legend will be displayed horizontally. If horiz = FALSE (by default), the legend will be displayed vertically.
savetable	This arguments permits to save directly the results of the function in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be ";" for the decimal point and a ";" for the separator. (by default savetable = FALSE)
file	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "HImeanIndivabs.csv")

Value

The function returns results of class "data.frame".

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
```

```

Data<-lateradata
HImeanindabs(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", horiz = FALSE)
## or
HImeanindabs(Data, horiz = FALSE)

## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
HImeanindabs(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left", horiz = FALSE)

```

HIndiv

HIndiv: this function calculates the Handedness Index of each individual for each activity and plots the corresponding histogram.

Description

The HIndiv function calculate the Handedness Index of each individual regarding to each task performed and plots the corresponding histogram for each individual. The results can be saved in a .csv file.

Usage

```

HIndiv(data, catch = "Food", hand = "Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", col = 1:length(levels
(data[[catch]])), ylab = "Handedness index",
main = "Hand preference regarding to the performed task by each individual",
cex.main = 1, legend.text = FALSE,
beside = TRUE, ylim = c(-1, 1), vlines = TRUE, hlines = TRUE,
legendlocation = TRUE, cex = 1, pt.cex = 2, pch = 15,
savetable = FALSE, file = "HIperIndiv.csv")

```

Arguments

data	The object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand), the individuals (indiv) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCaught", write catch = "ObjectCaught".
hand	The name/header of the column concerning the hand used (by default "Hand").
indiv	The name/header of the column concerning the individuals (by default "Indiv").
RightHand	The code used in the database (and particularly in the "hand" variable) for "RightHand". If "RightHand" is coded as "Right" write RightHand = "Right" (by default "R").

LeftHand	The code used in the database (and particularly in the "hand" variable) for "Left-Hand". If "LeftHand" is coded as "Left" write LeftHand = "Left" (by default "L").
col	A list of color for the bars of the histogram. By default it will automatically find the number of colors you need but it's using the 8 colors of the default palette of R. If you need more don't forget to select another palette or to name the color you want to add.
ylab	A title for the y axis.
main	The main title of the graph.
cex.main	A numeric giving the size of the main title characters.
legend.text	If legend.text = TRUE, the legend will be automatically placed on the graph. If legend.text = FALSE, no legend will appear except if legendlocation = TRUE.
beside	If FALSE, the columns of height are portrayed as stacked bars, and if TRUE the columns are portrayed as juxtaposed bars.
ylim	The minimum and maximum value of the y axis. For example ylim = c(0,500). By default (ylim = NULL) the values are automatically selected.
vlines	If vlines = TRUE (by default), vertical lines are drawn between the histogram of each individual.
hlines	If hlines = TRUE (by default), horizontal lines are drawn at y = 0 for each histogram.
legendlocation	If TRUE you will have to click where you want to place the legend after the plot is done.
cex	A numeric giving the size of the legend characters.
pt.cex	A numeric giving the size of the legend points.
pch	This can either be a single character or an integer code for one of a set of graphics symbols. This will be applied to the legend. (By default pch = 15 which is square).
savetable	This arguments permits to save directly the results of the function in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be "," for the decimal point and a ";" for the separator. (by default savetable = FALSE)
file	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "HlperIndiv.csv")

Value

The function returns results of class "matrix".

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
HIndiv(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", legendlocation=FALSE, legend.text=TRUE)
## or
HIndiv(Data, legendlocation=FALSE, legend.text=TRUE)

## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
HIndiv(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left", legendlocation=FALSE, legend.text=TRUE)
```

HIndivabs

HIndivabs: this function calculates the absolute Handedness Index of each individual for each activity and plots the corresponding histogram.

Description

The HIndivabs function calculate the absolute Handedness Index of each individual regarding to each task performed and plots the corresponding histogram for each individual. The results can be saved in a .csv file.

Usage

```
HIndivabs(data, catch = "Food", hand = "Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", col = 1:length(levels
(data[[catch]])), ylab = "Absolute handedness index",
main = "Hand preference regarding to the performed task by each individual",
cex.main = 1, legend.text = FALSE, beside = TRUE,
ylim = c(0, 1), vlines = TRUE, hlines = TRUE, legendlocation = TRUE,
cex = 1, pt.cex = 2, pch = 15, savetable = FALSE,
file = "HIperIndivabs.csv")
```

Arguments

data	The object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand), the individuals (indiv) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCaught", write catch = "ObjectCaught".

hand	The name/header of the column concerning the hand used (by default "Hand").
indiv	The name/header of the column concerning the individuals (by default "Indiv").
RightHand	The code used in the database (and particularly in the "hand" variable) for "RightHand". If "RightHand" is coded as "Right" write RightHand = "Right" (by default "R").
LeftHand	The code used in the database (and particularly in the "hand" variable) for "LeftHand". If "LeftHand" is coded as "Left" write LeftHand = "Left" (by default "L").
col	A list of color for the bars of the histogram. By default it will automatically find the number of colors you need but it's using the 8 colors of the default palette of R. If you need more don't forget to select another palette or to name the color you want to add.
ylab	A title for the y axis.
main	The main title of the graph.
cex.main	A numeric giving the size of the main title characters.
legend.text	If legend.text = TRUE, the legend will be automatically placed on the graph. If legend.text = FALSE, no legend will appear except if legendlocation = TRUE.
beside	If FALSE, the columns of height are portrayed as stacked bars, and if TRUE the columns are portrayed as juxtaposed bars.
ylim	The minimum and maximum value of the y axis. For example ylim = c(0,500). By default (ylim = NULL) the values are automatically selected.
vlines	If vlines = TRUE (by default), vertical lines are drawn between the histogram of each individual.
hlines	If hlines = TRUE (by default), horizontal lines are drawn at y = 0 for each histogram.
legendlocation	If TRUE you will have to click where you want to place the legend after the plot is done.
cex	A numeric giving the size of the legend characters.
pt.cex	A numeric giving the size of the legend points.
pch	This can either be a single character or an integer code for one of a set of graphics symbols. This will be applied to the legend. (By default pch = 15 which is square).
savetable	This arguments permits to save directly the results of the function in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be "," for the decimal point and a ";" for the separator. (by default savetable = FALSE)
file	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "HIpErIndivabs.csv")

Value

The function returns results of class "matrix".

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
HIndivabs(Data, catch="Food", hand="Hand", indiv = "Indiv",
RightHand = "R", LeftHand = "L", legendlocation=FALSE, legend.text=TRUE)
## or
HIndivabs(Data, legendlocation=FALSE, legend.text=TRUE)

## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
HIndivabs(Data, catch="Act", hand="HandPref", indiv = "Individual",
RightHand = "Right", LeftHand = "Left", legendlocation=FALSE, legend.text=TRUE)
```

later

later: this function calculates handedness index (HI) and z-score.

Description

The later function return an array with x dimensions corresponding to each activities performed. For each individual it will return the total of left and right hand grasp (and eventually other data like "bimanual" for example). The HI and the z-score is also returned for each individual with the corresponding p-value and each individual is classified as right handed (R), left handed (L) or ambiguous (A). These results can be saved directly in a .csv file (see "savetable" below).

Usage

```
later(data, catch = "Food", indiv = "Indiv", hand = "Hand",
RightHand = "R", LeftHand = "L", savetable = FALSE,
file = "HIz.csv")
```

Arguments

data	The object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand), the individuals (indiv) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCaught", write catch = "ObjectCaught".
indiv	The name/header of the column concerning the individuals (by default "Indiv").

hand	The name/header of the column concerning the hand used (by default "Hand").
RightHand	The code used in the database (and particularly in the "hand" variable) for "RightHand". If "RightHand" is coded as "Right" write RightHand = "Right" (by default "R").
LeftHand	The code used in the database (and particularly in the "hand" variable) for "LeftHand". If "LeftHand" is coded as "Left" write LeftHand = "Left" (by default "L").
savetable	This arguments permits to save directly the results of the function in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be "," for the decimal point and a ";" for the separator. (by default savetable = FALSE)
file	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "HIz.csv")

Details

The order of the columns of the database doesn't matter, the important is to give the correct code and header name to each argument of the function if the default ones are not appropriate.

Value

The function returns results of class "array".

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

References

Hopkins W.D.(1999) On the Other Hand: Statistical Issues in the Assessment and Interpretation of Hand Preference Data in Nonhuman Primates. International Journal of Primatology 20(6):851-866

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
later(Data, catch ="Food", indiv="Indiv", hand="Hand",
RightHand="R", LeftHand="L", savetable = FALSE, file = "HIz.csv")
## or
later(Data)

## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
later(Data, catch ="Act", indiv="Individual", hand="HandPref",
RightHand="Right", LeftHand="Left", savetable = FALSE,
file = "HIz.csv")
```

lateradata	<i>lateradata: data.frame for later-package examples</i>
------------	--

Description

This data.frame is a fake example made up to illustrate later-package.

Usage

```
data(lateradata)
```

Format

A data frame with 674 observations on the following 5 variables.

Individual a factor with levels Airly Biwa Doma Dudy Gogo Neil Olix Rali Raps Rexen Titi

Sex a factor with levels f m

Act a factor with levels Catching Grasping Hunting

HandPref a factor with levels Bimanual Left Right

PostureCorp a factor with levels A Bip BipGrill BipT NonObs T TT

Source

Fake data.

Examples

```
data(lateradata)
str(lateradata)
```

laterAFCM	<i>laterAFCM: this function calculates disjunctive table, Burt table and contributions for multiple correspondence analysis (MCA).</i>
-----------	--

Description

This function calculates disjunctive table, Burt table and contributions for MCA.

Usage

```
laterAFCM(data, scannf=FALSE, nf=2, saveDatadisj = FALSE, fileDatadisj = "Datadisj.csv",
saveSumcolDatadisj = FALSE, fileSumcolDatadisj = "SumcolDatadisj.csv",
saveDataburt = FALSE, fileDataburt = "Databurt.csv",
saveContributions = FALSE, fileContributions = "Contributions.csv")
```

Arguments

<code>data</code>	A <code>data.frame</code> with the qualitative variables which should be taken in account in the multiple correspondence analysis.
<code>scannf</code>	A logical value indicating whether the eigenvalues bar plot should be displayed; see <code>ade4</code> package (by default <code>scannf = FALSE</code>).
<code>nf</code>	If <code>scannf=FALSE</code> , an integer indicating the number of kept axes; see <code>ade4</code> package (by default <code>nf = 2</code>).
<code>saveDatadisj</code>	This arguments permits to save directly the results of the disjunctive table in a <code>.csv</code> file in the workspace of R. If <code>savetable = "csv"</code> there will be "." for the decimal point and a "," for the separator. If <code>savetable = "csv2"</code> there will be "," for the decimal point and a ";" for the separator. (by default <code>savetable = FALSE</code>)
<code>fileDatadisj</code>	This argument will work if <code>savetable = "csv"</code> or <code>"csv2"</code> . It gives the name of the csv file saved (by default <code>file = "Datadisj.csv"</code>)
<code>saveSumcolDatadisj</code>	This arguments permits to save directly the results of the sum of the column of the disjunctive table in a <code>.csv</code> file in the workspace of R. If <code>savetable = "csv"</code> there will be "." for the decimal point and a "," for the separator. If <code>savetable = "csv2"</code> there will be "," for the decimal point and a ";" for the separator. (by default <code>savetable = FALSE</code>)
<code>fileSumcolDatadisj</code>	This argument will work if <code>savetable = "csv"</code> or <code>"csv2"</code> . It gives the name of the csv file saved (by default <code>file = "SumcolDatadisj.csv"</code>)
<code>saveDataburt</code>	This arguments permits to save directly the results of the Burt table in a <code>.csv</code> file in the workspace of R. If <code>savetable = "csv"</code> there will be "." for the decimal point and a "," for the separator. If <code>savetable = "csv2"</code> there will be "," for the decimal point and a ";" for the separator. (by default <code>savetable = FALSE</code>)
<code>fileDataburt</code>	This argument will work if <code>savetable = "csv"</code> or <code>"csv2"</code> . It gives the name of the csv file saved (by default <code>file = "Databurt.csv"</code>)
<code>saveContributions</code>	This arguments permits to save directly the results of the contributions table in a <code>.csv</code> file in the workspace of R. If <code>savetable = "csv"</code> there will be "." for the decimal point and a "," for the separator. If <code>savetable = "csv2"</code> there will be "," for the decimal point and a ";" for the separator. (by default <code>savetable = FALSE</code>)
<code>fileContributions</code>	This argument will work if <code>savetable = "csv"</code> or <code>"csv2"</code> . It gives the name of the csv file saved (by default <code>file = "Contributions.csv"</code>)

Value

The function returns results of class "list".

Note

If you use this function please cite also `ade4`-package.

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com> based on functions from Daniel Chessel, Anne-Beatrice Dufour and Stephane Dray, with contributions from Thibaut Jombart, Jean R. Lobry, Sebastien Ollier, Sandrine Pavoine and Jean Thioulouse. Package ade4: Analysis of Ecological Data : Exploratory and Euclidean methods in Environmental sciences.

References

Chessel D., Dufour A.-B. and Dray S., with contributions from Jombart T., Lobry J.R., Ollier S., Pavoine S. and Thioulouse J. Package ade4: Analysis of Ecological Data : Exploratory and Euclidean methods in Environmental sciences.

See Also

[ade4](#), [inertia.dudi](#), [acm.disjonctif](#), [acm.burt](#), [dudi.acm](#)

Examples

```
library(ade4)
data(laterdata)

## Without saving:
laterAFCM(laterdata)

## With saving:
laterAFCM(laterdata, saveDatadisj="csv2", fileDatadisj="Datadisj.csv"
, saveSumcolDatadisj="csv2", fileSumcolDatadisj="SumcolDatadisj.csv"
, saveDataburt="csv2", fileDataburt="Databurt.csv"
, saveContributions="csv2", fileContributions="Contributions.csv")
```

laterdata

laterdata: data.frame for later-package examples

Description

This data.frame is a fake example made up to illustrate later-package.

Usage

```
data(laterdata)
```

Format

A data frame with 674 observations on the following 5 variables.

Indiv a factor with levels Airly Biwa Doma Dudy Gogo Neil Olix Rali Raps Rexen Titi

Sex a factor with levels f m

Food a factor with levels Apple Cricket Worm

Hand a factor with levels Bi L R

PostureCorp a factor with levels A Bip BipGrill BipT NonObs T TT

Source

Fake data.

Examples

```
data(laterdata)
str(laterdata)
```

laterhist	<i>laterhist: this function plots an histogram of the different type of grasp (Left, right, bimanual...) for each kind of activity.</i>
-----------	---

Description

The laterhist function counts the number of occurrences of each type of grasp and plot the corresponding histogram for each task performed.

Usage

```
laterhist(data, catch = "Food", hand = "Hand",
  col = 1:nlevels(data[[hand]]), ylim = NULL,
  ylab = "Number of grips",
  main = "Type of grips regarding to the performed task",
  legend.text = FALSE, beside = TRUE, legendlocation = TRUE,
  cex = 1, pt.cex = 2, pch = 15)
```

Arguments

data	the object (data.frame) containing your data with at least the qualitative variables concerning the hand used (hand) and the activity performed (catch).
catch	The name/header of the column concerning the activity carried out (by default "Food"), if you made individuals catching different objects (ob1, ob2, ob3, ob4) and named the variable "ObjectCatched", write catch = "ObjectCatched".
hand	The name/header of the column concerning the hand used (by default "Hand").
col	A list of color for the bars of the histogram. By default it will automatically find the number of colors you need but it's using the 8 colors of the default palette of R. If you need more don't forget to select another palette or to name the color you want to add.
ylim	The minimum and maximum value of the y axis. For example ylim = c(0,500). By default (ylim = NULL) the values are automatically selected.
ylab	A title for the y axis.
main	The main title of the graph.

legend.text	If legend.text = TRUE, the legend will be automatically placed on the graph. If legend.text = FALSE, no legend will appear except if legendlocation = TRUE.
beside	If FALSE, the columns of height are portrayed as stacked bars, and if TRUE the columns are portrayed as juxtaposed bars.
legendlocation	If TRUE you will have to click where you want to place the legend after the plot is done.
cex	A numeric giving the size of the legend characters.
pt.cex	A numeric giving the size of the legend points.
pch	This can either be a single character or an integer code for one of a set of graphics symbols. This will be applied to the legend. (By default pch = 15 which is square).

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com>

References

Meguerditchian A., Calcutt S.E., Lonsdorf E.V., Ross S.R. and Hopkins W.D. (2010) Brief communication: Captive Gorillas are right-handed for bimanual feeding. American Journal of Physical Anthropology 141:638-645.

See Also

[barplot](#)

Examples

```
## With arguments corresponding to the default ones:
data(laterdata)
str(laterdata)
Data<-laterdata
laterhist(Data, catch ="Food", hand="Hand",
legend.text = TRUE, legendlocation = FALSE)
## or
laterhist(Data, legend.text = TRUE, legendlocation = FALSE)

## With arguments different from the default ones:
data(lateradata)
str(lateradata)
Data<-lateradata
laterhist(Data, catch ="Act", hand="HandPref", legend.text = TRUE, legendlocation = FALSE)
```

IvisAFCM	<i>IvisAFCM: this function calculates disjunctive table, blurt table and contributions for AFCM and plots the corresponding graphs.</i>
----------	---

Description

This function combines "laterAFCM" and "visAFCM" functions. It calculates disjunctive table, Burt table and contributions for MCA and then plots multiple correspondence analysis graphs.

Usage

```
IvisAFCM(data, scannf=FALSE, nf=2, xax = 1, yax = 2, clab.row = FALSE, clab.col = 1,
permute = FALSE, posieig = "top", sub = NULL,
graphstyle = "unique", graphrow = 1, graphcol = 3, cpoint = 1,
clabel = 2, csub = 2, saveDatadisj = FALSE,
fileDatadisj = "Datadisj.csv", saveSumcolDatadisj = FALSE,
fileSumcolDatadisj = "SumcolDatadisj.csv", saveDataburt = FALSE,
fileDataburt = "Databurt.csv", saveContributions = FALSE,
fileContributions = "Contributions.csv")
```

Arguments

data	A data.frame with the qualitative variables which should be taken in account in the multiple correspondence analysis.
scannf	A logical value indicating whether the eigenvalues bar plot should be displayed; see ade4 package (by default scannf = FALSE).
nf	If scannf=FALSE, an integer indicating the number of kept axes; see ade4 package (by default nf = 2).
xax	A numeric giving the number of the first axis to plot (by default xax = 1).
yax	A numeric giving the number of the second axis to plot (by default yax = 2).
clab.row	A character size for the rows (by default clab.row = FALSE).
clab.col	A character size for the columns (by default clab.col = 1).
permute	If FALSE, the rows are plotted by points and the columns by arrows. If TRUE it is the opposite (by default permute = FALSE).
posieig	If "top" the eigenvalues bar plot is upside, if "bottom" it is downside, if "none" no plot. "topleft" and "bottomleft" are also possible (by default posieig = "top").
sub	A string of characters to be inserted as legend (by default sub = NULL).
graphstyle	Three kinds of graph can be selected. If graphstyle = "unique", all variables will be plotted on the same graph. If graphstyle = "multiple a" each variable will be plotted in different graphs (cf. graphrow and graphcol) with inertia ellipse. If graphstyle = "multiple b" each variable will be plotted in different graphs (cf. graphrow and graphcol) with convex hulls.
graphrow	The number of row for multiple graph. If one deal with 6 variables it is recommended to write graphrow = 2 and graphcol = 3.

graphcol	The number of column for multiple graph. If one deal with 6 variables it is recommended to write graphrow = 2 and graphcol = 3.
cpoint	A numeric for the size of the points.
clabel	A numeric for the size of the labels.
csub	A numeric for the size of the name of the variable written at the bottom of each chart.
saveDatadisj	This arguments permits to save directly the results of the disjunctive table in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be ";" for the decimal point and a ";" for the separator. (by default savetable = FALSE)
fileDatadisj	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "Datadisj.csv")
saveSumcolDatadisj	This arguments permits to save directly the results of the sum of the column of the disjunctive table in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be ";" for the decimal point and a ";" for the separator. (by default savetable = FALSE)
fileSumcolDatadisj	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "SumcolDatadisj.csv")
saveDataburt	This arguments permits to save directly the results of the Burt table in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be ";" for the decimal point and a ";" for the separator. (by default savetable = FALSE)
fileDataburt	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "Databurt.csv")
saveContributions	This arguments permits to save directly the results of the contributions table in a .csv file in the workspace of R. If savetable = "csv" there will be "." for the decimal point and a "," for the separator. If savetable = "csv2" there will be ";" for the decimal point and a ";" for the separator. (by default savetable = FALSE)
fileContributions	This argument will work if savetable = "csv" or "csv2". It gives the name of the csv file saved (by default file = "Contributions.csv")

Value

The function returns results of class "list".

Note

If you use this function please cite also ade4-package.

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com> based on functions from Daniel Chessel, Anne-Beatrice Dufour and Stephane Dray, with contributions from Thibaut Jombart, Jean R. Lobry, Sebastien Ollier, Sandrine Pavoine and Jean Thioulouse. Package ade4: Analysis of Ecological Data : Exploratory and Euclidean methods in Environmental sciences.

References

Daniel Chessel, Anne-Beatrice Dufour and Stephane Dray, with contributions from Thibaut Jombart, Jean R. Lobry, Sebastien Ollier, Sandrine Pavoine and Jean Thioulouse. Package ade4: Analysis of Ecological Data : Exploratory and Euclidean methods in Environmental sciences.

See Also

[ade4](#), [inertia.dudi](#), [acm.disjonctif](#), [acm.burt](#), [dudi.acm](#), [scatter.dudi](#), [s.class](#), [s.chull](#)

Examples

```
data(laterdata)
## Without saving:
## "unique" graph:
lvisAFCM(laterdata)

## "multiple a" graph:
lvisAFCM(laterdata, xax = 1, yax = 2, clab.row = FALSE,
clab.col = 1, permute = FALSE, posieig = "top", sub = NULL,
graphstyle = "multiple a", graphrow = 2, graphcol = 3,
cpoint=3)

## "multiple b" graph:
lvisAFCM(laterdata, xax = 1, yax = 2, clab.row = FALSE,
clab.col = 1, permute = FALSE, posieig = "top", sub = NULL,
graphstyle = "multiple b", graphrow = 2, graphcol = 3)

## With saving:
## "unique" graph:
lvisAFCM(laterdata, saveDatadisj="csv2", fileDatadisj="Datadisj.csv"
, saveSumcolDatadisj="csv2", fileSumcolDatadisj="SumcolDatadisj.csv"
, saveDataburt="csv2", fileDataburt="Databurt.csv"
, saveContributions="csv2", fileContributions="Contributions.csv")

## "multiple a" graph:
lvisAFCM(laterdata, xax = 1, yax = 2, clab.row = FALSE, clab.col = 1,
permute = FALSE, posieig = "top", sub = NULL, graphstyle = "multiple a",
graphrow = 2, graphcol = 3, cpoint=3, saveDatadisj="csv2",
fileDatadisj="Datadisj.csv", saveSumcolDatadisj="csv2",
fileSumcolDatadisj="SumcolDatadisj.csv", saveDataburt="csv2",
fileDataburt="Databurt.csv", saveContributions="csv2",
fileContributions="Contributions.csv")

## "multiple b" graph:
```

```
lvisAFCM(laterdata, xax = 1, yax = 2, clab.row = FALSE, clab.col = 1,
permute = FALSE, posieig = "top", sub = NULL, graphstyle = "multiple b",
graphrow = 2, graphcol = 3, saveDatadisj="csv2",
fileDatadisj="Datadisj.csv", saveSumcolDatadisj="csv2",
fileSumcolDatadisj="SumcolDatadisj.csv", saveDataburt="csv2",
fileDataburt="Databurt.csv", saveContributions="csv2",
fileContributions="Contributions.csv")
```

visAFCM

visAFCM: this function plots multiple correspondence analysis graphs based on ade4 package functions.

Description

This function plots multiple correspondence analysis graphs. The graphs can be unique or multiple which is sometimes necessary for better lisibility.

Usage

```
visAFCM(data, scannf=FALSE, nf=2, xax = 1, yax = 2, clab.row = FALSE, clab.col = 1,
permute = FALSE, posieig = "top", sub = NULL, graphstyle = "unique",
graphrow = 1, graphcol = 3, cpoint = 1, clabel = 2, csub = 2)
```

Arguments

data	A data.frame with the qualitative variables which should be taken in account in the multiple correspondence analysis.
scannf	A logical value indicating whether the eigenvalues bar plot should be displayed; see ade4 package (by default scannf = FALSE).
nf	If scannf=FALSE, an integer indicating the number of kept axes; see ade4 package (by default nf = 2).
xax	A numeric giving the number of the first axis to plot (by default xax = 1).
yax	A numeric giving the number of the second axis to plot (by default yax = 2).
clab.row	A character size for the rows (by default clab.row = FALSE).
clab.col	A character size for the columns (by default clab.col = 1).
permute	If FALSE, the rows are plotted by points and the columns by arrows. If TRUE it is the opposite (by default permute = FALSE).
posieig	If "top" the eigenvalues bar plot is upside, if "bottom" it is downside, if "none" no plot. "topleft" and "bottomleft" are also possible (by default posieig = "top").
sub	A string of characters to be inserted as legend (by default sub = NULL).
graphstyle	Three kinds of graph can be selected. If graphstyle = "unique", all variables will be plotted on the same graph. If graphstyle = "multiple a" each variable will be plotted in different graphs (cf. graphrow and graphcol) with inertia ellipse. If graphstyle = "multiple b" each variable will be plotted in different graphs (cf. graphrow and graphcol) with convex hulls.

graphrow	The number of row for multiple graph. If one deal with 6 variables it is recommended to write graphrow = 2 and graphcol = 3.
graphcol	The number of column for multiple graph. If one deal with 6 variables it is recommended to write graphrow = 2 and graphcol = 3.
cpoint	A numeric for the size of the points.
clabel	A numeric for the size of the labels.
csub	A numeric for the size of the name of the variable written at the bottom of each chart.

Note

If you use this function please cite also ade4-package.

Author(s)

Borel A., Pouydebat E., Reghem E. <antony.borel@gmail.com> based on functions from Daniel Chessel, Anne-Beatrice Dufour and Stephane Dray, with contributions from Thibaut Jombart, Jean R. Lobry, Sebastien Ollier, Sandrine Pavoine and Jean Thioulouse. Package ade4: Analysis of Ecological Data : Exploratory and Euclidean methods in Environmental sciences.

References

Daniel Chessel, Anne-Beatrice Dufour and Stephane Dray, with contributions from Thibaut Jombart, Jean R. Lobry, Sebastien Ollier, Sandrine Pavoine and Jean Thioulouse. Package ade4: Analysis of Ecological Data : Exploratory and Euclidean methods in Environmental sciences.

See Also

[scatter.dudi](#), [s.class](#), [s.chull](#)

Examples

```
data(laterdata)
## "unique" graph:
visAFCM(laterdata)

## "multiple a" graph:
visAFCM(laterdata, xax = 1, yax = 2, clab.row = FALSE, clab.col = 1,
permute = FALSE, posieig = "top", sub = NULL, graphstyle = "multiple a",
graphrow = 2, graphcol = 3, cpoint=3)

## "multiple b" graph:
visAFCM(laterdata, xax = 1, yax = 2, clab.row = FALSE, clab.col = 1,
permute = FALSE, posieig = "top", sub = NULL, graphstyle = "multiple b",
graphrow = 2, graphcol = 3)
```

Index

*Topic **AFCM**

laterAFCM, 18
Laterality-package, 2
lvisAFCM, 23
visAFCM, 26

*Topic **HI**

HImeanact, 4
HImeanactabs, 6
HImeanind, 8
HImeanindabs, 10
HIndiv, 12
HIndivabs, 14
later, 16
Laterality-package, 2
laterhist, 21

*Topic **MCA**

laterAFCM, 18
Laterality-package, 2
lvisAFCM, 23
visAFCM, 26

*Topic **correspondence**

laterAFCM, 18
Laterality-package, 2
lvisAFCM, 23
visAFCM, 26

*Topic **datasets**

lateradata, 18
laterdata, 20

*Topic **handedness index**

HImeanact, 4
HImeanactabs, 6
HImeanind, 8
HImeanindabs, 10
HIndiv, 12
HIndivabs, 14
later, 16
Laterality-package, 2
laterhist, 21

*Topic **laterality**

HImeanact, 4
HImeanactabs, 6
HImeanind, 8
HImeanindabs, 10
HIndiv, 12
HIndivabs, 14
later, 16
laterAFCM, 18
Laterality-package, 2
laterhist, 21
lvisAFCM, 23
visAFCM, 26

*Topic **manual preference**

HImeanact, 4
HImeanactabs, 6
HImeanind, 8
HImeanindabs, 10
HIndiv, 12
HIndivabs, 14
later, 16
laterAFCM, 18
Laterality-package, 2
laterhist, 21
lvisAFCM, 23
visAFCM, 26

*Topic **zscore**

HImeanact, 4
HImeanactabs, 6
HImeanind, 8
HImeanindabs, 10
HIndiv, 12
HIndivabs, 14
later, 16
Laterality-package, 2
laterhist, 21

acm.burt, 20, 25
acm.disjonctif, 20, 25
ade4, 3, 20, 25

barplot, [22](#)

dudi.acm, [20](#), [25](#)

HImeanact, [4](#)
HImeanactabs, [6](#)
HImeanind, [8](#)
HImeanindabs, [10](#)
HIndiv, [12](#)
HIndivabs, [14](#)

inertia.dudi, [20](#), [25](#)

later, [16](#)
lateradata, [18](#)
laterAFCM, [18](#)
Laterality (Laterality-package), [2](#)
Laterality-package, [2](#)
laterdata, [20](#)
laterhist, [21](#)
lvisAFCM, [23](#)

s.chull, [25](#), [27](#)
s.class, [25](#), [27](#)
scatter.dudi, [25](#), [27](#)

visAFCM, [26](#)