

Package ‘RH2’

September 14, 2014

Version 0.2.3

Date 2014-08-19

Title DBI/RJDBC interface to h2 Database

Author G. Grothendieck. Author of h2 is Thomas Mueller.

Maintainer ``David M. Kaplan" <dmkaplan2000@gmail.com>

Description DBI/RJDBC interface to h2 database. h2 version 1.3.175 is included.

Depends chron, methods, RJDBC, rJava

SystemRequirements java runtime

License Mozilla Public License 1.1

URL <https://github.com/dmkaplan2000/RH2.git>

NeedsCompilation no

Repository CRAN

Date/Publication 2014-09-14 15:28:38

R topics documented:

H2	2
H2Connection-class	3
H2Connection-methods	4
H2Driver-class	4
H2Driver-methods	5
H2Result-class	5
H2Result-methods	6
Index	7

H2 *H2 engine*

Description

H2 creates a new DBI driver that can be used to start connections.

Usage

```
H2(driverClass='org.h2.Driver',
  identifier.quote="\'", jars = getOption("RH2.jars"), ...)
```

Arguments

<code>driverClass</code>	name of the Java class of the driver to load. If empty, it is assumed that corresponding drivers were loaded by other means.
<code>identifier.quote</code>	character to use for quoting identifiers in automatically generated SQL statements or NA for no quoted identifiers.
<code>jars</code>	pathname to H2 jar file. If omitted it will use the version of H2 included in RH2.
<code>...</code>	further arguments passed to <code>.jpackage</code>

Details

The H2 function initializes the Java VM, loads the H2 driver and creates a proxy R object which can be used to a call `dbConnect` which actually creates a connection.

It handles "integer", "Date", chron "times", "POSIXct" and "numeric" classes using the H2 types of "integer", "date", "time", "timestamp" and "double precision". All other R classes are converted to "character" and stored as `varchar(255)`.

Value

Returns a H2Driver object that can be used in calls to `dbConnect`.

See Also

[dbConnect](#)

Examples

```
## Not run:
library(RJDBC)

con <- dbConnect(H2(), "jdbc:h2:~/test", "sa", "")

# create table, populate it and display it
s <- 'create table tt("id" int primary key, "name" varchar(255))'
```

```
dbSendUpdate(con, s)
dbSendUpdate(con, "insert into tt values(1, 'Hello')")
dbSendUpdate(con, "insert into tt values(2, 'World')")
dbGetQuery(con, "select * from tt")

# transfer a data frame to H2 and then display it from the database
dbWriteTable(con, "BOD", BOD)
dbGetQuery(con, "select * from BOD")

dbDisconnect(con)

# connect to a different version of H2 and show version
con <- dbConnect(H2(jars = "c:/tmp2/h2-1.3.155.jar"))
s <- "select VALUE from INFORMATION_SCHEMA.SETTINGS where NAME = 'info.VERSION'"
dbGetQuery(con, s)
dbDisconnect(con)

## End(Not run)
```

H2Connection-class *Class "H2Connection"*

Description

Class representing a (DBI) database connection which uses H2 to connect to a database.

Generators

Objects can be created by call to `dbConnect` of a `JDBC` driver.

Slots

`jc`: Java object representing the connection.

`identifier.quote`: Quote character to use for quoting identifiers in automatically generated SQL statements or NA for no such quoting. Usually the value is inherited from the "`H2Driver`".

Extends

Class "`JDBCConnection-class`", directly.

Methods

No methods defined with class "H2Connection" in the signature.

See Also

`JDBC`, "`JDBCDriver`"

H2Connection-methods *Methods for the class 'H2Connect' in Package 'H2'*

Description

Methods for the class 'H2Connection' in Package 'H2'.

Methods

dbWriteTable signature(conn = "H2Connection", ...)

H2Driver-class *Class "H2Driver"*

Description

A DBI driver to access the H2 databases.

Generators

Objects can be created by calls to [H2](#) or [dbDriver](#).

Slots

identifier.quote: Quote character to use for identifiers in automatically generated SQL statements or NA if quoted identifiers are not desired.

jdrv: Java object reference to an instance of the driver if the driver can be instantiated by a default constructor. This object is only used as a fall-back when the driver manager fails to find a driver.

Extends

Class "[JDBCdriver-class](#)", directly.

Methods

No methods defined with class "H2Driver" in the signature.

See Also

[JDBCdriver-class](#)

H2Driver-methods	<i>Methods for the class JDBCDriver in Package 'RJDBC'</i>
------------------	--

Description

Methods for the class 'H2Driver' in Package 'H2'. In addition to methods listed here there are methods inherited from JDBCDriver.

dbConnect creates a new H2 connection.

Methods

dbConnect signature(drv = "H2Driver", ...)

Examples

```
## Not run:
# in memory database
con <- dbConnect(H2(), "jdbc:h2:mem:")
dbDisconnect(con)

# external database
con <- dbConnect(H2(), "jdbc:h2:~/test")
dbDisconnect(con)

# same but run in MySQL compatibility mode
con <- dbConnect(H2(), "jdbc:h2:~/test;MODE=MYSQL")

## End(Not run)
```

H2Result-class	<i>Class "H2Result"</i>
----------------	-------------------------

Description

Representation of a DBI result set returned from a H2 connection.

Generators

Objects can be created by call to [dbSendQuery](#).

Slots

jr: Java reference to the H2 result set

md: Java reference to the H2 result set meta data

Extends

Class "[DBIResult-class](#)", directly.

Methods

No methods defined with class "H2Result" in the signature.

See Also

[H2](#), [dbSendQuery](#)

H2Result-methods

Methods for the class H2Result in Package 'H2'

Description

Methods for the class 'H2Result' in Package 'H2'.

`fetch` retrieves the content of the result set in the form of a data frame.

Other methods are inherited from the RJDBC package.

Methods

fetch signature(res = "H2Result", ...)

Index

*Topic **classes**

H2Connection-class, 3

H2Driver-class, 4

H2Result-class, 5

*Topic **interface**

H2, 2

*Topic **methods**

H2Connection-methods, 4

H2Driver-methods, 5

H2Result-methods, 6

dbConnect, 2, 3

dbConnect, H2Driver-method
(H2Driver-methods), 5

dbDataType, H2Connection-method
(H2Connection-methods), 4

dbDriver, 4

dbGetQuery, H2Connection, character-method
(H2Connection-methods), 4

dbSendQuery, 5, 6

dbSendQuery, H2Connection, character-method
(H2Connection-methods), 4

dbWriteTable, H2Connection-method
(H2Connection-methods), 4

fetch, H2Result, numeric-method
(H2Result-methods), 6

H2, 2, 4, 6

H2Connection-class, 3

H2Connection-methods, 4

H2Driver, 3

H2Driver-class, 4

H2Driver-methods, 5

H2Result-class, 5

H2Result-methods, 6

JDBC, 3

JDBCdriver, 3