

# Package ‘SpatialVx’

July 2, 2014

**Version** 0.2-1

**Date** 2011-12-09

**Title** Spatial Forecast Verification

**Author** Eric Gilleland <EricG@ucar.edu>

**Maintainer** Eric Gilleland <EricG@ucar.edu>

**Depends** R (>= 2.10.0), spatstat (>= 1.37-0), fields (>= 6.8),smoothie, smatr, turboEM

**Imports** distillery, maps, boot, CircStats, fastcluster, waveslim

**Suggests** shapes

**Description** Functions to perform spatial forecast verification

**License** GPL (>= 2)

**URL** <http://www.ral.ucar.edu/projects/icp>

**BugReports** <http://www.ral.ucar.edu/projects/icp/SpatialVx>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2014-05-13 17:45:05

## R topics documented:

SpatialVx-package . . . . .	3
abserrloss . . . . .	8
Aindex . . . . .	10
bearing . . . . .	12
centdist . . . . .	13
Cindex . . . . .	15
clusterer . . . . .	16
combiner . . . . .	21

compositer . . . . .	22
convthresh . . . . .	25
CSIsamples . . . . .	29
deltamm . . . . .	32
EBS . . . . .	37
ExampleSpatialVxSet . . . . .	39
FeatureAxis . . . . .	40
FeatureMatchAnalyzer . . . . .	43
FeatureProps . . . . .	47
FeatureTable . . . . .	48
FQI . . . . .	51
fss2dfun . . . . .	53
fss2dPlot . . . . .	56
GeoBoxPlot . . . . .	58
GFSNAMfcstEx . . . . .	59
gmm2d . . . . .	60
griddedVgram . . . . .	64
hiw . . . . .	66
hoods2d . . . . .	70
hoods2dPlot . . . . .	74
hump . . . . .	76
interester . . . . .	77
locmeasures2d . . . . .	81
locperf . . . . .	84
LocSig . . . . .	87
make.SpatialVx . . . . .	89
MCdof . . . . .	94
MergeForce . . . . .	96
metrV . . . . .	98
obs0426 . . . . .	101
OF . . . . .	105
optflow . . . . .	108
pphindcast2d . . . . .	110
S1 . . . . .	113
saller . . . . .	115
Sindex . . . . .	117
spatbiasFS . . . . .	119
spatMLD . . . . .	121
structurogram . . . . .	125
structurogram.matrix . . . . .	127
surrogater2d . . . . .	129
UKobs6 . . . . .	131
upscale2d . . . . .	133
vxstats . . . . .	135
waveIS . . . . .	138
wavePurifyVx . . . . .	141
waverify2d . . . . .	144

## Description

**SpatialVx** contains functions to perform many spatial forecast verification methods.

## Details

Primary functions include:

0. `make.SpatialVx`: An object that contains the verification sets and pertinent information.

1. Filter Methods:

1a. Neighborhood Methods:

Neighborhood methods generally apply a convolution kernel smoother to one or both of the fields in the verification set, and then apply the traditional scores. Most of the methods reviewed in Ebert (2008, 2009) are included in this package. The main functions are:

`hoods2d`, `pphindcast2d`, `kernel2dsmooth`, and `plot.hoods2d`.

1b. Scale Separation Methods:

Scale separation refers to the idea of applying a band-pass filter (and/or doing a multi-resolution analysis, MRA) to the verification set. Typically, skill is assessed on a scale-by-scale basis. However, other techniques are also applied. For example, denoising the field before applying traditional statistics, using the variogram, or applying a statistical test based on the variogram (these last are less similar to the spirit of the scale separation idea, but are at least somewhat related).

There is functionality to do the wavelet methods proposed in Briggs and Levine (1997). In particular, to simply denoise the fields before applying traditional verification statistics, use `wavePurifyVx`.

To apply verification statistics to detail fields (in either the wavelet or field space), use: `waverify2d` (dyadic fields) or `mowaverify2d` (non-dyadic or dyadic) fields.

The intensity-scale technique introduced in Casati et al. (2004) and the new developments of the technique proposed in Casati (2010) can be performed with `waveIS`.

Although not strictly a “scale separation” method, the structure function (for which the variogram is a special case) is in the same spirit in the sense that it analyzes the field for different separation distances, and these “scales” are separate from each other (i.e., the score does not necessarily improve or decline as the scale increases). This package contains essentially wrapper functions to the `vgram.matrix` and `plot.vgram.matrix` functions from the `fields` package, but there is also a function called

`variogram.matrix`

that is a modification of `vgram.matrix` that allows for missing values. The primary function for doing this is called

`griddedVgram`, which has a `plot` method function associated with it.

There are also slight modifications of these functions (small modifications of the fields functions) to calculate the structure function of Harris et al. (2001). These functions are called `structurogram` (for non-gridded fields) and `structurogram.matrix` (for gridded fields).

The latter allows for ignoring zero-valued grid points (as detailed in Harris et al., 2001) where the former does not (they must be removed prior to calling the function).

## 2. Displacement Methods:

In Gilleland et al (2009), this category was broken into two main types as field deformation and features-based. The former lumped together binary image measures/metrics with field deformation techniques because the binary image measures inform about the “similarity” (or dissimilarity) between the spatial extent or pattern of two fields (across the entire field). Here, they are broken down further into those that yield only a single (or small vector of) metric(s) or measure(s) (location measures), and those that have mechanisms for moving grid-point locations to match the fields better spatially (field deformation).

### 2a. Location Measures:

Included here are the well-known Hausdorff metric, the partial-Hausdorff measure, FQI (Venugopal et al., 2005), Baddeley’s delta metric (Baddeley, 1992; Gilleland, 2011; Schwedler et al., 2011), `metrV` (Zhu et al., 2011), as well as the localization performance measures described in Baddeley, 1992: mean error distance, mean square error distance, and Pratt’s Figure of Merit (FOM).

`locmeasures2d`, `metrV`, `distob`, `locperf`

### 2b. Field deformation:

Thanks to Caren Marzban for supplying his optical flow code for this package (it has been modified some). These functions perform the analyses described in Marzban and Sandgathe (2010) and are based on the work of Lucas and Kanade (1981). See the help file for `OF`.

A separate image warping package is in the works, and functionality will be included here probably with some wrapper functions specific to spatial forecast verification needs.

2c. Features-based methods: These methods are also sometimes called object-based methods (the term “features” is used in this package in order to differentiate from an R object), and have many similarities to techniques used in Object-Based Image Analysis (OBIA), a relatively new research area that has emerged primarily as a result of advances in earth observations sensors and GIScience (Blaschke et al., 2008). It is attempted to identify individual features within a field, and subsequently analyze the fields on a feature-by-feature basis. This may involve intensity error information in addition to location-specific error information. Additionally, contingency table verification statistics can be found using new definitions for hits, misses and false alarms (correct negatives are more difficult to assess, but can also be done).

Currently, there is functionality for performing the analyses introduced in Davis et al. (2006,2009), including the merge/match algorithm of Gilleland et al (2008), as well as the SAL technique of Wernli et al (2008, 2009). Some functionality for composite analysis (Nachamkin, 2004) is provided by way of placing individual features onto a relative grid so that each shares the same centroid. Shape analysis is partially supported by way of functions to identify boundary points (Micheas et al. 2007; Lack et al. 2010). In particular, see:

Functions to identify features: `convthresh`, `threshfac`, `threshsizer`

Functions to match/merge features: `centmatch`, `deltamm`

Functions to diagnose features and/or compare matched features:

FeatureAxis, FeatureComps, FeatureMatchAnalyzer, FeatureProps

See `compositer` for setting up composited objects, and see `hiw` for some shape analysis functionality.

The cluster analysis methods of Marzban and Sandgathe (2006; 2008) have been added. The former method was written from scratch by Eric Gilleland

`clusterer`

and the latter variation was modified from code originally written by Hilary Lyons

`CSIsamples`.

2d. Geometrical characterization measures:

Perhaps the measures in this sub-heading are best described as part-and-parcel of 2c. They are certainly useful in that domain, but have been proposed also for entire fields by AghaKouchak et al. (2011); though similar measures have been applied in, e.g., MODE. The measures introduced in AghaKouchak et al. (2011) available here are: connectivity index (Cindex), shape index (Sindex), and area index (Aindex):

Cindex, Sindex, Aindex

3. Statistical inferences for spatial (and/or spatiotemporal) fields:

In addition to the methods categorized in Gilleland et al. (2009), there are also functions for making comparisons between two spatial fields. The field significance approach detailed in Elmore et al. (2006), which requires a temporal dimension as well, involves using a circular block bootstrap (CBB) algorithm (usually for the mean error) at each grid point (or location) individually to determine grid-point significance (null hypothesis that the mean error is zero), and then a semi-parametric Monte Carlo method viz. Livezey and Chen (1983) to determine field significance.

`spatbiasFS`, `LocSig`, `MCdof`

In addition, the mean loss differential approach of Hering and Genton (2011) is included via the function, `spatMLD`, including the loss functions: absolute error (`abserrloss`), square error (`sqerrloss`) and correlation skill (`corrskill`), as well as the distance map loss function (`distmaploss`) introduced in Gilleland (2013).

4. Other:

The bias corrected TS and ETS (or TS dHdA and ETS dHdA) introduced in Mesinger (2008) are now included within the `vxstats` function.

The 2-d Gaussian Mixture Model (GMM) approach introduced in Lakshmanan and Kain (2010) can be carried out using the

`gmm2d`

function (to estimate the GMM) and the associated summary function calculates the parameter comparisons. Also available are `plot` and `predict` method functions, but it can be very slow to run. The `gmm2d` employs an initialization function that takes the K largest object areas (connected components) and uses their centroids as initial estimates for the means, and uses the axes as initial guesses for the standard deviations. However, the user may supply their own initial estimate function.

The S1 score and anomaly correlation (ACC) are available through the functions

`S1` and `ACC`.

See Brown et al. (2012) and Thompson and Carter (1972) for more on these statistics.

Also included is a function to do the geographic box-plot of Willmott et al. (2007). Namely, GeoBoxPlot.

Datasets:

All of the initial Spatial Forecast Verification Inter-Comparison Project (ICP, <http://www.ral.ucar.edu/projects/icp>) data sets used in the special collection of the Weather and Forecasting journal are included. See the help file for

obs0426,

which gives information on all of these datasets that are included, as well as two examples for plotting them: one that does not preserve projections, but plots the data without modification, and another that preserves the projections, but possibly with some interpolative smoothing.

Ebert (2008) provides a nice review of these methods. Roberts and Lean (2008) describes one of the methods, as well as the primary boxcar kernel smoothing method used throughout this package. Gilleland et al. (2009, 2010) provides an overview of most of the various recently proposed methods, and Ahijevych et al. (2009) describes the data sets included in this package. Some of these have been applied to the ICP test cases in Ebert (2009).

Additionally, one of the NIMROD cases (as provided by the UK Met Office) analyzed in Casati et al (2004) (case 6) is included along with approximate lon/lat locations. See the help file for UKObs6 more information.

A spatio-temporal verification dataset is also included for testing the method of Elmore et al. (2006). See the help file for

GFSNAMfcstEx.

A simulated dataset similar to the one used in Marzban and Sandgathe (2010) is also available and is called

hump.

### Author(s)

Eric Gilleland

### References

- AghaKouchak, A., Nasrollahi, N. Li, J. Imam, B. and Sorooshian, S. (2011) Geometrical characterization of precipitation patterns. *J. Hydrometeorology*, **12**, 274–285, doi:10.1175/2010JHM1298.1.
- Ahijevych, D., Gilleland, E., Brown, B. G. and Ebert, E. E. (2009) Application of spatial verification methods to idealized and NWP gridded precipitation forecasts. *Wea. Forecasting*, **24** (6), 1485–1497.
- Baddeley, A. J. (1992) An error metric for binary images. In *Robust Computer Vision Algorithms*, Forstner, W. and Ruwiedel, S. Eds., Wichmann, 59–78.
- Blaschke, T., Lang, S. and Hay, G. (Eds.) (2008) *Object-Based Image Analysis*. Berlin, Germany: Springer-Verlag, 818 pp.
- Briggs, W. M. and Levine, R. A. (1997) Wavelets and field forecast verification. *Mon. Wea. Rev.*, **125**, 1329–1341.

- Brown, B. G., Gilleland, E. and Ebert, E. E. (2012) Chapter 6: Forecasts of spatial fields. pp. 95–117, In *Forecast Verification: A Practitioner's Guide in Atmospheric Science*, 2nd edition. Edts. Jolliffe, I. T. and Stephenson, D. B., Chichester, West Sussex, U.K.: Wiley, 274 pp.
- Casati, B. (2010) New Developments of the Intensity-Scale Technique within the Spatial Verification Methods Inter-Comparison Project. *Wea. Forecasting* **25**, (1), 113–143, doi:10.1175/2009WAF2222257.1.
- Casati, B., Ross, G. and Stephenson, D. B. (2004) A new intensity-scale approach for the verification of spatial precipitation forecasts. *Meteorol. Appl.* **11**, 141–154.
- Davis, C. A., Brown, B. G. and Bullock, R. G. (2006) Object-based verification of precipitation forecasts, Part I: Methodology and application to mesoscale rain areas. *Mon. Wea. Rev.*, **134**, 1772–1784.
- Ebert, E. E. (2008) Fuzzy verification of high resolution gridded forecasts: A review and proposed framework. *Meteorol. Appl.*, **15**, 51–64. DOI: 10.1002/met.25 Available at <http://www.ecmwf.int/newsevents/meetings/workshops/2007/jwgv/METspecialissueemail.pdf>
- Ebert, E. E. (2009) Neighborhood verification: A strategy for rewarding close forecasts. *Wea. Forecasting*, **24**, 1498–1510, doi:10.1175/2009WAF2222251.1.
- Elmore, K. L., Baldwin, M. E. and Schultz, D. M. (2006) Field significance revisited: Spatial bias errors in forecasts as applied to the Eta model. *Mon. Wea. Rev.*, **134**, 519–531.
- Gilleland, E. (2013) Testing competing precipitation forecasts accurately and efficiently: The spatial prediction comparison test. *Mon. Wea. Rev.*, **141**, (1), 340–355.
- Gilleland, E. (2011) Spatial forecast verification: Baddeley's delta metric applied to the ICP test cases. *Wea. Forecasting*, **26**, 409–415, doi:10.1175/WAF-D-10-05061.1.
- Gilleland, E., Lee, T. C. M., Halley Gotway, J., Bullock, R. G. and Brown, B. G. (2008) Computationally efficient spatial forecast verification using Baddeley's delta image metric. *Mon. Wea. Rev.*, **136**, 1747–1757.
- Gilleland, E., Ahijevych, D., Brown, B. G., Casati, B. and Ebert, E. E. (2009) Intercomparison of Spatial Forecast Verification Methods. *Wea. Forecasting*, **24**, 1416–1430, doi:10.1175/2009WAF2222269.1.
- Gilleland, E., Ahijevych, D. A., Brown, B. G. and Ebert, E. E. (2010) Verifying Forecasts Spatially. *Bull. Amer. Meteor. Soc.*, October, 1365–1373.
- Harris, D., Foufoula-Georgiou, E., Droegemeier, K. K. and Levit, J. J. (2001) Multiscale statistical properties of a high-resolution precipitation forecast. *J. Hydrometeorol.*, **2**, 406–418.
- Hering, A. S. and Genton, M. G. (2011) Comparing spatial predictions. *Technometrics* **53**, (4), 414–425.
- Lack, S., Limpert, G. L. and Fox, N. I. (2010) An object-oriented multiscale verification scheme. *Wea. Forecasting*, **25**, 79–92, DOI: 10.1175/2009WAF2222245.1
- Lakshmanan, V. and Kain, J. S. (2010) A Gaussian Mixture Model Approach to Forecast Verification. *Wea. Forecasting*, **25** (3), 908–920.
- Livezey, R. E. and Chen, W. Y. (1983) Statistical field significance and its determination by Monte Carlo techniques. *Mon. Wea. Rev.*, **111**, 46–59.
- Lucas, B D. and Kanade, T. (1981) An iterative image registration technique with an application to stereo vision. *Proc. Imaging Understanding Workshop*, DARPA, 121–130.
- Marzban, C. and Sandgathe, S. (2006) Cluster analysis for verification of precipitation fields. *Wea. Forecasting*, **21**, 824–838.

- Marzban, C. and Sandgathe, S. (2008) Cluster Analysis for Object-Oriented Verification of Fields: A Variation. *Mon. Wea. Rev.*, **136**, (3), 1013–1025.
- Marzban, C. and Sandgathe, S. (2009) Verification with variograms. *Wea. Forecasting*, **24** (4), 1102–1120, doi: 10.1175/2009WAF2222122.1
- Marzban, C. and Sandgathe, S. (2010) Optical flow for verification. *Wea. Forecasting*, **25**, 1479–1494, doi:10.1175/2010WAF2222351.1.
- Mesinger, F. (2008) Bias adjusted precipitation threat scores. *Adv. Geosci.*, **16**, 137–142.
- Micheas, A. C., Fox, N. I., Lack, S. A. and Wikle, C. K. (2007) Cell identification and verification of QPF ensembles using shape analysis techniques. *J. of Hydrology*, **343**, 105–116.
- Nachamkin, J. E. (2004) Mesoscale verification using meteorological composites. *Mon. Wea. Rev.*, **132**, 941–955.
- Roberts, N. M. and Lean, H. W. (2008) Scale-selective verification of rainfall accumulations from high-resolution forecasts of convective events. *Mon. Wea. Rev.*, **136**, 78–97. doi:10.1175/2007MWR2123.1.
- Schwedler, B. R. J. and Baldwin, M. E. (2011) Diagnosing the sensitivity of binary image measures to bias, location, and event frequency within a forecast verification framework. *Wea. Forecasting*, **26**, 1032–1044, doi:10.1175/WAF-D-11-00032.1.
- Thompson, J. C. and Carter, G. M. (1972) On some characteristics of the S1 score. *J. Appl. Meteorol.*, **11**, 1384–1385.
- Venugopal, V., Basu, S. and Foufoula-Georgiou, E. (2005) A new metric for comparing precipitation patterns with an application to ensemble forecasts. *J. Geophys. Res.*, **110**, D08111, doi:10.1029/2004JD005395, 11pp.
- Wernli, H., Paulat, M., Hagen, M. and Frei, C. (2008) SAL—A novel quality measure for the verification of quantitative precipitation forecasts. *Mon. Wea. Rev.*, **136**, 4470–4487.
- Wernli, H., Hofmann, C. and Zimmer, M. (2009) Spatial forecast verification methods intercomparison project: Application of the SAL technique. *Wea. Forecasting*, **24**, 1472–1484, doi:10.1175/2009WAF2222271.1
- Willmott, C. J., Robeson, S. M. and Matsuura, K. (2007) Geographic box plots. *Physical Geography*, **28**, 331–344, DOI: 10.2747/0272-3646.28.4.331.
- Zhu, M., Lakshmanan, V. Zhang, P. Hong, Y. Cheng, K. and Chen, S. (2011) Spatial verification using a true metric. *Atmos. Res.*, **102**, 408–419, doi:10.1016/j.atmosres.2011.09.004.

## Examples

```
## See help files for above named functions and datasets
## for specific examples.
```

---

abserrloss

*Loss functions for the spatial prediction comparison test (SPCT)*

---

## Description

Loss functions for applying the spatial prediction comparison test (SPCT) for competing forecasts.



**Usage**

```
abserrloss(x, y, ...)
corrskill(x, y, ...)
sqerrloss(x, y, ...)
distmaploss(x, y, threshold = 0, const = Inf, ...)
```

**Arguments**

<code>x,y</code>	m by n numeric matrices against which to calculate the loss (or skill) functions.
<code>threshold</code>	numeric giving the threshold over which (and including) binary fields are created from x and y in order to make a distance map.
<code>const</code>	numeric giving the constant beyond which the differences in distance maps between x and y are set to zero. If Inf (default), then no cut-off is taken. The SPCT is probably not powerful for large values of const.
<code>...</code>	Not used by <code>abserrloss</code> or <code>sqerrloss</code> (there for consistency only, and in order to work with <code>spatMLD</code> ). For <code>corrskill</code> , these are optional arguments to <code>sd</code> . For <code>distmaploss</code> , these are optional arguments to the <code>distmap</code> function from package <b>spatstat</b> .

**Details**

These are simple loss functions that can be used in conjunction with `spatMLD` to carry out the spatial prediction comparison test (SPCT) as introduced in Hering and Genton (2011); see also Gilleland (2013) in particular for details about the distance map loss function.

The distance map loss function does not zero-out well as the other loss functions do. Therefore, `zero.out` should be `FALSE` in the call to `spatMLD`. Further, as pointed out in Gilleland (2013), the distance map loss function can easily be hedged by having a lot of correct negatives. The image warp loss function is probably better for this purpose if, e.g., there are numerous zero-valued grid points in all fields.

**Value**

numeric m by n matrices containing the value of the loss (or skill) function at each location i of the original set of locations (or grid of points).

**Author(s)**

Eric Gilleland

**References**

Gilleland, E. (2013) Testing competing precipitation forecasts accurately and efficiently: The spatial prediction comparison test. *Mon. Wea. Rev.*, **141**, (1), 340–355.

Hering, A. S. and Genton, M. G. (2011) Comparing spatial predictions. *Technometrics* **53**, (4), 414–425.

**See Also**

[spatMLD](#), [vgram.matrix](#), [vgram](#)

**Examples**

```
# See help file for spatMLD for examples.
```

---

Aindex

*Area Index*

---

**Description**

Calculate Area index described in AghaKouchak et al. (2011).

**Usage**

```
Aindex(x, thresh = NULL, dx = 1, dy = 1, ...)
```

```
## Default S3 method:
```

```
Aindex(x, thresh = NULL, dx = 1, dy = 1, ...)
```

```
## S3 method for class 'SpatialVx'
```

```
Aindex(x, thresh = NULL, dx = 1, dy = 1, ...,
       time.point=1, model=1)
```

**Arguments**

<code>x</code>	Default: m by n numeric matrix giving the field for which the area index is to be calculated. Aindex.SpatialVx: list object of class “SpatialVx”.
<code>thresh</code>	Values under this threshold are set to zero. If NULL, it will be set to 1e-8 (a very small value).
<code>dx, dy</code>	numeric giving the grid point size in each direction if it is desired to apply such a correction. However, the values are simply canceled out in the index, so these arguments are probably not necessary. If it is desired to only get the area of the non-zero values in the field, or the convex hull, then these make sense.
<code>time.point</code>	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>...</code>	Not used.

**Details**

The area index introduced in AghaKouchak et al. (2011) is given by

$$Aindex = A/Aconvex,$$

where  $A$  is the area of the pattern, and  $Aconvex$  the area of its convex hull (area.owin from package spatstat is used to calculate this latter area, and the functions as.im and solutionset from spatstat are also used by this function). Values are between 0 and 1. Values closer to unity indicate a more structured pattern, and values closer to zero indicate higher dispersiveness of the pattern, but note that two highly structured patterns far away from each other may also give a low value (see examples below). Because of this, this measure is perhaps best applied to individual features in a field.

**Value**

numeric vector (or two-row matrix in the case of Aindex.SpatialVx) with named components (columns):

Aindex	numeric giving the area index.
A, Aconvex	numeric giving the area of the pattern and the convex hull, resp.
dx, dy	the values of dx and dy as input to the function.

**Author(s)**

Eric Gilleland

**References**

AghaKouchak, A., Nasrollahi, N., Li, J., Imam, B. and Sorooshian, S. (2011) Geometrical characterization of precipitation patterns. *J. Hydrometeorology*, **12**, 274–285, doi:10.1175/2010JHM1298.1.

**See Also**

[as.im](#), [solutionset](#), [convexhull](#), [Cindex](#), [Sindex](#)

**Examples**

```
# Gemetric shape that is highly structured.
data(geom000)
Aindex(geom000)
Aindex(geom000, dx=4, dy=4)

## Not run:
# Two separate areas with highly structured shapes, but far away from each other.
data(pert000)
data(pert006)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert006, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
```

```

data.name=c("ICP Perturbed Cases", "pert000", "pert006")

plot(hold, set.pw=TRUE)

Aindex(hold, thresh=20, dx=4, dy=4)

## End(Not run)

```

---

bearing

*Bearing from One Spatial Location to Another*


---

### Description

Find the bearing from one spatial location to another.

### Usage

```
bearing(point1, point2, deg = TRUE, aty = "compass")
```

### Arguments

`point1`, `point2` two-column numeric matrices giving lon/lat coordinates for the origin point(s) (`point1`) and the destination point(s) (`point2`).

`deg` logical, should the output be converted from radians to degrees?

`aty` character stating either "compass" (default) or "radial". The former gives the standard compass bearing angle (0 is north, increase clockwise), and the latter is for polar coordinates (0 is East, increase counter-clockwise).

### Details

The bearing,  $\beta$ , of a point B as seen from a point A is given by

$$\beta = \text{atan2}(S, T)$$

where

$$S = \cos(\phi_B) * \sin(L_A - L_B), \text{ and}$$

$$T = \cos(\phi_A) * \sin(\phi_B) - \sin(\phi_A) * \cos(\phi_B) * \cos(L_A - L_B)$$

where  $\phi_A$  ( $\phi_B$ ) is the latitude of point A (B), and  $L_A$  ( $L_B$ ) is the longitude of point A (B).

Note that there is no simple relationship between the bearing of A to B vs. the bearing of B to A. The bearing given here is in the usual R convention for lon/lat information, which gives points east of Greenwich as negative longitude, and south of the equator as negative latitude.

### Value

numeric giving the bearing angle.

**Author(s)**

Eric Gilleland and Randy Bullock, bullock "at" ucar.edu

**References**

Keay, W. (1995) Land Navigation: Routefinding with Map & Compass, Coventry, UK: Clifford Press Ltd., ISBN 0319008452, 978-0319008454

**See Also**

[atan2](#), [FeatureAxis](#), [rdist.earth](#)

**Examples**

```
# Boulder, Colorado and Wallaroo, Australia.
A <- rbind(c(-105.2833, 40.0167), c(137.65, -33.9333))

# Wallaroo, Australia and Boulder, Colorado.
B <- rbind(c(137.65, -33.9333), c(-105.2833, 40.0167))

bearing(A,B)
bearing(A,B,aty="radial")

plot(A, type="n", xlab="", ylab="")
points(A[,1], A[,2], pch="*", col="darkblue")

# Boulder, Colorado to Wallaroo, Australia.
arrows(A[1,1], A[1,2], A[2,1], A[2,2], col="red", lwd=1.5)
```

---

centdist

*Centroid Distance Between Two Identified Objects*

---

**Description**

Find the centroid distance between two identified objects/features.

**Usage**

```
centdist(x, y, distfun = "rdist", loc = NULL, ...)
```

## Arguments

<code>x,y</code>	objects of class “owin” (package <b>spatstat</b> ) containing binary images of features of interest.
<code>distfun</code>	character string naming a distance function that should take arguments <code>x1</code> and <code>x2</code> as 1 by 2 matrices, and return a single numeric value. Default uses the <b>fields</b> function, <code>rdist</code> , where the fields function <code>rdist.earth</code> is an obvious alternative.
<code>loc</code>	two-column matrix giving the location values for which to calculate the centroids. If NULL, indices according to the dimension of the fields are used.
<code>...</code>	optional arguments to <code>distfun</code> .

## Details

This is a simple function that calculates the centroid for each of `x` and `y` (to get their centroids), and then finds the distance between them according to `distfun`. The centroids are calculated using `FeatureProps`.

## Value

numeric giving the centroid distance.

## Author(s)

Eric Gilleland

## See Also

[FeatureProps](#), [as.im](#), [solutionset](#), [FeatureMatchAnalyzer](#), [FeatureComps](#)

## Examples

```
x <- y <- matrix(0, 10, 12)
x[2:3,c(3:6, 8:10)] <- 1
y[c(4:7, 9:10),c(7:9, 11:12)] <- 1

x <- as.im(x)
x <- solutionset(x>0)
y <- as.im(y)
y <- solutionset(y>0)
centdist(x,y)
```

---

Cindex	<i>Connectivity Index</i>
--------	---------------------------

---

### Description

Calculate the connectivity index of an image.

### Usage

```
Cindex(x, thresh = NULL, connect.method = "C", ...)

## Default S3 method:
Cindex(x, thresh = NULL, connect.method = "C", ...)

## S3 method for class 'SpatialVx'
Cindex(x, thresh = NULL, connect.method = "C", ...,
       time.point = 1, model = 1)
```

### Arguments

x	Default: m by n numeric matrix giving the field for which the shape index is to be calculated. Sindex.SpatialVx: list object of class "SpatialVx".
thresh	Set values under (strictly less than) this threshold to zero, and calculate the connectivity index for the resulting image. If NULL, no threshold is applied.
connect.method	character string giving the method argument for the connected function of package <b>spatstat</b> . This must be one of "C" or "interpreted". See the help file for connected for more details.
time.point	numeric or character indicating which time point from the "SpatialVx" verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
...	Not used.

### Details

The connectivity index is introduced in AghaKouchak et al. (2011), and is designed to automatically determine how connected an image is. It is defined by

$$Cindex = 1 - (NC - 1) / (\sqrt{NP} + NC),$$

where  $0 \leq Cindex \leq 1$  is the connectivity index (values close to zero are less connected, and values close to 1 are more connected), NP is the number of nonzero pixels, and NC is the number of isolated clusters.

The function `connected` from package **spatstat** is used to identify the number of isolated clusters.

**Value**

numeric giving the connectivity index.

**Author(s)**

Eric Gilleland

**References**

AghaKouchak, A., Nasrollahi, N., Li, J., Imam, B. and Sorooshian, S. (2011) Geometrical characterization of precipitation patterns. *J. Hydrometeorology*, **12**, 274–285, doi:10.1175/2010JHM1298.1.

**See Also**

[connected](#), [as.im](#), [Sindex](#), [Aindex](#)

**Examples**

```
data(geom000)
Cindex(geom000)

data(pert000)
Cindex(pert000)

## Not run:
# Two separate areas with highly structured shapes, but far away from each other.
data(pert006)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert006, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert006"))

plot(hold, set.pw=TRUE)

Cindex(hold)

## End(Not run)
```

**Description**

Perform Cluster Analysis (CA) verification per Marzban and Sandgathe (2006).



**Usage**

```

clusterer(X, Y = NULL, ...)

## Default S3 method:
clusterer(X, Y = NULL, ..., xloc = NULL, xyp = TRUE, threshold = 1e-08,
  linkage.method = "complete", stand = TRUE, trans = "identity",
  a = NULL, verbose = FALSE)

## S3 method for class 'SpatialVx'
clusterer(X, Y = NULL, ..., time.point = 1, model = 1, xyp = TRUE,
  threshold = 1e-08, linkage.method = "complete", stand = TRUE,
  trans = "identity", verbose = FALSE)

## S3 method for class 'clusterer'
plot(x, ..., set.pw = FALSE, icol = c("gray", tim.colors(64)),
  horizontal = FALSE)

## S3 method for class 'summary.clusterer'
plot(x, ...)

## S3 method for class 'clusterer'
print(x, ...)

## S3 method for class 'clusterer'
summary(object, ...)

```

**Arguments**

X,Y	clusterer default method, these are m by n matrices giving the verification and forecast fields, resp. "SpatialVx" method function, X is an object of class "SpatialVx" and Y is not used (a warning is given if it is not missing and not NULL).
object, x	list object of class "clusterer" as returned by clusterer (or summary.clusterer in the case of plot.summary.clusterer).
xloc	(optional) numeric mn by 2 matrix giving the gridpoint locations. If NULL, this will be created using 1:m and 1:n.
xyp	logical, should the cluster analysis be performed on the locations and intensities (TRUE) or only the locations (FALSE)?
threshold	numeric of length one or two giving the threshold to apply to each field (>=). If length is two, the first value corresponds to the threshold for the verification field, and the second to the forecast field.
linkage.method	character naming a valid linkage method accepted by hclust.
stand	logical, should the data matrices consisting of xloc and each field first be standardized before performing cluster analysis?
trans	character naming a function to be applied to the field intensities before performing the CA. Only used if xyp is TRUE. Default applies no transformation.

<code>time.point</code>	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>a</code>	(optional) list giving object attributes associated with a “SpatialVx” class object. The <code>clusterer</code> method for “SpatialVx” objects calls the default method function, and uses this argument to pass the attributes through to the final returned object, as well as to grab location information.
<code>set.pw</code>	logical, should a panel of plots be determined and set by the function.
<code>icol</code>	color vector for image plots of fields after applying the threshold(s).
<code>horizontal</code>	logical, should the image plot color legend be placed horizontally or vertically? Only for image plot sof the fields.
<code>verbose</code>	logical, should progress information be printed to the screen?
<code>...</code>	optional arguments to the <code>hclust</code> function. In the case of the summary method function, <code>z</code> and/or <code>sigma</code> giving a numeric value used to find the cut-off given by $\text{median} + z * \text{sigma}$ for detemining matched objects (see Marzban and Sandgathe 2006) where defaults of 1 and the standard deviation of minimum inter-cluster distances are used, and <code>silent</code> (logical should information be printed to the screen (FALSE) or not (TRUE); default is to print to the screen. In the case of the <code>plot</code> method functions, these are optional arguments to the summary method function.

## Details

This function performs cluster analysis (CA) on positive values from each of two fields in a verification set using the `hclust` function from package `fastcluster`. Inter-cluster distances are computed between each cluster of each field at every level of the CA. The function `clusterer` performs CA on both fields, and finds the inter-cluster distances across fields for every possible combination of objects at each iteration of each CA. The summary method function finishes the analysis by determining hits, misses and false alarms as well as the numbers of clusters. It also computes CSI for each number of cluster combinations. This is the verification approach described in Marzban and Sandgathe (2006).

The `plot` method function creates a 4 by 2 panel of plots. The top two plots give image plots of the verification and forecast fields with grid points below the threshold(s) showing zero. The next two plots are dendrograms as performed by the `plot` method function for `hclust` (dendrogram) objects. The next row gives a histogram of the minimum inter-cluster distances, then box plots showing the hits, misses and false alarms for every possible combination of levels of each CA. Finally, the bottom two plots show, for each combination of CA level (i.e., numbers of clusters), the CSI and average error (inter-cluster distance) for all matched objects. These last three plots are the ones made by the `plot` method for values returned from the summary method function.

`print` is currently not very useful here, but it prevents printing a big mess to the screen.

## Value

A list object of class “clusterer” is returned with components:

`linkage.method` character vector of length one or two giving the linkage method as passed into the function. The length is two only if the McQuitty method is chosen in which

	case this method is used for the CA, but not for the inter-cluster differences across fields (average is used for that instead).
trans	character naming the transformation function applied to the intensities.
N	numeric giving the size of the fields.
threshold	numeric of length two giving the threshold applied to each field.
NCo,NCf	numeric vectors giving the number of clusters at each iteration of the CA for the verification and forecast fields, resp.
cluster.identifiers	a list with components X and Y giving lists of lists identifying specific CA components at each level of the CA for both fields.
idX,idY	logical vectors describing which grid points were included in the CA for each field (i.e., which grid points were $\geq$ threshold and had non-missing values).
cluster.objects	a list with components X and Y giving the objects returned by hclust for each field.
inter.cluster.dist	a list of list objects with NCf by NCo matrix components giving the inter-cluster distances (between verification and forecast fields) for each iteration of CA for each field.
min.intercluster.dists	numeric vector giving the minimum values inter.cluster.dist at each iteration. Used to determine the cut-off for matched objects.

The summary method function returns a list with the same components as above, but also the components:

cutoff	The cut-off value used for determining matches.
csi,AvgErr	NCo by NCf numeric matrix giving the critical success index (CSI) and average intercluster error (distance) based on matched/un-matched objects.
HMF	NCo by NCf by 3 array giving the hits, misses and false alarms based on matched/un-matched objects.

If the argument a is not NULL, then these are returned as attributes of the returned object. In the case of "SpatialVx" objects, the attributes are preserved.

plot and print methods do not return anything.

### Warning

Although some effort has been put into making the functions in this package as computationally efficient as possible, there is a lot of bookkeeping involved with this approach, and the current functions are probably not as efficient as they could be. In any case, they will likely be slow for large data sets. The function can work quickly on large fields if an adequately high threshold is used (e.g., if threshold=10 is replaced for 16 in the not run example below, the function is VERY slow). Performing the actual cluster analysis on each field is fast because the hclust function from the fast-cluster package is used, which works very well. However, bookkeeping after the CA is done employs a lot of loops within loops, which possibly can be made more efficient (and maybe someday will be), but for now...

If it is desired to simply look at the CA for the two fields, the function `hclust` from `fastcluster` can be used, which essentially replaces the `hclust` function from the `stats` package with a faster version, but otherwise operates the same as far as what is returned, etc., and the same method functions can be employed.

### Note

Contact Caren Marzban, marzban “at” u.washington.edu, for questions about the method, and Eric Gilleland, ericg “at” ucar.edu, for problems with the code.

### Author(s)

Eric Gilleland

### References

Marzban, C. and Sandgathe, S. (2006) Cluster analysis for verification of precipitation fields. *Wea. Forecasting*, **21**, 824–838.

### See Also

[hclust](#), [hclust](#), [as.dendrogram](#), [cutree](#), [make.SpatialVx](#), [CSIsamples](#)

### Examples

```
data(UKobs6)
data(UKfcst6)
look <- clusterer(X=UKobs6, Y=UKfcst6, threshold=16, trans="log", verbose=TRUE)
plot(look, set.pw=TRUE)

## Not run:
data(UKloc)

# Now, do the same thing, but using a "SpatialVx" object.
hold <- make.SpatialVx(UKobs6, UKfcst6, loc=UKloc, map=TRUE,
  field.type="Rainfall", units="mm/h",
  data.name=c("Nimrod", "obs 6", "fcst 6"))

look2 <- clusterer(hold, threshold=16, trans="log", verbose=TRUE)
plot(look2, set.pw=TRUE)
# Note that values differ because now we're using the
# actual locations instead of integer indicators of
# positions.

## End(Not run)
```

---

`combiner`*Combine Features/Matched Objects*

---

**Description**

Combine two or more features or matched class objects into one object for aggregation purposes.

**Usage**

```
combiner(...)
```

**Arguments**

... Two or more objects of class “features” or “matched” (can also be a list of these objects).

**Details**

Useful for functions such as `compositer` and/or (coming soon) aggregating results for feature-based methods.

**Value**

A list object of class “combined” with the same components as the input arguments, but where some components (namely, `X`, `Xhat`, `X.labeled`, `Y.labeled`) are now arrays containing these values from each combined object. The lists of lists contained in the `X.feats` and `Y.feats` include one long list of lists containing all of the individual features from each object.

**Author(s)**

Eric Gilleland

**See Also**

Functions that create objects of class “features” and “matched”: [convthresh](#), [threshfac](#), [threshsizer](#), [centmatch](#), and [deltamm](#).

**Examples**

```
# TO DO
```

---

 compositer

*Create Composite Features*


---

## Description

After identifying features in a verification set, re-grid them so that their centroids are all the same, and the new grid is as small as possible to completely contain all of the features in the verification set.

## Usage

```
compositer(x, level = 0, verbose = FALSE, ...)

## S3 method for class 'features'
compositer(x, level = 0, verbose = FALSE, ...)

## S3 method for class 'matched'
compositer(x, level = 0, verbose = FALSE, ...)

## S3 method for class 'combined'
compositer(x, level = 0, verbose = FALSE, ...)

## S3 method for class 'composited'
plot(x, ..., type = c("all", "X", "Xhat", "X|Xhat", "Xhat|X"),
     dist.crit = 100, FUN = "mean", col = c("gray", tim.colors(64)))
```

## Arguments

<code>x</code>	compositer: an object of class “features”, “matched”, or “combined”. plot: an object of class “composited”.
<code>type</code>	character, stating which composite features should be plotted. Default makes a two by two panel of plots with all of the choices.
<code>dist.crit</code>	maximum value beyond which any minimum centroid distances are considered too far for features to be “present” in the area.
<code>FUN</code>	name of a function to be applied to the composites in order to give the distributional summary.
<code>col</code>	color palette to be used.
<code>level</code>	numeric used in shrinking the grid to a smaller size.
<code>verbose</code>	logical, should information be printed to the screen?
<code>...</code>	Not used by compositer. plot: Optional arguments to <code>image.plot</code> (only for the scale legend), such as <code>legend.only</code> , <code>legend.lab</code> , <code>legend.mar</code> , <code>horizontal</code> , etc.

## Details

This is functionality for performing an analysis similar to the composite verification method of Nachamkin (2004). See also Nachamkin et al. (2005) and Nachamkin (2009). The main difference is that this function centers all features to the same point, then re-sizes the grid to the smallest possible size to contain all features. The "existence" of a feature at the same time point is determined by the centroid distance (because, here, the compositing is done for a large field rather than a small area), but it does not allow for having half of the feature in the domain in order to be considered.

`compositer` takes an object of class "features" or "matched" and centers all of the identified features onto the same point so that all features have the same centroid. It also then re-grids the composited features so that they are contained on the smallest possible domain that includes all of the features in the verification set.

Generally, because the composite approach is distributional in nature, it makes sense to look at features across multiple time points. The function `combiner` allows for combining features from more than one object of class "features" or "matched" in order to subsequently run with `compositer`.

`plot` takes the composite features and adds them together creating a density of the composite features, then, Depending on the `type` argument, the verification (`type = "X"`), model (`type = "Xhat"`), verification conditioned on the model (`type = "X|Xhat"`), or the model conditioned on the verification composite features are plotted. In the case of `type = "all"`, then a panel of four plots are made with all of these choices. In the case of the conditional plots, the sum of composites for one field are masked out so that only the density of the other field is plotted where composited features from the first field exist.

## Value

A list object of class "composited" is returned with all of the same components and attributes as the `x` argument, but with additional components:

- |   |   |
|---|---|
| <code>distances</code>                          | List with components <code>X</code> and <code>Xhat</code> giving the minimum centroid distances from each feature in <code>X</code> ( <code>Xhat</code> ) to a feature in the other field (used for determining the conditional distributions; i.e., a feature is present if its centroid distance is less than some pre-specified amount). |
| <code>Xcentered</code> , <code>Ycentered</code> | list of "owin" objects containing each feature similar to <code>X.feats</code> and <code>Y.feats</code> , but centered on the same spot and re-gridded  |

## Note

centroids are rounded to the nearest whole number so that interpolation is not necessary. This may introduce a slight bias in results, but it should not be a major issue.

## Author(s)

Eric Gilleland

## References

Nachamkin, J. E. (2004) Mesoscale verification using meteorological composites. *Mon. Wea. Rev.*, **132**, 941–955.

Nachamkin, J. E. (2009) Application of the Composite Method to the Spatial Forecast Verification Methods Intercomparison Dataset. *Wea. Forecasting*, **24**(5), 1390–1400, DOI: 10.1175/2009WAF2222225.1.

Nachamkin, J. E., Chen, S. and Schmidt, J. S. (2005) Evaluation of heavy precipitation forecasts using composite-based methods: A distributions-oriented approach. *Mon. Wea. Rev.*, **133**, 2163–2177.

## See Also

Identifying features: [convthresh](#), [threshfac](#), [threshsizer](#)

## Examples

```
x <- y <- matrix(0, 100, 100)
x[2:3,c(3:6, 8:10)] <- 1
y[c(4:7, 9:10),c(7:9, 11:12)] <- 1

x[30:50,45:65] <- 1
y[c(22:24, 99:100),c(50:52, 99:100)] <- 1

hold <- make.SpatialVx(x, y, field.type="contrived", units="none",
  data.name=c("Example", "x", "y"))

look <- convthresh(hold, smoothpar=0.5)

look2 <- compositer(look)
plot(look2, horizontal = TRUE)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004,
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert004"))

look <- convthresh(hold, smoothpar=10.5, thresh = 5)
plot(look)

look2 <- compositer(look)
plot(look2, horizontal = TRUE)

# TO DO: show examples with combiner.

## End(Not run)
```



---

convthresh                      *Convolution Threshold Feature Identification*

---

### Description

Identify features within a field via thresholding a convolution-smoothed version of the field.

### Usage

```
convthresh(object, smoothfun = "disk2dsmooth", smoothpar = 1,
  smoothfunargs = NULL, thresh = 1e-08, idfun = "disjointer",
  zero.down = FALSE, time.point = 1, model = 1, ...)

threshsizer(object, thresh = 1e-08, Ncontig = 50, idfun = "disjointer",
  time.point = 1, model = 1, ...)

threshfac(object, fac = 0.06666667, q = 0.95, wash.out = NULL,
  thresh = NULL, idfun = "disjointer", time.point = 1, model = 1,
  ...)

disjointer(x, method = "C")

## S3 method for class 'features'
plot(x, ..., type = c("both", "obs", "model"))

## S3 method for class 'features'
print(x, ...)

## S3 method for class 'features'
summary(object, ...)

## S3 method for class 'summary.features'
plot(x, ...)
```

### Arguments

object	convthresh, threshfac and threshsizer: list object of class "SpatialVx". summary: an object of class "features" (e.g., as returned by convthresh or threshfac).
x	binary matrix identifying event points. For plot method functions, this is the output object returned from either convthresh or threshfac (or other feature identifying function that returns objects of class "features") or by their summary method function.
smoothfun	character naming a convolution smoothing function that takes argument x (the field to be smoothed, not the same as the argument to disjointer) and a smoothing parameter as the first two arguments. Other arguments are allowed, and are included through smoothfunargs. Default is a disk kernel smoothing function.

smoothpar	single numeric giving the smoothing parameter for smoothfun.
smoothfunargs	list object with named additional arguments to smoothfun.
Ncontig	single numeric giving the number of contiguous grid points that must exceed the threshold in order to be considered as an object.
fac	numeric giving a factor by which to multiply the R quantile in determining the threshold from the fields. Default is to multiply by $\sim 1/15$ as in Wernli et al (2008, 2009). This is not used if thresh is supplied.
thresh	numeric vector of length one or two giving the threshold over which (and including, i.e., $\geq$ ) events are defined. If different thresholds are used for the forecast and verification fields, then the first element is the threshold for the forecast, and the second is that for the verification field. For threshfac, if this value is NULL, the thresholds are determined by $\text{fac} * R_q$ , where $R_q$ is the q-th quantile of the field (different thresholds for each field are used).
q	If thresh is NULL, then this is the quantile used to determine the thresholds for the two fields.
idfun	character naming the function used to identify (and label) individual features in the convolved and thresholded field. Must take argument x, which is the convolved and thresholded (binary) field.
wash.out	(optional) numeric giving a lower threshold over which the quantile for determining the threshold should be found. If NULL, this is not performed. Only used if thresh is NULL.
zero.down	logical, should negative values and relatively very small values be set to zero after smoothing the fields? For thresholds larger than such values, this argument is moot. zapsmall is used to set the very small positive values to zero.
method	character giving the connected components algorithm to be used in function connected from <b>spatstat</b> .
time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
type	character string stating which features to plot (observed, forecast or both). If both, a panel of two plots will be made side-by-side.
...	convthresh and threshfac: additional arguments to idfun. plot method function has optional arguments to image.plot for the color legend bar only. Not used by the print or summary method functions. The summary method function can take the argument: silent-logical, should information be printed to the screen (FALSE) or not (TRUE).

## Details

convthresh:

The convolution threshold technique is a simple way of identifying features (referred to as objects in image analysis circles where features are the attributes thereof) within a field. First, the field is smoothed using a convolution smoother, and then it is set to a binary image where everything above

a given threshold is set to one. Individual features are identified through any choice of function given by `idfun`. The default is to use a connected components algorithm using the **spatstat** function `connected`.

This is the method used by Davis et al. (2006a,b).

`threshsizer`:

This is the method described in, e.g., Nachamkin (2009) or Lack et al. (2010). Objects are identified as contiguous grid points above a threshold where at least `Ncont ig` connected points are above the threshold. This effectively allows only larger objects to be defined.

`threshfac`:

This is the method described in Wernli et al. (2009). Objects are identified via a possibly modified threshold.

### Value

`convthresh` and `threshfac` return a list object of class “features” with components:

`data.name` character vector naming the verification and forecast (R object) fields, resp.

`X.feats`, `Y.feats`

The identified features for the verification and forecast fields as returned by the `idfun` function.

`X.labeled`, `Y.labeled`

matrices of same dimension as the forecast and verification fields giving the images of the convolved and thresholded verification and forecast fields, but with each individually identified object labeled 1 to the number of objects in each field.

`identifier.function`, `identifier.label`

character strings naming the function and giving the long name (for use with `plot` method function).

The `plot` method functions do not return anything.

The `summary` method function for objects of class “features” returns a list with components:

`X`, `Y`

matrices whose rows are objects and columns are properties: `centroidX` and `centroidY` (the x- and y- coordinates for the feature centroids), `area` (the area of each feature in squared grid points), the orientation angle for the fitted major axis, the aspect ratio, `Intensity0.25` and `Intensity0.9` (the lower quartile and 0.9 quantile of intensity values for each feature).

### Author(s)

Eric Gilleland

### References

Davis, C. A., Brown, B. G. and Bullock, R. G. (2006a) Object-based verification of precipitation forecasts, Part I: Methodology and application to mesoscale rain areas. *Mon. Wea. Rev.*, **134**, 1772–1784.

Davis, C. A., Brown, B. G. and Bullock, R. G. (2006b) Object-based verification of precipitation forecasts, Part II: Application to convective rain systems. *Mon. Wea. Rev.*, **134**, 1785–1795.

Lack, S. A., Limpert, G. L. and Fox, N. I. (2010) An object-oriented multiscale verification scheme. *Wea. Forecasting*, **25**, 79–92, doi:10.1175/2009WAF2222245.1.

Nachamkin, J. E. (2009) Application of the composite method to the spatial forecast verification methods intercomparison dataset. *Wea. Forecasting*, **24**, 1390–1400, doi:10.1175/2009WAF2222225.1.

Wernli, H., Paulat, M. Hagen, M. and Frei, C. (2008) SAL—A novel quality measure for the verification of quantitative precipitation forecasts. *Mon. Wea. Rev.*, **136**, 4470–4487.

Wernli, H., Hofmann, C. and Zimmer, M. (2009) Spatial forecast verification methods intercomparison project: Application of the SAL technique. *Wea. Forecasting*, **24**, 1472–1484, doi:10.1175/2009WAF2222271.1.

### See Also

[connected](#), [as.im](#), [tess](#), [tiles](#), [owin](#), [make.SpatialVx](#)

### Examples

```
x <- y <- matrix(0, 10, 12)
x[2:3,c(3:6, 8:10)] <- 1
y[c(4:7, 9:10),c(7:9, 11:12)] <- 1

hold <- make.SpatialVx(x, y, field.type="contrived", units="none",
  data.name=c("Example", "x", "y"))

look <- convthresh(hold, smoothpar=0.5)
length(look$X.feats) # two objects in x.
length(look$Y.feats) # four objects in y.

plot(look$X.feats)
plot(look$Y.feats)

plot(look)
look2 <- summary(look)
plot(look2)

look3 <- threshsizer(hold, Ncontig=5)
plot(look3)

look4 <- threshfac(hold)
plot(look4)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Perturbed ICP Cases", "pert000", "pert004"))
```

```

look <- convthresh(hold, smoothpar=3.5)

length(look$X.feats)
length(look$Y.feats)

image.plot(look$sIx)
image.plot(look$sIy)

plot(look)
look2 <- summary(look, silent=TRUE)
plot(look2)

## End(Not run)

```

**Description**

A variation on cluster analysis for forecast verification as proposed by Marzban and Sandgathe (2008).

**Usage**

```

CSIsamples(x, ...)

## Default S3 method:
CSIsamples(x, ..., xhat, nbr.csi.samples = 100, threshold = 20,
  k = 100, width = 25, stand = TRUE, z.mult = 0, hit.threshold = 0.1,
  max.csi.clust = 100, diss.metric = "euclidean", linkage.method = "average",
  verbose = FALSE)

## S3 method for class 'SpatialVx'
CSIsamples(x, ..., time.point = 1, model = 1, nbr.csi.samples = 100,
  threshold = 20, k = 100, width = 25, stand = TRUE, z.mult = 0,
  hit.threshold = 0.1, max.csi.clust = 100, diss.metric = "euclidean",
  linkage.method = "average", verbose = FALSE)

## S3 method for class 'CSIsamples'
summary(object, ...)

## S3 method for class 'CSIsamples'
plot(x, ...)

## S3 method for class 'summary.CSIsamples'
plot(x, ...)

```

```
## S3 method for class 'CSIsamples'
print(x, ...)
```

### Arguments

<code>x, xhat</code>	default method: matrices giving the verification and forecast fields, resp. “SpatialVx” method: <code>x</code> is an object of class “SpatialVx”. <code>plot</code> , <code>print</code> methods: list object of class “CSIsamples” or “summary.CSIsamples” (in the case of <code>plot</code> ).
<code>object</code>	list object of class “CSIsamples”.
<code>nbr.csi.samples</code>	integer giving the number of samples to take at each level of the CA.
<code>threshold</code>	numeric giving a value over which is to be considered an event.
<code>k</code>	numeric giving the value for centers in the call to <code>kmeans</code> .
<code>width</code>	numeric giving the size of the samples for each cluster sample.
<code>stand</code>	logical, should the data first be standardized before applying CA?
<code>z.mult</code>	numeric giving a value by which to multiply the <code>z</code> - component. If zero, then the CA is performed on locations only. Can be used to give more or less weight to the actual values at these locations.
<code>hit.threshold</code>	numeric between zero and one giving the threshold for the proportion of a cluster that is from the verification field vs the forecast field used for determining whether the cluster constitutes a hit (vs false alarm or miss depending).
<code>max.csi.clust</code>	integer giving the maximum number of clusters allowed.
<code>diss.metric</code>	character giving which method to use in the call to <code>dist</code> (which dissimilarity metric should be used?).
<code>linkage.method</code>	character giving the name of a linkage method acceptable to the method argument from the <code>hclust</code> function of package <b>fastcluster</b> .
<code>time.point</code>	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>verbose</code>	logical, should progress information be printed to the screen?
<code>...</code>	Not used by <code>CSIsamples</code> method functions. summary method function: the argument <code>silent</code> may be specified, which is a logical stating whether to print the information to the screen (FALSE) or not (TRUE). If not given, the summary information will be printed to the screen. Not used by the <code>plot</code> method function.

### Details

This function carries out the procedure described in Marzban and Sandgathe (2008) for verifying forecasts. Effectively, it combines the verification and forecast fields (keeping track of which values belong to which field) and applies CA to the combined field. Clusters identified with a proportion of values belonging to the verification field within a certain range (defined by the `hit.threshold`

argument) are determined to be hits, misses or false alarms. From this information, the CSI (at each number of clusters; scale) is calculated. A sampling scheme is used to speed up the process.

The plot and summary functions all give the same information, but in different formats: i.e., CSI by number of clusters (scale).

### Value

A list is returned by CSIsamples with components:

data.name	character vector giving the names of the verification and forecast fields analyzed, resp.
call	an object of class “call” giving the function call.
results	max.csi.clust by nbr.csi.samples matrix giving the calculated CSI for each sample and iteration of CA.

The summary method function invisibly returns the same list, but with the additional component:

csi	vector of length max.csi.clust giving the sample average CSI for each iteration of CA.
-----	--

The plot method functions do not return anything. Plots are created.

### Note

Special thanks to Caren Marzban, marzban “at” u.washington.edu, for making the CSIsamples (originally called csi.samples) function available for use with this package.

### Author(s)

Hillary Lyons, h.lyons “at” comcast.net, and modified by Eric Gilleland

### References

Marzban, C., Sandgathe, S. (2008) Cluster Analysis for Object-Oriented Verification of Fields: A Variation. *Mon. Wea. Rev.*, **136**, (3), 1013–1025.

### See Also

[hclust](#), [hclust](#), [kmeans](#), [clusterer](#)

### Examples

```
## Not run:
grid<- list( x= seq( 0,5,,100), y= seq(0,5,,100))
obj<-Exp.image.cov( grid=grid, theta=.5, setup=TRUE)
look<- sim.rf( obj)
look2 <- sim.rf( obj)

res <- CSIsamples(x=look, xhat=look2, 10, threshold=0, k=100,
                 width=2, z.mult=0, hit.threshold=0.25, max.csi.clust=75)
plot(res)
```

```

y <- summary(res)
plot(y)

## End(Not run)
## Not run:
data(UKfcst6)
data(UKobs6)
data(UKloc)

hold <- make.SpatialVx(UKobs6, UKfcst6, thresholds=0,
  loc=UKloc, map=TRUE, field.type="Rainfall", units="mm/h",
  data.name=c("Nimrod", "obs 6", "fcst 6"))

res <- CSIsamples(hold, threshold=0, k=200, z.mult=0.3, hit.threshold=0.2,
  max.csi.clust=150, verbose=TRUE)

plot(res)
summary(res)
y <- summary(res)
plot(y)

## End(Not run)

```

---

deltamm

---

*Merge and/or Match Identified Features Within Two Fields*


---

## Description

Merge and/or match identified features within two fields using the delta metric method described in Gilleland et al. (2008), or the matching only method of Davis et al. (2006a).

## Usage

```

deltamm(x, p = 2, max.delta = Inf, const = Inf, verbose = FALSE, ...)

## S3 method for class 'matched'
plot(x, ..., type = c("both", "obs", "model"))

## S3 method for class 'matched'
print(x, ...)

centmatch(x, criteria = 1, const = 14, distfun = "rdist", areafac = 1,
  verbose = FALSE, ...)

```

## Arguments

**x** For `deltamm` and `centmatch`, an object of class “features” with components `X.labeled`, `Y.labeled` (matrices with numbered features), as well as, `X.feats` and `Y.feats`, each of which are list objects containing numbered components within which are objects of class “owin” containing logical matrices that define



	features for the forecast (Y) and verification (X) fields, resp. For example, as returned by the <code>convthresh</code> function. For <code>plot</code> an object of class "matched". Argument <code>y</code> is used if it is not NULL, otherwise argument <code>x</code> is used (but only one of <code>x</code> or <code>y</code> is used). If <code>x</code> and <code>y</code> are missing, but not object, then object will be used, in which case it must be of class "features".
<code>p</code>	Baddeley delta metric parameter. A value of 1 gives arithmetic averages, Inf gives the Hausdorff metric and -Inf gives a minimum. The default of 2 is most common.
<code>max.delta</code>	single numeric giving a cut-off value for delta that disallows two features to be merged or matched if the delta between them is larger than this value.
<code>const</code>	<code>deltamm</code> : a constant value over which the shortest distances in a distance map are set. See Gilleland (2011) and Schwedler and Baldwin (2011) for more information about this parameter. <code>centmatch</code> : numeric giving the number of grid squares whereby if the centroid distance (D) is less than this value, a match is declared (only used if <code>criteria</code> is 3).
<code>criteria</code>	1, 2 or 3 telling which criteria for determining a match based on centroid distance, D, to use. The first (1) is a match if D is less than the sum of the sizes of the two features in question (size is the square root of the area of the feature). The second is a match if D is less than the average size of the two features in question. The third is a match if D is less than a constant given by the argument <code>const</code> .
<code>distfun</code>	character string naming a distance function. Default uses <code>rdist</code> from the <b>fields</b> package.
<code>areafac</code>	single numeric used to multiply by grid-space based area in order to at least approximate the correct distance (e.g., using the ICP test cases, 4 would make the areas approximately square km instead of grid points). This should not be used unless <code>distfun</code> is "rdist.earth" in which case it will use the locations given in the call to <code>make.SpatialVx</code> , which are assumed to be lat/lon coordinates.
<code>verbose</code>	logical, should progress information be printed to the screen?
<code>type</code>	character string naming which plot should be created.
<code>...</code>	For <code>deltamm</code> : additional optional arguments to the <code>distmap</code> function from package <b>spatstat</b> . For <code>centmatch</code> : optional arguments to <code>distfun</code> . For <code>plot.matched</code> , additional arguments to <code>image.plot</code> concerning the color legend bar only.

## Details

`deltamm`:

Gilleland et al. (2008) describe a method for automatically merging, and simultaneously, matching identified features within two fields (a verification set). The method was proposed with the general method for spatial forecast verification introduced by Davis et al. (2006 a,b) in mind. It relies heavily on use of a binary image metric introduced by Baddeley (1992a,b) for comparing binary images; henceforth referred to as the delta metric, or just delta.

The procedure is as follows. Suppose there are  $m$  identified forecast features and  $n$  identified verification features.

1. Compute delta for each feature identified in the forecast field against each feature identified in the verification field. Store these values in an  $m$  by  $n$  matrix, Upsilon.

2. For each of the  $m$  rows of Upsilon, rank the values of delta to identify the features,  $j_1, \dots, j_n$  that provide the lowest (best) to highest (worst) value, and do the same for each of the  $n$  columns to find the forecast features  $i_1, \dots, i_m$  that yield the lowest to highest values for each verification feature.
3. Create a new  $m$  by  $n$  matrix, Psi, whose columns contain delta computed between each of the individual features in the forecast and (first column) the corresponding  $j_1$  feature from the verification field, and each successive column,  $k$ , has delta between the  $i$ -th forecast feature and the union of  $j_1, j_2, \dots, j_k$ .
4. Create a similar  $m$  by  $n$  matrix, Ksi, that has delta computed between each individual feature in the verification field and the successively bigger unions  $i_1, \dots, i_l$  for the  $l$ -th column.
5. Let  $Q=[\text{Upsilon}, \text{Psi}, \text{Ksi}]$ , and merge and match features based on the rankings of delta in  $Q$ . That is, find the smallest delta in  $Q$ , and determine which mergings (if any) and matchings correspond to this value. Remove the appropriate row(s) and column(s) of  $Q$  corresponding to the already determined matchings and/or mergings. Repeat this until all features in at least one field have been exhausted.

The above algorithm suffers from two deficiencies. First, features that are merged in one field cannot be matched to merged features in another field. One possible remedy for this is to run this algorithm twice, though this is not a universally good solution. Second, features can be merged and/or matched to features that are very different from each other. A possible remedy for this is to use the cut-off argument,  $\text{max.delta}$ , to disallow mergings or matchings between features whose delta value is not  $\leq$  this cut-off. In practice, these two deficiencies are not likely very problematic.

centmatch:

This function works similarly as `deltamm`, though it does not merge features. It is based on the method proposed by Davis et al. (2006a). It is possible for more than one object to be matched to the same object in another field. As a result, when plotting, it might appear that features have been merged, but they have not been. For informational purposes, the criteria, `appelled.criteria.values` (as determined by the `criteria` argument), along with the centroid distance matrix, `appelled.centroid.distances`, are returned.

`plot`: The `plot` method function for matched features plots matched features across fields in the same color using `rainbow`. Unmatched features in either field are all colored gray. Zero values are colored white. In the case of features created by `centmatch`, multiple features from one field could be matched to the same feature in the other so that, in such cases, it is not possible to decipher which feature in one field is matched to which feature in the other exactly. The `print` method function will tell you which features matched between fields, so one can plot the originally derived features (e.g., from `convthresh`) to identify matched features. On the other hand, one can subjectively determine if same colored features should be merged or not.

## Value

A list object of class “`matched`” is returned by both `centmatch` and `deltamm` containing several components added to the value of  $x$  or  $y$  passed in, and possibly with attributes inherited from object.

- `match.message` A character string stating how features were matched.
- `match.type` character string naming the matching function used.

matches	two-column matrix with forecast object numbers in the first column and corresponding matched observed features in the second column. If no matches, this will have value integer(0) for each column giving a matrix with dimension 0 by 2.
unmatched	list with components X and Xhat giving the unmatched object numbers, if any, from the observed and forecast fields, resp. If none, the value will be integer(0).
Q	(deltamm only) an array of dimension n by m by 3 giving all of the delta values that were computed in determining the mergings and matchings.
criteria	(centmatch only) 1, 2, or 3 as given by the criteria argument.
criteria.values, centroid.distances	(centmatch only) matrices giving the forecast by observed object criteria and centroid distances.
implicit.merges	(centmatch only) list displaying multiple matches for each field (this could define potential merges). Each component of the list is a unified set of matched features in the form of two-column matrices analogous to the matches component. If there are no implicit mergings or no matched features, this component will be named, but also NULL. Note: such implicit mergings may or may not make physical sense, and are not considered to be merged generally, but will show up as having been merged/clustered when plotted.

If the argument ‘object’ is passed in, then the list object will also contain nearly the same attributes, with the data.name attribute possibly changed to reflect the specific model used. It will also contain a time.point and model attribute.

### Author(s)

Eric Gilleland

### References

- Baddeley, A. (1992a) An error metric for binary images. In *Robust Computer Vision Algorithms*, W. Forstner and S. Ruwiedel, Eds., Wichmann, 59–78.
- Baddeley, A. (1992b) Errors in binary images and an Lp version of the Hausdorff metric. *Nieuw Arch. Wiskunde*, **10**, 157–183.
- Davis, C. A., Brown, B. G. and Bullock, R. G. (2006a) Object-based verification of precipitation forecasts, Part I: Methodology and application to mesoscale rain areas. *Mon. Wea. Rev.*, **134**, 1772–1784.
- Davis, C. A., Brown, B. G. and Bullock, R. G. (2006b) Object-based verification of precipitation forecasts, Part II: Application to convective rain systems. *Mon. Wea. Rev.*, **134**, 1785–1795.
- Gilleland, E. (2011) Spatial Forecast Verification: Baddeley’s Delta Metric Applied to the ICP Test Cases. *Wea. Forecasting*, **26** (3), 409–415.
- Gilleland, E., Lee, T. C. M., Halley Gotway, J., Bullock, R. G. and Brown, B. G. (2008) Computationally efficient spatial forecast verification using Baddeley’s delta image metric. *Mon. Wea. Rev.*, **136**, 1747–1757.

Schwedler, B. R. J. and Baldwin, M. E. (2011) Diagnosing the sensitivity of binary image measures to bias, location, and event frequency within a forecast verification framework. *Wea. Forecasting*, **26**, 1032–1044.

### See Also

To identify features: [convthresh](#), [threshfac](#), [threshsizer](#)

To force merges (implicit or otherwise): [MergeForce](#),

Other functions used to identify features within the above mentioned functions (all from **spatstat**):

[disjoiner](#), [deltametric](#), [owin](#), [tess](#), [tiles](#), [connected](#)

### Examples

```
x <- y <- matrix(0, 100, 100)
x[2:3,c(3:6, 8:10)] <- 1
y[c(4:7, 9:10),c(7:9, 11:12)] <- 1

x[30:50,45:65] <- 1
y[c(22:24, 99:100),c(50:52, 99:100)] <- 1

hold <- make.SpatialVx(x, y, field.type="contrived", units="none",
  data.name=c("Example", "x", "y"))

look <- convthresh(hold, smoothpar=0.5)
par( mfrow=c(1,2))
image.plot(look$X.labeled)
image.plot(look$Y.labeled)

look2 <- deltamm(look)

FeatureTable(look2)

look3 <- centmatch(look)

FeatureTable(look3)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004,
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert004"))

look <- convthresh(hold, smoothpar=10.5, thresh = 5)
plot(look)

look2 <- deltamm(look, verbose = TRUE)
plot(look2)
```

```
## End(Not run)
```

---

EBS	<i>Elmore, Baldwin and Schultz Method for Field Significance for Spatial Bias Errors</i>
-----	--

---

### Description

Apply the method of Elmore, Baldwin and Schultz (2006) for calculating field significance of spatial bias errors.

### Usage

```
EBS(object, model = 1, block.length = NULL, alpha.boot = 0.05,
     field.sig = 0.05, bootR = 1000, ntrials = 1000,
     verbose = FALSE)
```

```
## S3 method for class 'EBS'
plot(x, ..., set.pw = FALSE, col, horizontal)
```

### Arguments

object	list object of class “SpatialVx”.
x	object of class “EBS” as returned by EBS.
model	number or character describing which model (if more than one in the “SpatialVx” object) to compare.
block.length	numeric giving the block length to be used in the block bootstrap algorithm. If NULL, floor(sqrt(n)) is used.
alpha.boot	numeric between 0 and 1 giving the confidence level desired for the bootstrap algorithm.
field.sig	numeric between 0 and 1 giving the desired field significance level.
bootR	numeric integer giving the number of bootstrap replications to use.
ntrials	numeric integer giving the number of Monte Carol iterations to use.
set.pw	logical, should the plotting panels be set by the function?
col, horizontal	optional arguments to image.plot from <b>fields</b> .
verbose	logical, should progress information be printed to the screen?
...	optional arguments to image.plot from <b>fields</b> .

### Details

this is a wrapper function for the spatbiasFS function utilizing the “SpatialVx” object class to simplify the arguments.

**Value**

A list object of class “EBS” with the same attributes as the input object and additional attribute (called “arguments”) that is a named vector giving information provided by the user. Components of the list include:

```
block.boot.results      object of class “LocSig”.
sig.results            list object containing information about the significance of the results.
```

**Author(s)**

Eric Gilleland

**References**

Elmore, K. L., Baldwin, M. E. and Schultz, D. M. (2006) Field significance revisited: Spatial bias errors in forecasts as applied to the Eta model. *Mon. Wea. Rev.*, **134**, 519–531.

**See Also**

[boot](#), [tsboot](#), [spatbiasFS](#), [LocSig](#), [poly.image](#), [image.plot](#), [make.SpatialVx](#)

**Examples**

```
data(GFSNAMfcstEx)
data(GFSNAMobsEx)
data(GFSNAMlocEx)

id <- GFSNAMlocEx[, "Lon"] >=-95
id <- id & GFSNAMlocEx[, "Lon"] <= -75
id <- id & GFSNAMlocEx[, "Lat"] <= 32

##
## This next step is a bit awkward, but these data
## are not in the format of the SpatialVx class.
## These are being set up with arbitrarily chosen
## dimensions (49 X 48) for the spatial part. It
## won't matter to the analyses or plots.
##
Vx <- GFSNAMobsEx
Fcst <- GFSNAMfcstEx
Ref <- array(t(Vx), dim=c(49, 48, 361))
Mod <- array(t(Fcst), dim=c(49, 48, 361))

hold <- make.SpatialVx(Ref, Mod, loc=GFSNAMlocEx,
  projection=TRUE, map=TRUE, loc.byrow = TRUE, subset=id,
  field.type="Precipitation", units="mm",
  data.name=c("GFS/NAM", "Reference", "Model"))

look <- EBS(hold, bootR=500, ntrials=500, verbose=TRUE)
plot(look, set.pw=TRUE)
```

```
## Not run:
# Same as above, but now we'll do it for all points.
# A little slower, but not terribly bad.

hold <- make.SpatialVx(Ref, Mod, loc=GFSNAMlocEx,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", reg.grid=FALSE, units="mm",
  data.name=c("GFS/NAM", "Reference", "Model"))

look <- EBS(hold, bootR=500, ntrials=500, verbose=TRUE)
plot(look, set.pw=TRUE)

## End(Not run)
```

---

ExampleSpatialVxSet    *Simulated Spatial Verification Set*

---

## Description

A simulated spatial verification set for use by various examples for this package.

## Usage

```
data(ExampleSpatialVxSet)
```

## Format

The format is: List of 2 \$ vx : num [1:50, 1:50] 0 0 0 0 0 0 0 0 0 0 ... \$ fcast: num [1:50, 1:50] 0.0141 0 0 0 0 ...

## Details

The data here were generated using the `sim.rf` function from **fields** (Furrer et al., 2012):

```
x <- y <- matrix(0, 10, 12) x[2:3,c(3:6, 8:10)] <- 1 y[c(1:2, 9:10),c(3:6)] <- 1
grid <- list(x=seq(0,5,,50), y=seq(0,5,,50)) obj <- Exp.image.cov(grid=grid, theta=0.5, setup=TRUE)
x <- sim.rf(obj) x[x < 0] <- 0 x <- zapsmall(x)
y <- sim.rf(obj) y[y < 0] <- 0 y <- zapsmall(y)
```

## References

Reinhard Furrer, Douglas Nychka and Stephen Sain (2012). `fields`: Tools for spatial data. R package version 6.6.3. <http://CRAN.R-project.org/package=fields>

**Examples**

```

data(ExampleSpatialVxSet)
x <- ExampleSpatialVxSet$vx
xhat <- ExampleSpatialVxSet$fcst
par(mfrow=c(1,2))
image.plot(x, col=c("gray",tim.colors(64)))
image.plot(xhat, col=c("gray",tim.colors(64)))

```

FeatureAxis

*Major and Minor Axes of a Feature***Description**

Calculate the major and minor axes of a feature and various other properties such as the aspect ratio.

**Usage**

```
FeatureAxis(x, fac = 1, flipit = FALSE, twixt = FALSE)
```

```
## S3 method for class 'FeatureAxis'
plot(x, ..., zoom = FALSE)
```

```
## S3 method for class 'FeatureAxis'
summary(object, ...)
```

**Arguments**

x	For FeatureAxis this is an object of class “owin” containing a binary image matrix defining the feature. In the case of plot.FeatureAxis, this is the value returned from FeatureAxis.
object	list object of class “FeatureAxis” as returned by FeatureAxis.
fac	numeric, in determining the lengths of the axes, they are multiplied by a factor of fac (e.g., if the grid points are k by k km each, then one could set this to k so that the resulting lengths are in terms of km rather than grid points.
flipit	logical, should the objects be flipped over x and y? The disjointer function results in images that are flipped, this would flip them back.
twixt	logical, should the major axis angle be forced to be between +/- 90 degrees?
zoom	logical, should the object be plotted on its bounding box (TRUE) or on the original grid (FALSE, default)? Useful if the feature is too small to be seen well on the original gid.
...	For plot.FeatureAxis these are additional arguments to the plot function. Not used by summary.FeatureAxis.



## Details

This function attempts to identify the major and minor axes for a pre-defined feature (sometimes referred to as an object). This function relies heavily on the **spatstat** and **smatr** packages. First, the convex hull of the feature is determined using the `convexhull` function from the **spatstat** package. The major axis is then found using the `sma` function from package **smatr**, which is then converted into a `psp` object (see `as.psp` from **spatstat**) from which the axis angle and length are found (using `angles.psp` and `lengths.psp`, resp., from **spatstat**).

The minor axis angle is easily found after rotating the major axis 90 degrees using `rotate.psp` from **spatstat**. The length of the minor axis is more difficult. Here, it is found by rotating the convex hull of the feature by the major axis angle (so that it is upright) using `rotate.owin` from **spatstat**, and then computing the bounding box (using `bounding.box` from **spatstat**). The difference is then taken between the range of x- coordinates of the bounding box. This seems to give a reasonable value for the length of the minor axis. A `psp` object is then created using the mid point of the major axis (which should be close to the centroid of the feature) using `as.psp` and `midpoints.psp` from **spatstat** along with the length and angle already found for the minor axis.

See the help files for the above mentioned functions for references, etc.

## Value

FeatureAxis: A list object of class “FeatureAxis” is returned with components:

<code>z</code>	same as the argument <code>x</code> passed in.
<code>MajorAxis, MinorAxis</code>	a <code>psp</code> object with one segment that is the major (minor) axis.
<code>OrientationAngle</code>	list with two components: <code>MajorAxis</code> (the angle in degrees of the major axis wrt the abscissa), <code>MinorAxis</code> (the angle in degrees wrt the abscissa).
<code>aspect.ratio</code>	numeric giving the ratio of the length of the minor axis to that of the major axis (always between 0 and 1).
<code>MidPoint</code>	an object of class “ <code>ppp</code> ” giving the mid point of the major (minor) axis.
<code>lengths</code>	list object with components: <code>MajorAxis</code> giving the length (possibly multiplied by a factor) of the major axis, and <code>MinorAxis</code> same as <code>MajorAxis</code> but for the minor axis.
<code>sma.fit</code>	The fitted object returned by the <code>sma</code> function. This is useful, e.g., if confidence intervals for the axis are desired. See the <code>sma</code> help file for more details.

No value is returned from the `plot` or `summary` method functions.

## Author(s)

Eric Gilleland

## See Also

[owin](#), [convexhull](#), [sma](#), [as.psp](#), [angles.psp](#), [rotate.owin](#), [rotate.psp](#), [bounding.box](#), [midpoints.psp](#), [lengths.psp](#), [inframe](#), [clip.inframe](#), [deltamm](#), [convthresh](#), [disjoiner](#), [connected](#), [tiles](#), [tess](#), [solutionset](#)

**Examples**

```

data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx

look <- disk2dsmoother(x,5)
u <- quantile(look,0.99)
sIx <- matrix(0, 100, 100)
sIx[ look > u] <- 1
look2 <- disjointer(sIx)[[1]]
look2 <- flipxy(look2)
tmp <- FeatureAxis(look2)
plot(tmp)
summary(tmp)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004,
  loc=ICPg240Locs, projection=TRUE, map=TRUE,
  loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Perturbed ICP Cases", "pert000", "pert004"))

look <- convthresh(hold, smoothpar=10.5)
par(mfrow=c(1,2))
plot(look)

par(mfrow=c(2,2))
image.plot(look$X.labeled)
image.plot(look$Y.labeled)

# The next line will likely be very slow.
look2 <- deltam(x=look, verbose=TRUE)
image.plot(look2$X.labeled)
image.plot(look2$Y.labeled)

look2$mm.new.labels # the first seven features are matched.

ang1 <- FeatureAxis(look2$X.feats[[1]])
ang2 <- FeatureAxis(look2$Y.feats[[1]])
plot(ang1)
plot(ang2)
summary(ang1)
summary(ang2)

ang3 <- FeatureAxis(look2$X.feats[[4]])
ang4 <- FeatureAxis(look2$Y.feats[[4]])
plot(ang3)
plot(ang4)

```

```
summary(ang3)
summary(ang4)

## End(Not run)
```

---

FeatureMatchAnalyzer *Analyze Features of a Verification Set*

---

## Description

Analyze matched features of a verification set.

## Usage

```
FeatureMatchAnalyzer(x, which.comps=c("cent.dist", "angle.diff", "area.ratio", "int.area",
  "bdelta", "haus", "ph", "mhd", "med", "msd", "fom", "minsep",
  "bearing"), sizefac=1, alpha=0.1, k=4, p=2, c=Inf,
  distfun="distmapfun", ...)

## S3 method for class 'matched.centmatch'
FeatureMatchAnalyzer(x, which.comps=c("cent.dist", "angle.diff",
  "area.ratio", "int.area", "bdelta", "haus", "ph", "mhd", "med",
  "msd", "fom", "minsep", "bearing"), sizefac=1, alpha=0.1, k=4, p=2,
  c=Inf, distfun="distmapfun", ...)

## S3 method for class 'matched.deltamm'
FeatureMatchAnalyzer(x, which.comps = c("cent.dist", "angle.diff",
  "area.ratio", "int.area", "bdelta", "haus", "ph", "mhd", "med", "msd",
  "fom", "minsep", "bearing"), sizefac = 1, alpha = 0.1, k = 4, p = 2,
  c = Inf, distfun = "distmapfun", ..., y = NULL, matches = NULL,
  object = NULL)

## S3 method for class 'FeatureMatchAnalyzer'
summary(object, ...)

## S3 method for class 'FeatureMatchAnalyzer'
plot(x, ..., type = c("all", "ph", "mhd", "med", "msd",
  "fom", "minsep", "cent.dist", "angle.diff", "area.ratio",
  "int.area", "bearing", "bdelta", "haus"))

## S3 method for class 'FeatureMatchAnalyzer'
print(x, ...)

FeatureComps(Y, X, which.comps=c("cent.dist", "angle.diff", "area.ratio", "int.area",
  "bdelta", "haus", "ph", "mhd", "med", "msd", "fom", "minsep", "bearing"),
  sizefac=1, alpha=0.1, k=4, p=2, c=Inf, distfun="distmapfun", deg = TRUE,
```

```

    aty = "compass", loc = NULL, ...)

## S3 method for class 'FeatureComps'
distill(x, ...)

```

### Arguments

<code>x,y,matches</code>	<code>x</code> , <code>y</code> and <code>matches</code> are list objects with components as output by <code>deltamm</code> or similar function. Only one is used, and it first checks for <code>matches</code> , then <code>y</code> , and finally <code>x</code> . It expects a component named <code>mm.new.labels</code> that gives the number of matched objects. In the case of the <code>plot</code> and <code>print</code> method functions, <code>x</code> is a list object as returned by <code>FeatureMatchAnalyzer</code> . <code>distill</code> : output from <code>FeatureComps</code> .
<code>X,Y</code>	list object giving a pixel image as output from <code>solutionset</code> from package <b>spatstat</b> for the verification and forecast fields, resp. These arguments are passed directly to the <code>locperf</code> function.
<code>object</code>	list object returned of class "FeatureMatchAnalyzer", this is the returned value from the self-same function.
<code>which.comps,type</code>	character vector indicating which properties of the features are to be analyzed ( <code>which.comps</code> ) or plotted ( <code>type</code> ).
<code>sizefac</code>	single numeric by which area calculations should be multiplied in order to get the desired units. If unity (default) results are in terms of grid squares.
<code>alpha</code>	numeric value for the FOM measure (see the help file for <code>locperf</code> ).
<code>k</code>	numeric indicating which quantile to use if the partial Hausdorff measure is to be used.
<code>p</code>	numeric giving the value of the parameter <code>p</code> for the Baddeley metric.
<code>c</code>	numeric giving the cut-off value for the Baddeley metric.
<code>distfun</code>	character naming a distance functions to use in calculating the various binary image measures. Default is Euclidean distance.
<code>deg, aty</code>	optional arguments to the bearing function.
<code>loc</code>	two-column matrix giving location coordinates for centroid distance. If <code>NULL</code> , uses an indices based on the dimension of the field.
<code>...</code>	Additional arguments to <code>deltametric</code> from package <b>spatstat</b> . In case of the <code>summary</code> method function, additional optional arguments may be passed, which include <code>silent</code> (logical, should the information be printed to the screen or not?), <code>interest</code> (numeric vector defining an interest value for calculating total interest for each matched object, if <code>NULL</code> , this is not performed), <code>con</code> (name of function that takes three arguments, the first two are matrices whose rows are objects and columns are matched feature properties, where the former is a matrix of matched feature property values (e.g., angle difference) and the latter is a matrix of interest values determined by the <code>interest</code> argument (whereby each row is identical), the third argument to <code>con</code> must be called <code>which.comps</code> , and it gives the short-form feature property names (i.e., same as <code>which.comps</code> argument); see details section). In the case of the <code>plot</code> method function, these are optional arguments to the function <code>barplot</code> . Not used by <code>distill</code> .

## Details

FeatureMatchAnalyzer operates on objects of class “matched”. It is set up to calculate the values discussed in sec. 4 of Davis et al. (2006) for a single verification set (i.e., mean and standard deviation are not computed because it is only a single case). If criteria is 1, then features separated by a distance  $D <$  the sum of the sizes of the two features (size of a feature is defined as the square root of its area) are considered a match. If criteria is 2, then a match is made if  $D <$  the average of the sizes of the two features. Finally, criteria 3 decides a match as being anything less than a pre-determined constant.

FeatureComps is the primary function called by FeatureMatchAnalyzer, and is designed as a more stand-alone type of function. Several of the measures that can be calculated are simply the binary image measures/metrics available via, e.g., locperf. It calculates comparisons between two matched features (i.e., between the verification and forecast fields).

distill reduces a “FeatureComps” list object to a named numeric vector containing (in this order) the components that exist from "cent.dist", "angle.diff", "area.ratio", "int.area", "bdelta", "haus", "ph", "mhd", "med", "msd", "fom", and "minsep". This is used, for example, by interester, which is why the order is important.

The summary method function for FeatureMatchAnalyzer allows for passing a function, con, to determine confidence for each interest value. The idea being to set the interest to zero when the particular interest value does not make sense. For example, angle difference makes no sense if both objects are circles. Currently, no functions are included in this package for actually doing this, and so the functionality itself has not been tested.

The print method function for FeatureMatchAnalyzer first converts the object to a simple named matrix, then prints the matrix out. The resulting matrix is returned invisibly.

## Value

FeatureMatchAnalyzer returns a list of list objects. The specific components depend on the 'which.comps' argument, and are the same as those returned by FeatureComps. These can be any of the following.

cent.dist	numeric giving the centroid (Euclidean) distance.
angle.diff	numeric giving the orientation (major axis) angle difference.
area.ratio	numeric giving the area ratio, which is always between 0 and 1 because this is defined by Davis et al. (2006) to be the area of the smaller feature divided by that of the larger feature regardless of which field the feature belongs to.
int.area	numeric giving the intersection area of the features.
bdelta	numeric giving Baddeley’s delta metric between the two features.
haus, ph, mhd, med, msd, fom, minsep	numeric, see locperf for specific information.
bearing	numeric giving the bearing from the forecast object centroid to the observed object centroid.

The summary method for FeatureMatchAnalyzer invisibly returns a matrix with the same information, but where each matched object is a row and each column is the specific statistic. Or, if optional interest argument is passed, a list with components:

print returns a named vector invisibly.

**Author(s)**

Eric Gilleland

**References**

Davis, C. A., Brown, B. G. and Bullock, R. G. (2006) Object-based verification of precipitation forecasts, Part I: Methodology and application to mesoscale rain areas. *Mon. Wea. Rev.*, **134**, 1772–1784.

**See Also**

Functions to identify features: [convthresh](#), [threshfac](#), [threshsizer](#)

Functions to merge and/or match objects: [deltamm](#), [centmatch](#), [MergeForce](#)

Functions to compute feature properties: [locperf](#), [deltametric](#), [bearing](#)

Function to calculate fuzzy logic interest values: [interester](#)

**Examples**

```
data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx
xhat <- ExampleSpatialVxSet$fcst

hold <- make.SpatialVx(x, xhat, field.type="Example",
  units="units", data.name=c("Example", "x", "xhat"))

look <- convthresh(hold, smoothpar=1.5)
look2 <- centmatch(look)

tmp <- FeatureMatchAnalyzer(look2)
tmp
summary(tmp)
plot(tmp)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Perturbed ICP Cases", "pert000", "pert004"))

look <- convthresh(hold, smoothpar=10.5)
look2 <- centmatch(look)
tmp <- FeatureMatchAnalyzer(look2)
summary(tmp)
plot(tmp)
```

```
## End(Not run)
```

---

 FeatureProps

*Single Feature Properties*


---

### Description

Calculate properties for an identified feature.

### Usage

```
FeatureProps(x, Im = NULL, which.props = c("centroid", "area", "axis", "intensity"),
  areafac = 1, q = c(0.25, 0.9), loc = NULL, ...)
```

### Arguments

x	object of class “owin” containing a binary image matrix defining the feature.
Im	Matrix giving the original values of the field from which the feature was extracted. Only needed if the feature intensity is desired.
which.props	character vector giving one or more of “centroid”, “area”, “axis” and “intensity”. If “axis” is given, then a call to FeatureAxis is made.
areafac	numeric, in determining the lengths of the axes, they are multiplied by a factor of fac (e.g., if the grid points are k by k km each, then one could set this to k so that the resulting lengths are in terms of km rather than grid points.
q	numeric vector of values between 0 and 1 inclusive giving the quantiles for determining the intensity of the feature.
loc	optional argument giving a two-column matrix of grid locations for finding the centroid. If NULL, indices based on the dimension of x are used.
...	additional arguments to FeatureAxis.

### Details

This function takes an owin image and returns several property values for that image, including: centroid, spatial area, major and minor axis angle/length, as well as the overall intensity of the field (cf., Davis et al., 2006a, b).

### Value

list object with components depending on the which.props argument. One or more of:

centroid	list with components x and y giving the centroid of the object.
area	numeric giving the area of the feature.
axis	list object of class FeatureAxis as returned by the same-named function.

**Author(s)**

Eric Gilleland

**References**

Davis, C. A., Brown, B. G. and Bullock, R. G. (2006a) Object-based verification of precipitation forecasts, Part I: Methodology and application to mesoscale rain areas. *Mon. Wea. Rev.*, **134**, 1772–1784.

Davis, C. A., Brown, B. G. and Bullock, R. G. (2006b) Object-based verification of precipitation forecasts, Part II: Application to convective rain systems. *Mon. Wea. Rev.*, **134**, 1785–1795.

**See Also**

[FeatureAxis](#), [owin](#), [convexhull](#), [sma](#), [as.psp](#), [angles.psp](#), [rotate.owin](#), [rotate.psp](#), [bounding.box](#), [midpoints.psp](#), [lengths.psp](#), [inline](#), [clip.inline](#), [deltamm](#), [convthresh](#), [disjoiner](#), [connected](#), [tiles](#), [tess](#), [solutionset](#)

**Examples**

```
data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx

look <- disk2dsmooth(x,5)
u <- quantile(look,0.99)
sIx <- matrix(0, 100, 100)
sIx[ look > u] <- 1
look2 <- disjoiner(sIx)[[1]]
look2 <- flipxy(look2)

FeatureProps(look2,
  which.props=c("centroid", "area", "axis"))
```

---

FeatureTable

*Feature-Based Contingency Table*


---

**Description**

Create a feature-based contingency table from a matched object and calculate some summary scores with their standard errors.

**Usage**

```
FeatureTable(x, fudge = 1e-08, hits.random = NULL, correct.negatives = NULL, fA = 0.05)

## S3 method for class 'FeatureTable'
ci(x, alpha = 0.05, ...)
```



```
## S3 method for class 'FeatureTable'
print(x, ...)

## S3 method for class 'FeatureTable'
summary(object, ...)
```

### Arguments

x	FeatureTable: An object of class “matched” (e.g., from del tamm or centmatch. print: An object of class “FeatureTable”.
object	An object of class “FeatureTable”.
fudge	value added to denominators of scores to ensure no division by zero. Set to zero if this practice is not desired.
hits.random	If a different value for random hits in the calculation of GSS than provided is desired, it can be given here. Default uses Eq (3) from Davis et al (2009).
correct.negatives	If a different value for correct negatives than provided is desired, it can be given here. Default uses Eq (4) from Davis et al (2009).
fA	numeric between zero and 1 giving the fraction of area occupied for the purpose of matching as in Davis et al (2009).
alpha	numeric between zero and one giving the $(1 - \alpha) * 100$ percent confidence level.
...	Additional arguments to ci.

### Details

This function takes an object of class “matched” and calculates a contingency table based on matched and unmatched objects. If no value for correct negatives is given, then it will also determine them based on Eq (3) from Davis et al (2009). The following contingency table scores and their standard errors (based on their usual traditional version) are returned. It should be noted that the standard errors may not be entirely meaningful because they do not capture the uncertainty associated with identifying, merging and matching features within the fields. Nevertheless, they are calculated here for investigative purposes. Note that hits are determined by number of matched objects, which for some matching algorithms can mean that features are matched more than once (e.g., if using centmatch). In essence, this fact may artificially increase the number of hits. On the other hand, situations exist where such handling may be more appropriate than not having duplicate matches.

hits are determined by the total number of matched features.

false alarms are the total number of unmatched forecast features.

misses are the total number of unmatched observed features.

correct negatives are less obviously defined. If the user does not supply a value, then these are calculated according to Eq (4) in Davis et al (2009).

GSS: Gilbert skill score (aka Equitable Threat Score) based on Eq (2) of Davis et al (2009).

POD: probability of detecting an event (aka the hit rate).

false alarm rate: (aka probability of false detection) is the ratio of false alarms to the number of false alarms and correct negatives.

FAR: the false alarm ratio is the ratio of false alarms to the total forecast events (in this case, the total number of forecast features in the field).

HSS: Heidke skill score

The `print` method function simply calls `summary`, which prints the feature-based contingency table in addition to calling `ci`. The confidence intervals are based on the normal approximation method using the estimated standard errors, which themselves are suspicious. In any case, the intervals can give a feel for some of the uncertainty associated with the scores, but should not be considered as solid.

### Value

A list with inherited attributes from `x` and components:

<code>estimates</code>	named numeric vector giving the estimated scores.
<code>se</code>	named numeric vector giving the estimated standard errors of the scores.
<code>feature.contingency.table</code>	named numeric vector giving the feature-based contingency table.

### Note

Standard error estimates are based on the univariate equivalent formulations, which do not account for uncertainties introduced in the feature identification, merging/clustering and matching. They should not be considered as legitimate, and resulting confidence intervals should be mistrusted.

### Author(s)

Eric Gilleland

### References

Davis, C. A., Brown, B. G., Bullock, R. G. and Halley Gotway, J. (2009) The Method for Object-based Diagnostic Evaluation (MODE) applied to numerical forecasts from the 2005 NSSL/SPC Spring Program. *Wea. Forecasting*, **24**, 1252–1267, DOI: 10.1175/2009WAF2222241.1.

### See Also

To identify features in the fields: [convthresh](#), [threshfac](#), [threshsizer](#)

To match (and merge) features: [centmatch](#), [deltamm](#)

### Examples

```
##
## See help file for 'deltamm' for examples.
##
```

**Description**

Functions for calculating the Forecast Quality Index (FQI) and its components.

**Usage**

```
FQI(object, surr = NULL, k = 4, time.point = 1, model = 1, ...)
UIQI(X, Xhat, ...)
ampstats(X, Xhat, only.nonzero = FALSE)

## S3 method for class 'fqi'
print(x, ...)

## S3 method for class 'fqi'
summary(object, ...)
```

**Arguments**

<code>object</code>	list object of class “SpatialVx”. In the case of the summary method, object is the list object returned by FQI.
<code>X, Xhat</code>	numeric matrices giving the fields for the verification set.
<code>x</code>	list object of class “fqi” as returned by FQI.
<code>surr</code>	three-dimensional array containing surrogate fields for X, e.g. as returned by <code>surrogater2d</code> . If NULL, these will be calculated using <code>surrogater2d</code> .
<code>only.nonzero</code>	logical, should the means and variances of only the non-zero values of the fields be calculated (if so, the covariance is returned as NA)?
<code>k</code>	numeric vector for use with the partial Hausdorff distance. For k that are whole numerics or integers $\geq 1$ , then the k-th highest value is returned by <code>locmeasures2d</code> . If $0 \leq k < 1$ , then the corresponding quantile is returned.
<code>time.point</code>	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>...</code>	In the case of FQI, additional arguments to <code>surrogater2d</code> . Only used if <code>surr</code> is NULL. In the case of UIQI, additional arguments to <code>ampstats</code> . In the case of <code>summary.fqi</code> , these are not used.

## Details

The FQI was proposed as a spatial verification metric (a true metric in the mathematical sense) by Venugopal et al. (2005) to combine amplitude and displacement error information in a single summary statistic. It is given by

$$\text{FQI} = (\text{PHD}_k(X, \hat{X}) / \text{mean}(\text{PHD}_k(X, \text{surr}_i); i \text{ in } 1 \text{ to number of surrogates})) / (\text{brightness} * \text{distortion})$$

where the numerator is a normalized partial Hausdorff distance (see help file for `locperf`), brightness (also called bias) is given by  $2 * (\mu_1 * \mu_2) / (\mu_1^2 + \mu_2^2)$ , where  $\mu_1$  ( $\mu_2$ ) is the mean value of  $X$  ( $\hat{X}$ ), and the distortion term is given by  $2 * (\sigma_1 * \sigma_2) / (\sigma_1^2 + \sigma_2^2)$ , where  $\sigma_1^2$  ( $\sigma_2^2$ ) is the variance of  $X$  ( $\hat{X}$ ) values. The denominator is a modified UIQI (Universal Image Quality Index; Wang and Bovik, 2002), which itself is given by

$$\text{UIQI} = \text{cor}(X, \hat{X}) * \text{brightness} * \text{distortion}.$$

Note that if `only.nonzero` is TRUE in the call to UIQI, then the modified UIQI used in the FQI formulation is returned (i.e., without multiplying by the correlation term).

The `print` method so far just calls the `summary` method.

## Value

FQI returns a list with with the following components:

<code>phd.norm</code>	matrix of normalized partial Hausdorff distances for each value of $k$ (rows) and each threshold (columns).
<code>uiqi.norm</code>	numeric vector of modified UIQI values for each threshold.
<code>fqi</code>	matrix of FQI values for each value of $k$ (rows) and each threshold (columns).

It will also have the same attributes as the “SpatialVx” object with additional attributes defining the arguments specific to parameters used by the function.

UIQI returns a list with components:

<code>data.name</code>	character vector giving the names of the two fields.
<code>cor</code>	single numeric giving the correlation between the two fields.
<code>brightness.bias</code>	single numeric giving the brightness (bias) value.
<code>distortion.variability</code>	single numeric giving the distortion (variability) value.
<code>UIQI</code>	single numeric giving the UIQI (or modified UIQI if <code>only.nonzero</code> is set to TRUE) value.

`ampstats` returns a list object with components:

<code>mean.fcst, mean.vx</code>	single numerics giving the mean of $\hat{X}$ and $X$ , resp.
<code>var.fcst, var.vx</code>	single numerics giving the variance of $\hat{X}$ and $X$ , resp.
<code>cov</code>	single numeric giving the covariance between $\hat{X}$ and $X$ (if <code>only.nonzero</code> is TRUE, this will be NA).

**Author(s)**

Eric Gilleland

**References**

Venugopal, V., Basu, S. and Foufoula-Georgiou, E. (2005) A new metric for comparing precipitation patterns with an application to ensemble forecasts. *J. Geophys. Res.*, **110**, D08111, 11 pp., doi:10.1029/2004JD005395.

Wang, Z. and Bovik, A. C. (2002) A universal image quality index. *IEEE Signal Process. Lett.*, **9**, 81–84.

**See Also**

[locperf](#), [surrogater2d](#), [locmeasures2d](#)

**Examples**

```
data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx
xhat <- ExampleSpatialVxSet$fcst

# Now, find surrogates of the simulated field.
z <- surrogater2d(x, zero.down=TRUE, n=10)

u <- cbind( quantile( c(x), c(0.75, 0.9)),
            quantile( c(xhat), c(0.75, 0.9)))
hold <- make.SpatialVx(x, xhat, thresholds=u,
                      field.type="Example", units="none",
                      data.name=c("ExampleSpatialVxSet", "X", "Xhat"))
FQI(hold, surr=z, k=c(4, 0.75))
```

---

fss2dfun

*Various Verification Statistics on Possibly Neighborhood-Smoothed Fields.*


---

**Description**

Functions to calculate various verification statistics on possibly neighborhood smoothed fields. Used by hoods2d, but can be called on their own.

**Usage**

```
fss2dfun(sPy, sPx, subset = NULL, verbose = FALSE)
```

```
fuzzyjoint2dfun(sPy, sPx, subset = NULL)
```

```
MinCvg2dfun(sIy, sIx, subset = NULL)
```

```
multicon2dfun(sIy, Ix, subset = NULL)
```

```
pragmatic2dfun(sPy, Ix, mIx = NULL, subset = NULL)
```

```
upscale2dfun(sYy, sYx, threshold = NULL, which.stats = c("rmse", "bias", "ts", "ets"),
             subset = NULL)
```

### Arguments

sPy	n by m matrix giving a smoothed binary forecast field.
sPx	n by m matrix giving a smoothed binary observed field.
sIy	n by m matrix giving a binary forecast field.
sIx	n by m matrix giving a binary observed field (the s indicates that the binary field is obtained from a smoothed field).
Ix	n by m matrix giving a binary observed field.
mIx	(optional) single numeric giving the base rate. If NULL, this will be calculated by the function. Simply a computation saving step if this has already been calculated.
sYy	n by m matrix giving a smoothed forecast field.
sYx	n by m matrix giving a smoothed observed field.
threshold	(optional) numeric vector of length 2 giving the threshold over which to calculate the verification statistics: bias, ts and ets. If NULL, only the rmse will be calculated.
which.stats	character vector naming which statistic(s) should be calculated for upscale2dfun.
subset	(optional) numeric indicating over which points the summary scores should be calculated. If NULL, all of the points are used.
verbose	logical, should progress information be printed to the screen?

### Details

These are modular functions that calculate the neighborhood smoothing method statistics in spatial forecast verification (see, e.g., Ebert, 2008, 2009; Gilleland et al., 2009, 2010; Roberts and Lean, 2008). These functions take fields that have already had the neighborhood smoothing applied (e.g., using `kernel2d`) when appropriate. They are called by `hoods2d`, so need not be called by the user, but they can be.

### Value

In the case of `fss2dfun`, a single numeric giving the FSS value is returned. In the other cases, list objects are returned with one or more of the following components, depending on the particular function.

fuzzy	<code>fuzzyjoint2dfun</code> returns a list with this list as one component. The list component <code>fuzzy</code> has the components: <code>pod</code> , <code>far</code> and <code>ets</code> .
-------	---

joint	fuzzyjoint2dfun returns a list with this list as one component. The list component joint has the components: pod, far and ets.
pod	numeric giving the probability of detection, or hit rate.
far	numeric giving the false alarm ratio.
ets	numeric giving the equitable threat score, or Gilbert Skill Score.
f	numeric giving the false alarm rate.
hk	numeric giving the Hanssen-Kuipers statistic.
bs	Brier Score
bss	Brier Skill Score. The pragmatic2dfun returns the bs and bss values. The Brier Skill Score here uses the mean square error between the base rate and the Ix field as the reference forecast.
ts	numeric giving the threat score.
bias	numeric giving the frequency bias.

### Author(s)

Eric Gilleland

### References

- Ebert, E. E. (2008) Fuzzy verification of high resolution gridded forecasts: A review and proposed framework. *Meteorol. Appl.*, **15**, 51–64. doi:10.1002/met.25 Available at <http://www.ecmwf.int/newsevents/meetings/workshops/2007/jwgv/METspecialissueemail.pdf>
- Ebert, E. E. (2009) Neighborhood verification: A strategy for rewarding close forecasts. *Wea. Forecasting*, **24**, 1498–1510, doi:10.1175/2009WAF2222251.1.
- Gilleland, E., Ahijevych, D., Brown, B. G., Casati, B. and Ebert, E. E. (2009) Intercomparison of Spatial Forecast Verification Methods. *Wea. Forecasting*, **24**, 1416–1430, doi:10.1175/2009WAF2222269.1.
- Gilleland, E., Ahijevych, D. A., Brown, B. G. and Ebert, E. E. (2010) Verifying Forecasts Spatially. *Bull. Amer. Meteor. Soc.*, October, 1365–1373.
- Roberts, N. M. and Lean, H. W. (2008) Scale-selective verification of rainfall accumulations from high-resolution forecasts of convective events. *Mon. Wea. Rev.*, **136**, 78–97. doi:10.1175/2007MWR2123.1.

### See Also

[hoods2d, kernel2dsmooth, vxstats](#)

### Examples

```
x <- y <- matrix( 0, 100, 100)
x[ sample(1:100, 10), sample(1:100, 10)] <- 1
y[ sample(1:100, 20), sample(1:100, 20)] <- 1
Px <- kernel2dsmooth( x, kernel.type="boxcar", n=9, xdim=c(100, 100))
Py <- kernel2dsmooth( y, kernel.type="boxcar", n=9, xdim=c(100, 100))
par( mfrow=c(2,2))
image( x, col=c("grey", "darkblue"), main="Simulated Observed Events")
image( y, col=c("grey", "darkblue"), main="Simulated Forecast Events")
```

```

image( Px, col=c("grey", tim.colors(256)), main="Forecast Event Frequencies (9 nearest neighbors)")
image( Py, col=c("grey", tim.colors(256)), main="Smoothed Observed Events (9 nearest neighbors)")
fss2dfun( Py, Px)

## Not run:
data(pert004)
data(pert000)
fbin <- obin <- matrix(0, 601, 501)
fbin[ pert004 >= 12] <- 1
obin[ pert000 >= 12] <- 1
Pf <- kernel2dsmooth( fbin, kernel.type="boxcar", n=33, xdim=c(601, 501))
Po <- kernel2dsmooth( obin, kernel.type="boxcar", n=33, xdim=c(601, 501))
fss2dfun(Pf, Po)
fuzzyjoint2dfun(Pf, Po)
Pe <- 1/(33^2) # At least one event in the neighborhood.
MinCvg2dfun(Pf >= Pe, Po >= Pe)
multicon2dfun(Pf >= Pe, obin)
pragmatic2dfun(Pf, obin, mIx=mean( obin, na.rm=TRUE))
Sf <- kernel2dsmooth( pert004, kernel.type="boxcar", n=33, xdim=c(601, 501))
So <- kernel2dsmooth( pert000, kernel.type="boxcar", n=33, xdim=c(601, 501))
upscale2dfun( Sf, So, threshold=12)

## End(Not run)

```

---

fss2dPlot

---

*Create Several Graphics for List Objects Returned from hoods2d*


---

## Description

Creates several graphics for list objects returned from hoods2d. Mostly quilt and matrix plots for displaying results of smoothing fields over different neighborhood lengths and thresholds.

## Usage

```
fss2dPlot(x, ..., set.pw = FALSE, add.text = FALSE)
```

```
upscale2dPlot(object, args, ..., set.pw = FALSE, type = c("all",
  "gss", "ts", "bias", "rmse"))
```

## Arguments

- |        |   |
|--------|---|
| x      | list object with components fss, fss.random and fss.uniform. Effectively, it does the same thing as hoods2dPlot, but adds the fss.random and fss.uniform horizontal lines to the matrix plot. |
| object | list object with named components: rmse (numeric vector), ets, ts and bias all matrices whose rows represent neighborhood lengths, and whose columns represent thresholds.                    |
| args   | list object passed to hoods2dPlot, see its help file for more details.  |



set.pw	logical, should the plot window panels be set by the function?
add.text	logical, if TRUE, FSS values will be added to the quilt plot as text (in addition to the color).
type	character string stating which plots to make (default is "all").
...	Optional arguments to image and image.plot for fss2dPlot, and optional arguments to hoods2dPlot for upscale2dPlot

### Details

makes quilt and matrix plots for output from hoods2d.

### Value

No value is returned. A series of plots are created. It may be useful to use this function in conjunction with pdf in order to view all of the plots. See the help file for hoods2dPlot to plot individual results.

### Author(s)

Eric Gilleland

### See Also

[hoods2dPlot](#), [matplot](#), [image](#), [image.plot](#), [hoods2d](#), [pdf](#)

### Examples

```
##
## This is effectively an internal function, so the example is commented out
## in order for R's check to run faster.
##
## Not run:
data(geom001)
data(geom000)
data(ICPg240Locs)
hold <- make.SpatialVx( geom000, geom001, thresholds=c(0.01,50.01),
  loc=ICPg240Locs, map = TRUE, projection = TRUE, loc.byrow = TRUE,
  units="mm/h", data.name = c("Geometric", "observation", "case 1"))

look <- hoods2d(hold, levels=c(1, 3, 5, 33, 65),
  verbose=TRUE)
plot( look)

## End(Not run)
```

---

GeoBoxPlot

*Geographic Box Plot*

---

### Description

Make a geographic box plot as detailed in Willmott et al. (2007).

### Usage

```
GeoBoxPlot(x, areas, ...)
```

### Arguments

x	numeric giving the values to be box-plotted.
areas	numeric of same length as x giving the associated areas for each value.
...	optional arguments to the <code>boxplot</code> function of R. The argument <code>plot</code> is not allowed.

### Details

This function makes the geographic box plots described in Willmott et al. (2007) that calculates the five statistics in such a way as to account for the associated areas (e.g., over a grid where each grid box may have differing areas).

Missing values are not handled, and ideally should be handled before calling this routine.

In future, this function may allow other options for x than currently, but for now, only numeric vectors are allowed.

### Value

List with the same components as returned by `boxplot`.

### Author(s)

Eric Gilleland

### References

Willmott, C. J., Robeson, S. M. and Matsuura, K. (2007) Geographic box plots. *Physical Geography*, **28**, 331–344, doi:10.2747/0272-3646.28.4.331.

### See Also

[boxplot](#)

**Examples**

```
##
## Reproduce the boxplots of Fig. 1 in Willmott et al. (2007).
##
x <- c(4,9,1,3,10,6,7)
a <- c(rep(1,4),2,1,3)
boxplot( x, at=1, xlim=c(0,3))
GeoBoxPlot(x, a, at=2, add=TRUE)
axis( 1, at=c(1,2), labels=c("Traditional", "Geographic"))
```

GFSNAMfcstEx

*Example Verification Set***Description**

Example verification set of accumulated precipitation (mm) with 361 time points in addition to 2352 spatial locations on a grid. Taken from a real, but unknown, weather model and observation analysis (one of GFS or NAM). Accumulation is either 3-h or 24-h.

**Usage**

```
data(GFSNAMfcstEx)
data(GFSNAMobsEx)
data(GFSNAMlocEx)
```

**Format**

The format is: num [1:2352, 1:361] 0 0 0 0 ...

The format is: num [1:2352, 1:361] 0 0 0 0 ...

The format is: A data frame with 2352 observations on the following 2 variables.

Lat a numeric vector of latitude coordinates for GFS/NAM example verification set.

Lon a numeric vector of longitude coordinates for GFS/NAM example verification set.

**Details**

Example verification set with 2352 spatial locations over the United States, and 361 time points. For both the forecast (GFSNAMfcstEx) and verification (GFSNAMobsEx), these are numeric matrices whose rows represent time, and columns represent space. The associated lon/lat coordinates are provided by GFSNAMlocEx (2352 by 2 data frame with named components giving the lon and lat values).

Note that the available spatial locations are a subset of the original 70 X 100 60-km grid where each time point had no missing observations. This example set is included with the package simply to demonstrate some functionality that involves both space and time; though this is mostly a spatial-only package.

**Examples**

```

data(GFSNAMfcstEx)
data(GFSNAMobsEx)
data(GFSNAMlocEx)

x <- colMeans(GFSNAMfcstEx, na.rm=TRUE)
y <- colMeans(GFSNAMobsEx, na.rm=TRUE)
look <- as.image(x - y, x=GFSNAMlocEx)
image.plot(look)

```

gmm2d

*2-d Gaussian Mixture Models Verification***Description**

Use 2-d Gaussian Mixture Models (GMM) to assess forecast performance.

**Usage**

```

gmm2d(x, ...)

## Default S3 method:
gmm2d(x, ..., xhat, K = 3, gamma = 1, threshold = NULL,
      initFUN = "initGMM", verbose = FALSE)

## S3 method for class 'SpatialVx'
gmm2d(x, ..., time.point = 1, model = 1, K = 3, gamma = 1,
      threshold = NULL, initFUN = "initGMM", verbose = FALSE)

## S3 method for class 'gmm2d'
plot(x, ..., col = c("gray", tim.colors(64)),
     xlim = c(0, 1), horizontal = TRUE)

## S3 method for class 'gmm2d'
predict(object, ..., x)

## S3 method for class 'gmm2d'
print(x, ...)

## S3 method for class 'gmm2d'
summary(object, ...)

```

**Arguments**

`x, xhat` Default: `m` by `n` numeric matrices giving the verification and forecast fields, resp.  
`gmm2d.SpatialVx`: object of class "SpatialVx".

	plot and print: object returned by gmm2d.
	predict: k by 2 matrix of lon/lat coordinates on which to predict the model.
object	output from gmm2d.
K	single numeric giving the number of mixture components to use.
gamma	Value of the gamma parameter from Eq (11) of Lakshmanan and Kain (2010). This affects the number of times a location is repeated.
threshold	numeric giving a threshold over which (and including) the GMM is to be fit (zero-valued grid points are not included in the estimation here for speed). If NULL, no thresholding is applied.
initFUN	character naming a function to provide initial estimates for the GMM. Must take an m by n matrix as input, and return a dataframe a component called <code>ind</code> that is a vector indicating the order of the rows for which the first K will be used, a third column giving the x-coordinates of the initial estimate of the mean for the x direction, fourth column giving the initial estimate for the mean of the y-direction, and fifth and sixth columns giving initial estimates for the standard deviations of the x- and y-directions. The default identifies all connected components using the <code>disjoiner</code> function, then uses their centroids as the initial estimates of the means, and their axes as initial estimates for the standard deviations. The <code>ind</code> component gives the order of the object areas from largest to smallest so that the K largest objects are used to provide initial estimates. Note that this differs from the initial estimates in Lakshmanan and Kain (2010) where they break the field into different areas first.
verbose	logical, should progress information be printed to the screen?
time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
col, zlim, horizontal	optional arguments to <b>fields</b> function(s) <code>poly.image</code> , <code>image.plot</code> .
...	In the case of <code>gmm2d</code> : optional arguments to <code>initFUN</code> . In the case of <code>plot</code> : not used. In the case of <code>predict</code> : N by 2 matrix of grid point locations on which to predict the probability from the 2-d GMM model. In the case of <code>summary</code> : this can include the arguments: <code>silent</code> , logical stating whether to print summaries to the screen (FALSE) or not (TRUE), <code>e1</code> , <code>e2</code> , ..., <code>e5</code> , giving alternative weights in calculating the overall error (Eq 15 in Lakshmanan and Kain, 2010, but see details section below).

## Details

These functions carry out the spatial verification approach described in Lakshmanan and Kain (2010), which fits a 2-d Gaussian Mixture Model (GMM) to the locations for each field in the verification set, and makes comparisons using the estimated parameters. In fitting the GMMs, first an initial estimate is provided by using the `initFUN` argument, which is a function. The default function is relatively fast (it might seem slow, but for what it does, it is very fast!), but is typically the slowest part of the process. Although the EM algorithm is a fairly computationally intensive procedure, acceleration algorithms are employed (via the `turboem` function of the `turboEM` package) so that once initial estimates are found, the procedure is very fast.

Because the fit is to the locations only, Lakshmanan and Kain (2010) suggest two ways to incorporate intensity information. The first is to repeat points with higher intensities, and the second is to multiply the results by the total intensities over the fields. The points are repeated  $M$  times according to the formula (Eq 11 in Lakshmanan and Kain, 2010):

$$M = 1 + \text{gamma} * \text{round}(\text{CFD}(I_{xy})/\text{frequency}(I_{\text{MODE}})),$$

where CFD is the cumulative \*frequency\* distribution (here estimated from the histogram using the 'hist' function),  $I_{xy}$  is intensity at grid point  $(x,y)$ ,  $I_{\text{MODE}}$  is the mode of intensity values, and gamma is a user-supplied parameter controlling how much to repeat points where higher numbers will result in larger repetitions of high intensity values.

The function `gmm2d` fits the 2-d GMM to both fields, `plot.gmm2d` first uses `predict.gmm2d` to obtain probabilities for each grid point, and then makes a plot similar to those in Lakshmanan and Kain (2010) Figs. 3, 4 and 5, but giving the probabilities instead of the probabilities times  $A$ . Note that `predict.gmm2d` can be very slow to compute so that `plot.gmm2d` can also be very slow. Less effort was put into speeding these functions up because they are not necessary for obtaining results via the parameters. However, they can give the user an idea of how good the fit is.

The 2-d GMM is given by

$$G(x,y) = A * \text{sum}(\text{lambda} * f(x,y))$$

where  $\text{lambda}$  and  $f(x,y)$  are numeric vectors of length  $K$ ,  $\text{lambda}$  components describe the mixing, and  $f(x,y)$  is the bivariate normal distribution with mean  $(\mu_x, \mu_y)$  and covariance function. ' $A$ ' is the total sum of intensities over the field.

Comparisons between forecast and observed fields are carried out finally by the summary method function. In particular, the translation error

$$e_{tr} = \sqrt{(\mu_{xf} - \mu_{xo})^2 + (\mu_{yf} - \mu_{yo})^2},$$

where  $f$  means forecast and  $o$  verification fields, resp., and  $\mu_x$  is the mean in the  $x$ -direction, and  $\mu_y$  in the  $y$ -direction. The rotation error is given by

$$e_{rot} = (180/\pi) * \text{acos}(\text{theta}),$$

where  $\text{theta}$  is the dot product between the first eigenvectors of the covariance matrices for the verification and forecast fields. The scaling error is given by

$$e_{sc} = A_f * \text{lambda}_f / A_o * \text{lambda}_o,$$

where  $\text{lambda}$  is the mixture component and  $A_f/A_o$  is the forecast/observed total intensity.

The overall error (Eq 15 of Lakshmanana and Kain, 2010) is given by

$$e_{overall} = e_1 * \min(e_{tr}/e_2, 1) + e_3 * \min(e_{rot}, 180 - e_{rot})/e_4 + e_5 * (\max(e_{sc}, 1/e_{sc}) - 1),$$

where  $e_1$  to  $e_5$  can be supplied by the user, but the defaults are those given by Lakshmanan and Kain (2010). Namely,  $e_1 = 0.3$ ,  $e_2 = 100$ ,  $e_3 = 0.2$ ,  $e_4 = 90$ , and  $e_5 = 0.5$ .

## Value

For `gmm2d`, a list object of class "gmm2d" is returned with components:

<code>fitX, fitY</code>	list objects returned by the <code>turboem</code> function from the <b>turboEM</b> package that describe the EM estimates of the 2-d GMM parameters for the verification and forecast fields, resp.
-------------------------	---

<code>initX, initY</code>	numeric vectors giving the initial estimates used in the EM algorithm for the verification and forecast fields, resp. The first $2 \cdot K$ values are the initial mean estimates for the x- and y- directions, resp. The next $4 \cdot K$ values are the initial estimates of the covariances (note that the cross-covariance terms are zero regardless of initialization function employed (maybe this will be improved in the future)). The final $K$ values are the initial estimates for lambda.
<code>sX, sY</code>	$N$ by 2 matrix giving the repeated coordinates calculated per $M$ as described in the details section for the verification and forecast fields, resp.
<code>k</code>	single numeric giving the value of $K$
<code>Ax, Ay</code>	single numerics giving the value of $A$ (the total sum of intensities over the field) for the verification and forecast fields, resp.

For `plot.gmm2d` no value is returned. A plot is created.

For `predict.gmm2d`, a list is returned with components:

<code>predX, predY</code>	numeric vectors giving the GMM predicted values for the verification and forecast fields, resp.
---------------------------	---

For `summary.gmm2d`, a list is returned invisibly (if `silent` is `FALSE`, information is printed to the screen) with components:

<code>meanX, meanY</code>	Estimated mean vectors for each GMM component for the verification and forecast fields, resp.
<code>covX, covY</code>	Estimated covariances for each GMM component for the verification and forecast fields, resp.
<code>lambdasX, lambdasY</code>	Estimated mixture components for each GMM component for the verification and forecast fields, resp.
<code>e.tr, e.rot, e.sc, e.overall</code>	$K$ by $K$ matrices giving the errors between each GMM component in the verification field (rows) to each GMM component in the forecast field (columns). The errors are: translation ( <code>e.tr</code> ), rotation ( <code>e.rot</code> ), scaling ( <code>e.sc</code> ), and overall ( <code>e.overall</code> ).

### Author(s)

Eric Gilleland

### References

Lakshmanan, V. and Kain, J. S. (2010) A Gaussian Mixture Model Approach to Forecast Verification. *Wea. Forecasting*, **25** (3), 908–920.

### See Also

[turboem](#), [disjoiner](#), [connected](#)

**Examples**

```
## Not run:
data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx
xhat <- ExampleSpatialVxSet$fcst

u <- min(quantile(c(x[x > 0]), probs = 0.75),
        quantile(c(xhat[xhat > 0]), probs = 0.75))

look <- gmm2d(x, xhat=xhat, threshold=u, verbose=TRUE)
summary(look)
plot(look)

## End(Not run)
## Not run:
# Alternative method to skin the cat.
hold <- make.SpatialVx(x, xhat, field.type="MV Gaussian w/ Exp. Cov.",
                      units="units", data.name=c("Example", "x", "xhat"))

look2 <- gmm2d(hold, threshold=u, verbose=TRUE)
summary(look2)
plot(look2)

data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004, loc=ICPg240Locs,
                      map=TRUE, projection=TRUE, loc.byrow = TRUE,
                      field.type="Precipitation", units="mm/h",
                      data.name=c("ICP Perturbed Cases", "pert000", "pert004"))

look <- gmm2d(hold, threshold=10, verbose=TRUE)
plot(look) # This will take a long time!
summary(look)

## End(Not run)
```

---

griddedVgram

*Variograms for a Gridded Verification Set*


---

**Description**

Find (and plot) variograms for each field in a gridded verification set.

**Usage**

```
griddedVgram(object, zero.in = TRUE, zero.out = TRUE, time.point = 1,
```



```

    model = 1, ...)

## S3 method for class 'griddedVgram'
plot(x, ..., set.pw = FALSE)

```

### Arguments

object	list object of class “SpatialVx” containing information on the verification set.
zero.in, zero.out	logical, should the variogram be calculated over the entire field (zero.in), and/or over only the non-zero values (zero.out)?
x	list object as returned by griddedVgram.
time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
set.pw	logical, should a panel of plots be determined and set by the function.
...	In the case of griddedVgram, these are optional arguments to the vgram.matrix function from package fields. In the case of plot.griddedVgram, these are optional arguments to plot.vgram.matrix, which in turn are optional arguments to image.plot.

### Details

Here, the terms semi-variogram and variogram are used interchangeably.

This is a simple wrapper function to vgram.matrix (entire field) from **fields** and/or variogram.matrix (non-zero grid points only) for finding the variogram between two gridded fields. It calls this function for each of two fields in a verification set. This function allows one to do the diagnostic analysis proposed in Marzban and Sangathe (2009).

### Value

A list object containing the entire list passed in by the object argument, and components:

```
Vx.cgram.matrix, Fcst.vgram.matrix
```

list objects as returned by vgram.matrix containing the variogram information for each field.

No value is returned by plot.griddedVgram, plots are created showing the empirical variogram (circles), along with directional empirical variograms (dots), and the variogram by direction (image plot).

### Author(s)

Eric Gilleland

### References

Marzban, C. and Sandgathe, S. (2009) Verification with variograms. *Wea. Forecasting*, **24** (4), 1102–1120, doi:10.1175/2009WAF2222122.1.

**See Also**

[vgram.matrix](#), [make.SpatialVx](#)

**Examples**

```
data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx
xhat <- ExampleSpatialVxSet$fcst

hold <- make.SpatialVx(x, xhat, field.type="contrived",
  units="none", data.name=c("Example", "x", "xhat"))

res <- griddedVgram(hold,R=8)
plot(res, set.pw=TRUE)

## Not run:
data(pert004)
data(pert000)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Perturbed ICP Cases", "pert000", "pert004"))

res <- griddedVgram(hold, R=8)
plot(res, set.pw=TRUE)

## End(Not run)
```

---

hiw

*Spatial Forecast Verification Shape Analysis*


---

**Description**

Shape analysis for spatial forecast verification (hiw is OE for shape; yields MnE hue).

**Usage**

```
hiw(x, simplify = 0, A = pi * c(0, 1/16, 1/8, 1/6, 1/4, 1/2, 9/16, 5/8, 2/3, 3/4),
  verbose = FALSE, ...)
```

## S3 method for class 'hiw'

```
distill(x, ...)
```

## S3 method for class 'hiw'

```
plot(x, ..., which = c("X", "Xhat"), ftr.num = 1, zoom = TRUE,
  seg.col = "darkblue")
```

```
## S3 method for class 'hiw'
print(x, ...)

## S3 method for class 'hiw'
summary(object, ..., silent = FALSE)
```

### Arguments

x,object	hiw: object of class “features”. distill, plot, summary: object of class “hiw”.
simplify	dmin argument in call to simplify.owin from <b>spatstat</b> . If 0 (default), then no call is made to simplify.owin.
A	numeric vector of angles for which to apply shape analysis. Note that this vector will be rounded to 6 digits. If values are less than that, might be prudent to add 1e-6 to them.
verbose	logical, should progress information be printed to the screen?
which	character string naming whether to plot a feature from the observation field (default) or the forecast field.
ftr.num	integer stating which feature number to plot.
zoom	logical, should the feature be plotted within its original domain, or a blow-up of the feature (default)?
seg.col	color for the line segments.
silent	logical, should the summary information be printed to the screen?
...	Not used by hiw, distill, summary. Optional arguments to plot.

### Details

This function is an attempt to approximate the technique described first in Micheas et al. (2007) and as modified in Lack et al. (2010). It will only find the centroids, rays extending from them to the boundaries, and the boundary points. Use `distill` to convert this output into an object readable by, for example, `procGPA` from package **shapes**.

First, identified features (which may be identified by any feature identification function that yields an object of class “features”) are taken, the centroid is found (the centroid is found via `centroid.owin` so that the x- and y- coordinates are flipped from what you might expect) and very long line segments are found radiating out in both directions from the center. They are then clipped by where they cross the boundaries of the features.

The **spatstat** package is used heavily by this function. In particular, the function `as.polygonal` is applied to the `owin` objects (possible after first calling `simplify.owin`). Line segments are created using the feature centroids, as found by `centroid.owin`, and the user-supplied angles, along with a very long length (equal to the domain size). Boundary crossings are found using `crossing.psp`, and new line segment patterns are created using the centroids and boundary crossing information (extra points along line segments are subsequently removed through a painstaking process, and `as.psp` is called again, and any missing line segments are subsequently accounted for, for later

calculations). Additionally, lengths of line segments are found via `lengths.psp`. Angles must also be re-determined and corresponded to the originally passed angles. Therefore, it is necessary to round the angles to 6 digits, or “equal” angles may not be considered equal, which will cause problems.

The `hiw` function merely does the above step, as well as finds the lengths of the resulting line segments. For non-convex objects, the longest line segment is returned, and if the boundary crossings do not lie on opposite sides of the centroid, then the negative of the shortest segment is returned for that particular value. Also returned are the mean, min and maximum intensities for each feature, as well as the final angles returned. It is possible to have missing values for some of these components.

The `summary` function computes `SSloc`, `SSavg`, `SSmin`, and `SSmax` between each pair of features between fields. `distill` may be used to create an object that can be further analyzed (for shape) using the **shapes** package.

While any feature identification function may be used, it is recommended to throw out small sized features as the results may be misleading (e.g., comparisons between features consisting of single points, etc.).

## Value

A list object of class “hiw” is returned with components the same as in the original “features” class object, as well as:

<code>radial.segments</code>	a list with components <code>X</code> and <code>Xhat</code> each giving lists of the “psp” class (i.e., line segment) object for each feature containing the radial segments from the feature centroids to the boundaries.
<code>centers</code>	list with components <code>X</code> and <code>Xhat</code> giving two-column matrices containing the x- and y- coordinate centroids for each feature (as determined by <code>centroid.owin</code> ).
<code>intensities</code>	list with components <code>X</code> and <code>Xhat</code> giving three-column matrices that contain the mean, min and max intensities for each feature.
<code>angles,lengths</code>	list with components <code>X</code> and <code>Xhat</code> each giving lists containing the lengths of the line segments and their respective angles. Missing values are possible here.

`distill` returns an array whose dimensions are the number of landmarks (i.e., boundary points) by two by the number of observed and forecast features. An attribute called “`field.identifier`” is also given that is a character vector containing repeated “`X`” and “`Xhat`” values identifying which of the third dimension are associated with the observed field (`X`) and those identified with the forecast field (`Xhat`). Note that missing values may be present, which may need to be dealt with (by the user) before using functions from the **shapes** package.

`summary invisibly` returns a list object with components:

<code>X,Xhat</code>	matrices whose rows represent features and whose columns give their centroids (note that <code>x</code> refers to the columns and <code>y</code> to the rows), as well as the average, min and max intensities.
<code>SS</code>	matrix with four rows and columns equal to the number of possible combinations of feature matchings between fields. Gives the sum of square translation/location error (i.e., squared centroid distance), as well as the average, min and max squared differences between each combination of features.

ind two-column matrix whose rows indicate the feature numbers from each field being compared; corresponding to the columns of SS above.

### Author(s)

Eric Gilleland

### References

Lack, S. A., Limpert, G. L. and Fox, N. I. (2010) An object-oriented multiscale verification scheme. *Wea. Forecasting*, **25**, 79–92.

Micheas, A. C., Fox, N. I., Lack, S. A., and Wikle, C. K. (2007) Cell identification and verification of QPF ensembles using shape analysis techniques. *J. Hydrology*, **343**, 105–116.

### See Also

To identify features and create objects of class “features”, see, for example: [convthresh](#), [threshfac](#), [threshsizer](#).

[centroid.owin](#), [as.psp](#), [psp](#), [crossing.psp](#), [lengths.psp](#), [angles.psp](#)

### Examples

```
data(geom000)
data(geom001)
data(geom004)
data(ICPg240Locs)

hold <- make.SpatialVx(geom000, geom001, thresholds=c(0.01,50.01),
  projection=TRUE, map=TRUE, loc=ICPg240Locs, loc.byrow = TRUE,
  field.type="Geometric Objects Pretending to be Precipitation",
  units="mm/h", data.name=c("ICP Geometric Cases", "geom000", "geom001"))

look <- threshsizer(hold, thresh = 2, Ncontig = 200)

look <- hiw(look)

distill.hiw(look)

# Actually, you just need to type:
# distill(look)

summary(look)

# Note: procGPA will not allow missing values.

par(mfrow=c(1,2))
plot(look)
plot(look, which = "Xhat")

## Not run:
```

```

hold <- make.SpatialVx(geom000, geom004, thresholds=c(0.01,50.01),
  projection=TRUE, map=TRUE, loc=ICPg240Locs, loc.byrow = TRUE,
  field.type="Geometric Objects Pretending to be Precipitation",
  units="mm/h", data.name=c("ICP Geometric Cases", "geom000", "geom004"))

look <- threshsizer(hold)

look <- hiw(look)

par(mfrow=c(1,2))
plot(look)
plot(look, which = "Xhat")

## End(Not run)

```

---

hoods2d

*Neighborhood Verification Statistics for a Gridded Verification Set.*


---

### Description

Calculates most of the various neighborhood verification statistics for a gridded verification set as reviewed in Ebert (2008).

### Usage

```

hoods2d(object, which.methods = c("mincvr", "multi.event",
  "fuzzy", "joint", "fss", "pragmatic"), time.point = 1, model = 1,
  Pe = NULL, levels = NULL, max.n = NULL, smooth.fun = "hoods2dsmooth",
  smooth.params = NULL, verbose = FALSE)

## S3 method for class 'hoods2d'
plot(x, ..., set.pw=FALSE, add.text = FALSE)

## S3 method for class 'hoods2d'
print(x, ...)

```

### Arguments

object	list object of class "SpatialVx".
which.methods	character vector giving the names of the methods. Default is for the entire list to be executed. See Details section for specific option information.
time.point	numeric or character indicating which time point from the "SpatialVx" verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
Pe	(optional) numeric vector of length $q \geq 1$ to be applied to the fields sPy and possibly sPx (see details section). If NULL, then it is taken to be the most relaxed requirement (i.e., that an event occurs at least once in a neighborhood) of $Pe=1/(nlen^2)$ , where nlen is the length of the neighborhood.

<code>levels</code>	numeric vector giving the successive values of the smoothing parameter. For example, for the default method, these are the neighborhood lengths over which the $levels^2$ nearest neighbors are averaged for each point. Values should make sense for the specific smoothing function. For example, for the default method, these should be odd integers.
<code>max.n</code>	(optional) single numeric giving the maximum neighborhood length to use. Only used if <code>levels</code> are NULL.
<code>smooth.fun</code>	character giving the name of a smoothing function to be applied. Default is an average over the $n^2$ nearest neighbors, where <code>n</code> is taken to be each value of the <code>levels</code> argument.
<code>smooth.params</code>	list object containing any optional arguments to <code>smooth.fun</code> . Use NULL if none.
<code>verbose</code>	logical, should progress information be printed to the screen? Will also give the amount of time (in hours, minutes, or seconds) that the function took to run.
<code>x</code>	list object output from <code>hoods2d</code> .
<code>set.pw</code>	logical or length 2 vector, should the function try to set plot window panels within a device? Generally, it is better to do this yourself, or use this function in conjunction with something like <code>pdf</code> to allow each plot to print to a separate page. If <code>set.pw</code> is a length 2 vector, then this is the vector that is used in the call to <code>mfrow</code> . Note that if <code>mfcol</code> is desired instead (or some other plot layout), then <code>set.pw</code> should be set to FALSE (default).
<code>add.text</code>	logical, should the text values of FSS be added to its quilt plot?
<code>...</code>	not used.

## Details

`hoods2d` uses an object of class “SpatialVx” that includes some information utilized by this function, including the thresholds to be used. The neighborhood methods (cf. Ebert 2008, 2009; Gilleland et al., 2009, 2010) apply a (kernel) smoothing filter (cf. Hastie and Tibshirani, 1990) to either the raw forecast (and possibly also the observed) field(s) or to the binary counterpart(s) determined by thresholding.

The specific smoothing filter applied for these methods could be of any type, but those described in Ebert (2008) are generally taken to be “neighborhood” filters. In some circles, this is referred to as a convolution filter with a boxcar kernel. Because the smoothing filter can be represented this way, it is possible to use the convolution theorem with the Fast Fourier Transform (FFT) to perform the neighborhood smoothing operation very quickly. The particular approach used here “zero pads” the field, and replaces all missing values with zero as well, which is also the approach proposed in Roberts and Lean (2008). If any missing values are introduced after the convolution, they are removed.

To simplify the notation for the descriptions of the specific methods employed here, the notation of Ebert (2008) is adopted. That is, if a method uses neighborhood smoothed observations (NO), then the neighborhood smoothed observed field is denoted  $\langle X \rangle_s$ , and the associated binary field, by  $\langle I_x \rangle_s$ . Otherwise, if the observation field is not smoothed (denoted by SO in Ebert, 2008), then simply  $X$  or  $I_x$  are used. Similarly, for the forecast field,  $\langle Y \rangle_s$  or  $\langle I_y \rangle_s$  are used for neighborhood smoothed forecast fields (NF). If it is the binary fields that are smoothed (e.g., the original fields are thresholded before smoothing), then the resulting fields are denoted  $\langle P_x \rangle_s$  and  $\langle P_y \rangle_s$ , resp.

Below, NO-NF indicates that a neighborhood smoothed observed field ( $\langle Y_x \rangle_s$ ,  $\langle I_x \rangle_s$ , or  $\langle P_x \rangle_s$ ) is compared with a neighborhood smoothed forecast field, and SO-NF indicates that the observed field is not smoothed.

Options for which.methods include:

“mincvr”: (NO-NF) The minimum coverage method compares  $\langle I_x \rangle_s$  and  $\langle I_y \rangle_s$  by thresholding the neighborhood smoothed fields  $\langle P_x \rangle_s$  and  $\langle P_y \rangle_s$  (i.e., smoothed versions of  $I_x$  and  $I_y$ ) to obtain  $\langle I_x \rangle_s$  and  $\langle I_y \rangle_s$ . Indicator fields  $\langle I_x \rangle_s$  and  $\langle I_y \rangle_s$  are created by thresholding  $\langle P_x \rangle_s$  and  $\langle P_y \rangle_s$  by frequency threshold  $P_e$  given by the obj argument. Scores calculated between  $\langle I_x \rangle_s$  and  $\langle I_y \rangle_s$  include: probability of detecting an event (pod, also known as the hit rate), false alarm ratio (far) and ets (cf. Ebert, 2008, 2009).

“multi.event”: (SO-NF) The Multi-event Contingency Table method compares the binary observed field  $I_x$  against the smoothed forecast indicator field,  $\langle I_y \rangle_s$ , which is determined similarly as for “mincvr” (i.e., using  $P_e$  as a threshold on  $\langle P_y \rangle_s$ ). The hit rate and false alarm rate (F) are calculated (cf. Atger, 2001).

“fuzzy”: (NO-NF) The fuzzy logic approach compares  $\langle P_x \rangle_s$  to  $\langle P_y \rangle_s$  by creating a new contingency table where hits =  $\sum_i \min(\langle P_x \rangle_{s_i}, \langle P_y \rangle_{s_i})$ , misses =  $\sum_i \min(\langle P_x \rangle_{s_i}, 1 - \langle P_y \rangle_{s_i})$ , false alarms =  $\sum_i \min(1 - \langle P_x \rangle_{s_i}, \langle P_y \rangle_{s_i})$ , and correct negatives =  $\sum_i \min(1 - \langle P_x \rangle_{s_i}, 1 - \langle P_y \rangle_{s_i})$  (cf. Ebert 2008).

“joint”: (NO-NF) Similar to “fuzzy” above, but hits =  $\sum_i \text{prod}(\langle P_x \rangle_{s_i}, \langle P_y \rangle_{s_i})$ , misses =  $\sum_i \text{prod}(\langle P_x \rangle_{s_i}, 1 - \langle P_y \rangle_{s_i})$ , false alarms =  $\sum_i \text{prod}(1 - \langle P_x \rangle_{s_i}, \langle P_y \rangle_{s_i})$ , and correct negatives =  $\sum_i \text{prod}(1 - \langle P_x \rangle_{s_i}, 1 - \langle P_y \rangle_{s_i})$  (cf. Ebert, 2008).

“fss”: (NO-NF) Compares  $\langle P_x \rangle_s$  and  $\langle P_y \rangle_s$  directly using a Fractions Brier and Fractions Skill Score (FBS and FSS, resp.), where FBS is the mean square difference between  $\langle P_x \rangle_s$  and  $\langle P_y \rangle_s$ , and the FSS is one minus the FBS divided by a reference MSE given by the sum of the sum of squares of  $\langle P_x \rangle_s$  and  $\langle P_y \rangle_s$  individually, divided by the total (cf. Roberts and Lean, 2008).

“pragmatic”: (SO-NF) Compares  $I_x$  with  $\langle P_y \rangle_s$ , calculating the Brier and Brier Skill Score (BS and BSS, resp.), where the reference forecast used for the BSS is taken to be the mean square error between the base rate and  $I_x$  (cf. Theis et al., 2005).

## Value

A list object of class “hoods2d” with components determined by the which.methods argument. Each component is itself a list object containing relevant components to the given method. For example, hit rate is abbreviated pod here, and if this is an output for a method, then there will be a component named pod (all lower case). The Gilbert Skill Score is abbreviated 'ets' (equitable threat score; again all lower case here). The list components will be some or all of the following.

mincvr	list with components: pod, far and ets
multi.event	list with components: pod, f and hk
fuzzy	list with components: pod, far and ets
joint	list with components: pod, far and ets
fss	list with components: fss, fss.uniform, fss.random
pragmatic	list with components: bs and bss

New attributes are added giving the values for some of the optional arguments: levels, max.n, smooth.fun, smooth.params and  $P_e$ .



**Note**

Thresholded fields are taken to be  $\geq$  the threshold.

**Author(s)**

Eric Gilleland

**References**

- Atger, F. (2001) Verification of intense precipitation forecasts from single models and ensemble prediction systems. *Nonlin. Proc. Geophys.*, **8**, 401–417.
- Ebert, E. E. (2008) Fuzzy verification of high resolution gridded forecasts: A review and proposed framework. *Meteorol. Appl.*, **15**, 51–64. doi:10.1002/met.25 Available at <http://www.ecmwf.int/newsevents/meetings/workshops/2007/jwgv/METspecialissueemail.pdf>
- Ebert, E. E. (2009) Neighborhood verification: A strategy for rewarding close forecasts. *Wea. Forecasting*, **24**, 1498–1510, doi:10.1175/2009WAF2222251.1.
- Gilleland, E., Ahijevych, D., Brown, B. G., Casati, B. and Ebert, E. E. (2009) Intercomparison of Spatial Forecast Verification Methods. *Wea. Forecasting*, **24**, 1416–1430, doi:10.1175/2009WAF2222269.1.
- Gilleland, E., Ahijevych, D. A., Brown, B. G. and Ebert, E. E. (2010) Verifying Forecasts Spatially. *Bull. Amer. Meteor. Soc.*, October, 1365–1373.
- Hastie, T. J. and Tibshirani, R. J. (1990) *Generalized Additive Models*. Chapman & Hall/CRC Monographs on Statistics and Applied Probability 43, 335pp.
- Roberts, N. M. and Lean, H. W. (2008) Scale-selective verification of rainfall accumulations from high-resolution forecasts of convective events. *Mon. Wea. Rev.*, **136**, 78–97. doi:10.1175/2007MWR2123.1.
- Theis, S. E., Hense, A. Damrath, U. (2005) Probabilistic precipitation forecasts from a deterministic model: A pragmatic approach. *Meteorol. Appl.*, **12**, 257–268.
- Yates, E., Anquetin, S. Ducrocq, V., Creutin, J.-D., Ricard, D. and Chancibault, K. (2006) Point and areal validation of forecast precipitation fields. *Meteorol. Appl.*, **13**, 1–20.
- Zepeda-Arce, J., Foufoula-Georgiou, E., Droegemeier, K. K. (2000) Space-time rainfall organization and its role in validating quantitative precipitation forecasts. *J. Geophys. Res.*, **105**(D8), 10,129–10,146.

**See Also**

[fft](#), [kernel2dsmooth](#), [plot.hoods2d](#), [vxstats](#)

**Examples**

```
x <- y <- matrix( 0, 50, 50)
x[ sample(1:50,10), sample(1:50,10)] <- rexp( 100, 0.25)
y[ sample(1:50,20), sample(1:50,20)] <- rexp( 400)
hold <- make.SpatialVx(x, y, thresholds=c(0.1, 0.5), field.type="Random Exp. Var.")
look <- hoods2d( hold, which.methods=c("multi.event", "fss"), levels=c(1, 3, 19))
look
plot(look)

## Not run:
```

```

data(UKobs6)
data(UKfcst6)
data(UKloc)

hold <- make.SpatialVx(UKobs6, UKfcst6, thresholds=c(0.01, 20.01),
  projection=TRUE, map=TRUE, loc=UKloc, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Nimrod", "Observations 6", "Forecast 6"))

hold
plot(hold)
hist(hold, col="darkblue")

look <- hoods2d(hold, which.methods=c("multi.event", "fss"),
  levels=c(1, 3, 5, 9, 17), verbose=TRUE)
plot(look)

data(geom001)
data(geom000)
data(ICPg240Locs)

hold <- make.SpatialVx(geom000, geom001, thresholds=c(0.01,50.01),
  projection=TRUE, map=TRUE, loc=ICPg240Locs, loc.byrow = TRUE,
  field.type="Geometric Objects Pretending to be Precipitation",
  units="mm/h", data.name=c("ICP Geometric Cases", "geom000", "geom001"))

look <- hoods2d(hold, levels=c(1, 3, 9, 17, 33, 65, 129, 257), verbose=TRUE)

plot( look) # Might want to use 'pdf' first.

data(pert004)
data(pert000)
hold <- make.SpatialVx(pert000, pert004, thresholds=c(1,10,50),
  projection=TRUE, map=TRUE, loc=ICPg240Locs, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert004"))

plot(hold)

look <- hoods2d(hold, levels=c(1, 3, 17, 33, 65, 129, 257), verbose=TRUE)
plot(look)

## End(Not run)

```

---

hoods2dPlot

*Quilt Plot and a Matrix Plot.*


---

### Description

Function to make a quilt plot and a matrix plot for a matrix whose rows represent neighborhood lengths, and whose columns represent different threshold choices.

**Usage**

```
hoods2dPlot(x, args, ...)
```

**Arguments**

<code>x</code>	l by q numeric matrix.
<code>args</code>	list object with components: <code>threshold</code> (numeric vector giving the threshold values), <code>qs</code> (optional numeric vector giving the quantiles used if the thresholds represent quantiles rather than hard values), <code>levels</code> (numeric giving the neighborhood lengths (in grid squares) used), <code>units</code> (optional character giving the units for the thresholds)
<code>...</code>	optional arguments to <code>image</code> and <code>image.plot</code> functions. May not include <code>xaxt</code> , <code>yaxt</code> , <code>lab</code> , <code>col</code> , or <code>legend.only</code>

**Details**

Used by `plot.hoods2d`, but can be useful for other functions. Generally, however, this is an internal function that should not be called by the user. However, it might be called instead of `plot.hoods2d` in order to make a subset of the available plots.

**Value**

No value is returned. A plot is created.

**Author(s)**

Eric Gilleland

**References**

Becker, R. A., Chambers, J. M. and Wilks, A. R. (1988) *The New S Language*. Wadsworth & Brooks/Cole.

**See Also**

[matplot](#), [image](#), [image.plot](#), [plot.hoods2d](#), [hoods2d](#)

**Examples**

```
x <- y <- matrix( 0, 50, 50)
x[ sample(1:50,10), sample(1:50,10)] <- rexp( 100, 0.25)
y[ sample(1:50,20), sample(1:50,20)] <- rexp( 400)
hold <- make.SpatialVx(x, y, thresholds=c(0.1, 0.5), field.type="random")
look <- hoods2d(hold, which.methods=c("multi.event", "fss"),
  levels=c(1, 3, 20))
hoods2dPlot( look$multi.event$hk, args=hold,
  main="Hanssen Kuipers Score (Multi-Event Cont. Table)")
## Not run:
data(geom001)
data(geom000)
```

```

data(ICPg240Locs)
hold <- make.SpatialVx(geom000, geom001, thresholds=c(0.01,50.01),
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Geometric ICP Test Cases", "geom000", "geom001"))
look <- hoods2d(hold, levels=c(1, 3, 5, 17, 33, 65), verbose=TRUE)
par(mfrow=c(1,2))
hoods2dPlot(look$pragmatic$bss, args=attributes(hold))

## End(Not run)

```

---

hump

*Simulated Forecast and Verification Fields*


---

### Description

Simulated forecast and verification fields for optical flow example

### Usage

```
data(hump)
```

### Format

The format is: List of 2 \$ initial: num [1:50, 1:50] 202 210 214 215 212 ... \$ final : num [1:50, 1:50] 244 252 257 258 257 ...

### Details

Although not identically the same as the data used in Fig. 1 of Marzban and Sandgathe (2010), these are forecast data simulated from the self-same distribution and perturbed in the same manner to get the observation. The component initial is the forecast and final is the observation.

The forecast is on a 50 X 50 grid simulated from a bivariate Gaussian with standard deviation of 11 and centered on the coordinate (10, 10). The observed field is the same as the forecast field, but shifted one grid length in each direction and has 60 added to it everywhere.

### References

Marzban, C. and Sandgathe, S. (2010) Optical flow for verification. *Wea. Forecasting*, **25**, 1479–1494, doi:10.1175/2010WAF2222351.1.

### Examples

```

data(hump)
str(hump)
## Not run:
initial <- hump$initial
final <- hump$final
look <- OF(final, initial, W=9, verbose=TRUE)

```

```
plot(look) # Compare with Fig. 1 in Marzban and Sandgathe (2010).
hist(look) # 2-d histogram.
plot(look, full=TRUE) # More plots.

## End(Not run)
```

interester

*Feature Interest*

### Description

Calculate interest maps for specific feature comparisons and compute the total interest, as well as median of maximum interest.

### Usage

```
interester(x, properties = c("cent.dist", "angle.diff", "area.ratio", "int.area",
  "bdelta", "haus", "ph", "mhd", "med", "msd", "fom", "minsep"),
  weights = c(0.24, 0.12, 0.17, 0.12, 0, 0, 0, 0, 0, 0, 0, 0.35),
  b1 = c(35, 30, 0, 0, 0.5, 35, 20, 20, 40, 120, 1, 40),
  b2 = c(100, 90, 0.8, 0.25, 85, 400, 200, 200, 200, 400, 0.25, 200),
  verbose = FALSE, ...)
```

```
## S3 method for class 'interester'
print(x, ...)
```

```
## S3 method for class 'interester'
summary(object, ...,
  min.interest = 0.8, long = TRUE, silent = FALSE)
```

### Arguments

x	interester: object of class “features” or “matched”. print: object of class “interester”.
object	object of class “interester”.
properties	character vector naming which properties from FeatureComps should be considered in the total interest.
weights	numeric of length equal to the length of properties. Weights equal to zero will result in the removal of those properties from properties so that the default computes only those values utilized in Davis et al (2009).
b1,b2	All interest maps (except that for “fom”) are piecewise linear, and of the form: $f(x) = 1,0$ (depending on the property) if $x < b1$ , $x \leq b1$ , $x > b2$ or $x \geq b2$ (see details for more information).
verbose	logical, should progress information be printed to the screen?

<code>min.interest</code>	numeric between zero and one giving the desired minimum value of interest. Only used for display purposes. If <code>long</code> is TRUE, a dashed line is printed where the total interest falls below this value. If <code>long</code> is FALSE, only the total interest values above this value are displayed. All values are returned invisibly regardless of the values of <code>min.interest</code> and <code>long</code> .
<code>long</code>	logical, should all interest values be displayed (TRUE) or only those above <code>min.interest</code> (FALSE)?
<code>silent</code>	logical, should summary information be displayed to the screen (FALSE)?
<code>...</code>	<code>interester</code> : optional arguments to <code>FeatueComps</code> . Not used by <code>print</code> or <code>summary</code> .

## Details

This function calculates the feature interest according to the MODE algorithm described in Davis et al (2009). Properties that can be computed are those available in `FeatureComps`, except for “bearing”. Interest maps are computed according to piece-wise linear functions (except for “fom”) depending on the property. For all properties besides “area.ratio”, “int.area” and “fom”, the interest maps are of the form:

$$f(x) = 1, \text{ if } x \leq b1$$

$$f(x) = a0 + a1 * x, \text{ if } x > b1 \text{ and } x \leq b2, \text{ where } a1 = -1/(b2 - b1) \text{ and } a0 = 1 - a1 * b1$$

$$f(x) = 0, \text{ if } x > b2$$

For properties “area.ratio” and “int.area”, the interest maps are of the form:

$$f(x) = 0, \text{ if } x < b1$$

$$f(x) = a0 + a1 * x, \text{ if } x \geq b1 \text{ and } x < b2, \text{ where } a1 = 1/(b2 - b1) \text{ and } a0 = 1 - a1 * b2$$

$$f(x) = 1, \text{ if } x \geq b2$$

Finally, for “fom”, a function that tries to give as much weight to values near one is applied. It is given by:

$$f(x) = b1 * \exp(-0.5 * ((x - 1) / b2)^4)$$

The default values for `b1` and `b2` will not necessarily give the same results as in Davis et al (2009), but also, the distance map for their intersection area ratio differs from that here. The interest function for FOM is further restricted to fall within the interval `[0, 1]`, so care should be taken if `b1` and/or `b2` are changed for this function.

The `interester` function calculates the individual interest values for each property and each pair of features, and returns both these individual interest values as well as a matrix of total interest. The `print` function will print the entire matrix of individual interest values if there are fewer than twenty pairs of features, and will print their summary otherwise. The `summary` function will order the total interest from highest to lowest and print this information (along with which feature pairs correspond to the total interest value). It will also calculate the median of maximum interest (MMI) as suggested by Davis et al (2009). If there is only one feature in either field, then this value will just be the maximum total interest.

The centroid distance property is less meaningful if the sizes of the two features differ greatly, and therefore, the interest value for this property is further multiplied by the area ratio of the two features. Similarly, angle difference is less meaningful if one or both of the features are circular in shape. Therefore, this property is multiplied by the following factor, following Davis et al (2009)

Eq (A1), where  $r_1$  and  $r_2$  are the aspect ratios (defined as the length of the minor axis divided by that of the major axis) of the two features, respectively.

$$\text{sqrt}([ (r_1 - 1)^2 / (r_1^2 + 1) ]^{0.3} * [ (r_2 - 1)^2 / (r_2^2 + 1) ]^{0.3} )$$

The `print` function displays either the individual interest values for each property and feature pairings, or more often, a summary of these values (if the display would otherwise be too large). It also shows a matrix whose rows are observed features and columns forecast features, with the total interest values therein associated.

`summary` shows the sorted total interest from highest to lowest for each pair. A dashed line separates the values above `min.interest` from those below, and if `long` is `TRUE`, then values below that line are not displayed. It also reports the median of maximum interest (MMI) defined by Davis et al (2009) as an overall feature-based summary of forecast performance. It is derived by collecting the row maxima and column maxima from the total interest matrix, shown by the `print` command, into a vector, and then finding the median of this vector.

**Value**

A list of class “`interester`” is returned with components:

- `interest`            matrix whose named rows correspond to the each property that was calculated and whose columns are feature pairings. The values are the interest calculated for the specific property and pair of features.
- `total.interest`    matrix of total interest for each pair of features where rows are observed features and columns are forecast features.

If no features are available in either field, `NULL` is returned.

Nothing is returned by `print`.

`summary` invisibly returns a list object of class “`summary.interester`” with components:

- `sorted.interest`    similar to the `interest` component from the value returned by `interester`, but sorted from highest to lowest interest, along with the feature number information for each field.
- `mmi`                 the median of maximum interest value.

**Note**

The terminology used for features within the entire **SpatialVx** package attempts to avoid conflict with terminology used by R. So, for example, the term `property` is used in lieu of “`attributes`” so as not to be confused with R object `attributes`. The term “`feature`” is used in place of “`object`” to avoid confusion with an R object, etc.

**Author(s)**

Eric Gilleland

## References

Davis, C. A., Brown, B. G., Bullock, R. G. and Halley Gotway, J. (2009) The Method for Object-based Diagnostic Evaluation (MODE) applied to numerical forecasts from the 2005 NSSL/SPC Spring Program. *Wea. Forecasting*, **24**, 1252–1267, DOI: 10.1175/2009WAF2222241.1.

## See Also

Functions for calculating the properties: [FeatureComps](#), [FeatureProps](#)

## Examples

```
x <- y <- matrix(0, 100, 100)
x[2:3,c(3:6, 8:10)] <- 1
y[c(4:7, 9:10),c(7:9, 11:12)] <- 1

x[30:50,45:65] <- 1
y[c(22:24, 99:100),c(50:52, 99:100)] <- 1

hold <- make.SpatialVx(x, y, field.type="contrived", units="none",
  data.name=c("Example", "x", "y"))

look <- convthresh(hold, smoothpar=0.5)

look2 <- interester(look)
look2
summary(look2)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004,
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert004"))

look <- convthresh(hold, smoothpar=10.5, thresh = 5)

look2 <- interester(look, verbose = TRUE)
look2
summary(look2)

## End(Not run)
```



---

locmeasures2d *Binary Image Measures*


---

**Description**

Calculate some binary image measures between two fields.

**Usage**

```
locmeasures2d(object, which.stats = c("bdelta", "haus", "ph",
  "mhd", "med", "msd", "fom"), distfun = "distmapfun", distfun.params = NULL,
  k = NULL, alpha = 0.1, bdconst = NULL, p = 2, ...)
```

```
## Default S3 method:
```

```
locmeasures2d(object, which.stats = c("bdelta", "haus", "ph",
  "mhd", "med", "msd", "fom"), distfun = "distmapfun", distfun.params = NULL,
  k = NULL, alpha = 0.1, bdconst = NULL, p = 2, ..., Y, thresholds=NULL)
```

```
## S3 method for class 'SpatialVx'
```

```
locmeasures2d(object, which.stats = c("bdelta", "haus", "ph",
  "mhd", "med", "msd", "fom"), distfun = "distmapfun", distfun.params = NULL,
  k = NULL, alpha = 0.1, bdconst = NULL, p = 2, ..., time.point = 1,
  model = 1)
```

```
## S3 method for class 'locmeasures2d'
```

```
print(x, ...)
```

```
## S3 method for class 'locmeasures2d'
```

```
summary(object, ...)
```

**Arguments**

- |                |   |
|----------------|---|
| object         | For locmeasures2d, an object of class “SpatialVx” or a valid matrix in which case Y must be explicitly provided. For summary method function, a list object output from locmeasures2d.  |
| x              | returned object from locmeasures2d.   |
| which.stats    | character vector telling which measures should be calculated.   |
| distfun        | character naming a function to calculate the shortest distances between each point x in the grid and the set of events. Default is the Euclidean distance metric. Must take x as an argument, which is the event field for which the distances are to be calculated. Must return a matrix of the same dimension as x. |
| distfun.params | list with named components giving any additional arguments to the distfun function.   |
| k              | numeric vector for use with the partial Hausdorff distance. For k that are whole numerics or integers $\geq 1$ , then the k-th highest value is returned by locmeasures2d. If $0 \leq k < 1$ , then the corresponding quantile is returned.   |

<code>alpha</code>	numeric giving the alpha parameter for Pratt's Figure of Merit (FOM). See the help file for <code>locperf</code> for more details.
<code>bdconst</code>	numeric giving the cut-off value for Baddeley's delta metric.
<code>p</code>	numeric vector giving one or more values for the parameter <code>p</code> in Baddeley's delta metric. Usually this is just 2.
<code>Y</code>	$m \times n$ matrix giving the forecast field.
<code>thresholds</code>	numeric or two-column matrix giving the threshold to be applied to the verification (column one) and forecast (column two) fields. If a vector, same thresholds are applied to both fields.
<code>time.point</code>	numeric or character indicating which time point from the "SpatialVx" verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>...</code>	optional arguments to <code>deltametric</code> and <code>distmap</code> from package <code>spatstat</code> . Not used by the summary or print methods here.

## Details

It is useful to introduce some notation. Let  $d(x,A)$  be the shortest distance from a point  $x$ , anywhere in the grid, to a set  $A$  contained in the grid. Here, Euclidean distance is used (default) for  $d(x,A)$ , but note that some papers (e.g., Venugopal et al., 2005) use other distances, such as the taxi-cab distance (use `distfun` argument to change the distance method).

The Hausdorff distance between two sets  $A$  and  $B$  contained in the finite grid is given by  $\max(\max(d(x,A), x \text{ in } B), \max(d(x,B), x \text{ in } A))$ , and can be re-written as  $H(A,B) = \max(\text{abs}(d(x,A) - d(x,B)))$ , where  $x$  is taken over all points in the grid. Several of the distances here are modifications of the Hausdorff distance. The Baddeley metric, for example, is the  $L_p$  norm of  $\text{abs}(w(d(x,A)) - w(d(x,B)))$ , where again  $x$  is taken from over the entire grid, and  $w$  is any concave continuous function that is strictly increasing at zero. Here,  $w(t) = \min(t, c)$ , where  $c$  is some constant given by the `bdconst` argument.

Calculates one or more of the following binary image measures:

"bdelta" Baddeley delta metric (Baddeley, 1992a,b; Gilleland, 2011; Schwedler and Baldwin, 2011)

"haus" Hausdorff distance (Baddeley, 1992b; Schwedler and Baldwin, 2011)

"ph" Partial Hausdorff distance (Schwedler and Baldwin, 2011). See the help file for `locperf`.

"mhd" Modified Hausdorff Distance (Schwedler and Baldwin, 2011). See the help file for `locperf`.

"med" Mean Error Distance (Peli and Malah, 1982; Baddeley, 1992a). See the help file for `locperf`.

"msd" Mean Square Error Distance (Peli and Malah, 1982; Baddeley, 1992a). See the help file for `locperf`.

"fom" Pratt's Figure of Merit (Peli and Malah, 1982; Baddeley, 1992a, Eq (1)). See the help file for `locperf`.

These distances are summaries in and of themselves, so the summary method function simply displays the results in an easy to read manner.

**Value**

A list with at least one of the following components depending on the argument which.stats

bdelta	p by q matrix giving the Baddeley delta metric for each desired value of p (rows) and each threshold (columns)
haus	numeric vector giving the Hausdorff distance for each threshold
ph	k by q matrix giving the partial Hausdorff distance for each k-th largest value (rows) and each threshold (columns)
mhd	numeric vector giving the modified Hausdorff distance for each threshold.
med	numeric vector giving the mean error distance.
msd	numeric vector giving the mean square error distance.
fom	numeric vector giving Pratt's figure of merit.

**Note**

Binary fields are determined by having values  $\geq$  the thresholds.

**Author(s)**

Eric Gilleland

**References**

- Baddeley, A. (1992a) An error metric for binary images. In *Robust Computer Vision Algorithms*, W. Forstner and S. Ruwiedel, Eds., Wichmann, 59–78.
- Baddeley, A. (1992b) Errors in binary images and an  $L_p$  version of the Hausdorff metric. *Nieuw Arch. Wiskunde*, **10**, 157–183.
- Gilleland, E. (2011) Spatial forecast verification: Baddeley's delta metric applied to the ICP test cases. *Wea. Forecasting*, **26**, 409–415, doi:10.1175/WAF-D-10-05061.1.
- Peli, T. and Malah, D. (1982) A study on edge detection algorithms. *Computer Graphics and Image Processing*, **20**, 1–21.
- Schwedler, B. R. J. and Baldwin, M. E. (2011) Diagnosing the sensitivity of binary image measures to bias, location, and event frequency within a forecast verification framework. *Wea. Forecasting*, **26**, 1032–1044, doi:10.1175/WAF-D-11-00032.1.
- Venugopal, V., Basu, S. and Foufoula-Georgiou, E. (2005) A new metric for comparing precipitation patterns with an application to ensemble forecasts. *J. Geophys. Res.*, **110**, D08111, doi:10.1029/2004JD005395, 11pp.

**See Also**

[deltametric](#), [distmap](#), [make.SpatialVx](#)

**Examples**

```
x <- y <- matrix(0, 10, 12)
x[2,3] <- 1
y[4,7] <- 1
hold <- make.SpatialVx(x, y, thresholds=0.1,
  field.type="random", units="grid squares")
locmeasures2d(hold, k=1)

# Alternatively ...
locmeasures2d(x, thresholds=0.1, k=1, Y=y)

## Not run:
data(geom000)
data(geom001)
data(ICPg240Locs)
hold <- make.SpatialVx(geom000, geom001, thresholds=c(0.1,50.1),
  projection=TRUE, map=TRUE, loc=ICPg240Locs, loc.byrow = TRUE,
  field.type="Precipitation", units="in/100",
  data.name=c("ICP Geometric Cases", "geom000", "geom001"))
hold2 <- locmeasures2d(hold, k=c(4, 0.975), alpha=c(0.1,0.9))
summary(hold2)

## End(Not run)
```

---

locperf

*Localization Performance Measures*


---

**Description**

Some localization performance (distance) measures for binary images.

**Usage**

```
locperf(X, Y, which.stats = c("ph", "mhd", "med", "msd", "fom", "minsep"),
  alpha = 0.1, k = 4, distfun = "distmapfun", a=NULL, ...)
```

```
distob(X, Y, distfun = "distmapfun", ...)
```

```
distmapfun(x, ...)
```

**Arguments**

X	list object giving a pixel image as output from <code>solutionset</code> from package <b>spatstat</b> . This corresponds to the set B in the Details section below.
Y	list object giving a pixel image as output from <code>solutionset</code> from package <b>spatstat</b> . This corresponds to the set A in the Details section below.
x	list object of class "owin" as returned by <code>solutionset</code> from package <b>spatstat</b> .
which.stats	character vector stating which localization performance measure to calculate.

alpha	numeric giving the scaling constant for Pratt's figure of merit (FOM). Only used for which.stat method "fom".
k	single numeric giving the order for the partial Hausdorff distance. If $0 \leq k < 1$ , this is assumed to be a quantile for use with the quantile function. Otherwise, k should be a whole number such that $1 \leq k \leq N_{xy}$ , where $n_{xy}$ is the total number of grid points in the set.
distfun	character specifying a distance metric that returns a matrix of same dimension as X yielding, at each point x, the shortest distances from x to the set of events in the field. Default is distmapfun, which returns the Euclidean distances.
a	Not used. For compatibility with locmeasures2d.
...	Optional arguments to the distfun function. In the case of distmapfun, these are the optional arguments to distmap from package spatstat.

## Details

This function computes localization performance (or distance) measures detailed in Peli and Malah (1982) and Baddeley (1992), as well as a modification of one of these distances detailed in Zhu et al. (2011); distob.

First, it is helpful to establish some notation. Suppose a distance  $\rho(x,y)$  is defined between any two pixels  $x$  and  $y$  in the entire raster of pixels/grid (If distfun is distmapfun (default), then  $\rho$  is the Euclidean distance) that satisfies the formal mathematical axioms of a metric. Let  $d(x,A)$  denote the shortest distance (smallest value of  $\rho$ ) from the point  $x$  in the entire raster to the set  $A$  contained in the raster. That is,  $d(x,A) = \min(\rho(x,a) : a \text{ in } A \text{ contained in the raster})$  [formally, the minimum should be the infimum], with  $d(x, \text{empty set})$  defined to be infinity. Note that the distfun argument is a function that returns  $d(x,A)$  for all  $x$  in the raster.

The mean error distance ("med") is the mean of  $d(x,A)$  over the points in  $B$ . That is  $e.\bar{d} = \text{mean}(d(x,A))$ , over all  $x$  in  $B$ .

The mean square error distance ("msd") is the mean of the squared  $d(x,A)$  over the points in  $B$ . That is,  $e2.\bar{d} = \text{mean}(d(x,A)^2)$ , over all  $x$  in  $B$ .

Pratt's figure of merit ("fom") is given by:  $FOM(A,B) = \sum(1/(1+\alpha*d(x,A)^2))/\max(N(A),N(B))$ , where  $x$  in  $B$ , and  $N(A)$  ( $N(B)$ ) is the number of points in the set  $A$  ( $B$ ) and  $\alpha$  is a scaling constant (see, e.g., Pratt, 1977; Abdou and Pratt, 1979). The scaling constant is typically set to  $1/9$  when  $\rho$  is normalized so that the smallest nonzero distance between pixel neighbors is 1. The default (0.1) here is approximately  $1/9$ . If both  $A$  and  $B$  are empty, the value returned for  $\max(N(A), N(B))$  is  $1e16$  and for  $d(x,A)$  for  $x$  in  $B$  is given a value of zero so that the returned value should be close to zero.

Minimum separation distance between boundaries ("minsep") is just the smallest value of the distance map of one field over the subset where events occur in the other. This is mainly for when single features within the fields are being compared.

distob is a modification of the mean error distance where if there are no events in either field, the value is 0, and if there are no events in one field only, the value is something large (in this case the length of the longest side of the grid).

The Hausdorff distance for a finite grid is given by  $\max(\max(d(x,B); x \text{ in } A), \max(d(x,A); x \text{ in } B))$ , and can be written as  $\max(\text{abs}(d(x,A) - d(x,B)), \text{over all } x \text{ in the raster})$ . The partial Hausdorff distance ("ph") is a modification that replaces the maximum in the latter equation with a  $k$ -th order

statistic (or quantile). The modified Hausdorff distance (“mhd”) is given by  $mhd(A,B) = \max(e.bar(A,B), e.bar(B,A))$ . See, e.g., Baddeley, (1992) and Schwedler and Baldwin (2011).

For computational efficiency, the distance transform method is used via `distmap` from package **spatstat** for calculating  $d(x,A)$   $x$  in the raster.

### Value

`locperf` returns a list object with components depending on which `.stats`: one or more of the following, each of which is a single numeric, except as indicated.

<code>bdelta</code>	matrix or numeric depending on <code>p</code> and number of thresholds.
<code>haus</code>	numeric giving the Hausdorff distances for each threshold.
<code>ph</code>	matrix or numeric, depending on <code>k</code> and number of thresholds, giving the value of the partial Hausdorff distance for each threshold.
<code>mhd</code>	numeric giving the value of the modified Hausdorff distance for each threshold.
<code>med,msd</code>	numeric giving the value of the mean error/square error distance for each threshold.
<code>fom</code>	matrix or numeric, depending on <code>alpha</code> and number of thresholds, giving the value of Pratt his Figure of Merit for each threshold.
<code>minsep</code>	numeric giving the value of the minimum boundary separation distance for each threshold.

`distob` returns a single numeric.

`distmapfun` returns a matrix of same dimension as the input argument’s field.

### Author(s)

Eric Gilleland

### References

- Abdou, I. E. and Pratt, W. K. (1979) Quantitative design and evaluation of enhancement/thresholding edge detectors. *Proc. IEEE*, **67**, 753–763.
- Baddeley, A. (1992) An error metric for binary images. In *Robust Computer Vision Algorithms*, W. Forstner and S. Ruwiedel, Eds., Wichmann, 59–78.
- Peli, T. and Malah, D. (1982) A study on edge detection algorithms. *Computer Graphics and Image Processing*, **20**, 1–21.
- Pratt, W. K. (1977) *Digital Image Processing*. John Wiley and Sons, New York.
- Schwedler, B. R. J. and Baldwin, M. E. (2011) Diagnosing the sensitivity of binary image measures to bias, location, and event frequency within a forecast verification framework. *Wea. Forecasting*, **26**, 1032–1044, doi:10.1175/WAF-D-11-00032.1.
- Zhu, M., Lakshmanan, V. Zhang, P. Hong, Y. Cheng, K. and Chen, S. (2011) Spatial verification using a true metric. *Atmos. Res.*, **102**, 408–419, doi:10.1016/j.atmosres.2011.09.004.

### See Also

[distmap](#), [solutionset](#), [im](#), [bounding.box](#), [as.rectangle](#), [metrV](#), [locmeasures2d](#)

**Examples**

```
x <- y <- matrix( 0, 10, 12)
x[2,3] <- 1
y[4,7] <- 1
x <- im( x)
y <- im( y)
x <- solutionset( x > 0)
y <- solutionset( y > 0)
locperf( x, y)
par( mfrow=c(1,2))
image.plot( distmapfun(x))
image.plot( distmapfun(y))
```

---

LocSig

*Temporal Block Bootstrap Keeping Locations in Space Constant*


---

**Description**

Temporal block bootstrap for data at spatial locations (holding locations constant at each iteration). This is a wrapper function to the `tsboot` or `boot` functions for use with the field significance approach of Elmore et al. (2006).

**Usage**

```
LocSig(Z, numrep = 1000, block.length = NULL, bootfun = "mean",
      alpha = 0.05, bca = FALSE, ...)
```

```
## S3 method for class 'LocSig'
plot(x, loc = NULL, nx = NULL, ny = NULL, ...)
```

**Arguments**

<code>Z</code>	<code>n</code> by <code>m</code> numeric matrix whose rows represent contiguous time points, and whose columns represent spatial locations.
<code>numrep</code>	numeric/integer giving the number of bootstrap replications to use.
<code>block.length</code>	positive numeric/integer giving the desired block lengths. If <code>NULL</code> , <code>floor(sqrt(n))</code> is used. If <code>1</code> , then the IID bootstrap is performed, and the BCa method may be used to find CI's, if <code>bca</code> is <code>TRUE</code> .
<code>bootfun</code>	character naming an R function to be applied to each replicate sample. Must return a single number, but is otherwise the statistic argument for function <code>tsboot</code> (or <code>boot</code> if <code>block.length = 1</code> ).
<code>alpha</code>	numeric giving the value of $\alpha$ to obtain $(1-\alpha)*100$ percent CI's for <code>bootfun</code> .
<code>bca</code>	logical, should bias-corrected and adjusted (BCa) CI's be calculated? Only used if <code>block.length = 1</code> . Will give a warning if this argument is <code>TRUE</code> , and <code>block.length &gt; 1</code> , and will use the percentile method.

x	data frame of class “LocSig” as returned by LocSig.
loc	m by 2 matrix of location coordinates.
nx,ny	If loc is NULL, then nx and ny must be supplied. These give the number of rows and columns of a grid to make an image (using <code>as.image</code> ) for plotting. If these are used, the data Z must be from a regular grid of points.
...	LocSig: optional additional arguments to the <code>tsboot</code> (or <code>boot</code> if <code>block.length=1</code> ) function. <code>plot.LocSig</code> : optional additional arguments to <code>image.plot</code> .

### Details

This function performs the circular block bootstrap algorithm over time at each of m locations (columns of x). So, at each bootstrap iteration, entire blocks of rows of x are resampled with replacement. If Z represents forecast errors at grid points, and `bootfun=“mean”`, then this finds the grid-point CI’s in steps 1 (a) to 1 (c) of Elmore et al. (2006).

### Value

LocSig: A data frame with class attribute “LocSig” with components:

Estimate	numeric giving the estimated values of <code>bootfun</code> (the statistic for which CI’s are computed).
Lower, Upper	numeric giving the estimated lower (upper) $(1-\alpha)*100$ percent CI’s.

`plot.LocSig`: invisibly returns a list containing the estimate as returned by LocSig, and the confidence range.

### Author(s)

Eric Gilleland

### References

Elmore, K. L., Baldwin, M. E. and Schultz, D. M. (2006) Field significance revisited: Spatial bias errors in forecasts as applied to the Eta model. *Mon. Wea. Rev.*, **134**, 519–531.

### See Also

[spatbiasFS](#), [tsboot](#), [boot](#), [boot.ci](#), [MCdof](#), [sig.cor.t](#), [sig.cor.Z](#), [cor.test](#), [image.plot](#), [as.image](#)

### Examples

```
## Not run:
data(GFSNAMfcstEx)
data(GFSNAMobsEx)
data(GFSNAMlocEx)
id <- GFSNAMlocEx[,"Lon"] >=-90 & GFSNAMlocEx[,"Lon"] <= -75 & GFSNAMlocEx[,"Lat"] <= 40
look <- LocSig(GFSNAMfcstEx[,id] - GFSNAMobsEx[,id], numrep=500)
stats(look)
plot(look, loc=GFSNAMlocEx[id,])
```



```
## End(Not run)
```

---

```
make.SpatialVx      Spatial Verification Sets – SpatialVx Object
```

---

## Description

A list object containing the verification sets of spatial verification and forecast fields with pertinent information.

## Usage

```
make.SpatialVx(X, Xhat, thresholds = NULL,
  loc = NULL, projection = FALSE, subset = NULL,
  time.vals = NULL, reg.grid = TRUE, map = FALSE,
  loc.byrow = FALSE, field.type = "", units = "",
  data.name = c("X", "Xhat"),
  q = c(0, 0.1, 0.25, 0.33, 0.5, 0.66, 0.75, 0.9, 0.95),
  qs = NULL)

## S3 method for class 'SpatialVx'
hist(x, ..., time.point = 1, model = 1)

## S3 method for class 'SpatialVx'
plot(x, ..., set.pw = FALSE, time.point = 1, model = 1,
      col, zlim, horizontal = TRUE)

## S3 method for class 'SpatialVx'
print(x, ...)

## S3 method for class 'SpatialVx'
summary(object, ...)
```

## Arguments

X	An n X m matrix or n X m X T array giving the verification field of interest. If an array, T is the number of time points.
Xhat	An n X m matrix or n X m X T array giving the forecast field of interest, or a list of such matrices/arrays with each component of the list an n X m matrix or n X m X T array defining a separate forecast model.
thresholds	single numeric, numeric vector, or Nu X Nf matrix, where Nu are the number of thresholds and Nf the number of forecast models plus one (for the verification) giving the threshold values of interest for the verification set or components of the set. If NULL (default), then thresholds will be calculated as the quantiles (defined through argument q) of each field. If a single numeric or a numeric vector, then an n X 2 matrix will be created (with column names "X" and "Xhat")

where each column is identical. Otherwise, different thresholds may be applied to each of the verification and forecast fields. For example, if quantiles are used for thresholds, then each field will have their own unique thresholds.

loc	If lon/lat coordinates are available, then this is an $n * m \times 2$ matrix giving the lon/lat coordinates of each grid point or location. Should follow the convention used by the <b>maps</b> package.
projection	logical, are the grids projections onto the globe? If so, when plotting, it will be attempted to account for this by using the <code>poly.image</code> function from package <code>fields</code> . In this case, each column of <code>loc</code> will be converted to a matrix using <code>byrow</code> equal to the value of <code>loc.byrow</code> .
subset	vector identifying which specific grid points should be included (if not all of them). This argument may be ignored by most functions and is included for possible future functionality.
time.vals	If more than one time point is available in the set (i.e., the set is of $n \times m \times T$ arrays, with $T > 1$ ), then this argument can be used to define the time points. If missing, the default will yield the vector $1:T$ . But, it is possible to include actual time information. This is also a forward looking feature that may or may not have any subsequent functionality.
reg.grid	logical, is the verification set on a regular grid? This is another feature intended for possible future functionality. Most functions in this package assume the set is on a regular grid.
map	logical, should the plot function attempt to place a map onto the plot? Only possible if the <code>loc</code> argument is given.
field.type, units	character used for plot labelling and printing information to the screen. Describes what variable and in what units the field represents.
data.name	character vector describing the verification set. May have length equal to the number of forecasts and verification fields or it may additionally have as the first entry an overall name for the set. For example, for the geometric cases from the ICP, one might have a vector that begins with "ICP geometric cases" followed by "geom000", "geom001", "geom002", etc. Subsequent plot labels, etc., may (or may not) make use of this information.
q	numeric vector giving the values of quantiles to be used for thresholds. Only used if <code>thresholds</code> is NULL.
qs	character vector describing the quantiles used. Again, only used if <code>thresholds</code> is NULL. This is for subsequent plot/print labelling purposes.
set.pw	logical, should a panel of plots be determined and set by the function.
time.point	numeric or character indicating which time point from the "SpatialVx" verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
col, zlim, horizontal	optional arguments to <code>image</code> , and/or <b>fields</b> functions <code>poly.image</code> and <code>image.plot</code>
x, object	list object of class "SpatialVx".

loc.byrow	logical determining whether to set up the location matrices using byrow = TRUE or FALSE (for use with poly.image).
...	hist method: optional arguments to hist. plot method: if time.point is a function, then these allow for optional arguments to this function to be passed. print and summary methods: Not used.

## Details

This function merely describes a spatial verification set that includes the actual data as well as numerous attributes that are used by several of the subsequent functions that might be employed. In many cases, the attribute information may be passed on to output from other functions for plot labelling and printing purposes (e.g., in order to identify the verification set, time point(s), etc.).

All (or perhaps most) subsequent functions in this package utilize objects of this class and the information contained in the attributes. This function simply gathers information and data sets into a particular form.

The plot method function attempts to create an image plot of each field in the set (at each time point). If projection is TRUE, then it will attempt to preserve the projection (via poly.image of package **fields**). It will also add white contour lines showing the thresholds. If map is TRUE and loc was supplied, then a map will also be added, if possible.

## Value

A list object with two (unnamed) components:

1	matrix or array (same as input argument) giving the observation
2	Either a matrix or array (same as input argument) or a list of such objects if more than one forecast model.

Several attributes are also included among the following:

xdim	numeric of length 2 or 3 giving the dimensions of the verification set (i.e., m, n and T, if relevant).
time	vector giving the time values
thresholds	matrix giving the thresholds for each field. If there is more than one forecast, and they use the same threshold, this matrix may have only two columns.
udim	the dimensions of the thresholds matrix.
loc	nm X 2 matrix giving the locations. If loc was not given, this will be c(rep(1:n, m), rep(1:m, each=n)).
subset	If given, this is a numeric vector describing a subset of loc to be used.
data.name	character vector giving (same as input argument).
nforecast	single numeric giving the number of different forecast models contained in the object.
field.type, units	character strings, same as input arguments.
projection	logical, is the grid a projection?

<code>reg.grid</code>	logical, is the grid a regular grid?
<code>map</code>	logical, should a map be added to image plots of the data?
<code>qs</code>	character vector giving the names of the threshold quantiles.
<code>msg</code>	A message involving the data name, field type and units for adding info to plots, etc.

**Author(s)**

Eric Gilleland

**See Also**[hoods2d](#), [poly.image](#)**Examples**

```

data(UKobs6)
data(UKfcst6)
data(UKloc)

hold <- make.SpatialVx(UKobs6, UKfcst6, thresholds=c(0.01, 20.01),
  loc=UKloc, field.type="Precipitation", units="mm/h",
  data.name=c("Nimrod", "Observations 6", "Forecast 6"), map=TRUE)

hold

plot(hold)

## Not run:
# Stage 2 Observation files from
# NSSL/NCEP Spring 2005 Forecast Experiment.
data(obs0426)
data(obs0513)
data(obs0514)
data(obs0518)
data(obs0519)
data(obs0525)
data(obs0601)
data(obs0603)
data(obs0604)

st2 <- array(c(c(obs0426), c(obs0513), c(obs0514), c(obs0518),
  c(obs0519), c(obs0525), c(obs0601), c(obs0603), c(obs0604)),
  dim=c(601, 501, 9))

rm(obs0426, obs0513, obs0514, obs0518, obs0519, obs0525, obs0601,
  obs0603, obs0604)

# wrf2caps
data(wrf2caps0425)
data(wrf2caps0512)

```

```
data(wrf2caps0513)
data(wrf2caps0517)
data(wrf2caps0518)
data(wrf2caps0524)
data(wrf2caps0531)
data(wrf2caps0602)
data(wrf2caps0603)

# wrf4ncar
data(wrf4ncar0425)
data(wrf4ncar0512)
data(wrf4ncar0513)
data(wrf4ncar0517)
data(wrf4ncar0518)
data(wrf4ncar0524)
data(wrf4ncar0531)
data(wrf4ncar0602)
data(wrf4ncar0603)

# wrf4ncep
data(wrf4ncep0425)
data(wrf4ncep0512)
data(wrf4ncep0513)
data(wrf4ncep0517)
data(wrf4ncep0518)
data(wrf4ncep0524)
data(wrf4ncep0531)
data(wrf4ncep0602)
data(wrf4ncep0603)

wrf2caps <- array(c(c(wrf2caps0425), c(wrf2caps0512),
  c(wrf2caps0513), c(wrf2caps0517), c(wrf2caps0518),
  c(wrf2caps0524), c(wrf2caps0531), c(wrf2caps0602),
  c(wrf2caps0603)),
  dim=c(601, 501, 9))

wrf4ncar <- array(c(c(wrf4ncar0425), c(wrf4ncar0512),
  c(wrf4ncar0513), c(wrf4ncar0517), c(wrf4ncar0518),
  c(wrf4ncar0524), c(wrf4ncar0531), c(wrf4ncar0602),
  c(wrf4ncar0603)),
  dim=c(601, 501, 9))

wrf4ncep <- array(c(c(wrf4ncep0425), c(wrf4ncep0512),
  c(wrf4ncep0513), c(wrf4ncep0517), c(wrf4ncep0518),
  c(wrf4ncep0524), c(wrf4ncep0531), c(wrf4ncep0602),
  c(wrf4ncep0603)),
  dim=c(601, 501, 9))

rm(wrf2caps0425, wrf2caps0512, wrf2caps0513, wrf2caps0517,
  wrf2caps0518, wrf2caps0524, wrf2caps0531, wrf2caps0602,
  wrf2caps0603, wrf4ncar0425, wrf4ncar0512, wrf4ncar0513,
  wrf4ncar0517, wrf4ncar0518, wrf4ncar0524, wrf4ncar0531,
  wrf4ncar0602, wrf4ncar0603, wrf4ncep0425, wrf4ncep0512,
```

```

wrf4ncep0513, wrf4ncep0517, wrf4ncep0518, wrf4ncep0524,
wrf4ncep0531, wrf4ncep0602, wrf4ncep0603)

fcst <- list(wrf2caps, wrf4ncar, wrf4ncep)

rm(wrf2caps, wrf4ncar, wrf4ncep)

# Now, create the object.
data(ICPg240Locs)

ICPreal <- make.SpatialVx(st2, fcst, thresholds=c(0.1, 20.1),
  loc=ICPg240Locs, projection=TRUE, loc.byrow = TRUE,
  time.vals=c(2005042600, 2005051300, 2005051400, 2005051800,
    2005051900, 2005052500, 2005060100, 2005060300, 2005060400),
  map=TRUE, field.type="Precipitation", units="mm/h",
  data.name=c("Stage II Analysis", "WRF 2 CAPS", "WRF 4 NCAR",
    "WRF 4 NCEP"))

pdf("ICPreal.pdf")
plot(ICPreal, set.pw=FALSE)
dev.off()

## End(Not run)

```

---

MCdof

*Monte Carlo Degrees of Freedom*


---

### Description

Estimate the distribution of the proportion of spatial locations that contain significant correlations with randomly generated data along the lines of Livezey and Chen (1983).

### Usage

```
MCdof(x, ntrials = 5000, field.sig = 0.05, zfun = "rnorm", zfun.args = NULL,
  which.test = c("t", "Z", "cor.test"), verbose = FALSE, ...)
```

```
sig.cor.t(r, len = 40, ...)
```

```
sig.cor.Z(r, len = 40, H0 = 0)
```

```
fisherz(r)
```

### Arguments

x            n by m numeric matrix whose rows represent temporal points, and whose columns are spatial locations.

<code>ntrials</code>	numeric/integer giving the number of times to generate random samples of size <code>n</code> , and correlate them with the columns of <code>x</code> .
<code>field.sig</code>	numeric between 0 and 1 giving the desired fields significance level.
<code>zfun</code>	character naming a random number generator that takes <code>n</code> (the size of the sample to be drawn) as an argument, and any other arguments necessary.
<code>zfun.args</code>	list object giving the values for additional arguments to the function named by <code>zfun</code> .
<code>which.test</code>	character naming which type of test to do (default, “t”, is a t-test, calls <code>sig.cor.t</code> ). “Z” does Fisher’s Z transform (calls <code>sig.cor.Z</code> ). “cor.test” calls <code>cor.test</code> giving more options, but is also considerably slower than “t” or “Z”.
<code>r</code>	numeric giving the correlation value(s).
<code>len</code>	numeric giving the size of the data for the test.
<code>H0</code>	numeric giving the null hypothesis value (not used by MCdof).
<code>verbose</code>	logical, should progress information (including total run time) be printed to the screen?
<code>...</code>	optional arguments to <code>sig.cor.t</code> (not used), <code>sig.cor.Z</code> , or <code>cor.test</code> depending on argument <code>which.test</code> .

### Details

This function does the Livezey and Chen (1983) Monte Carlo step 2 (a) from Elmore et al. (2006). It generates a random sample of size `n`, and finds the p-values of a correlation test with this random sample and each column of `x`. From this, it estimates the proportion of spatial locations that could contain significant bias purely by chance.

### Value

MCdof returns a list object with components:

<code>MCprops</code>	numeric vector of length <code>ntrials</code> giving the proportion of locations with significant bias found by chance for each repetition of the experiment.
<code>minsigcov</code>	single numeric giving the $1 - \text{field.sig}$ quantile of the resulting proportions given by <code>MCprops</code> .

`sig.cor.t` and `sig.cor.Z` return umeric vectors of p-values, and `fisherz` returns a numeric vector of test statistics.

### Author(s)

Kimberly L. Elmore, Kim.Elmore “at” noaa.gov, and Eric Gilleland

### References

- Elmore, K. L., Baldwin, M. E. and Schultz, D. M. (2006) Field significance revisited: Spatial bias errors in forecasts as applied to the Eta model. *Mon. Wea. Rev.*, **134**, 519–531.
- Livezey, R. E. and Chen, W. Y. (1983) Statistical field significance and its determination by Monte Carlo techniques. *Mon. Wea. Rev.*, **111**, 46–59.

**See Also**

[spatbiasFS](#), [LocSig](#), [cor.test](#), [rnorm](#), [runif](#), [rexp](#), [rgamma](#)

**Examples**

```
data(GFSNAMfcstEx)
data(GFSNAMobsEx)
data(GFSNAMlocEx)
id <- GFSNAMlocEx[,"Lon"] >=-90 & GFSNAMlocEx[,"Lon"] <= -75 & GFSNAMlocEx[,"Lat"] <= 40
look <- MCdof(GFSNAMfcstEx[,id] - GFSNAMobsEx[,id], ntrials=500)
stats(look$MCprops)
look$minsigcov

fisherz( abs(cor(rnorm(10),rexp(10), use="pairwise.complete.obs")))
```

---

MergeForce

*Force Merges in Matched Feature Objects*


---

**Description**

Force merges in matched feature objects so that, among other things, subsequent analyses are quicker and cleaner.

**Usage**

```
MergeForce(x, verbose = FALSE)
```

**Arguments**

`x` list object of class “matched”.

`verbose` logical, should progress information be printed to the screen.

**Details**

Objects returned by functions such as `deltamm` and `centmatch` provide information necessary to merge and match features from “features” objects. In the case of `centmatch`, only implicit merges are given, and this function creates objects where the implicit merges are forced to be merged. In the case of `deltamm`, a second pass through might yield better merges/matches in that without a second pass, only features in one field or the other can be merged and matched (not both simultaneously). Using this function, and passing the result back through `deltamm` can result in subsequent matches of merged features from both fields simultaneously. Moreover, in some cases, it may be more computationally efficient to run this function once for subsequent analyses/plotting.



**Value**

A list object of class “matched” is returned containing several components and the same attributes as `x`.

<code>match.message</code>	A character string stating how features were matched with (merged) appended.
<code>match.type</code>	character of length 2 naming the original matching function used and this function to note that the features have been forced to be merged/clustered together.
<code>matches</code>	two-column matrix with forecast object numbers in the first column and corresponding matched observed features in the second column. If no matches, this will have value <code>integer(0)</code> for each column giving a matrix with dimension 0 by 2.
<code>unmatched</code>	list with components <code>X</code> and <code>Xhat</code> giving the unmatched object numbers, if any, from the observed and forecast fields, resp. If none, the value will be <code>integer(0)</code> .

Note that all of the same list components of `x` are passed back, except for special information (which is usually no longer relevant) such as `Q` (`deltamm`), `criteria`, `criteria.values`, `centroid.distances` (`centmatch`)

Additionally, `merges` and/or `implicit.merges` (`centmatch`) are not included as they have been merged.

**Author(s)**

Eric Gilleland

**See Also**

[deltamm](#), [centmatch](#), [plot.matched](#)

**Examples**

```
x <- y <- matrix(0, 100, 100)
x[2:3,c(3:6, 8:10)] <- 1
y[c(4:7, 9:10),c(7:9, 11:12)] <- 1

x[30:50,45:65] <- 1
y[c(22:24, 99:100),c(50:52, 99:100)] <- 1

hold <- make.SpatialVx(x, y, field.type="contrived", units="none",
  data.name=c("Example", "x", "y"))

look <- convthresh(hold, smoothpar=0.5)

look2 <- deltamm(look)

look2 <- MergeForce(look2)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)
```

```

hold <- make.SpatialVx(pert000, pert004,
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert004"))

look <- convthresh(hold, smoothpar=10.5, thresh = 5)

look2 <- deltamm(look, verbose = TRUE)

plot(look2)

look3 <- MergeForce(look2)

plot(look3) # same plot as for look2.

look4 <- deltamm(look3, verbose = TRUE) # Nothing changed.

plot(look4) # Nothing changed.

## End(Not run)

```

---

metrV

*Binary Location Metric Proposed in Zhu et al. (2011)*


---

## Description

Calculate the metric metrV proposed in Zhu et al (2011), which is a linear combination of the square root of the sum of squared error between two binary fields, and the mean error distance (Peli and Malah, 1982); or the difference in mean error distances between two forecast fields and the verification field, if the comparison is performed between two forecast models against the same verification field.

## Usage

```

metrV(x, ...)

## Default S3 method:
metrV(x, xhat, xhat2 = NULL, thresholds, lam1 = 0.5, lam2 = 0.5,
  distfun = "distmapfun", a = NULL, verbose = FALSE, ...)

## S3 method for class 'SpatialVx'
metrV(x, time.point = 1, model = 1, lam1 = 0.5, lam2 = 0.5,
  distfun = "distmapfun", verbose = FALSE, ...)

## S3 method for class 'metrV'
print(x, ...)

```

**Arguments**

<code>x</code>	Either a list object as returned by <code>make.SpatialVx</code> or a matrix representing a verification grid. For the <code>print</code> method, this is an object returned by <code>metrV</code> .
<code>xhat, xhat2</code>	( <code>xhat2</code> is optional) matrix representing a forecast grid.
<code>thresholds</code>	$q \times 2$ or $q \times 3$ (if <code>xhat</code> is not <code>NULL</code> ) matrix giving the thresholds to apply to the verification field (first column) and each forecast field.
<code>lam1</code>	numeric giving the weight to be applied to the square root of the sum of squared errors of binary fields term in <code>metrV</code> .
<code>lam2</code>	numeric giving the weight to be applied to the mean error distance term in <code>metrV</code> .
<code>distfun</code>	character naming a function with which to calculate the shortest distances between each point <code>x</code> in the grid and the set of events. Default is the Euclidean distance metric (see the help file for <code>locperf</code> for more information).
<code>a</code>	list object giving certain information about the verification set. These are the attributes of the “SpatialVx” object. May be used here to include information (as attributes of the returned object) that would otherwise not be available to the <code>print</code> method function. In particular, the components, <code>msg</code> , <code>data.name</code> and <code>qs</code> are printed if available.
<code>time.point</code>	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis. May have length one or two. If it has length two, the second value is taken to be the second forecast model (i.e., <code>xhat2</code> in the call to <code>metrV.default</code> ).
<code>verbose</code>	logical, should progress information be printed on the screen.
<code>...</code>	Optional arguments to the <code>distfun</code> function.

**Details**

The binary location metric proposed in Zhu et al. (2011) is a linear combination of two measures: the amount of overlap between events in two fields, given by `distOV` (simply the square root of sum of squared errors between two binary fields), and (if there are events in both fields) the mean error distance described in Peli and Malah (1982); see also Baddeley (1992). The metric can be computed between a forecast field, `M1`, and the verification field, `V`, or it can be compared between two forecast models `M1` and `M2` with reference to `V`. That is,

$$\text{metrV}(M1, M2) = \text{lam1} * \text{distOV}(I.M1, I.M2) + \text{lam2} * \text{distDV}(I.M1, I.M2),$$

where `I.M1` (`I.M2`) is the binary field determined by `M1 >= threshold` (`M2 >= threshold`),  $\text{distOV}(I.M1, I.M2) = \sqrt{\sum (I.M1 - I.M2)^2}$ ,  $\text{distDV}(I.M1, I.M2) = \text{abs}(\text{distob}(I.V, I.M1) - \text{distob}(I.V, I.M2))$ , where `distob(A,B)` is the mean error distance between `A` and `B`, given by:

$$e(A, B) = 1/(N(A)) * \sqrt{\sum d(x, B)},$$

where the summation is over all the points `x` corresponding to events in `A`, and `d(x,B)` is the minimum of the shortest distance from the point `x` to each point in `B`. `e(A,B)` is calculated by using the distance transform as calculated by the `distmap` function from package `spatstat` for computational efficiency.

Note that if there are no events in both fields, then by definition, the term `distob(A,B) = 0`, and if there are no events in one and only one of the two fields, then a large constant (here, the maximum dimension of the field), is returned. In this way, `distob` differs from the mean error distance described in Peli and Malah (1982).

If comparing between the verification field and one forecast model, then the distDV term simplifies to just distob(I.V,I.M1).

One final note is that Eq (6) that defines distOV in Zhu et al. (2011) is correct (or rather, what is used in the paper). It is not, as is stated below Eq (6) in Zhu et al. (2011) the root \*mean\* square error, but rather the root square error. This function computes Eq (6) as written.

### Value

list object of class “metrV” with components:

OvsM1	k by 3 matrix whose rows represent thresholds and columns give the component distOV, distob and metrV between the verification field and the forecast model 1.
OvsM2	If object2 supplied, k by 3 matrix whose rows represent thresholds and columns give the component distOV, distob and metrV between the verification field and the forecast model 2.
M1 vsM2	If object2 supplied, k by 3 matrix whose rows represent thresholds and columns give the component distOV, distob and metrV between model 1 and model 2.

May also contain attributes as passed by either the a argument or the “SpatialVx” object.

### Author(s)

Eric Gilleland

### References

- Baddeley, A. J. (1992) An error metric for binary images. In *Robust Computer Vision Algorithms*, W. Forstner and S. Ruwiedel, Eds., Wichmann, 59–78.
- Peli, T. and Malah, D. (1982) A study on edge detection algorithms. *Computer Graphics and Image Processing*, **20**, 1–21.
- Zhu, M., Lakshmanan, V. Zhang, P. Hong, Y. Cheng, K. and Chen, S. (2011) Spatial verification using a true metric. *Atmos. Res.*, **102**, 408–419, doi:10.1016/j.atmosres.2011.09.004.

### See Also

[distob](#), [distmap](#), [im](#), [solutionset](#), [deltametric](#), [locmeasures2d](#), [make.SpatialVx](#)

### Examples

```
A <- B <- B2 <- matrix( 0, 10, 12)
A[2,3] <- 3
B[4,7] <- 400
B2[10,12] <- 17
hold <- make.SpatialVx(A, list(B,B2), thresholds=c(0.1,3.1,500),
                      field.type="contrived", units="none",
                      data.name=c("Example", "A", "B", "B2"))
metrV(hold)
```

```

metrV(hold, model=c(1,2))

## Not run:
data(pert000)
data(pert001)
data(ICPg240Locs)
testobj <- make.SpatialVx(pert000, pert001, thresholds=1e-8,
                          projection=TRUE, map=TRUE, loc=ICPg240Locs, loc.byrow = TRUE,
                          field.type="Precipitation", units="mm/h",
                          data.name=c("ICP Perturbed Cases", "pert000", "pert001"))
metrV(testobj)
# compare above to results in Fig. 3 (top right panel) of Zhu et al. (2011).

data(geom000)
data(geom001)
testobj <- make.SpatialVx(geom000, geom001, thresholds=0,
                          projection=TRUE, map=TRUE, loc=ICPg240Locs, loc.byrow = TRUE,
                          field.type="Precipitation", units="mm/h",
                          data.name=c("ICP Geometric Cases", "geom000", "geom001"))
metrV(testobj)
# compare above to results in Fig. 2 (top right panel)
# of Zhu et al. (2011). Note that they differ wildly.
# Perhaps because an actual elliptical area is taken in
# the paper instead of finding the values from the fields
# themselves?

## End(Not run)

```

---

obs0426

*Spatial Forecast Verification Methods Inter-Comparison Project (ICP)  
Test Cases and other example verification sets*


---

## Description

Test cases used for the ICP. In particular, those actually analyzed in the special collection of the journal, *Weather and Forecasting*. Includes the nine “real” cases, five simple geometric cases, and the seven perturbed “real” cases.

## Usage

```

data(obs0426)
data(obs0513)
data(obs0514)
data(obs0518)
data(obs0519)
data(obs0525)
data(obs0601)

```

data(obs0603)  
data(obs0604)

data(wrf2caps0425)  
data(wrf2caps0512)  
data(wrf2caps0513)  
data(wrf2caps0517)  
data(wrf2caps0518)  
data(wrf2caps0524)  
data(wrf2caps0531)  
data(wrf2caps0602)  
data(wrf2caps0603)

data(wrf4ncar0425)  
data(wrf4ncar0512)  
data(wrf4ncar0513)  
data(wrf4ncar0517)  
data(wrf4ncar0518)  
data(wrf4ncar0524)  
data(wrf4ncar0531)  
data(wrf4ncar0602)  
data(wrf4ncar0603)

data(wrf4ncep0425)  
data(wrf4ncep0512)  
data(wrf4ncep0513)  
data(wrf4ncep0517)  
data(wrf4ncep0518)  
data(wrf4ncep0524)  
data(wrf4ncep0531)  
data(wrf4ncep0602)  
data(wrf4ncep0603)

data(geom000)  
data(geom001)  
data(geom002)  
data(geom003)  
data(geom004)  
data(geom005)

data(pert000)  
data(pert001)  
data(pert002)  
data(pert003)  
data(pert004)  
data(pert005)  
data(pert006)  
data(pert007)

data(ICPg240Locs)

### Format

The format is: num [1:601, 1:501] 0 0 0 0 0 0 0 0 0 ...

The format is: num [1:301101, 1:2] -110 -110 -110 -110 ... - attr(\*, "dimnames")=List of 2 ..\$ : NULL ..\$ : chr [1:2] "lon" "lat"

### Details

The nine “real” cases are forecast model output from three different versions of the Weather Research Forecast (WRF) model denoted `wrf2caps`, `wrf4ncar` and `wrf4ncep` (see Kain et al. 2008; Ahijevych et al., 2009 for complete details), and the corresponding “observed” fields are stage II reanalyses denoted here by “obs”. The models are 24-h forecasts so that the valid time is for the next day (e.g., `obs0426` corresponds with `wrf2caps0425`). The final four digits for the “real” cases give the month and day of the forecast/observation. These data were from the 2005 Spring Program of the Storm Prediction Center/National Severe Storms Laboratory (SPC/NSSL, cf. Weiss et al., 2005; Kain et al., 2008). Units for the real cases are in mm/h, and are on the NCEP g240 grid (~4-km resolution) with 601 X 501 grid points. Both SPC and NSSL should be cited as sources for these cases, as well as Weiss et al. (2005) and possibly also Kain et al. (2008). The data were made available to the ICP by M. E. Baldwin.

The five geometric cases are simple ellipses (each with two intensities) that are compared against the verification case (`geom000`) on the same NCEP g240 grid as the nine real cases. See Ahijevych et al. (2009) for complete details. Case `geom001` is exactly the same as `geom000`, but is displaced 50 grid points to the right (i.e., ~200 km too far east). Case `geom002` is also identical to `geom000`, but displaced 200 grid points to the right. Case `geom003` is displaced 125 grid points to the right, and is also too big (i.e., has a spatial extent, or coverage, bias). Case `geom004` is also displaced 125 grid points to the right, but also has a different orientation (note, however, that it is not a true rotation of `geom000`). Case `geom005` is displaced 125 grid points to the right, and has a huge spatial extent bias. This last case is also the only one that actually overlaps with `geom000`, and therefore may be regarded by some as the best case. It is certainly the case that comes out on top by the traditional verification statistics that are calculated on a grid point by grid point basis. Ahijevych et al. (2009) should be cited if these geometric cases are used for publications, etc.

The seven perturbed cases (denoted here by `pert00x`) are perturbations of `pert000`, which is adapted from `wrf2caps0531` (again, see Ahijevych et al, 2009 for more details). Case `pert001` shifts `pert000` three grid points to the right, and five grid points down (i.e., ~12 km to the east and ~20 km to the south). Case `pert002` is a shift six points to the right, and ten points down. Case `pert003` is a shift 12 points to the right and 20 points down. Case 4 is a shift 24 points to the right, and 40 points down. Case `pert005` is a shift 48 points to the right and 80 points down. Case `pert006` is a shift 12 points to the right, and 20 points down, and the entire field is multiplied by 1.5. Case `pert007` has the same spatial displacements as `pert003` and `pert006`, but also subtracts 1.27 from the entire field. Ahijevych et al. (2009) should be cited if these perturbed cases are used for publications, etc.

The longitude and latitude information for each grid (the NCEP g240 grid) is contained in the `ICPg240Locs` dataset.

These constitute all of the official data test cases used for the first round of the ICP, and in the special collection of papers for *Wea. Forecasting*. Other data sets for the ICP can be obtained from the ICP

web site (<http://www.ral.ucar.edu/projects/icp>). Future data sets for the next round of the ICP will also be available there, and may potentially also be made available here.

### Source

<http://www.ral.ucar.edu/projects/icp/datacases.html>

### References

Ahijevych, D., Gilleland, E., Brown, B. G. and Ebert, E. E. (2009) Application of spatial verification methods to idealized and NWP gridded precipitation forecasts. *Wea. Forecasting*, **24** (6), 1485–1497.

Kain, J. S., Weiss, S. J., Bright, D. R., Baldwin, M. E. Levit, J. J. Carbin, G. W. Schwartz, C. S. Weisman, M. L. Droegemeier, K. K. Weber, and D. B. Thomas, K. W. (2008) Some Practical Considerations Regarding Horizontal Resolution in the First Generation of Operational Convection-Allowing NWP. *Wea. Forecasting*, **23**, 931–952.

Weiss, S., Kain, J. Levit, J. Baldwin, M. E., Bright, D. Carbin, G. and Hart, J. (2005) NOAA Hazardous Weather Testbed. SPC/NSSL Spring Program 2005 Program Overview and Operations Plan. 61pp. Available at: [http://www.spc.ncep.noaa.gov/exper/Spring\\_2005/2005\\_ops\\_plan.pdf](http://www.spc.ncep.noaa.gov/exper/Spring_2005/2005_ops_plan.pdf)

### Examples

```
## Not run:
data(obs0426)
data(wrf2caps0425)
data(wrf4ncar0425)
data(wrf4ncep0425)
data(ICPg240Locs)
## Plot verification sets with a map.
## Two different methods.

# First way does not preserve projections.
locr <- c( range( ICPg240Locs[,1]), range( ICPg240Locs[,2]))
z1 <- range( c( c(obs0426), c( wrf2caps0425), c( wrf4ncar0425),
c( wrf4ncep0425)))
par( mfrow=c(2,2), mar=rep(0.1,4))
image( obs0426, axes=FALSE, col=c("grey", tim.colors(256)), zlim=z1)
par( usr=locr)
if( map.available) map( add=TRUE, database="state")
image( wrf2caps0425, axes=FALSE, col=c("grey", tim.colors(256)), zlim=z1)
par( usr=locr)
if( map.available) map( add=TRUE, database="state")
image( wrf4ncar0425, axes=FALSE, col=c("grey", tim.colors(256)), zlim=z1)
par( usr=locr)
if( map.available) map( add=TRUE, database="state")
image( wrf4ncep0425, axes=FALSE, col=c("grey", tim.colors(256)), zlim=z1)
par( usr=locr)
if( map.available) map( add=TRUE, database="state")
image.plot( obs0426, legend.only=TRUE, horizontal=TRUE,
col=c("grey", tim.colors(256)), zlim=z1)
```



```

# Second way preserves projections, but values are slightly interpolated.
z1 <- range( c( c(obs0426), c( wrf2caps0425), c( wrf4ncar0425),
              c( wrf4ncep0425)))
par( mfrow=c(2,2), mar=rep(2.1,4))
image(as.image(c(t(obs0426))), x=ICPg240Locs, nx=601, ny=501, na.rm=TRUE), zlim=z1,
      col=c("grey", tim.colors(64)), axes=FALSE, main="Stage II Reanalysis 4/26/05 0000 UTC")
map(add=TRUE, lwd=1.5)
map(add=TRUE, database="state", lty=2)
image(as.image(c(t(wrf2caps0425))), x=ICPg240Locs, nx=601, ny=501, na.rm=TRUE), zlim=z1,
      col=c("grey", tim.colors(64)), axes=FALSE, main="WRF CAPS valid 4/26/05 0000 UTC")
map(add=TRUE, lwd=1.5)
map(add=TRUE, database="state", lty=2)
image(as.image(c(t(wrf4ncar0425))), x=ICPg240Locs, nx=601, ny=501, na.rm=TRUE), zlim=z1,
      col=c("grey", tim.colors(64)), axes=FALSE, main="WRF NCAR valid 4/26/05 0000 UTC")
map(add=TRUE, lwd=1.5)
map(add=TRUE, database="state", lty=2)
image(as.image(c(t(wrf4ncep0425))), x=ICPg240Locs, nx=601, ny=501, na.rm=TRUE), zlim=z1,
      col=c("grey", tim.colors(64)), axes=FALSE, main="WRF NCEP valid 4/26/05 0000 UTC")
map(add=TRUE, lwd=1.5)
map(add=TRUE, database="state", lty=2)
image.plot(obs0426, col=c("grey", tim.colors(64)), zlim=z1, legend.only=TRUE, horizontal=TRUE)

## End(Not run)

```

**Description**

Perform verification using optical flow as described in Marzban and Sandgathe (2010).

**Usage**

```

OF(x, ...)

## Default S3 method:
OF(x, ..., xhat, W = 5, grads.diff = 1, center = TRUE,
   cutoffpar = 4, verbose = FALSE)

## S3 method for class 'SpatialVx'
OF(x, ..., time.point = 1, model = 1, W = 5, grads.diff = 1,
   center = TRUE, cutoffpar = 4, verbose = FALSE)

## S3 method for class 'OF'
plot(x, ...)

## S3 method for class 'OF'
print(x, ...)

```

```
## S3 method for class 'OF'
hist(x, ...)

## S3 method for class 'OF'
summary(object, ...)
```

### Arguments

<code>x, xhat</code>	Default: $m$ by $n$ matrices describing the verification and forecast fields, resp. The forecast field is considered the initial field that is morphed into the final (verification) field. OF.SpatialVx: list object of class “SpatialVx”. plot, hist and print methods: list object as returned by OF.
<code>object</code>	list object as returned by OF.
<code>W</code>	numeric/integer giving the window size (should be no smaller than 5).
<code>grads.diff</code>	1 or 2 describing whether to use first or second differences in finding the first derivative.
<code>center</code>	logical, should the fields be centered before performing the optical flow?
<code>cutoffpar</code>	numeric, set to NaN everything exceeding median $\pm$ cutoffpar*sd.
<code>verbose</code>	logical, should progress information be printed to the screen?
<code>time.point</code>	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>...</code>	For OF: optional arguments to the <code>optim</code> function (cannot be <code>par</code> , <code>fn</code> , <code>gr</code> or <code>method</code> ). See details section for <code>plot</code> and <code>hist</code> method functions. Not used by the <code>summary</code> method function.

### Details

Estimates the optical flow of the forecast field into the verification field. Letting  $I_o(x,y)$  and  $I_f(x,y)$  represent the intensities of each field at coordinate  $(x,y)$ , the collection of pairs  $(dx, dy)$  is the optical flow field, where:

$$I_o(x,y) \sim I_f(x,y) + [\text{partial}(I_f) \text{ wrt } x]*dx + [\text{partial}(I_f) \text{ wrt } y]*dy.$$

The procedure follows that proposed by Lucas and Kanade (1981) whereby for some window,  $W$ , it is assumed that all  $dx$  ( $dy$ ) are assumed constant, and least squares estimation is used to estimate  $dx$  and  $dy$  (see Marzban and Sandgathe, 2010 for more on this implementation). This function iteratively calls `optflow` for each window in the field.

The above formulation is linear in the parameters. Marzban and Sandgathe (2010) also introduce an additive error component, which leads to a nonlinear version of the above. Namely,

$$I_o(x,y) \sim I_f(x,y) + [\text{partial}(I_f) \text{ wrt } x]*dx + [\text{partial}(I_f) \text{ wrt } y]*dy + A(x,y).$$

See Marzban and Sandgathe for more details.

The `plot` method function can produce a figure like that of Fig. 1, 5, and 6 in Marzban and Sandgathe (2010) or with option `full=TRUE`, even more plots. Optional arguments that may be passed in via

the ellipses include: `full` (logical, produce a figure analogous to Fig. 1, 5 and 6 from Marzban and Sandgathe (2010) (FALSE/default) or make more plots (TRUE)), `scale` (default is 1 or no scaling, any numeric value by which the fields are divided/scaled before plotting), `of.scale` (default is 1, factor by which display vectors can be magnified), `of.step` (plot OF vectors every `of.step`, default is 4), `prop` (default is 2, value for `prop` argument in the call to `rose.diag` from package **CircStats**), `nbins` (default is 40, number of bins to use in the call to `rose.diag`).

The `hist` method function produces a two-dimensional histogram like that of Fig. 3 and 7 in Marzban and Sandgathe (2010). It can also take various arguments passed via the ellipses. They include: `xmin`, `xmax`, `ymin`, `ymax` (lower and upper bounds for the histogram breaks in the x- (angle) and y- (magnitude/displacement error) directions, resp. Defaults to (0,360) and (0,4)), `nbreaks` (default is 100, the number of breaks to use).

The `summary` method mostly uses the `stats` function from package **fields** to summarize results of the errors, but also uses `circ.summary` from package **CircStats** for the angular errors.

### Value

OF returns a list object of class “OF” with components:

<code>data</code>	list with components <code>x</code> and <code>xhat</code> containing the data.
<code>data.name</code>	character vector giving the names of the verification and forecast fields.
<code>call</code>	object of class “call” giving the original function call.
<code>rows,cols</code>	numeric vector giving the rows and columns used for finding the centers of windows. Needed by the plot and hist method functions.
<code>err.add.lin</code>	m by n matrix giving the linear additive errors (intensities).
<code>err.mag.lin</code>	m by n matrix giving the linear magnitude (displacement) errors.
<code>err.ang.lin</code>	m by n matrix giving the linear angular errors.
<code>err.add.nlin, err.mag.nlin, err.ang.nlin</code>	same as above but for nonlinear errors.
<code>err.vc.lin, err.vr.lin, err.vc.nlin, err.vr.nlin</code>	m by n matrices giving the x- and y- direction movements for the linear and nonlinear cases, resp.

The `hist` method function invisibly returns a list object of class “OF” that contains the same object that was passed in along with new components:

<code>breaks</code>	a list with components <code>x</code> and <code>y</code> giving the breaks in each direction
<code>hist.vals</code>	itself a list with components <code>xb</code> , <code>yb</code> (the number of breaks -1 used for each direction), and <code>nb</code> (the histogram values for each break)

The plot and summary method functions do not return anything.

### Author(s)

Caren Marzban, marzban “at” u.washington.edu, with modifications by Eric Gilleland

## References

- Lucas, B D. and Kanade, T. (1981) An iterative image registration technique with an application to stereo vision. *Proc. Imaging Understanding Workshop*, DARPA, 121–130.
- Marzban, C. and Sandgathe, S. (2010) Optical flow for verification. *Wea. Forecasting*, **25**, 1479–1494, doi:10.1175/2010WAF2222351.1.

## See Also

[optflow](#), [optim](#), [circ.summary](#)

## Examples

```
## Not run:
data(hump)
initial <- hump$initial
final <- hump$final
look <- OF(final, xhat=initial, W=9, verbose=TRUE)
plot(look) # Compare with Fig. 1 in Marzban and Sandgathe (2010).
par(mfrow=c(1,1))
hist(look) # 2-d histogram.
plot(look, full=TRUE) # More plots.
summary(look)

# Another way to skin the cat.
hold <- make.SpatialVx(final, initial, field.type="Bi-variate Gaussian",
  data.name=c("final", "initial"))

look2 <- OF(hold, W=9, verbose=TRUE)
plot(look2)
par(mfrow=c(1,1))
hist(look2)
plot(look2, full=TRUE)
summary(look2)

## End(Not run)
```

---

optflow

*Optical Flow*

---

## Description

Estimate the optical flow from one gridded field (image) to another.

## Usage

```
optflow(initial, final, grads.diff = 1, mean.field = NULL, ...)
```

**Arguments**

<code>initial, final</code>	<code>m</code> by <code>n</code> matrices where the optical flow is determined from initial (forecast) to final (observation).
<code>grads.diff</code>	either 1 or 2, where 1 calculates first derivatives with first differences and 2 first derivatives with second differences.
<code>mean.field</code>	Should they first be centered? If so, give the value for the centering here (usually the mean of initial).
<code>...</code>	optional arguments to the <code>optim</code> function (cannot be <code>par</code> , <code>fn</code> , <code>gr</code> or <code>method</code> ).

**Details**

This function estimates the optical flow from the initial field (image) to the final one as described in Marzban and Sandgathe (2010). Letting  $I_o(x,y)$  and  $I_f(x,y)$  represent the intensities of each field at coordinate  $(x,y)$ , the collection of pairs  $(dx, dy)$  is the optical flow field, where:

$$I_o(x,y) \sim I_f(x,y) + [\text{partial}(I_f) \text{ wrt } x]*dx + [\text{partial}(I_f) \text{ wrt } y]*dy.$$

The procedure follows that proposed by Lucas and Kanade (1981) whereby for some window,  $W$ , it is assumed that all  $dx$  ( $dy$ ) are assumed constant, and least squares estimation is used to estimate  $dx$  and  $dy$  (see Marzban and Sandgathe, 2010 for more on this implementation). It is assumed that the fields (initial and final) include only the window around the point of interest (i.e., this function finds the optical flow estimate for a single window). See the function `OF`, which iteratively calls this function, for performing optical flow over the entire field.

The above formulation is linear in the parameters. Marzban and Sandgathe (2010) also introduce an additive error component, which leads to a nonlinear version of the above. Namely,

$$I_o(x,y) \sim I_f(x,y) + [\text{partial}(I_f) \text{ wrt } x]*dx + [\text{partial}(I_f) \text{ wrt } y]*dy + A(x,y).$$

See Marzban and Sandgathe for more details.

**Value**

numeric vector whose first three components are the optimized estimates (returned by the `par` component of `optim`) for the regression  $I_o(x,y) - I_f(x,y) = a_0 + a_1*[\text{partial}(I_f) \text{ wrt } x] + a_2*[\text{partial}(I_f) \text{ wrt } y]$  (i.e.,  $a_1$  and  $a_2$  are the estimates for  $dx$  and  $dy$ , resp.) and the latter three values are the initial estimates to `optim` as determined by linear regression (i.e., returned from the `lm` function).

**Author(s)**

Caren Marzban, marzban "at" u.washington.edu, and modified by Eric Gilleland

**References**

Lucas, B D. and Kanade, T. (1981) An iterative image registration technique with an application to stereo vision. *Proc. Imaging Understanding Workshop, DARPA*, 121–130.

Marzban, C. and Sandgathe, S. (2010) Optical flow for verification. *Wea. Forecasting*, **25**, 1479–1494, doi:10.1175/2010WAF2222351.1.

**See Also**

[OF](#), [optim](#), [lm](#)

**Examples**

```

x <- y <- matrix(0, 10, 10)
x[1:2,3:4] <- 1
y[3:4,5:6] <- 2

optflow(x,y)

## Not run:
initial <- hump$initial
final <- hump$final
look <- OF(final, initial, W=9, verbose=TRUE)
plot(look) # Compare with Fig. 1 in Marzban and Sandgathe (2010).
hist(look) # 2-d histogram.
plot(look, full=TRUE) # More plots.

## End(Not run)

```

pphindcast2d

*Practically Perfect Hindcast Neighborhood Verification Method***Description**

Function to perform the practically perfect hindcast neighborhood verification method. Finds the optimal threshold, Pthresh, and calculates the desired statistic for that threshold.

**Usage**

```

pphindcast2d(object, which.score = "ets", time.point = 1, model =
              1, levels = NULL, max.n = NULL, smooth.fun =
              "hoods2dsmoother", smooth.params = NULL, verbose =
              FALSE, ...)

## S3 method for class 'pphindcast2d'
plot(x, ..., set.pw = FALSE,
      type = c("quilt", "line"),
      col = heat.colors(12), horizontal = FALSE)

## S3 method for class 'pphindcast2d'
print(x, ...)

```

**Arguments**

object	A list object returned by the <code>make.SpatialVx</code> function.
which.score	character stating which verification score is to be used. Must be one that is accepted by <code>vxstats</code> .
time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.

<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>levels</code>	numeric vector giving the successive values of the smoothing parameter. For example, for the default method, these are the neighborhood lengths over which the $levels^2$ nearest neighbors are averaged for each point. Values should make sense for the specific smoothing function. For example, for the default method, these should be odd integers.
<code>max.n</code>	(optional) single numeric giving the maximum neighborhood length to use. Only used if <code>levels</code> are NULL.
<code>smooth.fun</code>	character giving the name of a smoothing function to be applied. Default is an average over the $n^2$ nearest neighbors, where $n$ is taken to be each value of the <code>levels</code> argument.
<code>smooth.params</code>	list object containing any optional arguments to <code>smooth.fun</code> . Use NULL if none.
<code>verbose</code>	logical, should progress information be printed to the screen?
<code>x</code>	An object of class “pphindcast2d” as returned by the self-same function.
<code>set.pw</code>	logical, should plotting panels be set by the function?
<code>type</code>	character specifying whether two quilt plots (one for the score and one for <code>Pthresh</code> ) should be made, or one line plot incorporating both the score and the <code>Pthresh</code> values; the latter’s values being displayed on the right axis.
<code>col, horizontal</code>	arguments used in the calls by <code>image</code> and <code>image.plot</code> .
<code>...</code>	pphindcast2d: optional arguments to the <code>optim</code> function. May not include <code>lower</code> , <code>upper</code> or <code>method</code> as these are hard coded into the function. plot method function: optional arguments to the <code>image</code> function. print method function: not used.

## Details

The practically perfect hindcast method is described in Ebert (2008). Using a similar notation as that described therein (and in the help page for `hoods2d`), the method is a SO-NF approach that first compares the observed binary field (obtained from the `trheshold(s)` provided by `object`),  $I_x$ , with the smoothed binary field,  $\langle P_x \rangle_s$ . This smoothed binary field is thresholded by `Pthresh` to obtain a new binary field. The value of `Pthresh` that maximizes the verification score (provided by the `which.score` argument) is then used to compare  $I_x$  with  $\langle I_y \rangle_s$ , the binary forecast field obtained by thresholding the smoothed binary forecast field  $I_y$  using the value of `Pthresh` found above. The verification statistic determined by `which.score` is calculated between  $I_x$  and  $\langle I_y \rangle_s$ .

## Value

A list object is returned with components:

<code>which.score</code>	value of <code>which.score</code> , same as the argument passed in.
<code>Pthresh</code>	1 by $q$ matrix giving the value of <code>Pthresh</code> applied at each level (rows) and threshold (columns).
<code>values</code>	1 by $q$ matrix giving the value of <code>which.score</code> found for each level (rows) and threshold (columns).

**Warning**

The value Pthresh is optimized under the assumption that larger values of which.score are better.

**Author(s)**

Eric Gilleland

**References**

Ebert, E. E. (2008) Fuzzy verification of high resolution gridded forecasts: A review and proposed framework. *Meteorol. Appl.*, **15**, 51–64. doi:10.1002/met.25 Available at <http://www.ecmwf.int/newsevents/meetings/workshops/2007/jwgv/METspecialissueemail.pdf>

**See Also**

[hoods2d](#), [kernel2dsmooth](#), [vxstats](#), [hoods2dPlot](#), [optim](#)

**Examples**

```
x <- y <- matrix( 0, 50, 50)
x[ sample(1:50,10), sample(1:50,10)] <- rexp( 100, 0.25)
y[ sample(1:50,20), sample(1:50,20)] <- rexp( 400)
hold <- make.SpatialVx(x, y, thresholds=c(0.1, 0.5),
  field.type="random")
look <- pphindcast2d(hold, levels=c(1, 3))
look
## Not run:
data(geom001)
data(geom000)
data(ICPg240Locs)

hold <- make.SpatialVx(geom000, geom001, thresholds=c(0.01,50.01),
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  data.name=c("Geometric", "geom000", "geom001"),
  field.type="Precipitation", units="mm/h")

look <- pphindcast2d( hold, levels=c(1, 3, 65), verbose=TRUE)

plot(look, set.pw=TRUE)
plot(look, set.pw=TRUE, type="line")

# Alternatively:
par(mfrow=c(1,2))
hoods2dPlot( look$values, args=attributes(look),
  main="Gilbert Skill Score")

## End(Not run)
```



**Description**

Calculate the S1 score and anomaly correlation for a verification set.

**Usage**

```
S1(x, ...)

## Default S3 method:
S1(x, ..., xhat, gradFUN = "KernelGradFUN")

## S3 method for class 'SpatialVx'
S1(x, ..., xhat, gradFUN = "KernelGradFUN",
    time.point = 1, model = 1)

ACC(x, ...)

## Default S3 method:
ACC(x, ..., xhat, xclim = NULL, xhatclim = NULL)

## S3 method for class 'SpatialVx'
ACC(x, ..., xclim = NULL, xhatclim = NULL,
    time.point = 1, model = 1)
```

**Arguments**

<code>x, xhat</code>	m by n matrices giving the verification and forecast fields, resp. For <code>S1.SpatialVx</code> and <code>ACC.SpatialVx</code> , x is an object of class “SpatialVx”.
<code>xclim, xhatclim</code>	m by n matrices giving the climatologies for X and Y, resp. If NULL, the result is simply a usual correlation.
<code>gradFUN</code>	character identifying a function used to calculate the gradient fields for X and Y. The default <code>KernelGradFUN</code> is to use a Laplacian of Gaussian kernel.
<code>time.point</code>	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
<code>model</code>	numeric indicating which forecast model to select for the analysis.
<code>...</code>	optional arguments to the <code>gradFUN</code> function. In the case of the default, the kernel can be changed (e.g., if only “laplacian” is desired), and optional arguments to the <code>kernel2dmeitsjer</code> function (in this case, <code>nx</code> , <code>ny</code> and <code>sigma</code> ). Not used by <code>ACC</code> .

**Details**

The S1 score is given by

$$S1 = 100 * \frac{\sum(\text{abs}(DY\_i - DX\_i))}{\sum(\max(\text{abs}(DY\_i), \text{abs}(DX\_i)))},$$

where  $DY\_i$  ( $DX\_i$ ) is the gradient at grid point  $i$  for the forecast (verification). See Brown et al. (2012) and Thompson and Carter (1972) for more on this score.

The ACC is just the correlation between  $X - X_{\text{clim}}$  and  $Y - Y_{\text{clim}}$ .

**Value**

single numeric

**Author(s)**

Eric Gilleland

**References**

Brown, B.G., Gilleland, E. and Ebert, E.E. (2012) Chapter 6: Forecasts of spatial fields. pp. 95–117, In *Forecast Verification: A Practitioner's Guide in Atmospheric Science*, 2nd edition. Edts. Jolliffe, I. T. and Stephenson, D. B., Chichester, West Sussex, U.K.: Wiley, 274 pp.

Thompson, J. C. and Carter, G. M. (1972) On some characteristics of the S1 score. *J. Appl. Meteorol.*, **11**, 1384–1385.

**See Also**

[kernel2dmeitsjer](#)

**Examples**

```
data(UKobs6)
data(UKfcst6)

S1(UKobs6, xhat=UKfcst6)
ACC(UKobs6, xhat=UKfcst6)

## Not run:
data(obs0426)
data(wrf4ncar0425)
data(ICPg240Locs)

hold <- make.SpatialVx(obs0426, wrf4ncar0425, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP NSSL/SPC Spring 2005 Cases",
    "obs0426", "wrf4ncar0425"))

plot(hold, set.pw=TRUE)

S1(hold)
```

```
ACC(hold)
## End(Not run)
```

---

saller *Feature-based Analysis of a Field (Image)*

---

### Description

Feature-based analysis of a field (image)

### Usage

```
saller(x, d = NULL, distfun = "rdist", ...)
## S3 method for class 'saller'
print(x, ...)
## S3 method for class 'saller'
summary(object, ...)
```

### Arguments

x	saller: x is a list object returned by convthresh or other feature identification function that returns a list with components X.feats, Y.feats (themselves lists with owin class objects defining separate features in the verification and forecast fields, resp.), and X.labeled, Y.labeled (fields with the numbers from 0 to the number of features also defining the separate feature locations (e.g., as returned by the connected function of package <b>spatstat</b> ). print: list object returned by saller.
object	summary: object the returned by saller.
d	(optional) the SAL (saller) method requires division by the longest distance between two border points. If NULL, this is taken to be simply the length of the longest side.
distfun	Function with which to calculate centroid distances. Default uses straight Euclidean. To do great-circle distance, use <code>rdist.earth</code> and be sure that object has a <code>loc</code> attribute with lon/lat coordinates.
...	Optional arguments to <code>distfun</code> . Not used by <code>print</code> or <code>summary</code> .

### Details

saller: Computes S, A, and L of the SAL method introduced by Wernli et al. (2008).

**Value**

saller returns a list with components:

A	numeric giving the amplitude component.
L	numeric giving the location component.
S	numeric giving the structure component.
L1, L2	numeric giving the values that sum together to give L.

print invisibly returns a named vector with S, A and L.

summary does not return anything.

**Note**

There are several ways to identify features, and some are provided by this package, but only a few. For example, the method for identifying features in the SAL method as introduced by Wernli et al. (2008) utilizes information from a contour field of a particular variable, and is therefore not currently included in this package. Users are encouraged to write their own such functions, and should feel free to contribute them to this package by contacting the maintainer.

The SAL method typically looks at a small domain, and it is up to the user to set this up before calling these functions, as they are not designed to handle such a situation.

**Author(s)**

Eric Gilleland

**References**

Wernli, H., Paulat, M., Hagen, M. and Frei, C. (2008) SAL—A novel quality measure for the verification of quantitative precipitation forecasts. *Mon. Wea. Rev.*, **136**, 4470–4487, doi:10.1175/2008MWR2415.1.

**See Also**

[centroid.owin](#), [connected](#), [tiles](#), [tess](#), [deltamm](#), [make.SpatialVx](#)

**Examples**

```
data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx
xhat <- ExampleSpatialVxSet$fcst

q <- mean( c(c(x[x>0]),c(xhat[xhat>0])), na.rm=TRUE)

hold <- make.SpatialVx(x, xhat, field.type="contrived", units="none",
  data.name=c("Example", "x", "xhat"))

hold2 <- convthresh(hold, smoothpar=5, thresh=q)
## Not run: plot(hold2)
```

```

look <- saller(hold2)
summary(look)

## Not run:
data(pert000)
data(pert004)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert004, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Perturbed ICP Cases", "pert000", "pert004"))

look <- convthresh(hold, smoothpar=10.5)
summary(look)
plot(look)

saller(look)

## End(Not run)

```

---

Sindex

*Shape Index*


---

### Description

Calculate the shape index (Sindex) as described in AghaKouchak et al. (2011)

### Usage

```

Sindex(x, thresh = NULL, ...)

## Default S3 method:
Sindex(x, thresh = NULL, ...,
  loc = NULL)

## S3 method for class 'SpatialVx'
Sindex(x, thresh = NULL, ...,
  time.point = 1, model = 1)

```

### Arguments

**x** Default: m by n numeric matrix giving the field for which the shape index is to be calculated.  
 Sindex.SpatialVx: list object of class "SpatialVx".

thresh	numeric giving a threshold under which (and including, i.e., <=) all values are set to zero, and the shape index is calculated for the non-zero (positive-valued) grid-points.
loc	(optional) mn by 2 numeric matrix giving the grid point locations. If NULL, the expanded grid with x=1:m and y=1:n is used.
time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
...	Not used.

### Details

The shape index introduced in AghaKouchak et al. (2011) is defined as

$$Sindex = Pmin/P,$$

where for  $n$  = the number of positive-valued grid points,  $Pmin = 4*\sqrt{n}$  if  $\text{floor}(\sqrt{n}) = \sqrt{n}$ , and  $Pmin = 2 * \text{floor}(2*\sqrt{n}+1)$  otherwise.  $P$  is the perimeter of the non-zero grid points. Range is 0 to 1. Values closer to 1 indicate shapes that are closer to circular.

### Value

numeric with named components:

Sindex            the shape index

Pmin,P            the numerator and denominator (perimeter) that make the Sindex.

For “SpatialVx” objects, the routine is applied to both the verification and forecast objects so that a two-row matrix is returned containing the above vectors for each field.

### Author(s)

Eric Gilleland

### References

AghaKouchak, A., Nasrohllahi, N., Li, J., Imam, B. and Sorooshian, S. (2011) Geometrical characterization of precipitation patterns. *J. Hydrometeorology*, **12**, 274–285, doi:10.1175/2010JHM1298.1.

### See Also

[Cindex](#), [Aindex](#)

### Examples

```
# Re-create Fig. 7a from AghaKouchak et al. (2011).
tmp <- matrix(0, 8, 8)
tmp[3,2:4] <- 1
tmp[5,4:6] <- 1
tmp[7,6:7] <- 1
```

```

Sindex(tmp)

## Not run:
# Two separate areas with highly structured shapes, but far away from each other.
data(pert000)
data(pert006)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, pert006, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert006"))

plot(hold, set.pw=TRUE)

Sindex(hold)

## End(Not run)

```

---

spatbiasFS

*Field Significance Method of Elmore et al. (2006)*


---

## Description

Apply field significance method of Elmore et al. (2006).

## Usage

```

spatbiasFS(X, Y, loc = NULL, block.length = NULL, alpha.boot = 0.05, field.sig = 0.05,
  bootR = 1000, ntrials = 1000, verbose = FALSE)

## S3 method for class 'spatbiasFS'
summary(object, ...)

## S3 method for class 'spatbiasFS'
plot(x, ...)

```

## Arguments

<code>X, Y</code>	<code>m</code> by <code>n</code> matrices giving the verification and forecast fields, resp., for each of <code>m</code> time points (rows) and <code>n</code> locations (columns).
<code>x, object</code>	list object as returned by <code>spatbiasFS</code> .
<code>loc</code>	optional (for subsequent plotting) <code>n</code> by 2 matrix giving the lon/lat coordinates for the locations.
<code>block.length</code>	numeric giving the block length to be used in the block bootstrap algorithm. If <code>NULL</code> , <code>floor(sqrt(n))</code> is used.

alpha.boot	numeric between 0 and 1 giving the confidence level desired for the bootstrap algorithm.
field.sig	numeric between 0 and 1 giving the desired field significance level.
bootR	numeric integer giving the number of bootstrap replications to use.
ntrials	numeric integer giving the number of Monte Carol iterations to use.
verbose	logical, should progress information be printed to the screen?
...	not used.

### Details

See Elmore et al. (2006) for details.

### Value

A list object with components:

data.name	character vector giving the name of the verification and forecast spatio-temporal fields used, and the associated location object (if not NULL).
block.boot.results	object of class LocSig
sig.results	list object containing information about the significance of the results.
field.significance, alpha.boot	field significance level and bootstrap CI level as input by field.sig alpha.boot arguments.
bootR, ntrials	same as arguments above.

### Author(s)

Eric Gilleland and Kimberly L. Elmore

### References

Elmore, K. L., Baldwin, M. E. and Schultz, D. M. (2006) Field significance revisited: Spatial bias errors in forecasts as applied to the Eta model. *Mon. Wea. Rev.*, **134**, 519–531.

### See Also

[MCdof](#), [LocSig](#), [tsboot](#)

### Examples

```
data(GFSNAMfcstEx)
data(GFSNAMobsEx)
data(GFSNAMlocEx)
id <- GFSNAMlocEx[, "Lon"] >=-95 & GFSNAMlocEx[, "Lon"] <= -75 & GFSNAMlocEx[, "Lat"] <= 32
loc <- GFSNAMlocEx[id, ]
GFSobsSub <- GFSNAMobsEx[, id]
GFSfcstSub <- GFSNAMfcstEx[, id]
```



```
look <- spatbiasFS(GFSobsSub, GFSfcstSub, loc=loc, bootR=500, ntrials=500)
plot(look)
summary(look)
```

---

spatMLD	<i>Test for Equal Predictive Ability on Average Over a Regularly Gridded Space</i>
---------	--

---

### Description

Test for equal predictive ability (for two forecast models) on average over a regularly gridded space using the method of Hering and Genton (2011).

### Usage

```
spatMLD(x, ...)

## Default S3 method:
spatMLD(x, ..., xhat1, xhat2, lossfun = "corrskill",
        trend = "ols", loc = NULL, maxrad = 20, dx = 1, dy = 1,
        zero.out = FALSE)

## S3 method for class 'SpatialVx'
spatMLD(x, ..., time.point = 1, model = c(1, 2),
        lossfun = "corrskill", trend = "ols", maxrad = 20, dx = 1, dy = 1,
        zero.out = FALSE)

fit.spatMLD(object, start.list = NULL)

## S3 method for class 'spatMLD'
summary(object, ...)

## S3 method for class 'spatMLD'
plot(x, ..., icol = c("gray", tim.colors(64)))
```

### Arguments

x, xhat1, xhat2	spatMLD: m by n matrices defining the (gridded) verification set where xhat1 and xhat2 are the two forecast models being compared. plot.spatMLD: x is a list returned by spatMLD.
object	fit.spatMLD this is the output returned by spatMLD. summary.spatMLD: list object returned by spatMLD or fit.spatMLD.
lossfun	character naming a loss function to use in finding the loss differential for the fields. Default is to use correlation as the loss function. Must have arguments x and y, and may have any additional arguments.

trend	character saying “ols” if it is desired to have the spatial trend of the loss differential estimated by ordinary least squares, or a matrix (of appropriate dimension) or single numeric giving the value of the spatial trend, or anything else (e.g., 0, NA or NULL) if trend is assumed to be constant.
loc	(optional) mn by 2 matrix giving location coordinates for each grid point. Only used if trend is “ols”. If NULL, they are taken to be the grid expansion of the dimension of x (i.e., <code>cbind(rep(1:dim(x)[1],dim(x)[2]), rep(1:dim(x)[2],each=dim(x)[1]))</code> ).
maxrad	numeric giving the maximum radius for finding variogram differences per the R argument of <code>vgram.matrix</code> .
dx, dy	dx and dy of <code>vgram.matrix</code> .
zero.out	logical, should the variogram be computed only over non-zero values of the process? If TRUE, a modified version of <code>vgram.matrix</code> is used ( <code>variogram.matrix</code> ).
start.list	list with components: s and r, which give initial estimates for <code>sqrt(sill)</code> and range parameters of the exponential variogram, resp.
time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
icol	(optional) color scheme.
...	spatMLD: optional additional arguments to <code>lossfun</code> . Not used by the summary or plot functions.

## Details

Hering and Genton (2011) introduce a test procedure for comparing spatial fields. First, a loss function,  $g(x,y)$ , is calculated, which can be any appropriate loss function. This is calculated for each of two forecast fields. The loss differential field is then given by:

$D(s) = g(x(s),y1(s)) - g(x(s),y2(s))$ , where s are the spatial locations, x is the verification field, and y1 and y2 are the two forecast fields.

It is assumed that  $D(s) = \phi(s) + \psi(s)$ , where  $\phi(s)$  is the mean trend and  $\psi(s)$  is a mean zero stationary process with unknown covariance function  $C(h) = \text{cov}(\psi(s),\psi(s+h))$ . In particular, the argument trend represents  $\phi(s)$ , and the default is that the mean is equal (and zero) over the entire domain. If it is believed that this is not the case, then it should be removed before finding the covariance. Currently, trend estimation is performed via `lm`, but it is also allowed to remove the trend using some other trend in numeric form of appropriate dimension (e.g., 1 or m by n, or something else that is allowed for M - N, where M is an m by n matrix). To estimate the trend in another way, see e.g. Hering and Genton (2011) and references therein.

A test is constructed to test the null hypothesis of equal predictive ability on average. That is,

$H_0: 1/|D| \int_D E[D(s)]ds = 0$ , where |D| is the area of the domain,

The test statistic is given by

$$S_V = \text{mean}(D(s))/\sqrt{\text{mean}(C(h))},$$

where  $C(h) = \gamma(\infty|p) - \gamma(h|p)$  is a fitted covariance function for the loss differential field. The test statistic is assumed to be  $N(0,1)$  so that if the p-value is smaller than the desired level of significance, the null hypothesis is not accepted.

For 'fit.spatMLD', an exponential variogram is used. Specifically,

$$\text{gamma}(h | \text{theta}=(s,r)) = s^2 * (1 - \exp(-h/r)),$$

where  $s$  is  $\sqrt{\text{sill}}$  and  $r$  is the range (nugget effects are not accounted for here). If `fit.spatMLD` should fail, and the empirical variogram appears to be reasonable (e.g., use the `plot` method function on `spatMLD` output to check that the empirical variogram is concave), then try giving alternative starting values for the `nls` function by using the `start.list` argument. The default is to use the variogram value for the shortest separation distance as an initial estimate for  $s$ , and `maxrad` as the initial estimate for  $r$ .

Currently, it is not possible to fit other variogram models with this function. Such flexibility may possibly be added in a future release. In the meantime, use `fit.spatMLD` as a template to make your own similar function; just be sure to return an object of class "nls", and it should work seamlessly with the `plot` and `summary` method functions for a "spatMLD" object. For example, if it is desired to include the nugget or an extra factor (e.g., 3 as used in Hering and Genton, 2011), then a new similar function would need to be created.

Also, although the testing procedure can be applied to irregularly spaced locations (non-gridded), this function is set up only for gridded fields in order to take advantage of computational efficiencies (i.e., use of `vgram.matrix`), as these are the types of verification sets in mind for this package. Eventually, a similar function will be added for non-gridded fields.

The above test assumes constant spatial trend. It is possible to remove any spatial trend in  $D(s)$  before applying the test.

The actual test statistic is computed by the `summary` function. Isotropy can be checked by the `plot` in the lower right panel of the result of the `plot` method function. The function `nls` is used to fit the variogram model.

For application to precipitation fields, and introduction to the image warp (coming soon) and distance map loss functions, see Gilleland (2013).

## Value

A list object is returned with possible components:

<code>data.name</code>	character vector naming the fields under comparison
<code>lossfun</code> , <code>lossfun.args</code> , <code>vgram.args</code>	same as the arguments input to the <code>spatMLD</code> function.
<code>d</code>	$m$ by $n$ matrix giving the loss differential field, $D(s)$ .
<code>trend</code>	If <code>trend</code> is "ols", a list object of class "lm". If <code>trend</code> is a numeric, it is the same as the value passed in.
<code>loc</code>	If <code>trend</code> is "ols" or a numeric, then this is the same as the argument passed in, or if <code>NULL</code> , it is the expanded grid coordinates.
<code>lossdiff.vgram</code>	list object as returned by <code>vgram.matrix</code>
<code>vgmodel</code>	list object as returned by <code>nls</code> containing the fitted exponential variogram model where $s$ is the estimate of $\sqrt{\text{sill}}$ , and $r$ of the range parameter (assuming 'fit.spatMLD' was used to fit the variogram model).

`summary.spatMLD` invisibly returns the same list object as above with additional components:

<code>Dbar</code>	the estimated mean loss differential (over the entire field).
-------------------	---

`test.statistic` the test statistic.

`p.value` list object with components: `two.sided`—the two-sided alternative hypothesis—, `less`—the one-sided alternative hypothesis that the true value  $\mu(D) < 0$ —and `greater`—the one-sided alternative hypothesis that  $\mu(D) > 0$ —, p-values under the assumption of standard normality of the test statistic.

### Author(s)

Eric Gilleland

### References

Gilleland, E. (2013) Testing competing precipitation forecasts accurately and efficiently: The spatial prediction comparison test. *Mon. Wea. Rev.*, **141**, (1), 340–355.

Hering, A. S. and Genton, M. G. (2011) Comparing spatial predictions. *Technometrics* **53**, (4), 414–425.

### See Also

[vgram.matrix](#), [nls](#), [corrskill](#), [abserrloss](#), [sqerrloss](#), [distmaploss](#)

### Examples

```
grid<- list( x= seq( 0,5,,25), y= seq(0,5,,25))
obj<-Exp.image.cov( grid=grid, theta=.5, setup=TRUE)
look<- sim.rf( obj)
look[ look < 0] <- 0
look <- zapsmall( look)

look2 <- sim.rf( obj)*.25
look2[ look2 < 0] <- 0
look2 <- zapsmall( look2)

look3 <- sim.rf( obj)*2 + 5
look3[ look3 < 0] <- 0
look3 <- zapsmall( look3)

res <- spatMLD(x=look, xhat1=look2, xhat2=look3, lossfun="abserrloss", maxrad=8)
res <- fit.spatMLD(res)
res <- summary(res)
plot(res)

## Not run:
data(pert000)
data(pert004)
data(pert006)
data(ICPg240Locs)

hold <- make.SpatialVx(pert000, list(pert004, pert006), loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
```

```

data.name=c("ICP Perturbed Cases", "pert000", "pert004", "pert006")

look <- spatMLD(hold, lossfun="abserrloss", maxrad=8)
look <- fit.spatMLD(look)
plot(look)
summary(look)

## End(Not run)

```

---

structurogram

*Structure Function for Non-Gridded Spatial Fields.*


---

### Description

Computes pairwise differences (raised to the q-th power) as a function of distance. Returns either raw values or statistics from binning.

### Usage

```

structurogram(loc, y, q = 2, id = NULL, d = NULL, lon.lat = FALSE, dmax = NULL,
  N = NULL, breaks = NULL)

```

```

## S3 method for class 'structurogram'
plot(x, ...)

```

### Arguments

loc	numeric matrix where each row is the coordinate of a point in the field.
x	list object returned by structurogram function.
y	numeric vector giving the value of the field at each location.
q	numeric giving the value to which the paired differences should be raised. Default (q=2) gives the usual semivariogram.
id	A 2 column matrix that specifies which variogram differences to find. If omitted all possible pairings are found. This can be used if the data has an additional covariate that determines proximity, for example a time window.
d	numeric matrix giving the distances among pairs (indexed by id). If not included, these are determined directly from loc.
lon.lat	logical, are the coordinates longitude/latitude coordinates? If so, distances are found using great-circle distance.
dmax	numeric giving the maximum distance for which to compute the structure function.
N	numeric giving the number of bins to use.
breaks	numeric vector giving bin boundaries for binning structure function values. Need not be equally spaced, but must be ordered.
...	optional arguments to plot function.

**Details**

This function is basically an exact copy of `vgram` from package **fields** whereby the differences are raised to a power of `q` instead of 2. That is, it calculates the structure function given by Eq (4) in harris et al. (2001). Namely,

$$S_q(l_x, l_y) = \langle |R(x+l_x, y+l_y) - R(x, y)|^q \rangle$$

where `R` is the field of interest,  $\langle \rangle$  denotes the average over pixels in the image (note, in Harris et al. (2001), this is only over non-zero pixels, so is only equivalent to this equation if zero-valued points are first removed from `y` and `loc`), `l_x` and `l_y` are lags in the `x` and `y` directions, resp. If `q=2`, then this is the semivariogram.

The `plot` method function plots the structure by separation distance (circles) along with a dark blue line giving the bin centers.

**Value**

A list object of class “structurogram” is returned with components:

<code>d</code>	numeric vector giving the pair-wise distances.
<code>val</code>	numeric vector giving the structure function values for each distance.
<code>q</code>	numeric giving the value of <code>q</code> passed into the function.
<code>call</code>	Calling string
<code>stats</code>	Matrix of statistics for values in each bin. Rows are the summaries returned by the <code>stats</code> function or <code>describe</code> (see package <code>fields</code> ). If either <code>breaks</code> or <code>N</code> arguments are not supplied then this component is not computed.
<code>centers</code>	numeric vector giving the bin centers.

The `plot` method function does not return anything.

**Author(s)**

Eric Gilleland

**References**

Harris, D., Foufoula-Georgiou, E., Droegemeier, K. K. and Levit, J. J. (2001) Multiscale statistical properties of a high-resolution precipitation forecast. *J. Hydrometeorol.*, **2**, 406–418.

**See Also**

[vgram](#), [vgram.matrix](#), [structurogram.matrix](#)

**Examples**

```
data( ozone2)
good<- !is.na(ozone2$y[16,])
x<- ozone2$lon.lat[good,]
y<- ozone2$y[16,good]

look <- structurogram( x,y, N=15, lon.lat=TRUE)
```

```

plot(look)
# Compare above with results from example for function vgram from package fields.

look <- structurogram( x,y, N=15, lon.lat=TRUE, q=1)
plot(look)

```

---

structurogram.matrix    *Structure Function for Gridded Fields*

---

### Description

Calculates the structure function to the q-th order for gridded fields.

### Usage

```

structurogram.matrix(dat, q = 2, R = 5, dx = 1, dy = 1, zero.out = FALSE)

## S3 method for class 'structurogram.matrix'
plot(x, ...)

```

### Arguments

dat	n by m matrix of numeric values defining a gridded spatial field (or image) such that distances can be determined from their positions in the matrix.
x	list object output from structurogram.matrix
q	numeric giving the order for the structure function (q = 2 yields the more common semi-variogram).
R	numeric giving the maximum radius for finding the structure differences assuming that the grid points are spaced one unit apart. Default is to go to a radius of 5.
dx, dy	numeric giving the spacing of the grid points on the x- (y-) axis. This is used to calculate the correct distance between grid points.
zero.out	logical, should zero-valued pixels be ignored?
...	optional arguments to the plot function.

### Details

This function is basically an exact copy of `variogram.matrix`, which itself is a copy of `vgram.matrix` from package **fields** (but allows and ignores missing values, in order to ignore zero-valued pixels and does not include Cressie's robust version of the variogram), whereby the differences are raised to a power of q instead of 2. That is, it calculates the structure function given by Eq (4) in harris et al. (2001). Namely,

$$S_q(l_x, l_y) = \langle |R(x+l_x, y+l_y) - R(x, y)|^q \rangle$$

where  $R$  is the field of interest,  $\langle \rangle$  denotes the average over pixels in the image (note, in Harris et al. (2001), this is only over non-zero pixels, so is only equivalent to this equation if `zero.out=TRUE`),  $l_x$  and  $l_y$  are lags in the  $x$  and  $y$  directions, resp. If  $q=2$ , then this is the semivariogram.

The `plot` method function makes two plots. The first shows the structure by separation distance ignoring direction (circles) and all values (i.e., for each direction, dots). The second shows the structure function values for separation distance and direction (see, e.g., `plot.vgram.matrix`).

### Value

A list with the following components:

<code>d</code>	numeric vector of distances for the differences (ignoring direction).
<code>vgram</code>	numeric vector giving the structure function values. Note that the term 'vgram' is used here for compatibility with the <code>plot.vgram.matrix</code> function, which is employed by the <code>plot</code> method function used here. This set of values ignores direction.
<code>d.full</code>	numeric vector of distances for all possible shifts up distance $R$ .
<code>ind</code>	two column matrix giving the $x$ - and $y$ - increment used to compute shifts.
<code>vgram.full</code>	numeric vector giving the structure function for each direction in addition to separation distance. Again, the word 'vgram' is used for compatibility with <code>plot.vgram.matrix</code> .

Note that the `plot` method function does not return anything.

### Author(s)

Eric Gilleland

### References

Harris, D., Foufoula-Georgiou, E., Droegemeier, K. K. and Levit, J. J. (2001) Multiscale statistical properties of a high-resolution precipitation forecast. *J. Hydrometeorol.*, **2**, 406–418.

### See Also

[vgram.matrix](#), [vgram](#), [structurogram](#), [plot.vgram.matrix](#)

### Examples

```
data(lennon)
look <- structurogram.matrix(lennon, q=2)
plot(look)
# Compare the above with
## Not run:
look2 <- vgram.matrix(lennon)
dev.new()
par(mfrow=c(1,2),bg="beige")
plot(look2$d, look2$vgram, xlab="separation distance", ylab="variogram")
points(look2$d.full, look2$vgram.full, pch=".")
plot.vgram.matrix(look2)
```



```

look <- structurogram.matrix(lennon, q=1)
plot(look)

look <- structurogram.matrix(lennon, q=1, zero.out=TRUE)
plot(look)

## End(Not run)

```

---

surrogater2d

*Create Surrogate Fields*


---

## Description

Create surrogate fields that have the same power spectrum and pdf as the original field.

## Usage

```

surrogater2d(Im, frac = 0.95, n = 10, lossfun = "mae", maxiter = 100, zero.down = TRUE,
             verbose = FALSE, ...)

aaft2d(Im, bigdim = NULL)

fft2d(x, bigdim = NULL, ...)

mae(x1, x2, ...)

```

## Arguments

Im	matrix from which surrogates are to be made.
x	matrix to be Fourier transformed.
x1, x2	numeric or array of same dimensions giving the two fields over which to calculate the mean absolute error.
frac	single numeric giving the fraction of original amplitudes to maintain.
n	single numeric giving the number of surrogate fields to create (should be a whole number).
lossfun	character naming the loss function to use in computing the error between simulated surrogate fields in the iterative process. Default is the mean absolute error given by the mae function detailed here.
maxiter	Maximum number of iterations allowed per surrogate.
zero.down	logical, does Im contain many zeros, and is otherwise positive? If so, this sets negative numbers and unusually small numbers to zero.
bigdim	numeric vector of length two giving the dimensions (larger than dimensions of Im) to compute the FFT's more efficiently (at least potentially).
verbose	logical, should progress information be printed to the screen?

... additional arguments: in the case of `fft2d`, they are additional arguments to `fft` (i.e., to use `inverse=TRUE`), in the case of `surrogater2d`, they are additional arguments to the loss function given by `lossfun`, and in the case of `mae` (default), these are not used.

## Details

The `fft2d` function was written to simplify some of the code in `surrogater2d` and `aaft2d`. It is simply a call to the R function `fft`, but it first resets the dimensions to ones that should maximize the efficiency. It will also return the dimensions if they are not passed in.

Surrogates are used in non-linear time series analysis to simulate similar time series for hypothesis testing purposes (e.g., Kantz and Schreiber, 1997). Venugopal et al. (2005) use surrogates of two-dimensional fields as part of their Forecast Quality Index (FQI); which is the intention here. Theiler et al. (1992) proposed a method known as the amplitude adjusted Fourier transform (AAFT) algorithm, and Schreiber and Schmitz (1996) proposed a modification to this approach in order to obtain surrogates with both the same power spectrum and pdf as the original series.

The AAFT method first renders the original data, denoted here as  $s_n$ , Gaussian via a rank ordering based on randomly generated Gaussian simulated data. The resulting series,  $s_n' = g(s_n)$ , is Gaussian and follows the same measured time evolution as  $s_n$ . Next, phase randomized surrogates are made for  $s_n'$ , call them  $s_n''$ . The rescaling  $g$  is then inverted by rank ordering  $s_n''$  according to the distribution of the original data,  $s_n$ . This algorithm yields surrogates with the same pdf of amplitudes as  $s_n$  by construction, but typically not the same power spectra. The algorithm proposed by Schreiber and Schmitz (1996) begins with the AAFT, and then iterates through a further algorithm as follows.

1. Hold a sorted list of  $s_n$  and the squared amplitudes of the Fourier transform of  $s_n$ , denote them by  $S2_k$ .
2. Take a random shuffle without replacement of the data, denote as  $s_n(0)$ .
3. Take the Fourier transform of  $s_n(i)$ .
4. Replace the  $S2_k(i)$  with  $S2_k$ .
5. Inverse the Fourier transform with the replaced amplitudes.
6. Rank order the series from 5 in order to assume exactly the values taken by  $s_n$ .
7. Check the accuracy of 6 using a loss function of some sort, and repeat steps 3 through 6 until a desired level of accuracy is achieved.

## Value

In the case of `surrogater2d`: A three dimensional array of matrices with same dimension as  $Im$ , and third dimension giving the  $n$  surrogate fields.

In the case of `aaft2d`: A matrix of the same dimension as  $Im$ .

In the case of `fft2d`: If `bigdim` is `NULL`, a list object is returned with components `fft` and `bigdim` giving the FFT of  $x$  and the larger dimensions used. Otherwise, a matrix of dimension  $x$  is returned giving the FFT (or inverse FFT) of  $x$ .

In the case of `mae`: a single numeric giving the mean absolute error between  $x1$  and  $x2$ .

**Author(s)**

Eric Gilleland, this code was adapted from matlab code written by Sukanta Basu (2007) available at: <http://www.ral.ucar.edu/projects/icp/Software/FeaturesBased/FQI/Perturbed.m>

**References**

- Kantz, H. and Schreiber, T. (1997) *Nonlinear time series analysis*. Cambridge University Press, Cambridge, U.K., 304pp.
- Schreiber, T. and Schmitz, A. (1996) Improved surrogate data for nonlinearity tests. *Physical Review Letters*, **77**(4), 635–638.
- Theiler, J., Eubank, S. Longtin, A. Galdrikian, B. and Farmer, J. D. (1992) *Physica* (Amsterdam) **58D**, 77.
- Venugopal, V., Basu, S. and Foufoula-Georgiou, E. (2005) A new metric for comparing precipitation patterns with an application to ensemble forecasts. *J. Geophys. Res.*, **110**, D08111, doi:10.1029/2004JD005395, 11pp.

**See Also**

[fft](#), [locmeasures2d](#), [UIQI](#), [ampstats](#)

**Examples**

```
data(ExampleSpatialVxSet)

x <- ExampleSpatialVxSet$vx

z <- surrogater2d( x, zero.down=FALSE, n=3)

## Not run:
par( mfrow=c(2,2))
image.plot( look)
image.plot( look2[, ,1])
image.plot( look2[, ,2])
image.plot( look2[, ,3])

data( pert000)
tmp <- surrogater( pert000, n=10, verbose=TRUE)
boxplot( cbind( c(pert000), apply( tmp, 3, c)))

## End(Not run)
```

**Description**

Example precipitation rate verification set from the very short-range mesoscale Numerical Weather Prediction (NWP) system used operationally at the UK Met Office.

**Usage**

```
data(UKobs6)
data(UKloc)
```

**Format**

The format is: chr "UKobs6"

The format is: num [1:65536, 1:2] -11 -10.9 -10.9 -10.8 -10.7 ...

**Details**

Precipitation rate (mm/h) verification set from the very short-range NWP system called NIMROD used operationally at the UK Met Office, and described in detail in Casati et al. (2004). In particular, this is case 6 from Casati et al. (2004), showing a front timing error. These data are made available for scientific purposes only. Please cite the source in any papers or presentations. The proper reference is the U.K. Met Office.

Refer to Casati et al. (2004) for more information on these data.

The original lon/lat information is not available. 'UKloc' was created to match reasonably well with the figures in Casati et al. (2004), but should not be considered definite.

**Source**

UK Met Office

**References**

Casati, B., Ross, G. and Stephenson, D. B. (2004) A new intensity-scale approach for the verification of spatial precipitation forecasts. *Meteorol. Appl.*, **11**, 141–154, doi:10.1017/S1350482704001239.

**Examples**

```
data(UKobs6)
data(UKfcst6)
data(UKloc)

z1 <- range(c(c(UKobs6), c(UKfcst6)))
par(mfrow=c(1,2))
image(UKobs6, col=c("grey", tim.colors(64)), zlim=z1, main="analysis", axes=FALSE)
par(usr=apply(UKloc, 2, range))
map(add=TRUE)
image.plot(UKfcst6, col=c("grey", tim.colors(64)), zlim=z1, main="forecast", axes=FALSE)
par(usr=apply(UKloc, 2, range))
map(add=TRUE)
```

upscale2d

*Upscaling Neighborhood Verification on a 2-d Verification Set***Description**

Perform upscaling neighborhood verification on a 2-d verification set.

**Usage**

```
upscale2d(object, thresholds = NULL, quantiles = NULL, q.gt.zero
          = FALSE, time.point = 1, model = 1, levels = NULL,
          max.n = NULL, smooth.fun = "hoods2dsmoother",
          smooth.params = NULL, verbose = FALSE)
```

```
## S3 method for class 'upscale2d'
plot(x, ..., set.pw = FALSE)
```

```
## S3 method for class 'upscale2d'
print(x, ...)
```

**Arguments**

object	list object of class "SpatialVx".
thresholds, quantiles	(optional) alternative thresholds (or quantiles of upscaled fields) to use on the upscaled fields. If both are NULL, the thresholds from the "SpatialVx" object are used.
q.gt.zero	logical, If quantiles are not NULL, then should the quantiles be calculated only for values greater than zero in the upscaled fields?
time.point	numeric or character indicating which time point from the "SpatialVx" verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
levels	numeric vector giving the successive values of the smoothing parameter. For example, for the default method, these are the neighborhood lengths over which the levels <sup>2</sup> nearest neighbors are averaged for each point. Values should make sense for the specific smoothing function. For example, for the default method, these should be odd integers.
max.n	(optional) single numeric giving the maximum neighborhood length to use. Only used if levels are NULL.
smooth.fun	character giving the name of a smoothing function to be applied. Default is an average over the n <sup>2</sup> nearest neighbors, where n is taken to be each value of the levels argument.
smooth.params	list object containing any optional arguments to smooth.fun. Use NULL if none.

verbose	logical, should progress information be printed to the screen?
x	list object of class “upscale2d” as returned by upscale2d.
set.pw	logical, should panels for the plot be set? Recommended here if you want to see all displays. Set to FALSE for printing to a pdf, for example, or for use with adding to other plots.
...	optional arguments to the image.plot function from package <b>fields</b> . Can also include the argument type, which must be one of “all”, “gss”, “ts”, “bias” or “rmse”.

### Details

Upscaling is performed via neighborhood smoothing. Here, a boxcar kernel is convolved (using the convolution theorem with FFT’s) to obtain an average over the nearest  $n^2$  grid squares at each grid point. This is performed on the raw forecast and verification fields. The root mean square error (RMSE) is taken for each threshold (Yates et al., 2006; Ebert, 2008). Further, binary fields are obtained for each smoothed field via thresholding, and frequency bias, threat score (ts) and equitable threat score (ets) are calculated (Zepeda-Arce et al., 2000; Ebert, 2008).

### Value

upscale2d returns a list of class “upscale2d” with components:

rmse	numeric vector giving the root mean square error for each neighborhood size provided by object.
bias, ts, ets	numeric matrices giving the frequency bias, ts and ets for each neighborhood size (rows) and threshold (columns).

### Author(s)

Eric Gilleland

### References

- Ebert, E. E. (2008) Fuzzy verification of high resolution gridded forecasts: A review and proposed framework. *Meteorol. Appl.*, **15**, 51–64. doi:10.1002/met.25 Available at <http://www.ecmwf.int/newsevents/meetings/workshops/2007/jwgv/METspecialissueemail.pdf>
- Yates, E., Anquetin, S., Ducrocq, V., Creutin, J.-D., Ricard, D. and Chancibault, K. (2006) Point and areal validation of forecast precipitation fields. *Meteorol. Appl.*, **13**, 1–20.
- Zepeda-Arce, J., Fofoula-Georgiou, E., Droegemeier, K. K. (2000) Space-time rainfall organization and its role in validating quantitative precipitation forecasts. *J. Geophys. Res.*, **105**(D8), 10,129–10,146.

### See Also

[hoods2d](#), [kernel2dsmooth](#), [kernel2dmeitsjer](#), [fft](#)

**Examples**

```

x <- matrix( 0, 50, 50)
x[ sample(1:50,10), sample(1:50,10)] <- rexp( 100, 0.25)
y <- kernel2dsmooth( x, kernel.type="disk", r=6.5)
x <- kernel2dsmooth( x, kernel.type="gauss", nx=50, ny=50, sigma=3.5)
hold <- make.SpatialVx(x, y, thresholds=c(1e-8, 0.05, 0.1),
  field.type="random")
look <- upscale2d( hold, thresholds=seq(0.01,1,,5), levels=c(1, 3, 20))
look
plot( look)

## Not run: plot( look)

## Not run:
data(geom001)
data(geom000)
data(ICPg240Locs)
hold <- make.SpatialVx(geom000, geom001, thresholds=c(0.01,50.01),
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Geometric", "geom000", "geom001"))

look <- upscale2d(hold, quantiles=c(0.25, 0.5, 0.75),
  levels=c(1, 3, 9, 17, 33, 65, 129, 257),
  verbose=TRUE)
plot(look, set.pw=TRUE)
look <- upscale2d(hold, quantiles=c(0.25, 0.5, 0.75),
  q.gt.zero=TRUE, verbose=TRUE)
plot(look)
look <- upscale2d(hold, thresholds=c(1e-8, 0.1, 0.5, 45, 50.1),
  verbose=TRUE)
plot(look)

## End(Not run)

```

---

vxstats

*Some Common Traditional Forecast Verification Statistics.*


---

**Description**

Calculates some common traditional forecast verification statistics.

**Usage**

```

vxstats(X, Xhat, which.stats = c("bias", "ts", "ets", "pod",
  "far", "f", "hk", "bcts", "bcets", "mse"), subset =
  NULL)

```

**Arguments**

<code>X, Xhat</code>	<code>k</code> by <code>m</code> matrix of verification and forecast values, resp.
<code>which.stats</code>	character vector giving the names of the desired statistics. See Details below.
<code>subset</code>	numeric vector indicating a subset of the verification set over which to calculate the verification statistics.

**Details**

Computes several traditional verification statistics (see Wilks, 2006, Ch. 7; Jolliffe and Stephenson, 2012 for more on these forecast verification statistics; as well as the Issues, Methods and FAQ web page of the Joint Working Group on Forecast Verification of the World Meteorological Organization at: <http://www.cawcr.gov.au/projects/verification/>) The possible statistics that can be computed, as determined by `which.stats` are:

“bias” the number of forecast events divided by the number of observed events (sometimes called frequency bias).

“ts” threat score, given by  $\text{hits}/(\text{hits} + \text{misses} + \text{false alarms})$

“ets” equitable threat score, given by  $(\text{hits} - \text{hits.random})/(\text{hits} + \text{misses} + \text{false alarms} - \text{hits.random})$ , where `hits.random` is the number of observed events times the number of forecast events divided by the total number of forecasts.

“pod” probability of detecting an observed event (aka, hit rate). It is given by  $\text{hits}/(\text{hits} + \text{misses})$ .

“far” false alarm ratio, given by  $(\text{false alarms})/(\text{hits} + \text{false alarms})$ .

“f” false alarm rate (aka probability of false detection) is given by  $(\text{false alarms})/(\text{correct rejections} + \text{false alarms})$ .

“hk” Hanssen-Kuipers Score is given by the difference between the hit rate (“pod”) and the false alarm rate (“f”).

“bcts”, “bcets”, Bias Corrected Threat Score (Equitable Threat Score) as introduced in Mesinger (2008); see also Brill and Mesinger (2009). Also referred to as the dHdA versions of these scores.

“mse” mean square error (not a contingency table statistic, but can be used with binary fields). This is the only statistic that can be calculated here that does not require binary fields for `Fcst` and `Obs`.

**Value**

A list with components determined by `which.stats`, which may include any or all of the following.

<code>bias</code>	numeric giving the frequency bias.
<code>ts</code>	numeric giving the threat score.
<code>ets</code>	numeric giving the equitable threat score, also known as the Gilbert Skill Score.
<code>pod</code>	numeric giving the probability of decking an event, also known as the hit rate.
<code>far</code>	numeric giving the false alarm ratio.
<code>f</code>	numeric giving the false alarm rate.
<code>hk</code>	numeric giving the Hanssen and Kuipers statistic.
<code>bcts, bcets</code>	numeric giving the bias corrected version of the threat- and/or equitable threat score.
<code>mse</code>	numeric giving the mean square error.



**Warning**

It is up to the user to provide the appropriate type of fields for the given statistics to be computed. For example, they must be binary for all types of which.stats except mse.

**Note**

See the web page: <http://www.cawcr.gov.au/projects/verification/> for more details about these statistics, and references.

**Author(s)**

Eric Gilleland

**References**

Brill, K. F. and Mesinger, F. (2009) Applying a general analytic method for assessing bias sensitivity to bias-adjusted threat and equitable threat scores. *Wea. Forecasting*, **24**, 1748–1754.

Jolliffe, I. T. and Stephenson, D. B., Edts. (2012) *Forecast Verification: A Practitioner's Guide in Atmospheric Science*, 2nd edition. Chichester, West Sussex, U.K.: Wiley, 274 pp.

Mesinger, F. (2008) Bias adjusted precipitation threat scores. *Adv. Geosci.*, **16**, 137–142.

Wilks, D. S. (2006) *Statistical Methods in the Atmospheric Sciences*. 2nd Edition, Academic Press, Burlington, Massachusetts, 627pp.

**See Also**

[hoods2d](#)

**Examples**

```
# Calculate the traditional verification scores for the first geometric case
# of the ICP.
data(geom001)
data(geom000)
rmse <- sqrt(vxstats( geom001, geom000, which.stats="mse")$mse)
rmse
vxstats( geom001 > 0, geom000 > 0, which.stats=c("bias", "ts", "ets", "pod", "far", "f", "hk"))

data(geom005)
vxstats( geom005 > 0, geom000 > 0, which.stats=c("ts", "ets", "bcts", "bcets"))
```

---

waveIS *Intensity Scale (IS) Verification*

---

### Description

Intensity Scale (IS) verification based on Casat et al (2004) and Casati (2010).

### Usage

```

waveIS(object, J = NULL, wavelet.type = "haar", time.point =
      1, model = 1, levels = NULL, max.n = NULL, smooth.fun
      = "hoods2dsmoother", smooth.params = NULL, verbose =
      FALSE)

## S3 method for class 'waveIS'
plot(x, main1 = "X", main2 = "Y",
     which.plots = c("all", "mse", "ss", "energy"),
     level.label = NULL, ...)

## S3 method for class 'waveIS'
summary(object, ...)

```

### Arguments

object	waveIS: A list object of class "SpatialVx". summary: list object returned by waveIS.
x	list object returned by waveIS.
main1,main2	character giving labels for the plots where main1 refers to the verification field and main2 to the forecast field.
which.plots	character vector naming one or more specific plots to do.
level.label	optional character vector to use for level names on the plot(s).
J	numeric integer giving the number of levels to use. If NULL and the field is dyadic, this will be $\log_2(\min(\dim(X)))$ , where $X$ is a field from the verification set. If NULL and the field is not dyadic, then $J$ is set equal to 4. Note that if the fields are not dyadic, the function will be much slower.
wavelet.type	character giving the name of the wavelet type to use as accepted by <code>dwt.2d</code> and <code>modwt.2d</code> .
time.point	numeric or character indicating which time point from the "SpatialVx" verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
levels	numeric vector giving the successive values of the smoothing parameter. For example, for the default method, these are the neighborhood lengths over which the $\text{levels}^2$ nearest neighbors are averaged for each point. Values should make sense for the specific smoothing function. For example, for the default method, these should be odd integers.

<code>max.n</code>	(optional) single numeric giving the maximum neighborhood length to use. Only used if <code>levels</code> are NULL.
<code>smooth.fun</code>	character giving the name of a smoothing function to be applied. Default is an average over the $n^2$ nearest neighbors, where <code>n</code> is taken to be each value of the <code>levels</code> argument.
<code>smooth.params</code>	list object containing any optional arguments to <code>smooth.fun</code> . Use NULL if none.
<code>verbose</code>	logical, should progress information be printed to the screen?
<code>...</code>	Not used by <code>plot.waveIS</code> . Only sort of used by <code>summary.waveIS</code> . One can put the argument <code>silent=TRUE</code> so that nothing is printed to the screen (useful if you just want the values calculated and stored without writing to the screen).

### Details

This function applies various statistics to the detail fields (in wavelet space) of a discrete wavelet decomposition (DWT) of the binary error fields for a verification set. In particular, the statistics described in Casati et al (2004) and Casati (2010) are calculated. This function depends on the `waverify2d` or `mowaverify2d` function (depending on whether the fields are dyadic or not, resp.), which themselves depend on the `dwt.2d` and `idwt.2d` or `modwt.2d` and `imodwt.2d` functions.

See the references herein and the help files and references therein for `dwt.2d` and `modwt.2d` for more information on this approach, as well as Percival and Guttorp (1994) and Lindsay et al. (1996).

### Value

A list object of class “waveIS” that contains the entire prep object passed in by `obj`, as well as additional components:

<code>EnVx, EnFcst</code>	J by q matrices giving the energy for the verification and forecast fields, resp., for each threshold (columns) and scale (rows).
<code>MSE, SS</code>	J by q matrices giving the mean square error and IS skill score for each threshold (column) and scale (rows).
<code>Bias</code>	numeric vector of length q giving the frequency bias of the original fields for each threshold.

`plot.waveIS` does not return any value. A plot is created on the current graphic device. `summary.waveIS` returns a list invisibly with the same components as returned by `waveIS` along with extra components:

<code>MSEu, SSu, EnVx.u, EnFcst.u</code>	length q numeric vectors giving the MSE, SS, and Vx and Fcst energy for each threshold (i.e., ignoring the wavelet decomposition).
<code>MSEperc, EnVx.perc, EnFcst.perc</code>	J by q numeric matrices giving percentage form of MSE, Vx Energy and Fcst Energy values, resp.
<code>EnRelDiff</code>	J by q numeric matrix giving the energy relative difference.

### Author(s)

Eric Gilleland

## References

- Casati, B., Ross, G. and Stephenson, D. B. (2004) A new intensity-scale approach for the verification of spatial precipitation forecasts. *Meteorol. Appl.* **11**, 141–154.
- Casati, B. (2010) New Developments of the Intensity-Scale Technique within the Spatial Verification Methods Inter-Comparison Project. *Wea. Forecasting* **25**, (1), 113–143, doi:10.1175/2009WAF2222257.1.
- Lindsay, R. W., Percival, D. B. and Rothrock, D. A. (1996) The discrete wavelet transform and the scale analysis of the surface properties of sea ice. *IEEE Transactions on Geoscience and Remote Sensing*, **34** (3), 771–787.
- Percival, D. B. and Guttorp, P. (1994) Long-memory processes, the Allan variance and wavelets. In *Wavelets in Geophysics*, Foufoula-Georgiou, E. and Kumar, P., Eds., New York: Academic, 325–343.

## See Also

IS, int.scale.verify from package **verification**,  
[dwt.2d](#), [modwt.2d](#), [idwt.2d](#), [imodwt.2d](#), [hoods2d](#)

## Examples

```
data(UKobs6)
data(UKfcst6)
data(UKloc)
hold <- make.SpatialVx( UKobs6, UKfcst6, thresholds=c(0.1,0.2,0.5,1,2,5,10,20,50),
  loc=UKloc, map=TRUE, field.type="Rainfall", units="mm/h",
  data.name=c("Nimrod", "UKobs6", "UKfcst6"))
look <- waveIS(hold, J=8, levels=2^(8-1:8), verbose=TRUE)
plot(look, which.plots="mse")
plot(look, which.plots="ss")
plot(look, which.plots="energy")
summary(look)

## Not run:
data(pert004)
data(pert000)

hold <- make.SpatialVx( pert000, pert004, thresholds=c(1,10,50),
  loc=ICPg240Locs, projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Perturbed ICP", "pert000", "pert004"))

look <- waveIS(hold, levels=1:4, verbose=TRUE)
plot(look, which.plots="mse")
plot(look, which.plots="ss")
plot(look, which.plots="energy")
summary(look)

## End(Not run)
```

---

 wavePurifyVx

 Apply Traditional Forecast Verification After Wavelet Denoising
 

---

## Description

Apply traditional forecast verification after wavelet denoising ala Briggs and Levine (1997).

## Usage

```

wavePurifyVx(x, y, object = NULL, climate = NULL, which.stats =
             c("bias", "ts", "ets", "pod", "far", "f", "hk",
               "mse"), thresholds = NULL, return.fields = FALSE,
             time.point = 1, model = 1, verbose = FALSE, ...)

```

```

## S3 method for class 'wavePurifyVx'
plot(x, ..., set.pw = FALSE, col, zlim, horizontal = TRUE,
     type = c("stats", "fields"))

```

```

## S3 method for class 'wavePurifyVx'
summary(object, ...)

```

## Arguments

<code>x,y</code>	For wavePurifyVx, m by n matrices giving the verification and forecast fields, resp. If either is not supplied, then object must be supplied, and the fields given by object are used instead (even if one of x or y are supplied. If one of these is missing, and object not supplied, the function will error out. For plot.wavePurifyVx, list object as output from wavePurifyVx.
<code>object</code>	For wavePurifyVx, a list object of class "SpatialVx". Not used if both x and y are given. For summary.wavePurifyVx, list object as returned by wavePurifyVx.
<code>climate</code>	m by n matrix defining a climatology field. If not NULL, then the anomaly correlation coefficient will be applied to the wavelet denoised fields.
<code>which.stats</code>	character describing which traditional verification statistics to calculate on the wavelet denoised fields. This is the argument passed to the argument of the same name in vxstats.
<code>thresholds</code>	If object is used, then this argument is ignored. Otherwise, it is used to define events for all of the verification statistics except MSE. However, if supplied or other statistics are to be computed, then MSE will be calculated for the fields at values $\geq$ thresholds. If only MSE is to be computed, and thresholds is NULL, then no thresholding is applied. If NULL, and any of the statistics besides MSE are to be calculated, then default values of the 0, 0.1, 0.25, 0.33, 0.5, 0.66, 0.75, 0.9 and 0.95 quantiles (for each field, so that the thresholds may differ between fields) are used. The same holds for anomaly correlation coefficient.
<code>return.fields</code>	logical, should the denoised fields be returned (e.g., for subsequent plotting)?

time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
verbose	logical, should progress information (including total run time) be printed to the screen?
set.pw	logical, should a panel of plots be determined and set by the function (generally ill advised).
col, zlim, horizontal	optional arguments to image, and/or <b>fields</b> functions poly.image and image.plot
type	character string stating whether to plot the resulting statistics or the original fields along with their de-noised counter parts.
...	For wavePurifyVx, optional additional arguments to denoise.dwt.2d (or denoise.modwt.2d) from package <b>waveslim</b> . Note that if the argument J is not passed, then it will be determined as $J = \log_2(\min(m,n))$ . If the fields are dyadic, then the usual DWT is used, otherwise the maximal overlap DWT is used instead. For the plot and summary method functions, these are not used.

### Details

If the fields are dyadic, then the denoise.dwt.2d function from package **waveslim** is applied to each field before calculating the chosen verification statistics. Otherwise denoise.modwt.2d from the same package is used. The result is that high-frequency fluctuations in the two fields are removed before calculating verification statistics so that the resulting statistics are less susceptible to small-scale errors (see Briggs and Levine, 1997). See Percival and Guttorp (1994) and Lindsay et al. (1996) for more on this type of wavelet analysis including maximal overlap DWT.

### Value

A list object of class “wavePurifyVx” is returned with possible components (depending on what is supplied in the arguments, etc.):

X2, Y2	m by n matrices of the denoised verification and forecast fields, resp. (only if return.fields is TRUE).
thresholds	q by 2 matrix of thresholds applied to the forecast (first column) and verification (second column) fields, resp. If climate is not NULL, then the same thresholds for the forecast field are applied to the climatology.
qs	If object and thresholds are NULL, and statistics other than MSE or ACC are desired, then this will be created along with the thresholds, and is just a character version of the thresholds.
args	list object containing all the optional arguments passed into ..., and the value of J used (e.g., even if not passed into ...).
bias, ts, ets, pod, far, f, hk, mse, acc	numeric vectors of length q (i.e., the number of thresholds) giving the associated verification statistics.

### Author(s)

Eric Gilleland

## References

- Briggs, W. M. and Levine, R. A. (1997) Wavelets and field forecast verification. *Mon. Wea. Rev.*, **125**, 1329–1341.
- Lindsay, R. W., Percival, D. B. and Rothrock, D. A. (1996) The discrete wavelet transform and the scale analysis of the surface properties of sea ice. *IEEE Transactions on Geoscience and Remote Sensing*, **34** (3), 771–787.
- Percival, D. B. and Guttorp, P. (1994) Long-memory processes, the Allan variance and wavelets. In *Wavelets in Geophysics*, Foufoula-Georgiou, E. and Kumar, P., Eds., New York: Academic, pp. 325–343.

## See Also

[denoise.dwt.2d](#), [denoise.modwt.2d](#), [waverify2d](#), [mowaverify2d](#), [waveIS](#), [vxstats](#)

## Examples

```
grid<- list( x= seq( 0,5,,100), y= seq(0,5,,100))
obj<-Exp.image.cov( grid=grid, theta=.5, setup=TRUE)
look<- sim.rf( obj)
look[ look < 0] <- 0
look <- zapsmall( look)

look2 <- sim.rf( obj)
look2[ look2 < 0] <- 0
look2 <- zapsmall( look2)

look3 <- sim.rf( obj)
look3[ look3 < 0] <- 0
look3 <- zapsmall( look3)

hold <- make.SpatialVx(look2, look2, thresholds=c(0.1,1),
                      field.type="random", units="units")
plot(hold, set.pw=TRUE)
res <- wavePurifyVx(object=hold, climate=look3, return.fields=TRUE)
plot(res, type="fields")
plot(res, type="stats")
summary(res)

## Not run:
data(UKobs6)
data(UKfcst6)
data(UKloc)

hold <- surrogater2d(UKobs6, n=1, maxiter=50, verbose=TRUE)
hold <- matrix(hold, 256, 256)

UKobj <- make.SpatialVx(UKobs6, UKfcst6, thresholds=c(0.1,2,5,10), loc=UKloc,
                      map=TRUE, field.type="Rainfall", units="mm/h",
                      data.name=c("Nimrod", "obs 6", "fcst 6"))

plot(UKobj, set.pw=TRUE)
```

```

look <- wavePurifyVx(object=UKobj, climate=hold, return.fields=TRUE, verbose=TRUE)
plot(look, type="fields", set.pw=TRUE)
plot(look, type="stats", set.pw=TRUE)
summary(look)

data(pert004)
data(pert000)
hold <- make.SpatialVx( pert000, pert004, thresholds=c(1,10,50), loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("Perturbed ICP Cases", "pert000", "pert004"))
plot(hold, set.pw=TRUE)
look <- wavePurifyVx(object=hold, return.fields=TRUE, verbose=TRUE)
plot(look, type="fields", set.pw=TRUE)
plot(look, type="stats", set.pw=TRUE)
summary(look)

## End(Not run)

```

---

waverify2d

*High-Resolution Gridded Forecast Verification Using Discrete  
Wavelet Decomposition*


---

## Description

High-resolution gridded forecast verification using discrete wavelet decomposition.

## Usage

```

waverify2d(X, ..., Clim = NULL, wavelet.type = "haar", J = NULL)

## Default S3 method:
waverify2d(X, ..., Y, Clim = NULL, wavelet.type = "haar", J =
  NULL, useLL = FALSE, compute.shannon = FALSE,
  which.space = "field", verbose = FALSE)

## S3 method for class 'SpatialVx'
waverify2d(X, ..., Clim = NULL, wavelet.type = "haar", J = NULL,
  useLL = FALSE, compute.shannon = FALSE, which.space = "field",
  time.point = 1, model = 1, verbose = FALSE)

mowaverify2d(X, ..., Clim = NULL, wavelet.type = "haar", J = 4)

## Default S3 method:
mowaverify2d(X, ..., Clim = NULL, Y, wavelet.type = "haar", J = 4,
  useLL = FALSE, compute.shannon = FALSE, which.space = "field", verbose = FALSE)

```



```

## S3 method for class 'SpatialVx'
mowaverify2d(X, ..., Clim = NULL, wavelet.type = "haar", J = 4,
  useLL = FALSE, compute.shannon = FALSE, which.space = "field",
  time.point = 1, model = 1, verbose = FALSE)

## S3 method for class 'waverify2d'
plot(x, ..., main1 = "X", main2 = "Y", main3 = "Climate",
  which.plots = c("all", "dwt2d", "details", "energy", "mse",
  "rmse", "acc"), separate = FALSE, col, horizontal = TRUE)

## S3 method for class 'waverify2d'
print(x, ...)

```

### Arguments

X,Y,Clim	m by n dyadic matrices (i.e., $m = 2^M$ and $n = 2^N$ , for M, N some integers) giving the verification and forecast fields (and optionally a climatology field), resp. Alternatively, X may be a “SpatialVx” object, in which case, Y is not given and in either case Clim must be provided if it is to be used.
x	list object of class “waverify2d” as returned by waverify2d.
wavelet.type	character naming the type of wavelet to be used. This is given as the wf argument to the dwt.2d function of package <b>waveslim</b> .
J	(optional) numeric integer giving the pre-determined number of levels to use. If NULL, J is set to be $\log_2(m) = M$ in waverify2d only.
useLL	logical, should the LL submatrix (i.e., the father wavelet or grand mean) be used to find the inverse DWT’s for calculating the detail fields?
compute.shannon	logical, should the Shannon entropy be calculated for the wavelet decomposition?
which.space	character (one of “field” or “wavelet”) naming from which space the detail fields should be used. If “field”, then it is in the original field (or image) space (i.e., the detail reconstruction), and if “wavelet”, it will be done in the wavelet space (i.e., the detail wavelet coefficients).
time.point	numeric or character indicating which time point from the “SpatialVx” verification set to select for analysis.
model	numeric indicating which forecast model to select for the analysis.
main1,main2,main3	optional characters naming each field to be used for the detail field plots and legend labelling on the energy plot.
which.plots	character vector describing which plots to make. The default is to make all of them. “dwt2d” option uses plot.dwt2d from <b>waveslim</b> . “details” option makes image plots of the detail fields on which the various statistics are calculated. The rest of the options give line plots showing the statistics.
separate	logical, should the plots be on their own devices (TRUE) or should some of them be put onto a single multi-panel device (FALSE, default)?

<code>col</code>	optional argument specifying the <code>col</code> argument in calls to functions like <code>image</code> . Default is a concatenation of gray with <code>time.colors(64)</code> .
<code>horizontal</code>	logical, should the legend on image plots be horizontal (TRUE, placed at the bottom of the plot) or vertical (FALSE, placed at the right side of the plot)?
<code>verbose</code>	logical, should progress information be printed to the screen, including total run time?
<code>...</code>	optional additional plot or <code>image.plot</code> parameters. If detail and energy, mse, rmse or acc plots are desired, must be applicable to both types of plots. Not used by <code>print</code> method function.

### Details

This is a function to use discrete wavelet decomposition to analyze verification sets along the lines of Briggs and Levine (1997), as well as Casati et al. (2004) and Casati (2009). In the originally proposed formulation of Briggs and Levine (1997), continuous verification statistics (namely, the anomaly correlation coefficient (ACC) and root mean square error (RMSE)) are calculated for detail fields obtained from wavelet decompositions of each of a forecast and verification field (and for ACC a climatology field as well). Casati et al. (2004) introduced an intensity scale approach that applies 2-d DWT to binary (obtained from thresholding) difference fields (Forecast - Verification), and applying a skill score at each level based on the mean square error (MSE). Casati (2009) extended this idea to look at the energy at each level as well.

This function makes use of the `dwt.2d` and `idwt.2d` functions from package **waveslim**, and `plot.waverify2d` uses the `plot.dwt.2d` function if `dwt2d` is selected through the `which.plots` argument. See the help file for these functions, the references therein and the references herein for more on these approaches.

Generally, it is not necessary to use the father wavelet for the detail fields, but for some purposes, it may be desired.

`mowaverify2d` is very similar to `waverify2d`, but it allows fields to be non-dyadic (and may subsequently be slower). It uses the `modwt.2d` and `imodwt.2d` functions from the package **waveslim**. In particular, it performs a maximal overlap discrete wavelet transform on a matrix of arbitrary dimension. See the help file and references therein for `modwt.2d` for more information, as well as Percival and Guttorp (1994) and Lindsay et al. (1996).

In Briggs and Levine (1997), they state that the calculations can be done in either the data (called field here) space or the wavelet space, and they do their examples in the field space. If the wavelets are orthogonal, then the detail coefficients (wavelet space), can be analyzed with the assumption that they are independent; whereas in the data space, they typically cannot be assumed to be independent. Therefore, most statistical tests should be performed in the wavelet space to avoid issues arising from spatial dependence.

### Value

A list object of class “waverify2d” with components:

<code>J</code>	single numeric giving the number of levels.
<code>X.wave</code> , <code>Y.wave</code> , <code>Clm.wave</code>	objects of class “dwt.2d” describing the wavelet decompositions for the verification and forecast fields (and climatology, if applicable), resp. (see the help file for <code>dwt.2d</code> from package <b>waveslim</b> for more about these objects).

Shannon.entropy	numeric matrix giving the Shannon entropy for each field.
energy	numeric matrix giving the energy at each level and field.
mse, rmse	numeric vectors of length J giving the MSE/RMSE for each level between the verification and forecast fields.
acc	If a climatology field is supplied, this is a numeric vector giving the ACC for each level.

**Author(s)**

Eric Gilleland

**References**

- Briggs, W. M. and Levine, R. A. (1997) Wavelets and field forecast verification. *Mon. Wea. Rev.*, **125**, 1329–1341.
- Casati, B., Ross, G. and Stephenson, D. B. (2004) A new intensity-scale approach for the verification of spatial precipitation forecasts. *Meteorol. Appl.* **11**, 141–154.
- Casati, B. (2010) New Developments of the Intensity-Scale Technique within the Spatial Verification Methods Inter-Comparison Project. *Wea. Forecasting* **25**, (1), 113–143, doi:10.1175/2009WAF2222257.1.
- Lindsay, R. W., Percival, D. B. and Rothrock, D. A. (1996) The discrete wavelet transform and the scale analysis of the surface properties of sea ice. *IEEE Transactions on Geoscience and Remote Sensing*, **34** (3), 771–787.
- Percival, D. B. and Guttorp, P. (1994) Long-memory processes, the Allan variance and wavelets. In *Wavelets in Geophysics*, Foufoula-Georgiou, E. and Kumar, P., Eds., New York: Academic, pp. 325–343.

**See Also**[dwt.2d](#), [idwt.2d](#), [hoods2d](#)**Examples**

```

grid<- list( x= seq( 0,5,,64), y= seq(0,5,,64))
obj<-Exp.image.cov( grid=grid, theta=.5, setup=TRUE)
look<- sim.rf( obj)
look[ look < 0] <- 0
look <- zapsmall( look)

look2 <- sim.rf( obj)
look2[ look2 < 0] <- 0
look2 <- zapsmall( look2)

res <- waverify2d(look, Y=look2)
plot(res)
summary(res)

## Not run:
data(UKobs6)

```

```

data(UKfcst6)
look <- waverify2d(UKobs6, Y=UKfcst6)
plot(look, which.plots="energy")
look2 <- mowaverify2d(UKobs6, UKfcst6, J=8)
plot(look2, which.plots="energy")

pdf("dyadicDWTex.pdf")
plot(look, main1="NIMROD Analysis", main2="NIMROD Forecast")
dev.off()

pdf("nondyadicMODWTex.pdf")
plot(look2, main1="NIMROD Analysis", main2="NIMROD Forecast")
dev.off()

# Alternative using "SpatialVx" object.
data(UKloc)
hold <- make.SpatialVx(UKobs6, UKfcst6, loc=UKloc,
  map=TRUE, field.type="Rainfall", units="mm/h",
  data.name=c("Nimrod", "Obs 6", "Fcst 6"))
look <- waverify2d(hold)

plot(look, which.plots="details")

data(pert000)
data(pert004)

# The following is slow, but does not require fields to be dyadic.
look <- mowaverify2d(pert000, Y=pert004, J=8, verbose=TRUE)

# Also can just do plot(look), but should print to a pdf file (e.g., using pdf()).
plot(look, which.plots="energy")

# Using a "SpatialVx" object.
data(ICPg240Locs)
hold <- make.SpatialVx(pert000, pert004, loc=ICPg240Locs,
  projection=TRUE, map=TRUE, loc.byrow = TRUE,
  field.type="Precipitation", units="mm/h",
  data.name=c("ICP Perturbed Cases", "pert000", "pert004"))

look <- mowaverify2d(hold, verbose=TRUE)

plot(look, which.plots="details")

# Try one with some kind of climatology field. Here using surrogater2d function.
hold <- surrogater2d(UKobs6, n=1, maxiter=50, verbose=TRUE)
hold <- matrix(hold, 256, 256)
image(hold, col=c("grey",tim.colors(64)), axes=FALSE)
image.plot(UKloc, col=c("grey",tim.colors(64)), legend.only=TRUE, horizontal=TRUE)

look <- waverify2d(UKobs6, Y=UKfcst6, Clim=hold)
pdf("waveletEx.pdf")
plot(look)
dev.off()

```

waverify2d

149

## End(Not run)

# Index

- \*Topic **cluster**
  - clusterer, 16
  - CSIsamples, 29
- \*Topic **datasets**
  - ExampleSpatialVxSet, 39
  - GFSNAMfcstEx, 59
  - hump, 76
  - obs0426, 101
  - UKobs6, 131
- \*Topic **distribution**
  - LocSig, 87
  - MCdof, 94
- \*Topic **graphs**
  - convthresh, 25
  - deltamm, 32
  - FeatureAxis, 40
- \*Topic **hplot**
  - clusterer, 16
  - compositer, 22
  - CSIsamples, 29
  - fss2dPlot, 56
  - GeoBoxPlot, 58
  - hoods2dPlot, 74
  - make.SpatialVx, 89
- \*Topic **htest**
  - EBS, 37
  - FeatureTable, 48
  - LocSig, 87
  - MCdof, 94
  - spatMLD, 121
- \*Topic **manip**
  - combiner, 21
  - compositer, 22
  - convthresh, 25
  - deltamm, 32
  - FeatureTable, 48
  - interester, 77
  - make.SpatialVx, 89
  - MergeForce, 96
  - surrogater2d, 129
- \*Topic **math**
  - abserrloss, 8
  - Aindex, 10
  - bearing, 12
  - centdist, 13
  - Cindex, 15
  - convthresh, 25
  - deltamm, 32
  - FeatureAxis, 40
  - FeatureMatchAnalyzer, 43
  - FeatureProps, 47
  - FQI, 51
  - fss2dfun, 53
  - gmm2d, 60
  - griddedVgram, 64
  - hoods2d, 70
  - locmeasures2d, 81
  - locperf, 84
  - metrV, 98
  - OF, 105
  - optflow, 108
  - pphindcast2d, 110
  - S1, 113
  - saller, 115
  - Sindex, 117
  - spatbiasFS, 119
  - structurogram, 125
  - structurogram.matrix, 127
  - surrogater2d, 129
  - upscale2d, 133
  - vxstats, 135
  - waveIS, 138
  - wavePurifyVx, 141
  - waverify2d, 144
- \*Topic **misc**
  - hiw, 66
- \*Topic **models**
  - gmm2d, 60

- \*Topic **nonparametric**
  - EBS, 37
  - LocSig, 87
  - MCdof, 94
- \*Topic **package**
  - SpatialVx-package, 3
- \*Topic **regression**
  - OF, 105
  - optflow, 108
- \*Topic **spatial**
  - EBS, 37
- \*Topic **ts**
  - EBS, 37
- \*Topic **univar**
  - gmm2d, 60
  - LocSig, 87
  - MCdof, 94
- aaft2d (surrogater2d), 129
- abserrloss, 8, 124
- ACC (S1), 113
- Aindex, 10, 16, 118
- ampstats, 131
- ampstats (FQI), 51
- angles.psp, 41, 48, 69
- as.dendrogram, 20
- as.im, 11, 14, 16, 28
- as.image, 88
- as.psp, 41, 48, 69
- as.rectangle, 86
- atan2, 13
- bearing, 12, 46
- boot, 38, 88
- boot.ci, 88
- bounding.box, 41, 48, 86
- boxplot, 58
- centdist, 13
- centmatch, 21, 46, 50, 97
- centmatch (deltamm), 32
- centroid.owin, 69, 116
- ci.FeatureTable (FeatureTable), 48
- Cindex, 11, 15, 118
- circ.summary, 108
- clip.inline, 41, 48
- clusterer, 16, 31
- combiner, 21
- compositer, 22
- connected, 16, 28, 36, 41, 48, 63, 116
- convexhull, 11, 41, 48
- convthresh, 21, 24, 25, 36, 41, 46, 48, 50, 69
- cor.test, 88, 96
- corrskill, 124
- corrskill (abserrloss), 8
- crossing.psp, 69
- CSIsamples, 20, 29
- cutree, 20
- deltametric, 36, 46, 83, 100
- deltamm, 21, 32, 41, 46, 48, 50, 97, 116
- denoise.dwt.2d, 143
- denoise.modwt.2d, 143
- disjoiner, 36, 41, 48, 63
- disjoiner (convthresh), 25
- distill.FeatureComps (FeatureMatchAnalyzer), 43
- distill.hiw (hiw), 66
- distmap, 83, 86, 100
- distmapfun (locperf), 84
- distmaploss, 124
- distmaploss (abserrloss), 8
- distob, 100
- distob (locperf), 84
- dwt.2d, 140, 147
- EBS, 37
- ExampleSpatialVxSet, 39
- FeatureAxis, 13, 40, 48
- FeatureComps, 14, 80
- FeatureComps (FeatureMatchAnalyzer), 43
- FeatureMatchAnalyzer, 14, 43
- FeatureProps, 14, 47, 80
- FeatureTable, 48
- fft, 73, 131, 134
- fft2d (surrogater2d), 129
- fisherz (MCdof), 94
- fit.spatMLD (spatMLD), 121
- FQI, 51
- fss2dfun, 53
- fss2dPlot, 56
- fuzzyjoint2dfun (fss2dfun), 53
- GeoBoxPlot, 58
- geom000 (obs0426), 101
- geom001 (obs0426), 101
- geom002 (obs0426), 101

- geom003 (obs0426), 101
- geom004 (obs0426), 101
- geom005 (obs0426), 101
- GFSNAMfcstEx, 59
- GFSNAMlocEx (GFSNAMfcstEx), 59
- GFSNAMobsEx (GFSNAMfcstEx), 59
- gmm2d, 60
- griddedVgram, 64
  
- hclust, 20, 31
- hist.OF (OF), 105
- hist.SpatialVx (make.SpatialVx), 89
- hiw, 66
- hoods2d, 55, 57, 70, 75, 92, 112, 134, 137, 140, 147
- hoods2dPlot, 57, 74, 112
- hump, 76
  
- ICPg240Locs (obs0426), 101
- idwt.2d, 140, 147
- im, 86, 100
- image, 57, 75
- image.plot, 38, 57, 75, 88
- imodwt.2d, 140
- inframe, 41, 48
- interester, 46, 77
  
- kernel2dmeitsjer, 114, 134
- kernel2dsmooth, 55, 73, 112, 134
- kmeans, 31
  
- lengths.psp, 41, 48, 69
- lm, 109
- locmeasures2d, 53, 81, 86, 100, 131
- locperf, 46, 53, 84
- LocSig, 38, 87, 96, 120
  
- mae (surrogater2d), 129
- make.SpatialVx, 20, 28, 38, 66, 83, 89, 100, 116
- matplotlib, 57, 75
- MCdof, 88, 94, 120
- MergeForce, 36, 46, 96
- metrV, 86, 98
- midpoints.psp, 41, 48
- MinCvg2dfun (fss2dfun), 53
- modwt.2d, 140
- mowaverify2d, 143
- mowaverify2d (waverify2d), 144
  
- multicon2dfun (fss2dfun), 53
  
- nls, 124
  
- obs0426, 101
- obs0513 (obs0426), 101
- obs0514 (obs0426), 101
- obs0518 (obs0426), 101
- obs0519 (obs0426), 101
- obs0525 (obs0426), 101
- obs0601 (obs0426), 101
- obs0603 (obs0426), 101
- obs0604 (obs0426), 101
- OF, 105, 109
- optflow, 108, 108
- optim, 108, 109, 112
- owin, 28, 36, 41, 48
  
- pdf, 57
- pert000 (obs0426), 101
- pert001 (obs0426), 101
- pert002 (obs0426), 101
- pert003 (obs0426), 101
- pert004 (obs0426), 101
- pert005 (obs0426), 101
- pert006 (obs0426), 101
- pert007 (obs0426), 101
- plot.clusterer (clusterer), 16
- plot.composited (compositer), 22
- plot.CSIsamples (CSIsamples), 29
- plot.EBS (EBS), 37
- plot.FeatureAxis (FeatureAxis), 40
- plot.FeatureMatchAnalyzer (FeatureMatchAnalyzer), 43
- plot.features (convthresh), 25
- plot.gmm2d (gmm2d), 60
- plot.griddedVgram (griddedVgram), 64
- plot.hiw (hiw), 66
- plot.hoods2d, 73, 75
- plot.hoods2d (hoods2d), 70
- plot.LocSig (LocSig), 87
- plot.matched, 97
- plot.matched (deltamm), 32
- plot.OF (OF), 105
- plot.pphindcast2d (pphindcast2d), 110
- plot.spatbiasFS (spatbiasFS), 119
- plot.SpatialVx (make.SpatialVx), 89
- plot.spatMLD (spatMLD), 121
- plot.structurogram (structurogram), 125



- plot.structurogram.matrix  
(structurogram.matrix), 127
- plot.summary.clusterer (clusterer), 16
- plot.summary.CSIsamples (CSIsamples), 29
- plot.summary.features (convthresh), 25
- plot.upscale2d (upscale2d), 133
- plot.vgram.matrix, 128
- plot.waveIS (waveIS), 138
- plot.wavePurifyVx (wavePurifyVx), 141
- plot.waverify2d (waverify2d), 144
- poly.image, 38, 92
- pphindcast2d, 110
- pragmatic2dfun (fss2dfun), 53
- predict.gmm2d (gmm2d), 60
- print.clusterer (clusterer), 16
- print.CSIsamples (CSIsamples), 29
- print.FeatureMatchAnalyzer  
(FeatureMatchAnalyzer), 43
- print.features (convthresh), 25
- print.FeatureTable (FeatureTable), 48
- print.fqi (FQI), 51
- print.gmm2d (gmm2d), 60
- print.hiw (hiw), 66
- print.hoods2d (hoods2d), 70
- print.interester (interester), 77
- print.locmeasures2d (locmeasures2d), 81
- print.matched (deltamm), 32
- print.metrV (metrV), 98
- print.OF (OF), 105
- print.pphindcast2d (pphindcast2d), 110
- print.saller (saller), 115
- print.SpatialVx (make.SpatialVx), 89
- print.upscale2d (upscale2d), 133
- print.waverify2d (waverify2d), 144
- psp, 69
  
- rdist.earth, 13
- rexp, 96
- rgamma, 96
- rnorm, 96
- rotate.owin, 41, 48
- rotate.psp, 41, 48
- runif, 96
  
- S1, 113
- saller, 115
- sig.cor.t, 88
- sig.cor.t (MCdof), 94
- sig.cor.Z, 88
  
- sig.cor.Z (MCdof), 94
- Sindex, 11, 16, 117
- sma, 41, 48
- solutionset, 11, 14, 41, 48, 86, 100
- spatbiasFS, 38, 88, 96, 119
- SpatialVx (SpatialVx-package), 3
- SpatialVx-package, 3
- spatMLD, 10, 121
- sqerrloss, 124
- sqerrloss (abserrloss), 8
- structurogram, 125, 128
- structurogram.matrix, 126, 127
- summary.clusterer (clusterer), 16
- summary.CSIsamples (CSIsamples), 29
- summary.FeatureAxis (FeatureAxis), 40
- summary.FeatureMatchAnalyzer  
(FeatureMatchAnalyzer), 43
- summary.features (convthresh), 25
- summary.FeatureTable (FeatureTable), 48
- summary.fqi (FQI), 51
- summary.gmm2d (gmm2d), 60
- summary.hiw (hiw), 66
- summary.interester (interester), 77
- summary.locmeasures2d (locmeasures2d),  
81
- summary.OF (OF), 105
- summary.saller (saller), 115
- summary.spatbiasFS (spatbiasFS), 119
- summary.SpatialVx (make.SpatialVx), 89
- summary.spatMLD (spatMLD), 121
- summary.waveIS (waveIS), 138
- summary.wavePurifyVx (wavePurifyVx), 141
- surrogater2d, 53, 129
  
- tess, 28, 36, 41, 48, 116
- threshfac, 21, 24, 36, 46, 50, 69
- threshfac (convthresh), 25
- threshsizer, 21, 24, 36, 46, 50, 69
- threshsizer (convthresh), 25
- tiles, 28, 36, 41, 48, 116
- tsboot, 38, 88, 120
- turboem, 63
  
- UIQI, 131
- UIQI (FQI), 51
- UKfcst6 (UKObs6), 131
- UKloc (UKObs6), 131
- UKObs6, 131
- upscale2d, 133

upscale2dfun (fss2dfun), [53](#)  
upscale2dPlot (fss2dPlot), [56](#)

vgram, [10](#), [126](#), [128](#)  
vgram.matrix, [10](#), [66](#), [124](#), [126](#), [128](#)  
vxstats, [55](#), [73](#), [112](#), [135](#), [143](#)

waveIS, [138](#), [143](#)  
wavePurifyVx, [141](#)  
waverify2d, [143](#), [144](#)

wrf2caps0425 (obs0426), [101](#)  
wrf2caps0512 (obs0426), [101](#)  
wrf2caps0513 (obs0426), [101](#)  
wrf2caps0517 (obs0426), [101](#)  
wrf2caps0518 (obs0426), [101](#)  
wrf2caps0524 (obs0426), [101](#)  
wrf2caps0531 (obs0426), [101](#)  
wrf2caps0602 (obs0426), [101](#)  
wrf2caps0603 (obs0426), [101](#)  
wrf4ncar0425 (obs0426), [101](#)  
wrf4ncar0512 (obs0426), [101](#)  
wrf4ncar0513 (obs0426), [101](#)  
wrf4ncar0517 (obs0426), [101](#)  
wrf4ncar0518 (obs0426), [101](#)  
wrf4ncar0524 (obs0426), [101](#)  
wrf4ncar0531 (obs0426), [101](#)  
wrf4ncar0602 (obs0426), [101](#)  
wrf4ncar0603 (obs0426), [101](#)  
wrf4ncep0425 (obs0426), [101](#)  
wrf4ncep0512 (obs0426), [101](#)  
wrf4ncep0513 (obs0426), [101](#)  
wrf4ncep0517 (obs0426), [101](#)  
wrf4ncep0518 (obs0426), [101](#)  
wrf4ncep0524 (obs0426), [101](#)  
wrf4ncep0531 (obs0426), [101](#)  
wrf4ncep0602 (obs0426), [101](#)  
wrf4ncep0603 (obs0426), [101](#)