

Amap Package

Antoine Lucas

March 1, 2014

Contents

1 Overview	1
2 Usage	1
2.1 Clustering	1
2.2 Robust tools	2
3 See Also	2

1 Overview

Amap package includes standard hierarchical clustering and k-means. We optimize implementation (with a parallelized hierarchical clustering) and allow the possibility of using different distances like Eulidean or Spearman (rank-based metric).

We implement a principal component analysis (with robust methods).

2 Usage

2.1 Clustering

The standard way of building a hierarchical clustering:

```
> library(amap)
> data(USArrests)
> h = hcluster(USArrests)
> plot(h)
```

Or for the “heatmap”:

```
> heatmap(as.matrix(USArrests),
+         hclustfun=hcluster,
+         distfun=function(u){u})
```

On a multiprocessor computer:

```
> h = hcluster(USArrests, nbproc=4)
```

The K-means clustering:

```
> Kmeans(USArrests, centers=3, method="correlation")
```

2.2 Robust tools

A robust variance computation:

```
> data(lubisch)
> lubisch <- lubisch[,-c(1,8)]
> varrob(scale(lubisch),h=1)
```

A robust principal component analysis:

```
> p <- acpgen(lubisch,h1=1,h2=1/sqrt(2))
> plot(p)
```

Another robust pca:

```
> p <- acprob(lubisch,h=4)
> plot(p)
```

3 See Also

Theses examples can be tested with command `demo(amac)`.

All functions has got man pages, try `help.start()`.

Robust tools has been published: [2] and [1].

References

- [1] H. Caussinus, M. Fekri, S. Hakam, and A. Ruiz-Gazen. A monitoring display of multivariate outliers. *Computational Statistics and Data Analysis*, 44:237–252, October 2003.
- [2] H. Caussinus, S. Hakam, and A. Ruiz-Gazen. Projections révélatrices contrôlées. recherche d'individus atypiques. *Revue de Statistique Appliquée*, 50(4), 2002.