

# Package ‘biglars’

July 2, 2014

**Type** Package

**Title** Scalable Least-Angle Regression and Lasso

**Version** 1.0.2

**Date** Tue Dec 27 15:06:08 PST 2011

**Author** Mark Seligman, Chris Fraley, Tim Hesterberg

**Maintainer** Mark Seligman <Mark.Seligman@insilicos.com>

**Description** Least-angle regression, lasso and stepwise regression for numeric datasets in which the number of observations is greater than the number of predictors. The functions can be used with the ff library to accomodate datasets that are too large to be held in memory.

**Depends** R (>= 2.10), ff

**License** GPL (>= 2)

**Repository** CRAN

**Date/Publication** 2011-12-28 13:50:26

**NeedsCompilation** yes

## R topics documented:

biglars.fit . . . . .	2
diabetes . . . . .	3
qrBlockApply . . . . .	5

<b>Index</b>	<b>6</b>
--------------	----------

biglars.fit

*Least-Angle, Lasso and Stepwise Regression***Description**

Least-angle, lasso and stepwise methods for linear regression.

**Usage**

```
biglars.fit(x, y, type = "lasso", removeColumns = TRUE,
           eps = sqrt(.Machine$double.eps), blockSize = NULL, maxStages = NULL)
```

**Arguments**

x	A matrix or ff of numeric predictors. The number of columns should not be larger than the number of rows.
y	A numeric response vector or 1-column ff.
type	The type of regression to be performed. The usual choices are <b>lasso</b> lasso method (L1 penalty) <b>lar</b> least-angle regression <b>stepwise</b> forward stepwise regression but see the details section below for other possibilities. Default is "lasso".
removeColumns	A logical scalar indicating whether columns with small variance should be removed from consideration as predictors; default 'TRUE'.
eps	Numerical tolerance used for assessment of sign, equality, rank determination, column removal, etc. The default is the square root of .Machine\$double.eps, the relative machine precision.
blockSize	If NULL, the block size is determined using methods of class ff. Otherwise the passed value is used.
maxStages	The maximum number of stages allowed in the algorithm. This argument applies only to the lasso option. The defaults is 2p for lasso, where p if the number of predictors.

**Details**

An intercept is always included in the regression. This function calls other routines to do the core calculations, one of `biglars.fit.lasso`, `biglars.fit.lar`, or `biglars.fit.stepwise`. These functions are associated with Fraley et-al. (2007) and will not be undergoing further development except for things like bug fixes. For ongoing development of least-angle regression, see the `glars` library.

**Value**

A list with the following elements:

coef	An array of regression coefficients for each stage.
moves	Any array describing variables added or removed at each stage.
RSS	Residual sum of squares.

**References**

B. Efron, T. Hastie, I. Johnstone and R. Tibshirani (2004), "Least Angle Regression" (with discussion), *Annals of Statistics* **32**, 407-499.

C. Fraley and T. Hesterberg (2007), "Least-Angle Regression for Large Datasets", Technical Report, Insightful Corporation.

**See Also**

[qrBlockApply](#)

**Examples**

```
data(diabetes)

larFit <- biglars.fit(diabetes$x, diabetes$y, type = "lar")
larFitBlocked <- biglars.fit(diabetes$x, diabetes$y, type = "lar",
                             blockSize = 50)

lassoFit <- biglars.fit(diabetes$x, diabetes$y, type = "lasso")
lassoFitBlocked <- biglars.fit(diabetes$x, diabetes$y, type = "lasso",
                               blockSize = 34)
```

---

diabetes

*Blood and other measurements in diabetics*

---

**Description**

The diabetes1 data frame has 442 rows and 1 columns. These are the data used in the Efron et al "Least Angle Regression" paper.

The diabetes data frame has 442 rows and 3 matrices, containing predictors, response, and interactions.

**Format**

diabetes1 is a data frame with 442 observations on the following 11 variables.

age a numeric vector  
sex a numeric vector  
bmi a numeric vector  
map a numeric vector  
tc a numeric vector  
ldl a numeric vector  
hdl a numeric vector  
tch a numeric vector  
ltg a numeric vector  
glu a numeric vector  
y a numeric vector

In the sex variable, 1 indicates female and 2 male.

diabetes is a data frame containing the following objects:

x a matrix with 10 columns—the first 10 columns from diabetes1, standardized  
y a numeric vector  
x2 a matrix with 64 columns—main effects and second-order interactions

**Details**

The x matrix is standardized to have unit L2 norm in each column and zero mean. The matrix x2 consists of x plus second-order powers and interactions, also standardized.

**Source**

[http://www-stat.stanford.edu/~hastie/Papers/LARS/LeastAngle\\_2002.ps](http://www-stat.stanford.edu/~hastie/Papers/LARS/LeastAngle_2002.ps)

**References**

B. Efron and T. Hastie (2003), "LARS software for R and Splus", <http://www-stat.stanford.edu/~hastie/Papers/LARS>  
B. Efron, T. Hastie, I. Johnstone and R. Tibshirani (2004), "Least Angle Regression" (with discussion), *Annals of Statistics* **32**, 407-499.

**Examples**

```
data(diabetes)

stepFit <- biglars.fit(diabetes$x, diabetes$y, type = "stepwise")
stepFitBlocked <- biglars.fit(diabetes$x, diabetes$y, type = "stepwise",
                             blockSize = 50)

lassoFit <- biglars.fit(diabetes$x, diabetes$y)
lassoFitBlocked <- biglars.fit(diabetes$x, diabetes$y, blockSize = 34)
```

---

`qrBlockApply`*Blockwise Cholesky Factorization*

---

**Description**

Cholesky factorization of a crossproduct matrix via blockwise orthogonal transformation.

**Usage**

```
qrBlockApply(x, y = NULL, blockSize = NULL)
```

**Arguments**

<code>x</code>	A numeric matrix or <code>ff</code> . The number of columns should not be larger than the number of rows.
<code>y</code>	An optional numeric vector or 1 column <code>ff</code> of responses.
<code>blockSize</code>	This is used for setting the block size for sequential access. The default is determined by methods from class <code>ff</code> .

**Value**

A list with the following elements:

<code>R</code>	Upper triangular Cholesky factor of <code>crossprod(x)</code> .
<code>Qty</code>	The corresponding transformation of <code>y</code> .

**References**

C. Fraley and T. Hesterberg (2007), "Least-Angle Regression for Large Datasets", Technical Report, Insightful Corporation.

**See Also**

[biglars.fit](#)

**Examples**

```
data(diabetes)

qrx <- qr(diabetes$x)

list(R = qr.R(qrx), Qty = crossprod(qr.Q(qrx), diabetes$y))

qrBlockApply(diabetes$x, diabetes$y, blockSize = 34)
```

# Index

\*Topic **datasets**

diabetes, [3](#)

\*Topic **regression**

biglars.fit, [2](#)

qrBlockApply, [5](#)

biglars.fit, [2](#), [5](#)

diabetes, [3](#)

diabetes1 (diabetes), [3](#)

qrBlock (qrBlockApply), [5](#)

qrBlockApply, [3](#), [5](#)