

Package ‘cocorresp’

July 2, 2014

Type Package

Title Co-correspondence analysis methods

Version 0.2-1

Date 2011-Sep-20

Depends stats, graphics, vegan (>= 1.17-12)

Author Original Matlab routines by C.J.F. ter Braak and A.P. Schaffers. R port by Gavin L. Simpson.
Function `simpls` based on `simpls.fit` (package `pls`) by Ron Wehrens and Bjorn-Helge Mevik.

Maintainer Gavin L. Simpson <ucfagls@gmail.com>

Description Fits predictive and symmetric co-correspondence analysis (CoCA) models to relate one data matrix to another data matrix. More specifically, CoCA maximises the weighted covariance between the weighted averaged species scores of one community and the weighted averaged species scores of another community. CoCA attempts to find patterns that are common to both communities.

License GPL-2

URL <http://cocorresp.r-forge.r-project.org>

BugReports

https://r-forge.r-project.org/tracker/?atid=737&group_id=181&func=browse

NeedsCompilation no

Repository CRAN

Date/Publication 2013-12-14 00:39:49

R topics documented:

cocorresp-package	2
beetles	3
bryophyte	4
coca	4
coinertia	8
coinertial	9
corAxis	10
crossval	11
envfit.coca	13
fitCoinertia	15
fitted.symcoca	17
mcChi	18
permutest.coca	19
plot.predcoca	21
plot.symcoca	23
points.coca	25
rescale	26
resid.symcoca	27
scaleChi	28
scores.predcoca	29
simpls	30
summary.predcoca	32
weights.symcoca	34

Index	36
--------------	-----------

cocorresp-package	<i>Co-correspondence analysis ordination methods for community ecology</i>
-------------------	--

Description

Fits predictive and symmetric co-correspondence analysis (CoCA) models to relate one data matrix to another data matrix. More specifically, CoCA maximises the weighted covariance between the weighted averaged species scores of one community and the weighted averaged species scores of another community. CoCA attempts to find patterns that are common to both communities.

Details

Package:	cocorresp
Type:	Package
Version:	0.2-1
Date:	2013-12-12
Depends:	vegan
License:	GPL Version 2
Encoding:	UTF-8

Author(s)

Original Matlab routines by C.J.F. ter Braak and A.P. Schaffers. R port by Gavin L. Simpson.
Function `simpls` based on `simpls.fit` (package `pls`) by Ron Wehrens and Bjorn-Helge Mevik.

Maintainer: Gavin L. Simpson <gavin.simpson@ucl.ac.uk>

beetles

Carabid beetles and vascular plants in Dutch roadside verges

Description

Counts of 126 beetle taxa and abundances of 173 vascular plant taxa (expressed on the 1-9 van der Maarel scale) in 30 road-side verges in the Netherlands.

Usage

`data(beetles)`

`data(plants)`

`data(verges)`

Details

This is the complete dataset of Raemakers et al (2001). ter Braak and Schaffers (2004) only analyse a subset of 91 beetle taxa.

Source

Raemakers, I.P., Schaffers, A.P., Sykora, V. and Heijerman, T. (2001) The importance of plant communities in road verges as habitat for insects. *Proceedings of the Section Experimental and Applied Entomology of the Netherlands Entomological Society* **12**, 101–106.

ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

Examples

`data(beetles)`

`data(plants)`

 bryophyte

Bryophytes and vascular plants in Carpathian spring meadows

Description

The data consist of observations on 30 bryophyte and 123 vascular plant species in 70 spring meadows (sites, samples). The species data are a subset of only those species occurring in five or more meadows.

Usage

```
data(bryophyte)
data(vascular)
```

Source

Hajek, M., Hekera, P. and Hajkova, P. (2002) Spring fen vegetations and water chemistry in the Western Carpathian flysch zone. *Folia geobotanica* **37**, 205–224

ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85(3)**, 834–846

Examples

```
data(bryophyte)
data(vascular)
```

 coCa

Fit Co-Correspondence Analysis Ordination Models

Description

coCa is used to fit Co-Correspondence Analysis (CoCA) models. It can fit predictive or symmetric models to two community data matrices containing species abundance data.

Usage

```
coCa(y, ...)

## Default S3 method:
coCa(y, x, method = c("predictive", "symmetric"),
     reg.method = c("simpls", "eigen"), weights = NULL,
     n.axes = NULL, symmetric = FALSE, ...)

## S3 method for class 'formula'
coCa(formula, data, method = c("predictive", "symmetric"),
     reg.method = c("simpls", "eigen"), weights = NULL,
     n.axes = NULL, symmetric = FALSE, ...)
```

Arguments

<code>y</code>	a data frame containing the response community data matrix.
<code>x</code>	a data frame containing the predictor community data matrix.
<code>formula</code>	a symbolic description of the model to be fit. The details of model specification are given below.
<code>data</code>	an optional data frame containing the variables in the model. If not found in <code>data</code> , the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>coca</code> is called.
<code>method</code>	a character string indicating which co-correspondence analysis method to use. One of "predictive"(default), or "symmetric", can be abbreviated.
<code>reg.method</code>	One of "simpls" (default) or "eigen". If <code>method</code> is "predictive" then <code>reg.method</code> controls whether the co-correspondence analysis should be fitted using the SIMPLS algorithm or via an eigen analysis.
<code>weights</code>	a vector of length <code>nrow(y)</code> of user supplied weights for R_0 . If <code>weights = NULL</code> (default) then the weights are determined from <code>y</code> (default) or <code>x</code> and <code>y</code> (<code>symmetric = TRUE</code> only).
<code>n.axes</code>	the number of CoCA axes to extract. If missing (default) the <code>n.axes</code> is $\min(ncol(y), ncol(x), nrow(y), nrow(x)) - 1$
<code>symmetric</code>	if <code>method</code> is "symmetric" then <code>symmetric</code> determines whether weights for R_0 are symmetric and taken as the average of the row sums of <code>x</code> and <code>y</code> (<code>symmetric = TRUE</code>). If <code>symmetric = FALSE</code> (default) then the weights R_0 are taken as the row sums of <code>y</code> unless user defined weights are provided via argument <code>weights</code> . Ignored if <code>method</code> is "predictive".
<code>...</code>	additional arguments to be passed to lower level methods.

Details

`coca` is the main user-callable function.

A typical model has the form `response ~ terms` where `response` is the (numeric) response data frame and `terms` is a series of terms which specifies a linear predictor for `response`. A typical form for `terms` is `.`, which is shorthand for "all variables" in `data`. If `.` is used, `data` must also be provided. If specific species (variables) are required then `terms` should take the form `spp1 + spp2 + spp3`.

The default is to fit a predictive CoCA model using SIMPLS via a modified version of `simpls.fit` from package `pls`. Alternatively, `reg.method = "eigen"` fits the model using an older, slower eigen analysis version of the SIMPLS algorithm. `reg.method = "eigen"` is about 100% slower than `reg.method = "simpls"`.

Value

`coca` returns a list with `method` and `reg.method` determining the actual components returned.

nam.dat	list with components namY and namX containing the names of the response and the predictor(s) respectively.
call	the matched call.
method	the CoCA method used, one of "predictive" or "symmetric".
scores	the species and site scores of the fitted model.
loadings	the site loadings of the fitted model for the response and the predictor. (Predictive CoCA via SIMPLS only.)
fitted	the fitted values for the response. A list with 2 components Yhat (the fitted values) and Yhat1 (the transformed fitted values. (Predictive CoCA via SIMPLS only.)
varianceExp	list with components Yblock and Xblock containing the variances in the response and the predictor respectively, explained by each fitted PLS axis. (Predictive CoCA via SIMPLS only.)
totalVar	list with components Yblock and Xblock containing the total variance in the response and the predictor respectively. (Predictive CoCA via SIMPLS only.)
lambda	the Eigenvalues of the analysis.
n.axes	the number of fitted axes
Ychi	a list containing the mean-centered chi-square matrices for the response (Ychi1) and the predictor (Ychi2). (Predictive CoCA only.)
R0	the (possibly user-supplied) row weights used in the analysis.
X	X-Matrix (symmetric CoCA only).
residuals	Residuals of a symmetric model (symmetric CoCA only).
inertia	list with components total and residual containing the total and residual inertia for the response and the predictor (symmetric CoCA only).
rowsum	a list with the row sums for the response (rsum1) and the predictor (rsum2) (symmetric CoCA only).
colsum	a list with the column sums for the response (csum1) and the predictor (csum2) (symmetric CoCA only).

Author(s)

Original Matlab code by C.J.F. ter Braak and A.P. Schaffers. R port by Gavin L. Simpson. Formula method for coca uses a modified version of [ordiParseFormula](#) by Jari Oksanen to handle formulae.

References

ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

See Also

[crossval](#) for cross-validation and [permutest.coca](#) for permutation test to determine the number of PLS axes to retain in for predictive CoCA.

[summary.predcoca](#) and [summary.symcoca](#) for summary methods.

Examples

```
## symmetric CoCA
data(beetles)
## log transform the beetle data
beetles <- log(beetles + 1)
data(plants)
## fit the model
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")
bp.sym
summary(bp.sym)
plot(bp.sym)

## predictive CoCA using SIMPLS and formula interface
bp.pred <- coca(beetles ~ ., data = plants)
## should retain only the useful PLS components for a parsimonious model

## Leave-one-out crossvalidation - this takes a while

## Not run:
crossval(beetles, plants)
## so 2 axes are sufficient
## permutation test to assess significant PLS components - takes a while
bp.perm <- permutest(bp.pred, permutations = 99)
bp.perm
## End(Not run)

## agrees with the Leave-one-out cross-validation
## refit the model with only 2 PLS components
bp.pred <- coca(beetles ~ ., data = plants, n.axes = 2)
bp.pred
summary(bp.pred)
plot(bp.pred)

## predictive CoCA using Eigen-analysis
data(bryophyte)
data(vascular)
carp.pred <- coca(y = bryophyte, x = vascular, reg.method = "eigen")
carp.pred

## determine important PLS components - takes a while
## Not run:
crossval(bryophyte, vascular)
(carp.perm <- permutest.coca(carp.pred, permutations = 99))
## End(Not run)

## 2 components again, refit
carp.pred <- coca(y = bryophyte, x = vascular,
                 reg.method = "eigen", n.axes = 2)
carp.pred
## plot
plot(carp.pred)
```

 coinertia

Co-inertia analysis

Description

Performs a co-inertia of the triplets (Q_1, K_1, R_0) and (Q_2, K_2, R_0) .

Usage

```
coinertia(y, ...)
```

```
## Default S3 method:
```

```
coinertia(y, x, n.axes = NULL, weights = NULL,
          symmetric = FALSE, ...)
```

Arguments

<code>y, x</code>	matrices or data frames of the two data sets for which axes of covariance are sought.
<code>n.axes</code>	numeric; the number of coinertia axes to retain.
<code>weights</code>	a vector of weights for the samples. If NULL, weights are chosen from the row sums of <code>y</code> (<code>symmetric = FALSE</code>) or the average of the row sums of <code>y</code> and <code>x</code> (<code>symmetric = TRUE</code>).
<code>symmetric</code>	logical; should a symmetric set of weights be used. See Details.
<code>...</code>	arguments passed to other functions. Currently ignored.

Value

An object of class "coinertia", which is a list with the following components:

<code>scores</code>	a list of ordination scores, with components <code>species</code> and <code>sites</code> , each of which is a list with components <code>Y</code> and <code>X</code> that refer to the scores for the input matrices <code>y</code> and <code>x</code> respectively.
<code>weights</code>	numeric vector of row weights used in the analysis.
<code>lambda</code>	numeric vector of Eigenvalues.
<code>n.axes</code>	numeric; the number of coinertia axes extracted
<code>symmetric</code>	logical; was a symmetric analysis performed?
<code>call</code>	the matched call.

Author(s)

Gavin L. Simpson, based on original Matlab code by C.J.F. ter Braak and A.P. Schaffers.

References

Ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

Doledec, S and Chessel, D. (1994) Co-inertia analysis: a method for studying species-environment relationships. *Freshwater Biology* **31**, 277–294

See Also

[symcoca](#) for the function that calls `fitCoinertia` and `coinertiaI` for co-inertia analysis using identity matrices for K_1 , K_2 , and R_0 .

Examples

```
data(beetles, plants)
coin <- coinertia(beetles, plants)
coin
```

`coinertiaI`*Coinertia analysis with identity matrices*

Description

Performs a co-inertia of the triplets (Q_1, K_1, R_0) and (Q_2, K_2, R_0) with identity matrices K_1, K_2, R_0 .

Usage

```
coinertiaI(X, Y, fast = TRUE)
```

Arguments

X	Species matrix X.
Y	Species Matrix Y.
fast	If "TRUE" only return the row scores of Y.

Details

Argument `fast` is used to return only the row scores of Y in function `permutest.coca`, which speeds the permutation test considerably.

Value

If `fast = TRUE`, a matrix of row scores for matrix `Y` (see scores below). If `fast = FALSE` a list with the following components:

<code>weights</code>	A list with components <code>X</code> and <code>Y</code> containing the left and right singular vectors respectively of the SVD on the triplets.
<code>scores</code>	A list with components <code>X</code> and <code>Y</code> , containing the row scores of the <code>X</code> and <code>Y</code> species matrices. These are the result of a matrix multiplication of <code>X</code> by the left singular vectors and <code>Y</code> by the right singular vectors.
<code>lambda</code>	the Eigenvalues of the analysis (the square of the singular values from the SVD).
<code>call</code>	the matched function call.

Note

This function is not meant to be called directly by the user. If you wish to use it study the code in [permutest.coca](#) to see how it should be called.

Author(s)

Original Matlab code by C.J.F. ter Braak and A.P. Schaffers. R port by Gavin L. Simpson.

References

Doledec, S and Chessel, D. (1994) Co-inertia analysis: a method for studying species-environment relationships. *Freshwater Biology* **31**, 277–294.

See Also

[coinertia](#)

corAxis

Correlation between ordination axes

Description

Calculates the Pearson product-moment correlation coefficient for the site scores of ordination axes.

Usage

```
corAxis(x, ...)

## Default S3 method:
corAxis(x, ...)

## S3 method for class 'symcoca'
corAxis(x, axes = c(1:min(6, x$n.axes)), ...)
```

Arguments

x	an ordination object. Only methods for objects of class <code>symcoca</code> are currently available.
axes	the number of axes to calculate the correlation coefficients for.
...	arguments to be passed on to other methods.

Value

A named vector containing the correlation coefficients for the requested axes.

Note

The arguments for `cor` are hard coded at their defaults, see `cor` for details. A more flexible version is planned that will allow arguments to be passed to `cor`.

Author(s)

Gavin L. Simpson

See Also

`cor`, for the main analysis function.

Examples

```
## load some data
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## symmetric Co-CA model
beetles.sym <- coca(beetles ~ ., data = plants, method = "symmetric")

## correlations between axes
corAxis(beetles.sym)
```

Description

Performs a leave-one-out cross-validation of a predictive Co-Correspondence Analysis model.

Usage

```
crossval(y, x, n.axes = min(dim(x), dim(y)) - 1,
        centre = TRUE, verbose = TRUE)
```

```
## S3 method for class 'crossval'
summary(object, axes = c(1:min(6, object$n.axes)), ...)
```

Arguments

y	the response species matrix.
x	the predictor species matrix.
n.axes	the number of axes to calculate the leave-one-out cross-validation for. Default is to perform the CV for all extractable axes.
centre	centre y and x during analysis? Currently ignored as it may not be necessary.
verbose	if TRUE, the default, print information on the progress of the cross-validation procedure.
object	an object of class <code>crossval</code> as returned by <code>crossval</code> .
axes	the number of axes to summarise results for.
...	further arguments to print - currently ignored.

Details

Performs a leave-one-out cross-validation of a predictive Co-Correspondence Analysis model. It can be slow depending on the number of columns in the matrices, and of course the number of sites.

Value

Returns a large list with the following components:

dimx, dimy	the dimensions of the input matrices x and y respectively.
press0	the <i>press</i> ₀ statistic.
n.axes	the number of axes tested.
CVfit	the cross-validatory fit.
varianceExp	list with components Yblock and Xblock containing the variances in the response and the predictor respectively, explained by each fitted PLS axis.
totalVar	list with components Yblock and Xblock containing the total variance in the response and the predictor respectively.
nam.dat	list with components namY and namX containing the names of the response and the predictor(s) respectively.
call	the R call used.

Note

This function is not a bit out-of-date compared to some of the other functions. It should have a formular interface like `coca` or work on the results from `coca`, although that will have to be altered to store a copy of the data?

Author(s)

Gavin L. Simpson, based on Matlab code by C.J.F. ter Braak and A.P. Schaffers.

See Also

The model fitting function `coca`

Examples

```
## load the data sets
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## predictive CoCA using SIMPLS and formula interface
bp.pred <- coca(beetles ~ ., data = plants)
## should retain only the useful PLS components for a
## parsimonious model

## Leave-one-out crossvalidation - this takes a while
## Not run:
crossval(beetles, plants)

## End(Not run)
## so 2 axes are sufficient
```

`envfit.coca`*Fit an environmental vector or factor to a Co-CA ordination*

Description

The function fits environmental vectors or factors to a Co-CA ordination. The projections of points onto vectors have maximum correlation with corresponding environmental variables, and the factors show the averages of factor levels.

Usage

```
## S3 method for class 'coca'
envfit(ord, env, which = c("response", "predictor"),
       choices = c(1, 2), scaling = FALSE, w, na.rm = FALSE,
       strata, permutations = 999, ...)
```

Arguments

ord	a Co-CA ordination object, the result of a call to coca .
env	a data frame, matrix or vector of environmental/external variable(s) to be fitted to the ordination. The variables may be of a mixed type (factors and continuous variables) in a data frame.
which	character; which of the response or predictor ordinations should be used during fitting of vectors and factors.
choices	numeric; the axes to which vectors and factors are fitted.
scaling	logical; should scaling be applied. See scores.symcoca .
w	weights used in fitting vectors and factors.
na.rm	Remove points with missing values in ordination scores or environmental variables. The operation is casewise; the whole row of data is removed if there is a missing value and na.rm = TRUE.
strata	An integer vector or factor specifying the strata for permutation. If supplied, observations are permuted only within the specified strata.
permutations	Number of permutations for assessing significance of vectors or factors. Set to 0 to skip permutations.
...	Arguments passed to vectorfit and factorfit .

Details

See [envfit](#) for details of the method.

Value

Returns an object of class [envfit](#).

Author(s)

Gavin L. Simpson. The code interfaces with and uses code from [envfit](#) for the main computations, which was written by Jari Oksanen.

See Also

[coca](#) for fitting models. [envfit](#) for details of the generic function and the computations performed.

Examples

```
## symmetric CoCA
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## fit the model
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")

## load the environmental data
data(verges)

## fit vectors for the environmental data
sol <- envfit(bp.sym, verges, which = "response")
sol

## plot the response matrix and the fitted vectors
plot(bp.sym)
plot(sol)
```

fitCoinertia

Co-inertia analysis

Description

Performs a co-inertia of the triplets (Q_1, K_1, R_0) and (Q_2, K_2, R_0) .

Usage

```
fitCoinertia(X, Dp, Y, Dq, Dn, n.axes)
```

```
## S3 method for class 'fitCoinertia'
summary(object, ...)
```

Arguments

X	Q_1 , matrix of expected abundances under row-column independence in the original Y species matrix when treated as a contingency table.
Dp	K_1 , species (column) weights for X.

Y	Q_2 , matrix of expected abundances under row-column independence in the original X species matrix when treated as a contingency table.
Dq	K_2 , species (column) weights for Y.
Dn	site weights R_0 .
n.axes	number of axes to calculate the co-inertia analysis for.
object	an object of class <code>coinertia</code> .
axes	the number of axes to display when printing.
...	arguments passed to other functions. Currently ignored.

Value

A list with the following components:

U1	column weights of X.
U2	column weights of Y.
X1	rowscores of X.
X2	rowscores of Y.
lambda	the Eigenvalues (squares of the singular values).
n.axes	number of axes requested.
call	the matched function call.

Note

This function is not yet meant to be called directly by the user. If you wish to use it directly, see the function definition for [symcoca](#) which demonstrates how to prepare the relevant input matrices.

Note that in this function, X corresponds to the input matrix y and Y corresponds to the input matrix x in [symcoca](#). Confusing! This will be changed in a future release but for now the arguments follow those of the original Matlab code - perhaps a little too closely!

Author(s)

Original Matlab code by C.J.F. ter Braak and A.P. Schaffers. R port by Gavin L. Simpson.

References

- Ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846
- Doledec, S and Chessel, D. (1994) Co-inertia analysis: a method for studying species-environment relationships. *Freshwater Biology* **31**, 277–294

See Also

[symcoca](#) for the function that calls `fitCoinertia` and `coinertiaI` for co-inertia analysis using identity matrices for K_1 , K_2 , and R_0

fitted.symcoca	<i>Fitted values of a Symmetric Co-Correspondence analysis model.</i>
----------------	---

Description

Calculates and extracts the fitted values of a Symmetric Co-Correspondence analysis model.

Usage

```
## S3 method for class 'symcoca'  
fitted(object, ...)
```

Arguments

object	an object of class "symcoca"
...	arguments to be passed to other methods.

Value

A list with the following components:

Yhat1	the fitted values for the "response" matrix.
Yhat2	the fitted values for the "predictor" matrix.
nam.dat	a vector containing the names of the "response" and "predictor" matrices respectively. Used for printing the results.

Note

This function needs an update and to allow option to restrict fitted values to specified axes, and the names of the returned objects need making more obvious!

Author(s)

Gavin L. Simpson, based on Matlab code by C.J.F. ter Braak and A.P. Schaffers.

References

Ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

See Also

The model fitting function [coca](#)

Examples

```
## symmetric CoCA
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## fit the model
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")

## fitted values
bp.fit <- fitted(bp.sym)
bp.fit
```

mcChi

Standardised chi-square residuals

Description

Scales a matrix, Y, to its standardised chi-square residuals $(o-e)/\sqrt{e}$ (if $R_0 = R$, where R contains the row sums of matrix Y) so that further analysis can be unweighted

Usage

```
mcChi(Y, R0, eps = 1e-06)
```

Arguments

Y	a matrix for which standardised chi-square residuals are to be calculated.
R0	row weights.
eps	tolerance - leave as default.

Details

This function implements equation 8 of ter Braak and Schaffers (2004) by firstly applying equation 7 to form matrix Q using row and column sums of Y as weights, and, secondly, by applying equation 8 to form a matrix of standardised chi-square residuals from Q by pre-multiplication of Q by $\sqrt{R_0}$ and post-multiplication of Q by \sqrt{K} , where K is the column sums of Y.

Value

A list with the following components:

Ychi	the matrix of standardised chi-squared residuals of Y
Kn	the column sums (K) of Y divided by sum(K)

Note

This function is not intended for casual use by users.

Author(s)

Gavin L. Simpson, based on Matlab code by C.J.F. ter Braak and A.P. Schaffers.

References

Ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85(3)**, 834–846

permutest.coca	<i>Permutation test for predictive co-correspondence analysis models</i>
----------------	--

Description

A permutation test for predictive co-correspondence analysis models to assess the significance of each CoCA ordination axes.

Usage

```
## S3 method for class 'coca'
permutest(x, R0 = NULL, permutations = 99,
          n.axes = x$n.axes, verbose = TRUE, ...)
```

```
## S3 method for class 'permutest.coca'
summary(object, ...)
```

Arguments

x	an object of class "predcoca".
R0	row weights to use in the analysis. If missing, the default, these are determined from x.
permutations	the number of permutations to perform.
n.axes	The number of axes to test. Defaults to the number of axes stated in x\$n.axes.
verbose	if TRUE, the default, print information on the progress of the permutation test procedure.
object	an object of class "permutest.coca".
...	arguments to be passed to other methods.

Details

An alternative approach to cross-validation (see [crossval](#)) to select the number of axes to retain in a predictive co-correspondence analysis is to test the statistical significance of each ordination axis using permutation tests.

The test statistic used is the F -ratio based on the fit of the first axis to the response data (ter Braak and Smilauer 2002). The second and subsequent axes are tested by treating previous axes as co-variables.

To be precise, this approach does not test the significance of SIMPLS axes, but those of NIPALS-PLS axes (ter Braak and de Jong 1998).

Value

A list with the following components:

pval	a vector of P -values for each ordination axis.
permstat	a vector of values for the test statistic for each axis.
total.inertia	the total inertia in the response matrix.
inertia	a vector containing the inertia explained by each ordination axis.
fitax	a vector containing the fit of each axis to response.
pcent.fit	a vector containing the fit of each axis to the response as a percentage of the total inertia (variance).
n.axes	the number of axes in the ordination.
call	the matched call.

Warning

This function is **slow**. Beware setting argument `permutations` higher than the default. Determine how long it takes for the default 99 permutations to complete before going crazy and asking for thousands of permutations - you've been warned, have a good book to hand.

Note

Argument `R0` is provided for compatibility with the original MATLAB code. The R usage paradigm makes this argument redundant in the current code and it may be invalid to supply different row weights (R_0) as `R0`. This argument will likely be removed in future versions.

Author(s)

Gavin L. Simpson, based on Matlab code by C.J.F. ter Braak and A.P. Schaffers.

References

- ter Braak, C.J.F. and de Jong, S. (1998) The objective function of partial least squares regression. *Journal of Chemometrics* **12**, 41–54.
- ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846.

ter Braak, C.J.F. and Smilauer, P. (2002) *Canoco reference manual and CanoDraw for Windows user's guide: software for canonical community ordination. Version 4.5*. New York: Microcomputer Power.

See Also

[coca](#), for the model fitting function, [crossval](#), for a leave-one-out cross-validation procedure, which is the preferred way to select axes in a predictive co-correspondence analysis.

Examples

```
## load some data
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)
## predictive CoCA using SIMPLS and formula interface
bp.pred <- coca(beetles ~ ., data = plants)

## should retain only the useful PLS components for a parsimonious model
## Not run:
## Leave-one-out crossvalidation - this takes a while
crossval(beetles, plants)
## so 2 axes are sufficient

## permutation test to assess significant PLS components - takes a while
bp.perm <- permutest(bp.pred, permutations = 99)
bp.perm
summary(bp.perm)

## End(Not run)

## permutation test, this time only testing the first 2 axes
bp.perm <- permutest(bp.pred, permutations = 99, n.axes = 2)
bp.perm
```

plot.predcoca

Biplots for predictive co-correspondence analysis

Description

Produces biplots of the response and predictor from the results of a predictive co-correspondence analysis.

Usage

```
## S3 method for class 'predcoca'
plot(x,
      which = c("response", "predictor"),
      choices = 1:2,
      display = c("species", "sites"),
      type,
      xlim = NULL,
      ylim = NULL,
      main = "",
      sub = "",
      ylab, xlab,
      ann = par("ann"),
      axes = TRUE,
      ...)
```

Arguments

x	an object of class "predcoca", the result of a call to coca .
which	character; should the response or predictor scores be plotted.
choices	a vector of length 2 indicating which predictive CoCA axes to plot.
display	which sets of scores are drawn. See scores.predcoca .
type	one of "points", "text", or "none". Determines how the site and species scores are displayed. If type = "points", scores are plotted as points. If type = "text", then the row names of the scores matrices are plotted. If type = "none", then the scores are not plotted.
xlim, ylim	limits for the x and y axes. If non supplied, suitable limits will be determined from the data.
xlab, ylab	labels for the x and y axes. If non supplied suitable labels are formed from the result object.
main, sub	the main and sub titles for the plot.
ann	logical, if TRUE plots are annotated and not if FALSE, currently ignored.
axes	a logical value indicating whether both axes should be drawn on the plot.
...	other graphical parameters as in 'par' may also be passed as arguments.

Author(s)

Gavin L. Simpson.

References

Ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

See Also[coca](#), [plot.default](#)**Examples**

```
## predictive CoCA
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## predictive CoCA using SIMPLS and formula interface
bp.pred <- coca(beetles ~ ., data = plants)

## draw the biplot for the response
plot(bp.pred)

## plot of both
layout(matrix(1:2, ncol = 2))
plot(bp.pred, which = "response", main = "Beetles")
plot(bp.pred, which = "predictor", main = "Plants")
layout(1)
```

plot.symcoca

Biplots for symmetric co-correspondence analysis

Description

Produces biplots of the response and predictor from the results of a symmetric co-correspondence analysis.

Usage

```
## S3 method for class 'symcoca'
plot(x,
      which = c("response", "predictor"),
      choices = 1:2,
      display = c("species", "sites"),
      scaling = FALSE,
      type,
      xlim = NULL,
      ylim = NULL,
      main = "",
      sub = "",
      ylab, xlab,
      ann = par("ann"),
      axes = TRUE,
      ...)
```

Arguments

x	an object of class "symcoca", the result of a call to symcoca .
which	character; should the response or predictor scores be plotted.
choices	a vector of length 2 indicating which predictive CoCA axes to plot.
display	which sets of scores are drawn. See scores.symcoca .
scaling	logical, whether scaling should be applied. See scores.symcoca .
type	one of "points", "text", or "none". Determines how the site and species scores are displayed. If type = "points", scores are plotted as points. If type = "text", then the row names of the scores matrices are plotted. If type = "none", then the scores are not plotted.
xlim, ylim	limits for the x and y axes. If non supplied, suitable limits will be determined from the data.
xlab, ylab	labels for the x and y axes. If non supplied suitable labels are formed from the result object.
main, sub	the main and sub titles for the plot.
ann	logical, if TRUE plots are annotated and not if FALSE, currently ignored.
axes	a logical value indicating whether both axes should be drawn on the plot.
...	other graphical parameters as in 'par' may also be passed as arguments.

Author(s)

Gavin L. Simpson.

References

Ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

See Also

[coca](#), [plot.default](#)

Examples

```
## symmetric CoCA
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## fit the model
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")

## draw a biplot of the response
plot(bp.sym)
```



```
## plot of both
layout(matrix(1:2, ncol = 2))
plot(bp.sym, which = "response", main = "Beetles")
plot(bp.sym, which = "predictor", main = "Plants")
layout(1)
```

points.coca

Add points to a Co-CA plot

Description

Draws points on the current graphic device based on in supplied [coca](#) model object.

Usage

```
## S3 method for class 'coca'
points(x, display = c("sites", "species"),
       which = c("response", "predictor"), choices = c(1, 2),
       scaling = FALSE, select, ...)
```

Arguments

x	an object inheriting from class coca .
display	character; one of the stated choices. Indicates which scores to use to draw points.
which	character; one of the stated choices. Indicates which of the response or predictor data sets is used to select scores from.
choices	The Co-CA axes to draw points for.
scaling	logical; should species scores in a symmetric Co-CA be rescaled?
select	Items to be displayed. This can either be a logical vector which is TRUE for displayed items or a vector of indices of displayed items.
...	Arguments passed to other methods

Details

The visual appearance of the plotted points can be controlled by supplying appropriate graphical parameters via the ... argument. See [par](#) for details.

Value

Returns the plotted x and y coordinates as a matrix.

Author(s)

Gavin L. Simpson

See Also

[plot](#) methods; [plot.predcoca](#) and [plot.symcoca](#).

Examples

```
## symmetric CoCA
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## fit the model
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")

## draw a biplot of the response
plot(bp.sym, type = "none")
points(bp.sym, display = "sites", col = "blue", pch = 16)
points(bp.sym, display = "species", col = "red", pch = 3, cex = 0.8)
```

rescale

Rescales CoCA species scores

Description

Rescales CoCA species scores to the quarter root of the eigenvalues.

Usage

```
rescale(object, ...)
```

Default S3 method:

```
rescale(object, ...)
```

S3 method for class 'symcoca'

```
rescale(object, axes = c(1:object$n.axes), ...)
```

Arguments

object an R object. Currently only objects of class "symcoca" are supported.

axes the number of axes to rescale

... other arguments to be passed to rescale methods. Currently not used here.

Details

Currently only implemented for objects of class "symcoca".

Author(s)

Gavin L. Simpson

See Also

[symcoca](#)

Examples

```
data(bryophyte)
data(vascular)
bryo.sym <- coca(bryophyte ~ ., data = vascular, method = "symmetric")
eps <- resid(bryo.sym)
```

scaleChi

Standardised chi-square residuals

Description

Scales a matrix, Y, to its standardised chi-square residuals $(o - e)/\sqrt{e}$ (given K_n and R_0 metrics derived from an external matrix Y_0) so that further analysis can be unweighted.

Usage

```
scaleChi(Y, Kn, R0, eps = 1e-06)
```

Arguments

Y	a matrix for which standardised chi-square residuals are to be calculated.
Kn	the column sums (K) of Y divided by sum(K).
R0	row weights.
eps	a tolerance.

Value

Yr the matrix of standardised chi-squared residuals of Y.

Note

This function is not intended for casual use by users.

Author(s)

Gavin L. Simpson, based on Matlab code by C.J.F. ter Braak and A.P. Schaffers.

References

Ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

scores.predcoca *Get Species or Site Scores from an Ordination*

Description

Function to access either species or site scores for specified axes in co-correspondence analysis ordination methods.

Usage

```
## S3 method for class 'predcoca'
scores(x, choices = c(1, 2),
       display = c("sites", "species"), ...)

## S3 method for class 'symcoca'
scores(x, choices = c(1, 2),
       display = c("sites", "species"), scaling = 1, ...)
```

Arguments

x	an ordination result
display	partial match to access scores for “sites” “species”, “loadings” or “xmatrix”. The latter two are only available for symcoca .
choices	numeric; the ordination axes to return.
scaling	numeric; whether the species scores should be rescaled to the quarter root of the eigenvalues using rescale.symcoca .
...	arguments to be passed to other methods.

Details

Implements a [scores](#) method for symmetric co-correspondence analysis ordination results.

Value

A list with one or more components containing matrices of the requested scores:

species	A list with two components, Y and X, containing the species scores for the response matrix Y and the predictor matrix X respectively.
sites	A list with two components, Y and X, containing the site scores for the response matrix Y and the predictor matrix X respectively.
loadings	A list with two components, Y and X containing the loadings for the response and predictor matrix. For symcoca only.
xmatrix	The X matrix. For symcoca only.

Author(s)

Gavin L. Simpson, based on Matlab code by C.J.F. ter Braak and A.P. Schaffers.

References

ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846

See Also

[scores](#), for further details on the method.

Examples

```
## load some data
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## fit the model, a symmetric CoCA
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")

## extract the scores
scr <- scores(bp.sym)

## predictive CoCA using SIMPLS and formula interface
bp.pred <- coca(beetles ~ ., data = plants)
scr2 <- scores(bp.pred)
```

simpls

Modified version of Sijmen de Jong's SIMPLS

Description

Fits a PLSR model with the SIMPLS algorithm, modified to allow a weighted analysis.

Usage

```
simpls(X, Y, ncomp, stripped = FALSE, ...)
```

Arguments

X	a matrix of observations. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
...	other arguments. Currently ignored.

Details

This function is a modified version of `simpls.fit` from package `pls`. Four modification have been made:

1. The input matrices X and Y are not centered,
2. The scores (`tt` in the code) are not centered,
3. Added code to calculate the total variance in the Y matrix, `Ytotvar`, and the variance in Y accounted for by each PLS axis, `Yvar` (See Value below), and
4. Additional components are returned if argument `stripped` is TRUE.

This function should not be called directly, but through the generic function `coca`.

SIMPLS is much faster than the NIPALS algorithm, especially when the number of X variables increases, but gives slightly different results in the case of multivariate Y. SIMPLS truly maximises the covariance criterion. According to de Jong, the standard PLS2 algorithms lie closer to ordinary least-squares regression where a precise fit is sought; SIMPLS lies closer to PCR with stable predictions.

Value

A list containing the following components is returned:

<code>coefficients</code>	an array of regression coefficients for 1, ..., <code>ncomp</code> components. The dimensions of <code>coefficients</code> are <code>c(nvar, npred, ncomp)</code> with <code>nvar</code> the number of X variables and <code>npred</code> the number of variables to be predicted in Y.
<code>scores</code>	a matrix of scores.
<code>loadings</code>	a matrix of loadings.
<code>Yscores</code>	a matrix of Y-scores.
<code>Yloadings</code>	a matrix of Y-loadings.
<code>projection</code>	the projection matrix used to convert X to scores.
<code>Xmeans</code>	a vector of means of the X variables.
<code>Ymeans</code>	a vector of means of the Y variables.
<code>fitted.values</code>	an array of fitted values. The dimensions of <code>fitted.values</code> are <code>c(nobj, npred, ncomp)</code> with <code>nobj</code> the number samples and <code>npred</code> the number of Y variables.
<code>residuals</code>	an array of regression residuals. It has the same dimensions as <code>fitted.values</code> .

Xvar	a vector with the amount of X-variance explained by each number of components.
Yvar	a vector with the amount of Y-variance explained by each number of components.
Xtotvar	Total variance in X.
Ytotvar	Total variance in Y.

If `stripped` is TRUE, only the components coefficients, `Xmeans` and `Ymeans`, `Xvar` and `Yvar`, and `Xtotvar` and `Ytotvar` are returned.

Author(s)

Based on [simpls.fit](#) by Ron Wehrens and Bjorn-Helge Mevik, with simple modifications by Gavin L. Simpson.

References

de Jong, S. (1993) SIMPLS: an alternative approach to partial least squares regression. *Chemometrics and Intelligent Laboratory Systems*, **18**, 251–263.

See Also

[coca](#)

summary.predcoca	<i>Summarizing Co-CA Model Fits</i>
------------------	-------------------------------------

Description

summary methods for classes "predcoca" and "symcoca". These provide a summary of the main results of a Co-Correspondence Analysis model.

Usage

```
## S3 method for class 'predcoca'
summary(object, axes = c(1:min(6, object$n.axes)),
        display = c("species", "sites"), ...)

## S3 method for class 'symcoca'
summary(object, axes = c(1:min(6, object$n.axes)),
        display = c("species", "sites"), scaling = 1, ...)
```


Arguments

object	an object of class "predcoca" or "symcoca". Generally the result of a call to coca .
axes	the number of CoCA axes to return in the result set.
display	one or both of "species" and/or "sites"
scaling	for objects of class "symcoca" only, the scaling to be applied to the results. One of "1" or "2". See below for details of scalings used.
...	arguments to be passed to other methods.

Value

A list with the some of the following components:

cocaScores	The site and or species scores for the axes requested.
call	The call used to fit the model.
lambda	The eigenvalues for the axes requested. Not for predcoca.simpls .
namY, namX	the names of the response and predictor either supplied by the user or derived from the original call.
loadings	a list with two components loadings1 and loadings2, which refer to the response and the predictor matrices respectively. (Only for predictive CoCA models.)
varianceExp	a list with components Yblock and Xblock containing the amount of variance explained on each CoCA axis in the response and the predictor respectively. (Only for predictive CoCA models.)
totalVar	a list with components Yblock and Xblock containing the total variance in the response and the predictor data sets respectively
inertia	a list with components total and residual containing the total and residual inertia (variance) in the response and the predictor matrices of a symmetric CoCA model. (Only for symmetric CoCA models.)
scaling	the scaling used/requested. (Only for symmetric CoCA models.)

Author(s)

Gavin L. Simpson

See Also

The model fitting function [coca](#)

Examples

```
## symmetric CoCA
data(beetles)
data(plants)
```

```
## log transform the beetle data
beetles <- log(beetles + 1)

## fit the model
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")
summary(bp.sym, axes = 1:4)

## Different scaling
summary(bp.sym, axes = 1:4, scaling = 2)

## Predictive CoCA
bp.pred <- coca(beetles ~ ., data = plants)
summary(bp.pred, axes = 1:2)
```

weights.symcoca	<i>Extract CoCA model weights</i>
-----------------	-----------------------------------

Description

Extractor function to identify and select appropriate analysis weights from Co-correspondence Analysis models.

Usage

```
## S3 method for class 'symcoca'
weights(object, ...)

## S3 method for class 'predcoca'
weights(object, ...)
```

Arguments

object	an object of class "symcoca" or "predcoca".
...	arguments passed to other methods. Not used.

Value

A numeric vector of common site weights is currently returned. These correspond to R_0 in ter Braak and Schaffers (2004).

Author(s)

Gavin L. Simpson

References

ter Braak, C.J.F and Schaffers, A.P. (2004) Co-Correspondence Analysis: a new ordination method to relate two community compositions. *Ecology* **85**(3), 834–846.

See Also

[envfit.coca](#) uses these weights to estimate weighted correlations in ordination space. See [coca](#) for details on creating CoCA models.

Examples

```
## symmetric CoCA
data(beetles)
data(plants)

## log transform the beetle data
beetles <- log(beetles + 1)

## fit the model
bp.sym <- coca(beetles ~ ., data = plants, method = "symmetric")

## weights == R[0]
weights(bp.sym)
```

Index

- *Topic **datasets**
 - beetles, 3
 - bryophyte, 4
- *Topic **hplot**
 - plot.predcoca, 21
 - plot.symcoca, 23
- *Topic **htest**
 - envfit.coca, 13
- *Topic **methods**
 - plot.symcoca, 23
 - points.coca, 25
 - scores.predcoca, 29
 - weights.symcoca, 34
- *Topic **models**
 - coca, 4
 - coinertia, 8
 - coinertiaI, 9
 - fitCoinertia, 15
- *Topic **multivariate**
 - coca, 4
 - coinertia, 8
 - coinertiaI, 9
 - crossval, 11
 - envfit.coca, 13
 - fitCoinertia, 15
 - fitted.symcoca, 17
 - mcChi, 18
 - permutest.coca, 19
 - rescale, 26
 - resid.symcoca, 27
 - scaleChi, 28
 - scores.predcoca, 29
 - simpls, 30
 - summary.predcoca, 32
- *Topic **package**
 - cocorresp-package, 2
- *Topic **regression**
 - coca, 4
 - simpls, 30
- *Topic **univar**
 - corAxis, 10
- *Topic **utilities**
 - weights.symcoca, 34
- beetles, 3
- bryophyte, 4
- coca, 4, 13, 14, 17, 21–25, 31–33, 35
- cocorresp (cocorresp-package), 2
- cocorresp-package, 2
- coinertia, 8, 10
- coinertiaI, 9, 9, 16
- cor, 11
- corAxis, 10
- crossval, 6, 11, 20, 21
- envfit, 14
- envfit.coca, 13, 35
- factorfit, 14
- fitCoinertia, 15
- fitted.symcoca, 17
- mcChi, 18
- ordiParseFormula, 6
- par, 25
- permutest.coca, 6, 9, 10, 19
- plants (beetles), 3
- plot, 26
- plot.default, 23, 24
- plot.predcoca, 21, 26
- plot.symcoca, 23, 26
- points.coca, 25
- predcoca.simpls, 33
- print.crossval (crossval), 11
- print.fitCoinertia (fitCoinertia), 15
- print.fitted.symcoca (fitted.symcoca), 17

print.permutest.coca (permutest.coca),
19

print.predcoca (coca), 4

print.summary.crossval (crossval), 11

print.summary.fitCoinertia
(fitCoinertia), 15

print.summary.permutest.coca
(permutest.coca), 19

print.summary.predcoca
(summary.predcoca), 32

print.summary.symcoca
(summary.predcoca), 32

print.symcoca (coca), 4

rescale, 26

rescale.symcoca, 29

resid.symcoca, 27

scaleChi, 28

scores, 29, 30

scores.predcoca, 22, 29

scores.symcoca, 14, 24

scores.symcoca (scores.predcoca), 29

simpls, 30

simpls.fit, 5, 31, 32

summary.crossval (crossval), 11

summary.fitCoinertia (fitCoinertia), 15

summary.permutest.coca
(permutest.coca), 19

summary.predcoca, 6, 32

summary.symcoca, 6

summary.symcoca (summary.predcoca), 32

symcoca, 9, 11, 16, 24, 27–29

vascular (bryophyte), 4

vectorfit, 14

verges (beetles), 3

weights.predcoca (weights.symcoca), 34

weights.symcoca, 34