

Package ‘confidence’

September 19, 2014

Type Package

Title Confidence Estimation of Environmental State Classifications

Description Functions for estimating and reporting multiyear averages and corresponding confidence intervals and distributions. A potential use case is reporting the chemical and ecological status of surface waters according to the European Water Framework Directive.

Version 1.0-0

Date 2014-09-18

Depends R (>= 3.0.0), tcltk

Imports knitr, markdown, plyr, xtable, ggplot2

Suggests testthat

VignetteBuilder knitr

License GPL (>= 3)

Author Willem M. G. M. van Loon [aut, cph], Dennis J. J. Walvoort [aut, cre]

Maintainer Dennis J. J. Walvoort <dennis.Walvoort@wur.nl>

NeedsCompilation no

Repository CRAN

Date/Publication 2014-09-19 14:57:31

R topics documented:

backtransform	2
conf	2
confidence-pkg	3
conf_input	4
DCA	5
EQR	5

metal	6
mya	7
sanitize	7
strip_spaces	8
transform	8

Index	9
--------------	----------

backtransform	<i>Back-transformations</i>
---------------	-----------------------------

Description

Performs inverse log or logit transformations.

Usage

```
backtransform(x, type = c("identity", "log", "logit", "none", NA_character_))
```

Arguments

x	value to back-transform
type	type of transform (log, logit).

Value

backtransformed value

conf	<i>Perform Confidence Run</i>
------	-------------------------------

Description

This function starts the ‘confidence tool’. The results will be stored in a subdirectory in the current working directory. See details section below.

Usage

```
conf(x = NULL, tmpdir = tempfile(pattern = "confidence"), browse = TRUE)
```

```
CONF(x = NULL, tmpdir = tempfile(pattern = "confidence"), browse = TRUE)
```

Arguments

x	name of the input file or a <code>data.frame</code> containing the input. If <code>x = NULL</code> (the default) a file dialog will appear for interactive selection of an input file. See the package vignette for details about the file format.
tmpdir	directory to store temporary files (for debugging only)
browse	load resulting report directly in a browser? TRUE or FALSE

Details

This function will create a subdirectory

- in the same directory as `x`, in case `x` is a filename or
- in the current working directory (see `getwd`), in case `x` is a `data.frame`.

The computer should have write permission to this directory, if not an error message will be raised. The subdirectory contains an HTML-report with all analysis results. For convenience, the results are also stored in CSV-format (tables) and png-format (figures) for further processing.

See Also

[confidence](#) and the package vignette (`vignette("confidence")`).

confidence-pkg

Confidence Estimation of Environmental State Classifications

Description

This package can be used to estimate the confidence of state classifications (e.g., with the classification ‘bad’, ‘moderate’, ‘good’) produced using environmental indicators and associated targets. The implementation closely follows Baggelaar et al. (2010) where the confidence intervals for the estimated multiyear averages are derived by assuming a Student’s t distribution for the errors. For more information about the package see the package-vignette (type: `vignette("confidence")` at the R-prompt to view the vignette.).

Author(s)

Willem M.G.M. van Loon and Dennis J.J. Walvoort

References

Baggelaar, P., O. van Tongeren, R. Knoben, and W. van Loon, 2010. Rapporteren van de betrouwbaarheid van KRW-beoordelingen (in Dutch, English translation: Reporting the confidence of WFD-assessments). H2O 16: 21–25

See Also

[conf](#) and the package vignette mentioned above.

conf_input	<i>Check Confidence data</i>
------------	------------------------------

Description

This function checks `data.frames` to be used by the confidence package. The format has been specified in Van Loon (2014) and should contain the following columns:

- OBJECTID: water body code, e.g., NL89_os;
- PAR: parameter, e.g., Cadmium;
- DATE: date according to ISO 8601 (YYYY-mm-dd) for point values or year YYYY for annual means;
- VALUE: numerical value.
- TARGET: target value for the European Water Framework Directive;
- UNIT: measurement unit of PAR. This unit should be the same for all records with the same PAR and is the same for both VALUE and TARGET;
- transform: data transformation, i.e., log, logit, NA.

Usage

```
conf_input(x)
```

Arguments

x `data.frame` to be checked

Details

The function performs the following tasks:

- checks availability of required columns (case insensitive);
- make column names case-insensitive;
- removes redundant spaces;
- checks on missing values in required columns;
- checks if DATE-field adheres to ISO 8601 (YYYY-mm-dd) or YYYY;
- checks mixtures of annual averages and point values for a each year;
- checks if measurement units are the same for a specific OBJECTID-PAR-pair;
- checks if TARGET-value is the same for a specific OBJECTID-PAR-pair;
- checks if transform is one of log, logit, NA in transform column;
- checks that the EQR-column contains identical values fo each OBJECTID-PAR combination.

Value

`data.frame` that has passed all checks

DCA

Annual Average 1,2-dichloroethane Concentration

Description

Annual arithmetic average concentration of 1,2-dichloroethane (DCA) in a specific water body ($\mu\text{g}/\text{l}$), based on Baggelaar et al., (2010)

Usage

data(DCA)

Details

The columns represent the following information:

- OBJECTID: water body code
- PAR: parameter, in this case 1,2-dichloroethane;
- color: colors in density function;
- DATE: year;
- VALUE: annual arithmetic average concentration
- TARGET: target according to the European Water Framework Directive;
- UNIT: measurement unit ($\mu\text{g}/\text{l}$).

References

Baggelaar, P., O. van Tongeren, R. Knobens, & W. van Loon, 2010. Rapporteren van de betrouwbaarheid van KRW-beoordelingen. H2O 16, p.21–25

EQR

Annual Average Environmental Quality Ratio for Macrofauna.

Description

Annual arithmetic average environmental quality ratio's (EQR) for Macrofauna in a specific water body, based on Baggelaar et al., (2010)

Usage

data(EQR)

Details

The columns represent the following information:

- OBJECTID: water body code
- PAR: parameter, in this case EQR;
- color: colors in density function;
- DATE: year;
- VALUE: annual arithmetic average EQR
- TARGET: target EQR;
- transform: applied transform

References

Baggelaar, P., O. van Tongeren, R. Knoben, & W. van Loon, 2010. Rapporteren van de betrouwbaarheid van KRW-beoordelingen. H2O 16, p.21–25

metal

Simulated Metal Contents

Description

A data set with two time-series of simulated metal contents. These data have mainly been used to test the package. Users may find this dataset convenient as an example to construct their own data sets. The columns represent the following information:

- OBJECTID: water body code, e.g., NL89_os;
- PAR: parameter, e.g., Cadmium;
- color: colors in density function;
- DATE: date according to ISO 8601 (YYYY-mm-dd) for point values or year YYYY for annual means;
- VALUE: numerical value.
- TARGET: e.g., the target value for the European Water Framework Directive;
- UNIT: measurement unit of PAR. This unit should be the same for all records with the same PAR and is the same for both VALUE and TARGET;
- transform: data transformation, i.e., log, logit, NA.

Usage

`data(metal)`

mya	<i>Multi-Year Average</i>
-----	---------------------------

Description

Estimates the multi-year average of environmental properties and associated confidence intervals.

Usage

```
mya(x, ...)
```

Arguments

x	object of class <code>conf_input</code> or a <code>data.frame</code> that can be coerced to an instance of class <code>conf_input</code> .
...	further arguments to be passed to other methods

Value

a `data.frame` with the following columns:

- MYA: the multi-year arithmetic average;
- PROB_lt: the probability that MYA is less than the target value specified;
- PROB_gt: the probability that MYA is greater than the target value specified;
- q05: the lowerbound of the 90% confidence interval of MYA
- q95: the upperbound of the 90% confidence interval of MYA

See Also

[conf](#)

sanitize	<i>Sanitize Text to Give Proper Filenames</i>
----------	-----------------------------------------------

Description

Sanitize Text to Give Proper Filenames

Usage

```
sanitize(x)
```

Arguments

x	character vector to sanitize
---	------------------------------

Value

sanitized character vector

strip_spaces	<i>Remove Redundant Spaces</i>
--------------	--------------------------------

Description

This function removes redundant spaces from character vectors

Usage

```
strip_spaces(x)
```

Arguments

x character vector

Value

character vector without trailing or multiple spaces

Examples

```
stopifnot(confidence:::strip_spaces(" Hello World ") == "Hello World")
```

transform	<i>Transformations</i>
-----------	------------------------

Description

Performs log or logit transformations.

Usage

```
transform(x, type = c("identity", "log", "logit", "none", NA_character_))
```

Arguments

x value to transform
 type type of transform (log, logit).

Value

transformed value

Index

*Topic **datasets**

DCA, [5](#)

EQR, [5](#)

metal, [6](#)

*Topic **package**

confidence-pkg, [3](#)

backtransform, [2](#)

CONF (conf), [2](#)

conf, [2](#), [3](#), [7](#)

conf_input, [4](#), [7](#)

confidence, [3](#)

confidence (confidence-pkg), [3](#)

confidence-pkg, [3](#)

confidence-pkg-package

(confidence-pkg), [3](#)

data.frame, [3](#), [7](#)

DCA, [5](#)

EQR, [5](#)

getwd, [3](#)

metal, [6](#)

mya, [7](#)

NULL, [3](#)

sanitize, [7](#)

strip_spaces, [8](#)

transform, [8](#)