

Package ‘gWidgets2’

July 2, 2014

Type Package

Title Rewrite of gWidgets API for simplified GUI construction

Version 1.0-5

Author John Verzani

Maintainer John Verzani <jverzani@gmail.com>

URL <https://github.com/jverzani/gWidgets2>

Description Re-implementation of gWidgets API. The API is defined in this package. A second, toolkit-specific package is required to use it. There are three in development: gWidgets2RGtk2, gWidgets2Qt, and gWidgets2tcltk.

Depends methods, digest

License GPL (>= 3)

LazyLoad yes

Collate 'misc.R' 'guiToolkit.R' 'BasicInterface.R' 'S4-methods.R' 'S3-methods.R' 'methods.R' 'dialogs.R' 'ws-model.R' 'command-stack.R' 'gWidgets2-package.R' 'gwindow.R' 'gaction.R' 'gbutton.R' 'gcalendar.R' 'gcheckbox.R' 'gcheckboxgroup.R' 'gcombobox.R' 'handler-methods.R' 'gdf.R' 'ggroup.R' 'gnotebook.R' 'gfile.R' 'gformlayout.R' 'gframe.R' 'ggraphics.R' 'ghtml.R' 'gimage.R' 'glabel.R' 'glayout.R' 'gmenu.R' 'gpanedgroup.R' 'gprogressbar.R' 'gradio.R' 'gseparator.R' 'gslider.R' 'gspinbutton.R' 'gstackwidget.R' 'gstatusbar.R' 'gtable.R' 'gtext.R' 'gtimer.R' 'gtoolbar.R' 'gtree.R' 'gedit.R' 'gexpandgroup.R' 'gvarbrowser.R' 'icons.R' 'gdfnotebook.R' 'gfilter.R' 'ggraphicsnotebook.R'

NeedsCompilation no

Repository CRAN

Date/Publication 2014-03-05 06:13:20

R topics documented:

gWidgets2-package	3
.gdfnotebook.default	7
add	8
addHandler	9
addSpring	15
addStockIcons	16
call_meth	18
check_deprecated	19
check_return_class	19
dispose	20
editable	20
enabled	21
flatten	22
focus	22
font	23
gaction	24
galert	25
gbasicdialog	25
gbutton	27
gcalendar	29
gcheckbox	30
gcheckboxgroup	32
gcombobox	34
gconfirm	36
gcontainer	36
gdf	37
gdfnotebook	38
gedit	39
getWidget.GDefaultWidget	40
getWithDefault	41
get_index_in_list	42
get_object_from_string	42
gexpandgroup	43
gfile	44
gfilter	46
gformlayout	48
gframe	49
ggraphics	50
ggraphicsnotebook	52
ggroup	53
ghtml	54
gimage	55
ginput	56
glabel	57
glayout	58
gmenu	60

gmessage	62
gnotebook	62
gpanedgroup	65
gprogressbar	66
gradio	67
gseparator	69
gslider	70
gspinbutton	72
gstackwidget	73
gstatusbar	74
gtable	75
gtext	78
gtimer	80
gtoolbar	81
gtoolkit	82
gtree	83
guiToolkit	86
guiWidgetsToolkit-class	87
gvarbrowser	88
gwidget	89
gwindow	90
installing_gWidgets_toolkits	92
isExtant	92
is_empty	92
is_MacOSX	93
is_Windows	93
observer	94
redo	94
short_summary	95
size	96
svalue	96
tag	98
tooltip	98
undo	99
visible	100
XXX	100
[.GDefaultWidget	101

Description

The **gWidgets2** package provides a programming interface for making graphical user interfaces within R. The package is a rewrite of the **gWidgets** package, introducing a few external changes but a significant number of internal ones. The package relies on one of several underlying toolkit packages providing access to the graphical libraries. These will include **RGtk2**, **tcltk**, **qtbase**, and a collection of browser widgets provided by ExtJS. As of now, only **gWidgets2RGtk2** is near completion.

Details

The package provides constructors to produce controls, the widgets that a user interacts with; containers, GUI objects used to organize the controls within a window; and dialogs, simple one-off windows for gathering quick user feedback. These objects are manipulated through various methods. The package provides a few new generics and, as much as possible, leverages existing methods for R.

Control constructors:

Controls are created by constructors. The package API includes the following. As much as possible these are implemented in the toolkit packages, but there may be instances where that is not possible.

- `gbutton` Provides a basic button to initiate an action
- `gcalendar` Provides a text entry area with selector for a date
- `gcheckbox` Provides a labeled checkbox to allow a user to toggle a selection
- `gcheckboxgroup` Provides a collection of checkboxes allowing selection of 0, 1, or several from many items
- `gcombobox` Provides a drop down list of choices to select from and possible and entry area for free response
- `gdf` Provides a data frame editing widget
- `gedit` Provides a single line text entry widget
- `ggraphics` Provides an embeddable graphic device
- `gimage` Provides a widget to hold images
- `glabel` Provides a widget to hold labels for other controls
- `gmenu` Provides menus for top-level windows and popup menus
- `gradio` Provides a means to select one of many items
- `gseparator` Provides a visual line to separate off parts of a window
- `gslider` Provides a means to select one value from a (seeming) continuum of values
- `gspinbutton` Provides means to select a value from s sequence of values
- `gstatusbar` Provides a widget to display status messages in a top-level window
- `gtable` Provides a widget to display tabular data for selection
- `gtext` Provides a multiline text-editing widget
- `gtimer` Provides a one-shot or repeatable timer
- `gtoolbar` Provides toolbars for top-level windows
- `gtree` Provides a display for heirarchical data
- `gvarbrowser` Provides a widget showing a shapshot of the current global workspace
- `gaction` Provides a means to encapsulate actions for use with menu bars, tool bars and buttons.

Containers are used to organize controls with a window. The package provides the following:

`gexpandgroup` Provides a container with an option to disclose or hide its children
`gframe` Provides a framed box container
`ggroup` Provides a horizontal or vertical box container for packing in child components
`glayout` Provides a container to organize data by row and column cell
`gnotebook` Provides a notebook container
`gpanedgroup` Provides a divided container with adjustable divider
`gstackwidget` Provides a container like a notebook, but without tab labels
`gwindow` Provides a top-level window

Dialog constructors:

Dialogs in **gWidgets2** are typically modal, meaning they block input to any other window and the R process. They do not return objects to be manipulated through methods, but rather return values selected by the user.

`gmessage` Produces a simple dialog to display a message
`gconfirm` Produces a dialog for a user to confirm an action
`ginput` Provides a dialog to gather user input
`gbasicdialog` Provides a means to produce general modal dialogs
`galert` Provides a short transient message dialog
`gfile` Provides a dialog to select a filename or directory name

Methods:

Except for dialogs, the constructors produce objects for which several methods are defined that allow the programmer access to getting and setting of the object state. For the most part these are S3 methods. The actual returned object is a reference class instance, as provided by an underlying toolkit. These may have toolkit-specific methods defined as reference class methods (i.e., call them using `$meth_name`). Any such methods are documented in the toolkit packages.

`svalue, svalue<-` The main new method. This is used to retrieve or set the main property associated with a widget
`enabled, enabled<-` A widget is enabled if it is sensitive to user input. Non-enabled widgets typically are rendered in a greyed out state.
`visible, visible<-` The generic idea of a visible widget is one that is drawn. However, several classes override this to mean part of the widget is visible or not visible.
`focus, focus<-` A widget with focus receives any keyboard input.
`editable, editable<-` A widget is editable if it can receive keyboard input.
`font, font<-` The font for an object is specified through this method using a convention illustrated in the help page.
`size, size<-` The size of a widget is retrieved or requested through these methods
`tooltip, tooltip<-` A tooltip provides contextual information when a mouse hovers over an object
`undo, redo` Some widgets support an undo and redo stack
`isExtant` A method to check if the GUI part of a widget still exists. (A constructor produces an R object and GUI object through the toolkit.)

`tag, tag<-` A method used to set attributes for an object that are stored in an environment so that they are passed by reference, not copy. This allows event handlers to manipulate an object's attributes outside the scope of the callback.

`getToolkitWidget` Returns the underlying toolkit object that is packaged into a **gWidgets2** object

`add` Method used to add a child component to a parent container

`delete` Method used to delete a component from its parent

`dispose` Method used to delete a component

The package overloads some familiar R methods.

`length, length<-` Returns the length of an object, typically related to the number of children a container has, or the length of the items that a user can selection from.

`dim` Used to return row and column size information as applicable.

`names, names<-` Used to set the names associated to an object. These may be column names in the table widget, or tab names in the notebook container.

`dimnames, dimnames<-` Used to set row and column names, as applicable.

`[, [<-` Used to update the underlying items that a selection widget offers. Also used to specify layout in glayout

`update` Call to update the state of a widget, when applicable.

Event handlers:

Graphical User Interfaces are made interactive by assigning a function (a callback) to be called when some event happens. In **gWidgets2** the `addHandlerXXX` methods are defined to assign this callback to a type of event specified through the `XXX`, detailed below. The generic `addHandlerChanged` is the most common event for a widget. This event can also have a handler specified through the `handler` argument of the widget constructor.

In **gWidgets2** handlers are functions which when called are passed a list as the first argument, and possibly toolkit-specific arguments for subsequent arguments. As such the signature typically looks like `(h, ...)`, where the list `h` has components `obj`, containing a reference to the widget emitting the event and `action` passing in any information specified to the `action` argument. Some events also pass back extra information, such as `x` and `y` for position, or `key` for key events, as appropriate.

`addHandlerChanged` Assigns callback for the most generic event

`addHandlerClicked` Assigns callback for a mouse click event

`addHandlerDoubleClick` Assigns callback for a mouse double-click event

`addHandlerRightclick` Assigns callback for a mouse right-click event

`addHandlerColumnclicked` Assigns callback for a column-click event

`addHandlerColumnDoubleclicked` Assigns callback for a column-double-click event

`addHandlerColumnRightclicked` Assigns callback for a column-right-click event

`addHandlerSelect` Assigns callback when the underlying selection is changed

`addHandlerFocus` Assigns a callback for when a widget receives focus

`addHandlerBlur` Assigns a callback for when a widget loses focus

`addHandlerDestroy` Assigns a callback for when a widget is destroyed

`addHandlerUnrealize` For `gwindow` this is called before the `destroy` event and may stop that from happening.

[addHandlerExpose](#) Assigns callback to be called when a widget is exposed
[addHandlerKeystroke](#) Assigns callback to be called when a key event occurs
[addHandlerMouseMotion](#) Assigns callback to be called when a mouse moves over a widget
[addHandler](#) Base method to add a callback though rarely called, as it is toolkit specific
[addHandlerIdle](#) Assign a callback to be called at periodic intervals. See also [gtimer](#)
[addPopupMenu](#) Add a popup menu
[add3rdmousePopupMenu](#) Add a popup menu for the right mouse (context menu)
[addDropSource](#) Specify widget as a source (drag area) for drag and drop
[addDropTarget](#) Specify widget as a target (drop area) for drag and drop
[addDragMotion](#) Assign callback for event that a drag event crosses a widget
[blockHandlers](#), [blockHandler](#) Block all handlers for a widget (or by single ID)
[unblockHandlers](#), [unblockHandler](#) Unblock any blocked handlers (or by single ID)
[removeHandler](#) Remove a handler by it ID

Author(s)

John Verzani <jverzani@gmail.com>

Maintainer: John Verzani <jverzani@gmail.com>

.gdfnotebook.default *Toolkit constructor*

Description

Toolkit constructor

Usage

```
## Default S3 method:  
.gdfnotebook(toolkit, items,  
             container = NULL, ...)
```

Arguments

toolkit	toolkit
items	data frame for initial page, when given
container	parent container
...	passed to add method of parent container

 add

Add a child object to parent container

Description

Add packs in child objects.

Basic S3 method for add

Delete may or may not remove a child. This is toolkit specific. It may also be tied up with garbage collection. To avoid that, keep a reference to the child object before deleting.

Basic S3 method for add

Usage

```
add(obj, child, expand = FALSE, fill = NULL,
    anchor = NULL, ...)
```

```
## Default S3 method:
add(obj, child, expand = FALSE,
    fill = NULL, anchor = NULL, ...)
```

```
delete(obj, child)
```

```
## S3 method for class 'GContainer'
delete(obj, child)
```

Arguments

obj	parent object
child	child widget
expand	NULL or logical. For box containers controls whether a child will expand to fill the allocated space.
fill	NULL or character. For box containers. The value of fill (not always respected) is used to control if expansion happens vertically (y), horizontally (x) or both (both or TRUE). For vertically filled box containers, children always fill horizontally (atleast) and for horizontally filled box containers, children always fill vertically (atleast). This is important to realize when trying to size buttons, say.
anchor	NULL or integer. For box containers. The anchor argument is used to position the child within the parent when there is more space allocated than the child requests. This is specified with a Cartesian pair in -1,0,1 x -1, 0, 1.
...	passed on to the

 addHandler

Generic method to add a handler passing a signal

Description

A GUI is made interactive by assigning handlers to user-generated events, such as a mouse click, change of widget state, or keyboard press. In **gWidgets2** handlers are assigned through various addHandlerXXX methods. The handlers are functions whose first argument should expect a list with components obj (to pass in the receiver object) and action (to pass in any user-supplied value to the action argument). Some handlers add other components, such as mouse position information on a click, or key information on a keyboard event.

Default S3 method

The "changed" event varies wildly amongst the widgets, but is meant to be the most "obvious" one. Typically this is also similar to "selected".

Default S3 method

Add handler for clicked event

Default S3 method

Add handler for double click event

Default S3 method

This may not be supported by all toolkits.

Default S3 method

For table widgets (gtable, gdf) clicking the column header should trigger this event. The column that is clicked on is passed back in the component column.

Default S3 method

If defined (gtable, gdf) calls event handler for double click event. Passes back column information through column component.

Default S3 method

Add handler for column right click event

Default S3 method

The select event defaults to the "changed" event.

Default S3 method

The "select" event is when a user "selects" an object, the "selection changed" event is when the selection changes. The distinction is in table and tree widgets where a user may select values with a single click yet want to initiate an action with a double click. The latter is the "addHandlerSelect" event, the former the "addHandlerSelectionChanged" event.

Default S3 method

When a widget has the focus, it will receive the keyboard input. This handler is called when a widget receives the focus.

Default S3 method

A blur or focus out event for a widget triggers this event handler

Default S3 method

When a widget is destroyed, a handler can be assigned to perform any clean up tasks that are needed.

Default S3 method

For gwindow objects this handler is called before the window is closed. If this handler returns TRUE the window will be closed, if FALSE the window will not be closed. In contrast, the "destroy" handler does not allow conditional destruction.

Default S3 method

Add handler for expose event (when a widget is exposed, say it had been covered)

Default S3 method

The "h" argument has components key for the key and possibly modifier for the modifier.

Default S3 method

Add handler for mousemotion events

Default S3 method

deprecated. See [gtimer](#).

Defaults to adding a 3rd mouse popup menu, better known as a context menu, though some toolkits have both this and the latter provided.

S3 method for popup menu

These menus are also known as context menus, though there isn't really a good mechanism within **gWidgets2** to make the menu items context sensitive.

S3 method for popup menu

Drag and drop requires one to register widgets as sources for dragging, a widget as a target for dropping.

Default S3 method

The handler is called on the drop event. The component dropdata passes in the value being transferred by dragging.

Default S3 method

When a drag event crosses over the object the handler is called.

Default S3 method

Block all handlers for an object. Removed via unblockHandlers.

S3 method to block all handlers

Block a handler

S3 method to block handler

The block is a counter that gets decremented. If more blockHandlers calls are made than unblockHandlers, the handlers will still be blocked.

S3 method to block handler

method call to unblock a blocked handler

S3 method to block handler

method call to unblock a remove permanently handler

S3 method to remove handler

The change handler for ggraphics is called when a rubber-band selection is completed

The click handler is called on a mouse click. The handler object should pass in value for x, y

Usage

```
addHandler(obj, signal, handler, action = NULL, ...)
```

```
## Default S3 method:
```

```
addHandler(obj, signal, handler,  
  action = NULL, ...)
```

```
addHandlerChanged(obj, handler, action = NULL, ...)
```

```
## Default S3 method:
```

```
addHandlerChanged(obj, handler,  
  action = NULL, ...)
```

```
addHandlerClicked(obj, handler, action = NULL, ...)
```

```
## Default S3 method:
```

```
addHandlerClicked(obj, handler,  
  action = NULL, ...)
```

```
addHandlerDoubleClick(obj, handler, action = NULL, ...)
```

```
## Default S3 method:
```

```
addHandlerDoubleClick(obj, handler,  
  action = NULL, ...)
```

```
addHandlerRightclick(obj, handler, action = NULL, ...)
```

```
## Default S3 method:
```

```
addHandlerRightclick(obj, handler,  
  action = NULL, ...)
```

```
addHandlerColumnClicked(obj, handler, action = NULL, ...)
```

```
## Default S3 method:
```

```
addHandlerColumnClicked(obj, handler,  
  action = NULL, ...)
```

```
addHandlerColumnDoubleClicked(obj, handler,  
  action = NULL, ...)
```

```
## Default S3 method:
```

```
addHandlerColumnDoubleClicked(obj,
```

```
    handler, action = NULL, ...)  
  
addHandlerColumnRightclicked(obj, handler, action = NULL,  
    ...)  
  
## Default S3 method:  
addHandlerColumnRightclicked(obj,  
    handler, action = NULL, ...)  
  
addHandlerSelect(obj, handler, action = NULL, ...)  
  
## Default S3 method:  
addHandlerSelect(obj, handler,  
    action = NULL, ...)  
  
addHandlerSelectionChanged(obj, handler, action = NULL,  
    ...)  
  
## Default S3 method:  
addHandlerSelectionChanged(obj,  
    handler, action = NULL, ...)  
  
addHandlerFocus(obj, handler, action = NULL, ...)  
  
## Default S3 method:  
addHandlerFocus(obj, handler,  
    action = NULL, ...)  
  
addHandlerBlur(obj, handler, action = NULL, ...)  
  
## Default S3 method:  
addHandlerBlur(obj, handler,  
    action = NULL, ...)  
  
addHandlerDestroy(obj, handler, action = NULL, ...)  
  
## Default S3 method:  
addHandlerDestroy(obj, handler,  
    action = NULL, ...)  
  
addHandlerUnrealize(obj, handler, action = NULL, ...)  
  
## Default S3 method:  
addHandlerUnrealize(obj, handler,  
    action = NULL, ...)  
  
addHandlerExpose(obj, handler, action = NULL, ...)
```

```
## Default S3 method:
addHandlerExpose(obj, handler,
  action = NULL, ...)

addHandlerKeystroke(obj, handler, action = NULL, ...)

## Default S3 method:
addHandlerKeystroke(obj, handler,
  action = NULL, ...)

addHandlerMouseMotion(obj, handler, action = NULL, ...)

## Default S3 method:
addHandlerMouseMotion(obj, handler,
  action = NULL, ...)

addHandlerIdle(...)

addPopupMenu(obj, menulist, action = NULL, ...)

## Default S3 method:
addPopupMenu(obj, menulist,
  action = NULL, ...)

add3rdmousePopupMenu(obj, menulist, action = NULL, ...)

## Default S3 method:
add3rdmousePopupMenu(obj, menulist,
  action = NULL, ...)

addDropSource(obj, handler, action = NULL,
  data.type = c("text", "object"), ...)

## Default S3 method:
addDropSource(obj, handler,
  action = NULL, data.type = c("text", "object"), ...)

addDropTarget(obj, handler, action = NULL, ...)

## Default S3 method:
addDropTarget(obj, handler,
  action = NULL, ...)

addDragMotion(obj, handler, action = NULL, ...)

## Default S3 method:
addDragMotion(obj, handler,
  action = NULL, ...)
```

```

blockHandlers(obj, ...)

## Default S3 method:
blockHandlers(obj, ...)

blockHandler(obj, ID, ...)

## Default S3 method:
blockHandler(obj, ID, ...)

unblockHandlers(obj, ...)

## Default S3 method:
unblockHandlers(obj, ...)

unblockHandler(obj, ID, ...)

## Default S3 method:
unblockHandler(obj, ID, ...)

removeHandler(obj, ID, ...)

## Default S3 method:
removeHandler(obj, ID, ...)

## Default S3 method:
addHandlerChanged(obj, handler,
  action = NULL, ...)

## Default S3 method:
addHandlerClicked(obj, handler,
  action = NULL, ...)

```

Arguments

obj	object receiving event and emitting a signal to the handler
signal	toolkit signal, e.g. "clicked"
handler	handler to assign when signal is emitted. A handler is a function, its first argument should expect a list with components obj containing a reference to the object and action. Some handlers are passed additional values.
action	passed to handler to parameterize call.
...	passed along
menulist	a list of gaction items or a gmenu instance
data.type	Type of data returned. It is either text or an object
ID	returned by addHandler. If missing will try to block all handler passed to constructor

Details

Although the `add_handler` method, to which `addHandler` dispatches, is basically the workhorse to add a handler to response to a signal, it generally isn't called directly, as its use is not cross toolkit. Rather, if possible, one should use the `addHandlerXXX` methods to add a handler. These dispatch to this (basically) but do so in a toolkit independent manner.

This call (and the others) returns a handler ID which may be used for some toolkits later on to remove, block or unblock the call. All handlers for a widget may be blocked or unblocked via `blockHandlers` and `unblockHandlers`.

The "changed" event is also the one that a handler passed to the constructor is called on.

To specify the values that is transferred in a drag and drop event, the handler specified here should return the value to pass via drag and drop. It will appear as the `dropdata` component of the list passed in as the first argument of the drop handler

Value

a handler ID which can be used to block/unblock or remove the handler

NULL

Note

This method is not toolkit independent, as the signal value depends on the toolkit

For the `gWidgets2Qt` package one can not block, unblock or remove a single handler, but rather must do all the objects handlers at once.

See Also

[blockHandlers](#), [unblockHandlers](#), [blockHandler](#), [unblockHandler](#), and [removeHandler](#)
[addHandlerUnrealize](#).

[blockHandlers](#) to block all handlers for widget

addSpring

Add a spring to box containers

Description

A spring will separate the children packed in the box container prior to the spring be added and those being added, pushing the two as far apart as the allocated space will allow.

Add spring to `GContainer` class

Inserts a specific amount of space between the previously packed child and next one.

Add space to `GContainer` class

Usage

```

addSpring(obj)

## S3 method for class 'GContainer'
addSpring(obj)

addSpace(obj, value)

## S3 method for class 'GContainer'
addSpace(obj, value)

```

Arguments

obj	GContainer object
value	space in pixels to add

Value

NULL
NULL

addStockIcons	<i>Method to add icon to list of stock icons</i>
---------------	--

Description

Method to add icon to list of stock icons
generic for dispatch
toolkit implementation
return list of available stock icons
generic for toolkit dispatch
default
Return stock icon name, filename, icon object from its by name
generic
default implementation
Find a stock icon from the given class
generic for dispatch
Default stock icon for a given class name
Find stock icon from the given object
generic for dispatch
get stock icon from object by class

Usage

```
addStockIcons(iconNames, iconFiles, ...,
              toolkit = guiToolkit())

.addStockIcons(toolkit, iconNames, iconFiles, ...)

## Default S3 method:
.addStockIcons(toolkit, iconNames,
               iconFiles, ...)

getStockIcons(..., toolkit = guiToolkit())

.getStockIcons(toolkit, ...)

## Default S3 method:
.getStockIcons(toolkit, ...)

getStockIconByName(name, ..., toolkit = guiToolkit())

.getStockIconByName(toolkit, name, ...)

## Default S3 method:
.getStockIconByName(toolkit, name,
                    file = TRUE, ...)

stockIconFromClass(theClass, ..., toolkit = guiToolkit())

.stockIconFromClass(toolkit, theClass, ...)

## Default S3 method:
.stockIconFromClass(toolkit, theClass,
                   ...)

stockIconFromObject(obj, ..., toolkit = guiToolkit())

.stockIconFromObject(toolkit, obj, ...)

## Default S3 method:
.stockIconFromObject(toolkit, obj,
                    ...)
```

Arguments

iconNames	names of icons
iconFiles	path of icons
...	ignored
toolkit	used to dispatch into toolkit if a separate implementation is made

name	of stock icon
file	logical If TRUE, return filename. If FALSE, return toolkit icon object (if possible).
theClass	name of class
obj	an R object

Value

list of icons with names the icon name and values the icon file name or icon object (as needed by the toolkit)

name of icon.

Examples

```
## Not run:
## we can add icon sets, say those of glyphicons.com. Steps are download files, unzip
## then point x to path, y to name. Imagine we download and current directory is
## png directory. (Won't work with tcltk by default as these are png files)
x <- Sys.glob("*.png")
path <- paste(getwd(), x, sep=.Platform$file.sep)
nm <- gsub("\\.png", "", x)
nm <- gsub("-", "_", nm)
nm <- gsub("\\+", "_plus", nm)
addStockIcons(nm, path)

## End(Not run)
```

call_meth

helper function to bypass lack of cached value in method call

Description

helper function to bypass lack of cached value in method call

Usage

```
call_meth(meth, obj)
```

Arguments

meth	method name
obj	method of object's class

Value

the method

Note

use as `do.call(call_meth, args)`

check_deprecated	<i>Method to send message if any deprecated arguments are being used</i>
------------------	--

Description

Many arguments were deprecated due to various reasons. This is meant to ease porting of code.

Usage

```
check_deprecated(deprecated_args = list(), ...)
```

Arguments

deprecated_args	named list of deprecated args
...	named avlues

check_return_class	<i>check that toolkit object return the right class</i>
--------------------	---

Description

The S3 dispatch assumes naming conventions in the class names. This offers some check.

Usage

```
check_return_class(obj, ret_class)
```

Arguments

obj	object with expected return class
ret_class	character string of class expected

Value

throws error if a mismatch

dispose	<i>Dispose of object</i>
---------	--------------------------

Description

Dispose of object, primarily a window though this is modified in GNoteBook and GText.
main dispose method. Calls dispose for GWindow

Usage

```
dispose(obj, ...)
```

```
## S3 method for class 'GComponent'
```

```
dispose(obj, ...)
```

Arguments

obj	object to dispose
...	passed along

editable	<i>Controls whether widget is editable or not</i>
----------	---

Description

Some widgets may be editable. If possible, the setter method can be used to toggle the state. This method indicates the state.

Basic S3 method

Set whether an object can be edited

Basic S3 method for editable

Usage

```
editable(obj, i)
```

```
## Default S3 method:
```

```
editable(obj, i)
```

```
editable(obj, i) <- value
```

```
editable(obj, i) <- value
```

Arguments

obj	object
i	index to apply to, when applicable
value	logical. Set editable state.

enabled	<i>enabled</i>
---------	----------------

Description

A widget is enabled if it is sensitive to user input

base S3 method for enabled.

Set whether widget is enabled or not

S3 method for setting enabled property

Usage

```
enabled(obj)

## Default S3 method:
enabled(obj)

enabled(obj) <- value

enabled(obj) <- value
```

Arguments

obj	object
value	logical

Value

logical indicating if widget is enabled

if value is logical and FALSE widget will be insensitive to user input and rendered in a muted state.

flatten	<i>Flatten a nested list</i>
---------	------------------------------

Description

Flatten a nested list

Usage

```
flatten(x)
```

Arguments

x	a list
---	--------

Author(s)

Tommy (<http://stackoverflow.com/questions/8139677/how-to-flatten-a-list-to-a-list-without-coercion>)

focus	<i>Does widget have focus</i>
-------	-------------------------------

Description

a widget has focus if it will receive input events

Basic S3 method

For some widgets, this sets user focus (e.g. gedit gets focus for typing). For others, setting the focus calls the raise methods. (for gwindow, it will raise the window)

Basic S3 method for focus

Usage

```
focus(obj)
```

```
## Default S3 method:  
focus(obj)
```

```
focus(obj) <- value
```

```
focus(obj) <- value
```

Arguments

obj	object
value	logical. Set focus state.

font	<i>Returns font specification for widget, if available</i>
------	--

Description

Returns font specification for widget, if available

Basic S3 method for font

Set font for a widget

Basic S3 method for setting font

The font assignment method is used to change the font of the currently selected text.

Usage

```
font(obj)

## Default S3 method:
font(obj)

font(obj) <- value

font(obj) <- value

## S3 replacement method for class 'GText'
font(obj) <- value
```

Arguments

obj	object
value	<p>The font specification is given in terms of a named vector or list where the names indicate a font attribute and the value a reasonable choice:</p> <p>weight c("light", "normal", "medium", "bold", "heavy")</p> <p>style c("normal", "oblique", "italic")</p> <p>family c("sans", "helvetica", "times", "monospace")</p> <p>size an integer, say c(6,8,10,11,12,14,16,18,20, 24,36,72)</p> <p>color (or foreground) One of colors()</p> <p>background One of colors()</p> <p>scale c("xx-large", "x-large", "large", "medium", "small", "x-small", "xx-small")</p> <p>These are from Gtk's font specs, which though fairly standard, may not be totally supported in the other toolkits.</p>

gaction

An action constructor

Description

A action object encapsulates an action (a callback) adding textual and graphic information. Actions may be proxied in buttons, menu bars or tool bars.

generic for toolkit dispatch

Usage

```
gaction(label, tooltip = NULL, icon = NULL,  
        key.accel = NULL, handler = NULL, action = NULL,  
        parent = NULL, ..., toolkit = guiToolkit())
```

```
.gaction(toolkit, label, tooltip = NULL, icon = NULL,  
        key.accel = NULL, handler = NULL, action = NULL,  
        parent = NULL, ...)
```

Arguments

label	label for action
tooltip	tooltip for action
icon	icon (stock icon name) for icon
key.accel	keyboard accelerator. If given, parent must be specified.
handler	handler to call when action is invoked
action	values passed to parameterize action
parent	parent window. Needed if keyboard accelerator used.
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through guiToolkit .

Value

a gaction instance

galert *Alert dialog to display transient messages*

Description

Alert dialog to display transient messages
generic for toolkit dispatch

Usage

```
galert(msg, title = "message", delay = 3, parent = NULL,
      ..., toolkit = guiToolkit())
```

```
.galert(toolkit, msg, title = "message", delay = 3,
      parent = NULL, ...)
```

Arguments

msg	character. main message. If length is 2, second component is used for detail, providing it is available.
title	Title (may not be displayed)
delay	length of time (in seconds) to display
parent	parent object to show near
...	ignored
toolkit	toolkit

gbasicdialog *Constructor for modal dialog that can contain an arbitrary widget*

Description

The basic dialog is basically a modal window. To use there is a 3 step process: 1) Create a container by calling this constructor, say dlg; 2) use dlg as a container for your subsequent GUI; 3) set the dialog to be modal by calling `visible(dlg)`. (One can't call `visible(dlg) <- TRUE`.)

generic for toolkit dispatch

We overrode the basic use of `visible` for the `gbasicdialog` container to have it become visible and modal after this call. The better suited call `visible(dlg) <- TRUE` does not work as wanted, for we want to capture the return value.

dispose method for a basic dialog

Usage

```

gbasicdialog(title = "Dialog", parent = NULL,
  do.buttons = TRUE, handler = NULL, action = NULL, ...,
  toolkit = guiToolkit())

.gbasicdialog(toolkit, title = "Dialog", parent = NULL,
  do.buttons = TRUE, handler = NULL, action = NULL, ...)

## S3 method for class 'GBasicDialog'
visible(obj, ...)

## S3 method for class 'GBasicDialog'
dispose(obj, ...)

```

Arguments

title	title for window
parent	parent to display by
do.buttons	FALSE to suppress buttons when no parent
handler	handler called when Ok button invoked
action	passed to handler for OK button
...	ignored
toolkit	toolkit
obj	dialog object

Value

A GBasicDialog instance with a visible method
 logical indicating which button was pushed (or TRUE if no buttons present)
 NULL

Examples

```

## Not run:
## a modal dialog for editing a data frme
fix_df <- function(DF, ...) {
  dfname <- deparse(substitute(DF))
  w <- gbasicdialog(..., handler=function(h,...) {
    assign(dfname, df[,], .GlobalEnv)
  })
  g <- ggroup(cont=w, horizontal=FALSE)
  glabel("Edit a data frame", cont=g)
  df <- gdf(DF, cont=g, expand=TRUE)
  size(w) <- c(400, 400)
  out <- visible(w)
}

```

```
m <- mtcars[1:3, 1:4]
fix_df(m)

## End(Not run)
```

gbutton

Basic button widget

Description

The basic button widget is a standard means to provide the user a mechanism to invoke an action. This action may be specified by a handler or by a gaction object. The main property for GButton is the label text. If this text matches a stock icon name and the toolkit supports it, an icon will accompany the button.

S3 generic whose methods are implemented in the toolkit packages

Change handler for a button is called when a button is activated (e.g., a mouse click)

The svalue method for a button object refers to its main property, the button label

Usage

```
gbutton(text = "", handler = NULL, action = NULL,
        container = NULL, ..., toolkit = guiToolkit())

.gbutton(toolkit, text, handler, action, container, ...)

## S3 method for class 'GButton'
addHandlerChanged(obj, handler,
                 action = NULL, ...)

## S3 method for class 'GButton'
svalue(obj, index = NULL, drop = NULL,
       ...)
```

Arguments

text	label text. If text matches a stock icon name, that is used as well
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through addHandlerChanged or at construction time. Handlers are functions whose first argument, h in the documentation, is a list with atleast two components obj, referring to the object emitting the signal and action, which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called

container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
obj	object receiving event and emitting a signal to the handler
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
drop	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Value

a GButton instance. While this object has its own (reference) methods, one primarily interacts with it through S3 methods defined within the package.

Examples

```
if(interactive()) {

  w <- gwindow("Buttons", visible=FALSE)
  g <- ggroup(cont=w, horizontal=FALSE)

  ## various buttons

  ## with icons
  b1 <- gbutton("open", cont=g)

  ## without icon
  b2 <- gbutton("ouvrir", cont=g)

  ## by an action
  act <- gaction("open", tooltip="open", icon="open", handler=function(...) {})
  b3 <- gbutton(action=act, cont=g)

  ## with a handler
  b4 <- gbutton("click me", cont=g, handler=function(h,...) {
    if(svalue(b2) == "open")
      svalue(b2) <- "ouvrir"
    else
      svalue(b2) <- "open"
  })

  visible(w) <- TRUE
}
```

gcalendar

A constructor for a date selection widget

Description

The date is the main property of this widget

generic for toolkit dispatch

Change handler for a calendar is called when the text value is updated

The svalue method for a calendar object returns the selected date

Usage

```
gcalendar(text = "", format = "%Y-%m-%d",
          handler = NULL, action = NULL, container = NULL, ...,
          toolkit = guiToolkit())

.gcalendar(toolkit, text = "", format = "%Y-%m-%d",
           handler = NULL, action = NULL, container = NULL, ...)

## S3 method for class 'GCalendar'
addHandlerChanged(obj, handler,
                 action = NULL, ...)

## S3 method for class 'GCalendar'
svalue(obj, index = NULL,
       drop = NULL, ...)
```

Arguments

text	initial text
format	Date format
handler	handler called when changed
action	passed to handler
container	parent container
...	passed to add method of parent
toolkit	toolkit
obj	receiver object
index	ignored
drop	if TRUE return a character, else a Date class object.

Value

Returns an object of class GCalendar for which the following methods are overridden:

1. svalue get the date
2. svalue<- set the date

The change handler is inherited from [gedit](#)

If drop=TRUE a character string, else a Date class object.

gcheckbox

constructor for checkbox widget

Description

A checkbox widget is used to toggle the state of a labeled boolean variable. The main property of this widget is that state, not the label. This variable may be proxied in the usual way – with a box that indicates or check if TRUE – or through a toggle button.

Generic for toolkit dispatch

The change handler for GCheckbox is called when the value toggles. You can inspect the current value in the callback to have an action based on the state.

The object state is referred to by svalue as a logical (TRUE for checked). The svalue<- method ensures the value is a logical vector of length 1.

The item to select is referred to by the [method, with only the first element being used.

Usage

```
gcheckbox(text = "", checked = FALSE,
        use.togglebutton = FALSE, handler = NULL,
        action = NULL, container = NULL, ...,
        toolkit = guiToolkit())

.gcheckbox(toolkit, text, checked = FALSE,
         use.togglebutton = FALSE, handler = NULL,
         action = NULL, container = NULL, ...)

## S3 method for class 'GCheckbox'
addHandlerChanged(obj, handler,
                  action = NULL, ...)

## S3 replacement method for class 'GCheckbox'
svalue(obj, index=NULL, ...) <-
  value

## S3 replacement method for class 'GCheckbox'
x[i, j, ...] <- value
```

Arguments

text	label text
checked	is button selected
use.togglebutton	Use a toggle button (shows depressed) not a check box
handler	Callback called when toggle is changed.
action	passed to handler
container	parent container
...	passed to add method of container
toolkit	toolkit
obj	receiver object
index	ignored. Input is coerced to logical.
value	assignment value
x	checkbox object
i	item index
j	ignored

Value

Returns an object of class GCheckbox.

Note

The value is coerced to character, then only first element used for checkbox label

Examples

```
if(interactive()) {
  w <- gwindow("Selection widgets")
  g <- gvbox(cont=w)

  fl <- gformlayout(cont=g)
  gcheckbox("checkbox", checked=TRUE, cont=f1, label="checkbox")
  gradio(state.name[1:4], selected=2, horizontal=TRUE, cont=f1, label="radio")
  gcheckboxgroup(state.name[1:4], horizontal=FALSE, cont=f1, label="checkbox group")

  bg <- ggroup(cont=g)
  gbutton("ok", cont=bg, handler=function(h,...) print(sapply(fl$children, svalue)))
}
```

gcheckboxgroup	<i>Constructor for checkbox group. A linked group of checkboxes, but not exclusive.</i>
----------------	---

Description

Constructor for checkbox group. A linked group of checkboxes, but not exclusive.

generic for toolkit dispatch

Change handler for a GCheckboxGroup is called when any of the checkboxes changes state.

The svalue methods refer to the selected values. By default these are the item values, coerced to characterq. When index=TRUE is specified, then the index is returned as an integer vector. For setting, one may also use a vector of logicals (which is recycled) for the index.

Usage

```
gcheckboxgroup(items, checked = FALSE,
             horizontal = FALSE, use.table = FALSE, handler = NULL,
             action = NULL, container = NULL, ...,
             toolkit = guiToolkit())
```

```
.gcheckboxgroup(toolkit, items, checked = FALSE,
             horizontal = FALSE, use.table = FALSE, handler = NULL,
             action = NULL, container = NULL, ...)
```

```
## S3 method for class 'GCheckboxGroup'
addHandlerChanged(obj, handler,
                 action = NULL, ...)
```

```
## S3 method for class 'GCheckboxGroup'
svalue(obj, index = NULL,
       drop = NULL, ...)
```

Arguments

items	checkbox labels
checked	logical. Are values checked
horizontal	logical. If true displayed horizontally, else vertically
use.table	logical. If supported, and TRUE then uses a table widget with scrollbars
obj	receiver object
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through addHandlerChanged or at construction time. Handlers are functions whose first argument, h in the documentation, is a list with atleast two components obj, referring to the object emitting the signal and action, which passes in user-specified data to parameterize the function call.

action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through guiToolkit .
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
drop	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Value

Returns an object of class GCheckboxGroup for which the following methods are overridden:

- `svalue` Return the selected values or an empty character vector. If `index=TRUE`, returns indices of selected values.
- `svalue<-` Set the selected values one of three ways: by label name, by a logical variable indicating which are selected (if ambiguous, logical wins), if `index=TRUE` by the indices to select.
- `[` returns labels
- `[<-` set the label values. Should be able to shorten or lengthen list

Examples

```
if(interactive()) {
  w <- gwindow("Selection widgets")
  g <- gvbox(cont=w)

  f1 <- gformlayout(cont=g)
  gcheckbox("checkbox", checked=TRUE, cont=f1, label="checkbox")
  gradio(state.name[1:4], selected=2, horizontal=TRUE, cont=f1, label="radio")
  gcheckboxgroup(state.name[1:4], horizontal=FALSE, cont=f1, label="checkbox group")

  bg <- ggroup(cont=g)
  gbutton("ok", cont=bg, handler=function(h,...) print(sapply(f1$children, svalue)))
}
```

gcombobox

*constructor for a combobox***Description**

A combobox can be either a drop down list (`editable=FALSE`), or a drop-down list and edit area (a combobox).

generic for toolkit dispatch

Alias for `gcombobox`. Deprecated

Non exported helper function to coerce items into a data frame. First column contains the values, second stock icons, third tooltips

Ensure that value is a data frame. One can pass a vector or a one-column data frame to indicate the possible values for selection, a second column is used for an icons (if possible), a third for a tooltip (if possible).

Change handler for a non-editable combobox is called when a new value is selected. For editable comboboxes, the handler is also called when the text entry box is activated.

The `svalue` method for a combobox object refers to its main property, the selected value. When `index=FALSE` (or `NULL`) the value is returned. If `index=TRUE` the index of the object within the set of items is used.

Usage

```
gcombobox(items, selected = 1, editable = FALSE,
  coerce.with = NULL, handler = NULL, action = NULL,
  container = NULL, ..., toolkit = guiToolkit())

.gcombobox(toolkit, items, selected = 1,
  editable = FALSE, coerce.with = NULL, handler = NULL,
  action = NULL, container = NULL, ...)

gdroplist(...)

.make_gcombobox_items(value)

## S3 replacement method for class 'GComboBox'
x[i , j, ...] <- value

## S3 method for class 'GComboBox'
addHandlerChanged(obj, handler,
  action = NULL, ...)

## S3 method for class 'GComboBox'
svalue(obj, index = NULL,
  drop = NULL, ...)
```

Arguments

items	Items to select from. A vector or a data frame. If a data frame, then first column is values. Second is optional, but can specify a stock icon name, third is optional and can be used to specify a tooltip. These may not be supported in all toolkits.
selected	integer. Which item (by index) is selected. Use -1 for no selection
editable	logical. Is user allowed to edit value
coerce.with	A function of function name to be called before selected value is returned by svalue
handler	Called when combobox value is changed.
action	passed to handler
container	parent container
...	passed to parent container's add method
toolkit	toolkit
x	combobox object
i	item index
j	ignored
value	new items for selection
obj	object receiving event and emitting a signal to the handler
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
drop	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Value

Returns an object of class GComboBox for which the following methods are overridden:

1. svalue Return selected value by name or (if index=TRUE by index). The latter only if editable=FALSE.
2. svalue<- Set the selected value by value or if index=TRUE by index.
3. [return items to select from
4. [<- Set items to select from.

gconfirm	<i>Constructor for modal dialog to get confirmation</i>
----------	---

Description

Constructor for modal dialog to get confirmation
 generic for toolkit dispatch

Usage

```
gconfirm(msg, title = "Confirm",
         icon = c("info", "warning", "error", "question"),
         parent = NULL, ..., toolkit = guiToolkit())

.gconfirm(toolkit, msg, title = "Confirm",
          icon = c("info", "warning", "error", "question"),
          parent = NULL, ...)
```

Arguments

msg	Character. Message to display.
title	Character. Title of window
icon	which icon to display
parent	gives hint as to where to place dialog
...	ignored
toolkit	toolkit

Value

logical indicating confirmation

gcontainer	<i>Common parts of a container widget</i>
------------	---

Description

Used as template for documentation

Usage

```
gcontainer(container = NULL, ..., toolkit = guiToolkit())
```

Arguments

container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

gdf

*Constructor for a data frame editor***Description**

Implementation varies wildly, but should provide at minimum functionality of `edit.data.frame`. A single mouse click on a cell should select that cell, a double click should initiate editing of that cell.

generic for toolkit dispatch

Assign handler to be called when a cell, row or column changes

For `gdf` `svalue` refers to the selected values.

`visible` is used to refer to which rows are being shown.

Usage

```
gdf(items = NULL, handler = NULL, action = NULL,
     container = NULL, ..., toolkit = guiToolkit())

.gdf(toolkit, items = NULL, handler = NULL,
      action = NULL, container = NULL, ...)

## S3 method for class 'Gdf'
addHandlerChanged(obj, handler,
                  action = NULL, ...)

## S3 method for class 'Gdf'
svalue(obj, index = NULL, drop = TRUE,
       ...)

## S3 replacement method for class 'Gdf'
visible(obj) <- value
```

Arguments

items	data frame to edit
container	parent container
handler	called on cell change
action	passed to handler
...	passed to container's add method
toolkit	toolkit
obj	object receiving event and emitting a signal to the handler
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
drop	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.
value	value to assign for selection or property

Details

The `save_data` reference class method can be called to save the data into a variable with the specified name.

Value

An object of class `gDf`.

Note

need example of `do.subset` feature using `visible<-`

<code>gdfnotebook</code>	<i>A notebook container for many gdf instances</i>
--------------------------	--

Description

A notebook container for many gdf instances
 S3 generic whose methods are implemented in the toolkit packages

Usage

```
gdfnotebook(items = NULL, container = NULL, ...,
            toolkit = guiToolkit())

.gdfnotebook(toolkit, items, container, ...)
```

Arguments

items	data frame for initial page, when given
container	parent container
...	passed to add method of parent container
toolkit	toolkit

gedit

Single line text edit constructor

Description

Single line text edit constructor

generic for toolkit dispatch

The default change handler call is when the user activates the entry, typically by pressing the enter key or when the widget loses the keyboard focus. Other possible events to consider are covered by: `addHandlerBlur` (when the widget loses focuses) and `addHandlerKeystroke` (called after each keystroke). For the latter, if the toolkit supports it, the handler's first argument has a component key passing back the keystroke information.

The `svalue` method for a edit object refers to its main property, the text in the box,

Usage

```
gedit(text = "", width = 25, coerce.with = NULL,
      initial.msg = "", handler = NULL, action = NULL,
      container = NULL, ..., toolkit = guiToolkit())

.gedit(toolkit, text = "", width = 25,
       coerce.with = NULL, initial.msg = "", handler = NULL,
       action = NULL, container = NULL, ...)

## S3 method for class 'GEdit'
addHandlerChanged(obj, handler,
                 action = NULL, ...)

## S3 method for class 'GEdit'
svalue(obj, index = NULL, drop = NULL,
      ...)
```

Arguments

text	initial text
width	number of characters
coerce.with	A function or name of function to coerce value with before returning by <code>svalue</code>

<code>initial.msg</code>	If no initial text is given but an initial message is, then this message is displayed until the widget receives the focus
<code>handler</code>	Change handler. Called when return key is hit
<code>action</code>	passed to handler
<code>container</code>	parent container
<code>...</code>	passed to add method of parent
<code>toolkit</code>	toolkit
<code>obj</code>	object receiving event and emitting a signal to the handler
<code>index</code>	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
<code>drop</code>	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Value

An object of class `GEdit`. This has sub-classed methods:

- 1.
2. `svalue` to retrieve the text
3. `svalue<-` to set the text
4. `[]` to get the autocomplete values
5. `[]<- Character`. To set autocomplete values
6. `visible<-` to specify a character to display instead of text (for passwords)

`getWidget.GDefaultWidget`

method for getWidget

Description

method for `getWidget`

At times a user may wish to access the underlying toolkit widget. Although this is not cross-platform, one often has access to many more methods of the object, than through those provided by `gWidgets`.

Basic S3 method

Get underlying toolkit widget from widget slot. Used internally

method for `getWidget`

Get underlying toolkit object from block slot

S3 method for `getBlock` generic

For `GWindow`, the block is NULL

Get toplevel window containing object

`getTopLevel` method for components

Usage

```

## S3 method for class 'GDefaultWidget'
getWidget(obj)

getToolkitWidget(obj)

## Default S3 method:
getToolkitWidget(obj)

getWidget(obj)

## S3 method for class 'GComponent'
getWidget(obj)

getBlock(obj)

## S3 method for class 'GComponent'
getBlock(obj)

## S3 method for class 'GWindow'
getBlock(obj)

getTopLevel(obj)

## S3 method for class 'GComponent'
getTopLevel(obj)

```

Arguments

obj object

getWithDefault	<i>Return x unless NULL, NA, length 0, ..., in which case we give default</i>
----------------	---

Description

Return x unless NULL, NA, length 0, ..., in which case we give default

Usage

```
getWithDefault(x, default)
```

Arguments

x value to return or its default
default default value

Value

x or default

get_index_in_list *get index of element of list*

Description

Like match, but works with a list

Usage

```
get_index_in_list(lst, ele)
```

Arguments

lst	a list to search through
ele	element of list

Value

returns index of element or integer(0)

get_object_from_string
Get an object from an environment specified by a string.

Description

Get an object from an environment specified by a string.

Usage

```
get_object_from_string(value, envir = .GlobalEnv)
```

Arguments

value	A single character value dispatches to get. For a length 2 or more, then assumes object is recursive and extracts named components
envir	environment to look for values.

Value

the object or an error

gexpandgroup	<i>Constructor of box container widget with disclosure trigger and label</i>
--------------	--

Description

Constructor of box container widget with disclosure trigger and label
generic for toolkit dispatch

For gexpandgroup, the visible assignment method is overridden to change the disclosure state

The change handler for a expandGroup is called when the group changes visibility

Usage

```
gexpandgroup(text = "", markup = FALSE,
             horizontal = TRUE, handler = NULL, action = NULL,
             container = NULL, ..., toolkit = guiToolkit())

.gexpandgroup(toolkit, text = "", markup = FALSE,
              horizontal = TRUE, handler = NULL, action = NULL,
              container = NULL, ...)

## S3 replacement method for class 'GExpandGroup'
visible(obj) <- value

## S3 method for class 'GExpandGroup'
addHandlerChanged(obj, handler,
                 action = NULL, ...)
```

Arguments

text	Label text
markup	logical. Does text have markup? (Toolkit dependent: only implemented for RGtk2, in qtbase one can pass HTML formatted text)
horizontal	horizontal (TRUE) or vertical packing.
handler	handler called when state is toggled
action	passed to handler
container	parent container
...	passed to parent's add method
toolkit	toolkit
value	logical. If TRUE show, FALSE hide.
obj	object receiving event and emitting a signal to the handler

Value

An object of class GExpandGroup inheriting from GFrame

See Also

[ggroup](#) and [gframe](#)

gfile

dialog for file and directory selection

Description

dialog for file and directory selection

generic for toolkit dispatch

Basically an entry box instance with a button to initiate gfile.

generic for toolkit dispatch

Usage

```
gfile(text = "", type = c("open", "save", "selectdir"),
      initial.filename = NULL, initial.dir = getwd(),
      filter = list(), multi = FALSE, ...,
      toolkit = guiToolkit())
```

```
.gfile(toolkit, text = "",
       type = c("open", "save", "selectdir"),
       initial.filename = NULL, initial.dir = getwd(),
       filter = list(), multi = FALSE, ...)
```

```
gfilebrowse(text = "Select a file...",
            type = c("open", "save", "selectdir"),
            initial.filename = NULL, initial.dir = getwd(),
            filter = list(), quote = TRUE, handler = NULL,
            action = NULL, container = NULL, ...,
            toolkit = guiToolkit())
```

```
.gfilebrowse(toolkit, text = "Select a file...",
             type = c("open", "save", "selectdir"),
             initial.filename = NULL, initial.dir = getwd(),
             filter = list(), quote = TRUE, handler = NULL,
             action = NULL, container = NULL, ...)
```

Arguments

text	initial text
type	type of browser: to open a file, to save a file or to select a directory
initial.filename	Suggested file name

<code>initial.dir</code>	initial directory. If a filename is given, and is not an absolute name, this will be prepended. If filename given initial directory will be taken from that.
<code>filter</code>	A filter specification. This can be a named character vector of file extensions or something toolkit specific. Here are some examples: <ul style="list-style-type: none"> • <code>characterc("csv"="csv","txt"="txt")</code> • RGtk2 Something like <pre>list("All files" = list(patterns = c("*")), "R files" = list(patterns = c("*R", "*.Rdata")), "text files" = list(mime.types = c("text/plain"))))</pre> • <code>tcltk</code> • <code>Qt</code>
<code>multi</code>	Logical. Allow multiple files to be selected?
<code>quote</code>	quote output
<code>...</code>	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
<code>toolkit</code>	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
<code>handler</code>	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
<code>action</code>	User supplied data passed to the handler when it is called
<code>container</code>	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)

Value

returns filename(s) or character(\emptyset) if no selection.

Returns an object of class `gFilebrowse`. This should inherit the methods of `gedit` instances.

gfilter

*A widget for filtering a data frame***Description**

This widget provides a simple means to subset, or filter, a data frame.

generic for toolkit dispatch

The `svalue` method for a filter object returns a logical containing which rows are selected. There is no assignment method.

The extraction method returns the child items of the filter, like a container object.

Default

Usage

```
gfilter(DF, allow.edit = TRUE, initial.vars = NULL,
        handler = NULL, action = NULL, container = NULL, ...,
        toolkit = guiToolkit())

.gfilter(toolkit, DF, allow.edit = TRUE,
         initial.vars = NULL, handler = NULL, action = NULL,
         container = NULL, ...)

## S3 method for class 'GFilter'
svalue(obj, index = NULL, drop = NULL,
       ...)

## S3 method for class 'GFilter'
x[i, j, ..., drop = TRUE]

## Default S3 method:
.gfilter(toolkit = guiToolkit(), DF,
         allow.edit = TRUE, initial.vars = NULL, handler = NULL,
         action = NULL, container = NULL, ...)
```

Arguments

DF	a data frame or Gdf instance to look variables up within.
allow.edit	logical. If TRUE a user may add new variables to filter by. If FALSE, then one should specify the variables a user can filter by to <code>initial.vars</code> .
initial.vars	When given, this is a data frame whose first column specifies the variables within DF to filter by and whose second column indicates the type of filter desired. The available types are <code>single</code> to select one from many, <code>multiple</code> , for multiple selection; and <code>range</code> , to specify a from and to value.
x	the GFilter object

i	passed to <code>get_items</code>
j	passed to <code>get_items</code>
...	dots argument
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
obj	object of method call
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
drop	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Value

returns GFilter object

Examples

```
## Not run:
DF <- mtcars[, c("mpg", "cyl", "hp", "am", "wt")]
w <- gwindow("Example of gfilter", visible=FALSE)
pg <- ggroup(container=w)
df <- gtable(DF, container=pg)
a <- gfilter(df, initial.vars=data.frame(names(DF),
                                       c("single", "multiple", "range", "single", "range"),
                                       stringsAsFactors=FALSE),
            allow.edit=TRUE,
            container=pg,
            handler=function(h,...) {
              visible(df) <- h$obj$get_value()
            }
            )
size(w) <- c(600, 400)
visible(w) <- TRUE

## End(Not run)
```

gformlayout *A form layout container*

Description

This convenience container is basically a simpler form of `glayout` to be used to layout two columns forms with a label on the left. The label can be passed in to the `add` method of the container as is done with notebook labels

`.gformlayout` generic for toolkit dispatch

The `svalue` method for `GFormLayout` returns a list of values created by calling `svalue` on each child. The returned list is named by the corresponding labels.

Usage

```
gformlayout(align = c("default", "left", "center"),
            spacing = 5, container = NULL, ...,
            toolkit = guiToolkit())
```

```
.gformlayout(toolkit, align = "left", spacing = 5,
            container = NULL, ...)
```

```
## S3 method for class 'GFormLayout'
svalue(obj, index = NULL,
       drop = NULL, ...)
```

Arguments

<code>align</code>	alignment of label. Left justify or center balance. Leave as "default" for underlying toolkit default.
<code>spacing</code>	spacing between columns
<code>container</code>	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
<code>...</code>	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
<code>toolkit</code>	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
<code>obj</code>	object of method call
<code>index</code>	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
<code>drop</code>	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Examples

```
## Not run:
w <- gwindow("gformlayout", visible=FALSE)
g <- gvbox(container=w)

flyt <- gformlayout(container=g)
gedit("", label="Name:", container=flyt)
gedit("", label="Rank:", container=flyt)
gedit("", label="Serial No.:", container=flyt)

b <- gbutton("Show me", container=g, handler=function(h,...) {
  print(svalue(flyt))
})

addSpring(g) ## better with Qt, else flyt expands to fill.
visible(w) <- TRUE

## End(Not run)
```

gframe

Constructor for framed box container with label

Description

The framed box container inherits from ggroup. The main addition is a label, which is accessed via the name method.

generic for toolkit dispatch

Usage

```
gframe(text = "", markup = FALSE, pos = 0,
        horizontal = TRUE, spacing = 5, container = NULL, ...,
        toolkit = guiToolkit())

.gframe(toolkit, text = "", markup = FALSE, pos = 0,
         horizontal = TRUE, spacing = 5, container = NULL, ...)
```

Arguments

text	frame label
markup	does label use markup (toolkit specific)
pos	position of label: 0=left, 1=right, some toolkit allow values in between
toolkit	toolkit
horizontal	logical. If TRUE, left to right layout, otherwise top to bottom
spacing	spacing around widget

container A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. **gWidgets2tcltk** or **gWidgets2WWW2**.)

... These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.

Note

to include a scrollwindow, place a ggroup within this window.

See Also

[ggroup](#) and [gexpandgroup](#)

Examples

```
## Not run:
w <- gwindow("gformlayout", visible=FALSE)
f <- gframe("frame", horizontal=FALSE, container=w)
glabel("Lorem ipsum dolor sit amet, \nconsectetur adipiscing elit.", container=f)
gbutton("change name", container=f, handler=function(h,...) {
  names(f) <- "new name"
})
visible(w) <- TRUE

## End(Not run)
```

ggraphics

Constructor for an embeddable graphics device

Description

Some toolkits provide an embeddable graphics device. When this is the case, this widget provides same.

generic for toolkit dispatch

Usage

```
ggraphics(width = dpi * 6, height = dpi * 6, dpi = 75,
  ps = 12, handler = NULL, action = NULL,
  container = NULL, ..., toolkit = guiToolkit())

.ggraphics(toolkit, width = dpi * 6, height = dpi * 6,
  dpi = 75, ps = 12, handler = NULL, action = NULL,
  container = NULL, ...)
```

Arguments

width	width of device (pixels)
height	hieght of widget (pixels)
dpi	dots per inch
ps	pointsize
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

Examples

```
## Not run:
## This shows how to use the device within a notebook

w <- gwindow("notebook example")
nb <- gnotebook(cont=w)

devs <- lapply(1:5, function(i) ggraphics(cont=nb, label=as.character(i)))

addHandlerChanged(nb, handler=function(h,...) {
  ## Tricky part is svalue(h$obj) is not the new page number -- but old
  ## so we use the pageno component here
  gg <- h$obj[h$pageno]
  visible(gg) <- TRUE
})

## End(Not run)
```

ggraphicsnotebook *A notebook widget holding plot devices*

Description

A notebook widget holding plot devices

S3 generic whose methods are implemented in the toolkit packages

toolkit implementation

Usage

```
ggraphicsnotebook(width = dpi * 6, height = dpi * 6,
  dpi = 75, container = NULL, ...,
  toolkit = guiToolkit())

.ggraphicsnotebook(toolkit, width, height, dpi,
  container, ...)

## Default S3 method:
.ggraphicsnotebook(toolkit, width,
  height, dpi, container, ...)
```

Arguments

width	width in pixels
height	height in pixels
dpi	screen resolution
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

gggroup

Basic box container

Description

Basic box container

S3 generic whose methods are implemented in the toolkit packages

The `svalue` method refers to the main property of the box container, its spacing. There are generally two types of spacing: padding around border of the box and spacing between each child that is packed in. The spacing here is the between-child-component spacing. The reference class method `set_borderwidth` can be used for the other.

Avoids need to type `horizontal=FALSE`

Usage

```
gggroup(horizontal = TRUE, spacing = 5,
         use.scrollwindow = FALSE, container = NULL, ...,
         toolkit = guiToolkit())
```

```
.gggroup(toolkit, horizontal = TRUE, spacing = 5,
         use.scrollwindow = FALSE, container = NULL, ...)
```

```
## S3 replacement method for class 'GGroup'
svalue(obj, index=TRUE, ...) <- value
```

```
gvbox(spacing = 5, use.scrollwindow = FALSE,
      container = NULL, ..., toolkit = guiToolkit())
```

Arguments

`horizontal` logical. If TRUE, left to right layout, otherwise top to bottom

`spacing` spacing around widget

`use.scrollwindow`

logical. Either TRUE, "TRUE", FALSE, "FALSE", "y", or "x". For all toolkits a non-FALSE value will place the child components into a scrollable container. For some toolkits this will only be in the direction of packing. If the toolkit allows it (RGtk2), then values of "x" or "y" can be used to override the default scrolling directions. A box container with scrollwindows should have its size set either directly or through packing with `expand=TRUE` as its size request will not reflect the size of its child components.

`obj` GGroup object

`index` ignored

`value` value (in pixels) for between child spacing

container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

Details

Child components are typically added to a box container through the child components constructor. The argument `expand`, `fill`, and `anchor` determine how the child is positioned within the container.

Value

- a GGroup instance.
- a GGroup instance with vertical packing.

See Also

[gframe](#) and [gexpandgroup](#)

Examples

```
if(interactive()) {
  w <- gwindow("Box containers")
  g <- gvbox(cont=w) # ggroup(horizontal=FALSE, ...)
  nb <- gnotebook(cont=g); gbutton("one", label="one", cont=nb)
  gframe("Frame", cont=g)
  pg <- gpanedgroup(cont=g); gbutton("one", cont=pg); gbutton("two", cont=pg)
}
```

ghtml

Widget for HTML display

Description

This widget, when supported by the toolkit (not **gWidgets2RGtk2** and **gWidgets2tcltk**) provides a simple means to display HTML formatted text.

S3 generic whose methods are implemented in the toolkit packages

Use to update displayed content. Value is HTML fragment or url

Usage

```

ghtml(x, container = NULL, ..., toolkit = guiToolkit())

.ghtml(toolkit, x, container = NULL, ...)

## S3 replacement method for class 'GHtml'
svalue(obj, index=TRUE, ...) <- value

```

Arguments

x	url or character vector of HTML formatted text. URLs marked by "http://" prefix
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through guiToolkit .
obj	object of method call
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
value	value to assign for selection or property

Value

a GHtml instance.

Author(s)

john verzani

gimage

A widget for displaying an image file

Description

A widget for displaying an image file
generic for toolkit dispatch

Usage

```
gimage(filename = "", dirname = "", stock.id = NULL,
        size = "", handler = NULL, action = NULL,
        container = NULL, ..., toolkit = guiToolkit())

.gimage(toolkit, filename = "", dirname = "",
         stock.id = NULL, size = "", handler = NULL,
         action = NULL, container = NULL, ...)
```

Arguments

filename	basename of file
dirname	dirname of file
stock.id	stock id of icon (if non NULL)
size	size of icon when a stock id (toolkit dependent)
handler	handler if image is clicked on.
action	passed to handler
container	parent container
...	passed to add method of parent
toolkit	toolkit

ginput

Constructor for modal dialog to collect a line of text

Description

Constructor for modal dialog to collect a line of text
generic for toolkit dispatch

Usage

```
ginput(msg, text = "", title = "Input",
       icon = c("info", "warning", "error", "question"),
       parent = NULL, ..., toolkit = guiToolkit())

.ginput(toolkit, msg, text = "", title = "Input",
        icon = c("info", "warning", "error", "question"),
        parent = NULL, ...)
```


Arguments

msg	Character. Message to display.
text	Character. Initial text
title	Character. Title of window
icon	which icon to display
parent	gives hint as to where to place dialog
...	ignored
toolkit	toolkit

Value

value typed into box or character(0)

glabel	<i>Basic label widget</i>
--------	---------------------------

Description

The basic label widget allows one to label areas of a GUI using text. The most common use would be to label fields in a form. For **gWidgets2** labels may be editable or responsive to mouse clicks, although it is the author's experience that such uses are not expected by the end user.

S3 generic whose methods are implemented in the toolkit packages

The svalue methods refer to the main property of the label, its text.

Usage

```
glabel(text = "", markup = FALSE, editable = FALSE,
       handler = NULL, action = NULL, container = NULL, ...,
       toolkit = guiToolkit())

.glabel(toolkit, text, markup = FALSE, editable = FALSE,
        handler = NULL, action = NULL, container = NULL, ...)

## S3 replacement method for class 'GLabel'
svalue(obj, index=TRUE, ...) <- value
```

Arguments

text	character. Collapsed using a newline to a single string.
markup	logical. If toolkit supports markup, this indicates it will be used. It is suggested that the font<- method be used, though for gWidgets2Qt markup is more convenient.
editable	If TRUE, then clicking on label will enable user-editing of the text.

handler	optional handler. If given, added through addHandlerChanged. Overridden if editable=TRUE.
action	passed to handler through action component of first argument of handler. For buttons, this may also be a GAction instance.
container	parent container (Optional for some toolkits, but not all).
...	passed to add method of parent container
toolkit	toolkit instance
obj	object of method call
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
value	value to assign for selection or property

Value

a GLabel instance. While this object has its own (reference) methods, one primarily interacts with it through S3 methods defined within the package.

Author(s)

john verzani

Examples

```
## Not run:
w <- gwindow("gformlayout", visible=FALSE)
g <- gvbox(container=w)
g$set_borderwidth(10)

l1 <- glabel("static label", container=g)
l2 <- glabel("bold label", container=g)
font(l2) <- list(weight="bold")
l3 <- glabel("editable label. Click me", editable=TRUE, container=g)

visible(w) <- TRUE

## End(Not run)
```

Description

The grid layout container uses matrix notation to position its child components. This allows one to align widgets both horizontally and vertically, as desired. There is some support for matrix methods, such as `dim` and `[]` to reference the child objects.

generic for toolkit dispatch

The `[]` method for the grid layout allows one to reference the child objects by index. The return value is non standard. It may be the item, a list (if one dimensional) or an array. The list format is convenient to refer to all the child objects in a column.

The matrix notation allows for spanning of multiple rows and or columns, but no holes. The `...` argument is used to pass in values for `expand`, `fill`, `anchor` (see the `add` method of `ggroup`) for their meaning).

Usage

```
glayout(homogeneous = FALSE, spacing = 10,
        container = NULL, ..., toolkit = guiToolkit())

.glayout(toolkit, homogeneous = FALSE, spacing = 10,
         container = NULL, ...)

## S3 method for class 'GLayout'
x[i, j, ..., drop = TRUE]

## S3 replacement method for class 'GLayout'
x[i, j, ...] <- value
```

Arguments

<code>homogeneous</code>	are cells all the same size
<code>spacing</code>	between cell spacing
<code>x</code>	object
<code>i</code>	row index
<code>j</code>	column index
<code>drop</code>	drop return type?
<code>value</code>	constructor for a widget using this object as the parent container
<code>container</code>	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
<code>...</code>	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
<code>toolkit</code>	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

See Also

[gformlayout](#) for a more convenient means to layout forms.

Examples

```
## Not run:

w <- gwindow("glayout example", visible=FALSE)
g <- gvbox(container=w)
lyt <- glayout(container=g)
lyt[1,1] <- "a label"
lyt[1,2] <- gedit("A widget", container=lyt)
lyt[2, 1:2] <- gcombobox(state.name, cont=lyt)
g1 <- ggroup(container=g)
addSpring(g1)
gbutton("values", container=g1, handler=function(h, ...) {
  print(sapply(lyt[,2], svalue))
})
visible(w) <- TRUE

## End(Not run)
```

gmenu

menu constructor, main and popup

Description

A menu may be viewed as a heirarchical collection of buttons, each invoked by clicking on the button. These buttons are exposed through submenus. More generally, a widget may replace the button. This widget intends to support buttons (gactions), separators (gseparator), radio button (gradio) and checkbutton (gcheckbox), but this may be toolkit independent. When using a radio button or checkbox, one should pass in a parent argument to the constructor – not a container.

generic for toolkit dispatch

add menubar items to a menu

For a menubar, svalue returns the list of action items etc. that defined the menubar. This can be useful to access the underlying item being proxied. (For gaction items the enabled<- method may be used on the item, but this may not extend to gradio and gcheckbox items)

for a menubar, svalue<- replaces the menubar items with new ones specified by value.

Usage

```
gmenu(menu.list, popup = FALSE, container = NULL, ...,
      toolkit = guiToolkit())

.gmenu(toolkit, menu.list = list(), popup = FALSE,
      container = NULL, ...)
```

```

## S3 method for class 'GMenuBar'
add(obj, child, expand = FALSE,
    fill = NULL, anchor = NULL, ...)

## S3 method for class 'GMenuBar'
svalue(obj, index = NULL,
    drop = NULL, ...)

## S3 replacement method for class 'GMenuBar'
svalue(obj, index=NULL, ...) <- value

```

Arguments

menu.list	A list defining the menu structure. Named sub lists determine the submenu titles and structure. The list may have components of class: GAction, mapped to a button; GSeparator, mapped to a horizontal separator; GRadio, mapped to linked buttons; or GCheckbox, mapped to a checkbox button.
popup	logical. If true, make a popup window to be added through a handler call
child	list. a menubar list or gmenu instance.
index	ignored
drop	ignored
value	a list or menu bar specifying the new menubar
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
obj	parent object
expand	NULL or logical. For box containers controls whether a child will expand to fill the allocated space.
fill	NULL or character. For box containers. The value of fill (not always respected) is used to control if expansion happens vertically (y), horizontally (x) or both (both or TRUE). For vertically filled box containers, children always fill horizontally (atleast) and for horizontally filled box containers, children always fill vertically (atleast). This is important to realize when trying to size buttons, say.
anchor	NULL or integer. For box containers. The anchor argument is used to position the child within the parent when there is more space allocated than the child requests. This is specified with a Cartesian pair in -1,0,1 x -1, 0, 1.

gmessage	<i>Constructor for modal message dialog</i>
----------	---

Description

Constructor for modal message dialog
generic for toolkit dispatch

Usage

```
gmessage(msg, title = "message",
         icon = c("info", "warning", "error", "question"),
         parent = NULL, ..., toolkit = guiToolkit())

.gmessage(toolkit, msg, title = "message", icon = "",
          parent = NULL, ...)
```

Arguments

msg	Character. message to display.
title	Character. Title
icon	What icon to show
parent	Hint as to where to display
...	ignored
toolkit	toolkit

Value

NULL
NULL

gnotebook	<i>Constructor for a tabbed notebook container</i>
-----------	--

Description

The tabbed notebook container allows one to hold many different pages with a mechanism – tabs – to switch between them. In gWidgets2 new pages are added through the add method. This is usually called implicitly in the child object's constructor. One passes in the tab label through the extra label argument. Labels may be subsequently changed through names<-.

generic for toolkit dispatch

Children added to notebooks need a label, a position and optionally a close button (if supported). The arguments expand, fill, anchor are not specified – children expand and fill the allocated space.

Dispose deletes the current page, not the entire notebook object. To delete a specific page, a combination of `svalue<-` and `dispose` may be used.

The names of a notebook are the page tab labels. These may be retrieved and set through the `names` method.

The change handler for the notebook is called when the page changes. The new page number is passed back in the `page.no` component of 'h', which in some cases may differ from the value given by `svalue` within the handler call.

Dispose deletes the current page, not the entire notebook object. To delete a specific page, a combination of `svalue<-` and `dispose` may be used.

Usage

```
gnotebook(tab.pos = 3, container = NULL, ...,
          toolkit = guiToolkit())

.gnotebook(toolkit, tab.pos = 3, container = NULL, ...)

## S3 method for class 'GNotebook'
add(obj, child, expand, fill,
     anchor, ...)

## S3 method for class 'GNotebook'
dispose(obj, ...)

## S3 method for class 'GNotebook'
names(x)

## S3 method for class 'GNotebook'
addHandlerChanged(obj, handler,
                  action = NULL, ...)

## S3 method for class 'GStackWidget'
dispose(obj, ...)
```

Arguments

<code>tab.pos</code>	integer. Position of tabs, 1 on bottom, 2 left, 3 top, 4 right. (If supported)
<code>obj</code>	gnotebook object
<code>child</code>	some child component to add
<code>x</code>	notebook object
<code>container</code>	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
<code>...</code>	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent

	argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
<code>toolkit</code>	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
<code>handler</code>	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
<code>action</code>	User supplied data passed to the handler when it is called
<code>expand</code>	NULL or logical. For box containers controls whether a child will expand to fill the allocated space.
<code>fill</code>	NULL or character. For box containers. The value of <code>fill</code> (not always respected) is used to control if expansion happens vertically (<code>y</code>), horizontally (<code>x</code>) or both (<code>both</code> or <code>TRUE</code>). For vertically filled box containers, children always fill horizontally (atleast) and for horizontally filled box containers, children always fill vertically (atleast). This is important to realize when trying to size buttons, say.
<code>anchor</code>	NULL or integer. For box containers. The anchor argument is used to position the child within the parent when there is more space allocated than the child requests. This is specified with a Cartesian pair in <code>-1,0,1 x -1, 0, 1</code> .

Value

none. called for its side effect.

Note

In **gWidgets2** the button arguments of the `gWidgets` constructor are removed. One passes the close button request to the `add` method.

To keep the signature the same as the generic, several arguments are passed in via ...:

label A character. Label text for tab

i An integer in 0 to `length(obj)` indicating the position to insert child. The new page is inserted to the right of page number `i`. When `i=0`, the page appears at the front, when `i` is not specified it appears at the end.

close.button A logical. If `TRUE` – and the toolkit supports it – the page tab will include a close button.

See Also

[gstackwidget](#) for a similar widget without tabs.

Examples

```
## Not run:

w <- gwindow("notebook example", visible=FALSE)
nb <- gnotebook(container=w)
gbutton("Page one", label="tab 1", container=nb) ## note label argument
gbutton("Page two", label="tab 2", container=nb)
svalue(nb) <- 1
addHandlerChanged(nb, handler=function(h,...) {
  message(sprintf("On page %s", h$page.no)) ## svalue(h$obj) not always right
})
svalue(nb) <- 2
dispose(nb)
length(nb)

## End(Not run)
```

gpanedgroup

constructor for a two-paned container

Description

A container for holding two child widgets where the space allocated to each can be manipulated by the user with a pane between the widgets, or programmatically via `svalue<-`. The value specified to `svalue<-` can be a number in $[0,1]$, in which case it is a proportion or an integer, in which case it is a pixel size (from the left or the top). The ambiguous case 1 or 1L is determined by class. The value of `svalue` is in proportion units.

generic for toolkit dispatch

Usage

```
gpanedgroup(horizontal = TRUE, container = NULL, ...,
  toolkit = guiToolkit())
```

```
.gpanedgroup(toolkit, horizontal = TRUE,
  container = NULL, ...)
```

Arguments

horizontal	direction of layout
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent

argument to pass in parent information, similar to how the argument is used with `gaction` and the dialogs.

`toolkit` Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through `guiToolkit`.

Details

Child widgets are added in the usual way, typically through the `container` argument of a constructor. Only two children may be added. Children expand and fill the allocated space.

Note

There were arguments to specify the children at construction, but these have been removed.

Examples

```
## Not run:
w <- gwindow("gpanedgroup", visible=FALSE)
pg <- gpanedgroup(cont=w)
gbutton("left", cont=pg)
gbutton("right", cont=pg)

visible(w) <- TRUE
svalue(pg) <- 0.33

## End(Not run)
```

gprogressbar

Basic progress bar widget

Description

Basic progress bar widget

S3 generic whose methods are implemented in the toolkit packages

Usage

```
gprogressbar(value = 10, container = NULL, ...,
             toolkit = guiToolkit())
```

```
.gprogressbar(toolkit, value, container, ...)
```

Arguments

value	Initial value, between 0 and 100. A value of NULL will make pulsing bar with indeterminate state. For some toolkits, this must be called periodically to pulse the bar.
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with gaction and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through guiToolkit .

Value

a GButton instance. While this object has its own (reference) methods, one primarily interacts with it through S3 methods defined within the package.

gradio

Constructor for radio button widget

Description

A radio button group allows a user to select one from many items. In **gWidgets2** the radio button widget shows 2 or more items. The items are coerced to characters, usually by the underlying toolkit. Use the `coerce_with` property to set a function, such as `as.numeric`, to coerce the return value during the `svalue` code. The items are referred to with the `[]` method, the selected one with `svalue`.

Generic for method dispatch

The `svalue` method returns the radio button label or its index if `index=TRUE`. Labels are coerced to character by many of the toolkits. To be sure to return a numeric value, one can assign to the `coerce_with` property, e.g., `obj$coerce_with <- as.numeric`. For all widgets, if a function is specified to `coerce_with` it will be called on the value returned by `svalue`.

For a radio button group, for `svalue` the value can be referred to by index or label.

Check for repeated items before passing on to `set_items`

Usage

```
gradio(items, selected = 1, horizontal = FALSE,
       handler = NULL, action = NULL, container = NULL, ...,
       toolkit = guiToolkit())
```

```

.gradio(toolkit, items, selected = 1, horizontal = FALSE,
        handler = NULL, action = NULL, container = NULL, ...)

## S3 method for class 'GRadio'
svalue(obj, index = NULL, drop = TRUE,
       ...)

## S3 replacement method for class 'GRadio'
svalue(obj, index=NULL, drop=TRUE, ...) <-
  value

## S3 replacement method for class 'GRadio'
x[i, j, ...] <- value

```

Arguments

items	items to select from
selected	index of initially selected item
horizontal	layout direction
x	GRadio object
i	button index. Leave as missing to replace items to select from.
j	ignored
value	items to assign a choice for the buttons
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with at least two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget hierarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
obj	object of method call
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
drop	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps some other means.

Examples

```

if(interactive()) {
  w <- gwindow("Selection widgets")
  g <- gvbox(cont=w)

  fl <- gformlayout(cont=g)
  gcheckbox("checkbox", checked=TRUE, cont=fl, label="checkbox")
  gradio(state.name[1:4], selected=2, horizontal=TRUE, cont=fl, label="radio")
  gcheckboxgroup(state.name[1:4], horizontal=FALSE, cont=fl, label="checkbox group")

  bg <- ggroup(cont=g)
  gbutton("ok", cont=bg, handler=function(h,...) print(sapply(fl$children, svalue)))
}

```

gseparator

constructor providing a widget for displaying a line in a GUI

Description

The `gseparator` widget provides a horizontal or vertical line to visually divide child components of its parent container. In addition to box containers this can be used within toolbars (where one uses parent and not container).

generic for toolkit dispatch

Usage

```

gseparator(horizontal = TRUE, container = NULL, ...,
           toolkit = guiToolkit())

.gseparator(toolkit, horizontal = TRUE, container = NULL,
           ...)

```

Arguments

horizontal	Logical. Is separator drawn horizontally?
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

Examples

```
## Not run:

w <- gwindow("Within page", visible=FALSE)
g <- gvbox(container=w)
glabel("Lorem ipsum ...", cont=g)
gseparator(cont=g)
bg <- ggrouop(cont=g); addSpring(bg)
gbutton("dismiss", container=bg, handler=function(h,...) dispose(w))
visible(w) <- TRUE

w1 <- gwindow("within layout", visible=FALSE)
lyt <- glayout(container=w1)
lyt[1,1] <- "label"
lyt[2,1:2] <- gseparator(container=lyt)
lyt[3,2] <- "asdf"
visible(w1) <- TRUE

w2 <- gwindow("Within toolbar", visible=FALSE)
l <- list(file=gaction("File", parent=w2),
          sep=gseparator(parent=w2),
          quit=gaction("quit", parent=w2))
gtoolbar(l, cont=w2)
glabel("Lorem ipsum ...", container=w2)
visible(w2) <- TRUE

## End(Not run)
```

gslider

slider widget constructor

Description

A slider widgets allows a selection from a range of numeric values. The widget presents the user with a quick to adjust, but relatively difficult to adjust precisely way to to pick a number.

generic for toolkit dispatch

Usage

```
gslider(from = 0, to = 100, by = 1, length.out = NULL,
        along.with = NULL, value = from[1], horizontal = TRUE,
        handler = NULL, action = NULL, container = NULL, ...,
        toolkit = guiToolkit())

.gslider(toolkit, from = 0, to = 100, by = 1,
        value = from, horizontal = TRUE, handler = NULL,
        action = NULL, container = NULL, ...)
```

Arguments

from	If a number of length one then a starting point, in which case to, by are passed to seq. Otherwise a sequence of values for which <code>sort(unique(from))</code> will order
to	ending point when from is starting point
by	step size if not specified by from
length.out	in place of by
along.with	in place of length.out
value	initial value
horizontal	Logical. Is separator drawn horizontally?
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

See Also

[gspinbutton](#)

Examples

```
if(interactive()) {
  ## a range widget uses either a slider or a linked spinbutton to select a value
  w <- gwindow("Range widget", visible=FALSE)
  g <- ggroup(cont=w, horizontal=TRUE)
  sl <- gslider(from=0, to=100, by=1, value=0, cont=g, expand=TRUE, fill="both")
  sp <- gspinbutton(from=0, to=100, by=1, value=0, cont=g)

  ## Two ways to do this:
  ## addHandlerChanged(sl, function(...) svalue(sp) <- svalue(sl))
  ## addHandlerChanged(sp, function(...) svalue(sl) <- svalue(sp))

  f <- function(h, ...) svalue(h$action) <- svalue(h$obj)
```

```

addHandlerChanged(sl, f, action=sp)
addHandlerChanged(sp, f, action=sl)

visible(w) <- TRUE
}

```

gspinbutton

Spinbutton constructor

Description

A spinbutton allows the user to select from a pre-selected range of numbers. Similar to a slider, but with more precision, but slower to adjust. The basic arguments mirror that of `seq.int`.

generic for toolkit dispatch

Usage

```

gspinbutton(from = 0, to = 10, by = 1, length.out = NULL,
  along.with = NULL, value = from, digits = 0,
  handler = NULL, action = NULL, container = NULL, ...,
  toolkit = guiToolkit())

```

```

.gspinbutton(toolkit, from = 0, to = 10, by = 1,
  value = from, digits = 0, handler = NULL,
  action = NULL, container = NULL, ...)

```

Arguments

from	from value
to	to value
by	step length
length.out	number of steps. Only one of by or length.out is used.
along.with	Take from
value	initial value
digits	number of digits to display, should the toolkit support it
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called

container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

See Also[gslider](#)**Examples**

```

if(interactive()) {
  ## a range widget uses either a slider or a linked spinbutton to select a value
  w <- gwindow("Range widget", visible=FALSE)
  g <- ggroup(cont=w, horizontal=TRUE)
  sl <- gslider(from=0, to=100, by=1, value=0, cont=g, expand=TRUE, fill="both")
  sp <- gspinbutton(from=0, to=100, by=1, value=0, cont=g)

  ## Two ways to do this:
  ## addHandlerChanged(sl, function(...) svalue(sp) <- svalue(sl))
  ## addHandlerChanged(sp, function(...) svalue(sl) <- svalue(sp))

  f <- function(h, ...) svalue(h$action) <- svalue(h$obj)
  addHandlerChanged(sl, f, action=sp)
  addHandlerChanged(sp, f, action=sl)

  visible(w) <- TRUE
}

```

`gstackwidget`*Constructor for a stack of widgets*

Description

This widget is like a notebook – it holds a stack of pages, but does not provide the tabs to work with. Most methods are inherited from `gnotebook`'s.

generic for toolkit dispatch

Usage

```
gstackwidget(container = NULL, ...,
             toolkit = guiToolkit())

.gstackwidget(toolkit, container = NULL, ...)
```

Arguments

container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through guiToolkit .

Examples

```
## Not run:
w <- gwindow("stack widget", visible=FALSE)
add_page <- function(cont, i) {
  g <- gvbox(container=cont)
  glabel(sprintf("page %s",i), container=g)
  bg <- ggroup(container=g); addSpring(bg)
  lb <- gbutton("Previous", container=bg, handler=function(h,...) {
    svalue(cont) <- max(1, i - 1)
  })
  rb <- gbutton("Next", container=bg, handler=function(h,...) {
    svalue(cont) <- min(i + 1, length(cont))
  })
}
sw <- gstackwidget(cont=w)
sapply(1:5, add_page, cont=sw)
visible(w) <- TRUE

## End(Not run)
```

gstatusbar

constructor to add a status bar to main window

Description

constructor to add a status bar to main window
generic for toolkit dispatch

Usage

```
gstatusbar(text = "", container = NULL, ...,
           toolkit = guiToolkit())

.gstatusbar(toolkit, text = "", container = NULL, ...)
```

Arguments

text	initial status text
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. gWidgets2tcltk or gWidgets2WWW2 .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through guiToolkit .

Examples

```
## Not run:
w <- gwindow("Statusbar", visible=FALSE)
sb <- gstatusbar("status text", container=w)
g <- g vbox(container=w)
gbutton("update", container=g, handler=function(...) svalue(sb) <- "new value")
visible(w) <- TRUE

## End(Not run)
```

gtable

A constructor for displaying tabular data for selection

Description

The tabular widget allows a user to select one (or more) row(s) using the mouse or keyboard selection. The selected rows are the main property and are returned by `svalue` through their key (from the column specified by `chosen.col`), or by index. The change handler changes on double-click event. Use `add handler click` to respond to a change in selection.

`.gtable` generic for toolkit dispatch

For `gtable` one can pass in `row(s)` to select by index (when `index=TRUE`) or by match among the values in the chosen column. For setting by index, a value of `0L` or `integer(0)` will clear the current selection

For `GTable` objects the `[` and `[<-` methods are (mostly) implemented. The `[` method allows one to access the object using the regular matrix notation (but there is no list notation, e.g. `$` or `[[,` defined). The `[<-` method is available, but for most toolkits is restricted: one can not add columns, add rows, remove columns, remove rows, or change the type of the column. For all of these actions,

one can reassign the items being displayed through the idiom `obj[] <- new_items`. This allows the widget to resize or redo the column renderers.

The change handler for `GTable` is called when the selection changes. This is often the result of a click event (but need not be), although we alias to `addHandlerClicked`. For double click events, see `addHandlerDoubleClick`.

Double clicking is used to activate an item (single click is selection). We also bind pressing the Return key on an item to initiate this signal

For `GTable`, visibility refers to which rows are currently shown, not whether the widget itself is shown or hidden. (For the latter, place the widget into a container and adjust that). One can use this method to perform filtering by adjusting which rows are displayed according to some criteria that returns a logical.

For `GTable` the `size<-` method is overridden to allow one to specify the column widths. To do so, pass in the values for width, height or `column.widths` as named components of a list. The value of `column.widths` should be a numeric vector of pixel widths of length matching the number of columns.

Usage

```
gtable(items, multiple = FALSE, chosen.col = 1,
        icon.col = NULL, tooltip.col = NULL, handler = NULL,
        action = NULL, container = NULL, ...,
        toolkit = guiToolkit())

.gtable(toolkit, items, multiple = FALSE, chosen.col = 1,
         icon.col = NULL, tooltip.col = NULL, handler = NULL,
         action = NULL, container = NULL, ...)

## S3 method for class 'GTable'
svalue(obj, index = NULL, ..., value)

## S3 method for class 'GTable'
x[i, j, ..., drop = TRUE]

## S3 method for class 'GTable'
addHandlerChanged(obj, handler,
                  action = NULL, ...)

## S3 method for class 'GTable'
addHandlerDoubleClick(obj, handler,
                      action = NULL, ...)

## S3 method for class 'GTable'
visible(obj, ...)

## S3 replacement method for class 'GTable'
size(obj) <- value
```

Arguments

items	data.frame specifies items for selection. May be a vector, matrix or data frame
multiple	logical allow multiple selection
chosen.col	which value from the row is returned by selection
icon.col	NULL or integer. If latter, specifies column containing stock icon
tooltip.col	NULL or integer. If latter, specifies column containing tooltip
x	GTable object
i	row index
j	column index
drop	do we drop when subsetting
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
obj	object of method call
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
value	value to assign for selection or property

Value

Returns an object of class `GTable`

Examples

```
## Not run:
w <- gwindow("gtable example", visible=FALSE)
g <- gvbox(cont=w)
tbl <- gtable(mtcars, cont=g, expand=TRUE, fill=TRUE)
addHandlerClicked(tbl, handler=function(h,...) sprintf("You selected %s", svalue(h$obj)))
```

```

visible(w) <- TRUE

## End(Not run)

```

gtext

Multiline text edit constructor

Description

The multiline text widget has its main property the text contained within.

- The `svalue` will return a string (length-1 character vector) with embedded newlines
- The "change" handler is `addHandlerKeystroke`
- Use `addHandlerSelectionChanged` to monitor the selection

generic for toolkit dispatch

insert text into a gtext buffer

insert method for gtext

dispose method for gtext clears buffer

The `svalue` method for a gtext object returns a) the buffers content, b) the selected text (if `drop=TRUE`, but not `NULL`), the index of the selection if `index=TRUE`

Usage

```

gtext(text = NULL, width = NULL, height = 300,
      font.attr = NULL, wrap = TRUE, handler = NULL,
      action = NULL, container = NULL, ...,
      toolkit = guiToolkit())

.gtext(toolkit, text = NULL, width = NULL, height = 300,
      font.attr = NULL, wrap = TRUE, handler = NULL,
      action = NULL, container = NULL, ...)

insert(obj, value,
      where = c("end", "beginning", "at.cursor"),
      font.attr = NULL, do.newline = TRUE, ...)

## S3 method for class 'GText'
insert(obj, value,
      where = c("end", "beginning", "at.cursor"),
      font.attr = NULL, do.newline = TRUE, ...)

## S3 method for class 'GText'
dispose(obj, ...)

```

```
## S3 method for class 'GText'
svalue(obj, index = NULL, drop = NULL,
...)
```

Arguments

text	initial text
width	width of widget
height	height of widget (when width is specified)
font.attr	font attributes for text buffer. One can also specify font attributes for insertion. The font attributes are specified with a named vector or list, with names and values coming from: weight in c("light", "normal", "bold", "heavy") style inc("normal", "oblique", "italic") family in c("sans", "helvetica", "times", "monospace") size in c("xx-small", "x-small", "small", "medium", "large", "x-large", "xx-large") foreground a value in colors() background a value in colors()
wrap	logical do lines wrap
obj	object
value	text to insert
where	position of insertion
do.newline	logical add a newline at end
handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will look up the toolkit through <code>guiToolkit</code> .
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.

drop NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Value

called for side effect

Note

with **gWidgetstcltk** the allocation of size to the widget may be incorrect. It is best to wait until the widget is added before displaying its parent window. See the `visible` argument for `gwindow`.

Examples

```
## Not run:
w <- gwindow("gtext example", visible=FALSE)
g <- gvbox(cont=w)
t1 <- gtext("initial text", container=g)
t2 <- gtext("monospace", font.attr=list(family="monospace"), container=g)
insert(t2, "new text in bold", font.attr=list(weight="bold"))
visible(w) <- TRUE

## End(Not run)
```

gtimer

Basic timer widget

Description

Calls FUN every ms/1000 seconds. A timer is stopped through its `stop_timer` method which is called using OO style: `obj$stop_timer()`.

S3 generic for dispatch

Usage

```
gtimer(ms, FUN, data = NULL, one.shot = FALSE,
       start = TRUE, toolkit = guiToolkit())

.gtimer(toolkit, ms, FUN, data = NULL, one.shot = FALSE,
        start = TRUE)
```

Arguments

<code>ms</code>	interval in milliseconds
<code>FUN</code>	FUnction to call. Has one argument, data passed in
<code>data</code>	passed to function
<code>one.shot</code>	logical. If TRUE, called just once, else repeats
<code>start</code>	logical. If FALSE, started by <code>start_timer</code> OO method. (Call <code>obj\$start_time()</code>).
<code>toolkit</code>	gui toolkit to dispatch into

Examples

```
## Not run:
i <- 0
FUN <- function(data) {i <- i + 1; if(i > 10) a$stop_timer(); print(i)}
a <- gtimer(1000, FUN)
##
## a one shot timer is run only once
FUN <- function(data) message("Okay, I can breathe now")
hold_breath <- gtimer(1000*60, FUN, one.shot=TRUE)

## End(Not run)
```

gtoolbar

*A toolbar constructor***Description**

A toolbar can be added to a main window to proxy various actions. Toolbars can also contain various widgets, such as buttons, checkboxes, radio buttons, etc. These should be constructed using a parent argument – not a container argument. In **gWidgets2** a toolbar is specified by a list of toolbar items. The `svalue` and `svalue<-` methods may be used to get or set the items.

generic for toolkit dispatch

A toolbar item is a list of action items or a toolbar instance

for a toolbar, `svalue<-` replaces the toolbar items with new ones specified by value.

Usage

```
gtoolbar(toolbar.list = list(),
  style = c("both", "icons", "text", "both-horiz"),
  container = NULL, ..., toolkit = guiToolkit())

.gtoolbar(toolkit, toolbar.list = list(),
  style = c("both", "icons", "text", "both-horiz"),
  container = NULL, ...)

## S3 method for class 'GToolBar'
add(obj, child, expand = FALSE,
  fill = NULL, anchor = NULL, ...)

## S3 replacement method for class 'GToolBar'
svalue(obj, index=NULL, ...) <- value
```

Arguments

`toolbar.list` list. A one-level list of `gaction` items, `gseparator` items or possibly other widgets. In the latter cases the `container` argument is not specified prior. (XXX Need to work this out with `gWidgetstcltk`)

style	style for icon or text.
container	a GWindow instance
...	ignored
toolkit	toolkit
obj	parent object
child	child widget
expand	NULL or logical. For box containers controls whether a child will expand to fill the allocated space.
fill	NULL or character. For box containers. The value of fill (not always respected) is used to control if expansion happens vertically (y), horizontally (x) or both (both or TRUE). For vertically filled box containers, children always fill horizontally (atleast) and for horizontally filled box containers, children always fill vertically (atleast). This is important to realize when trying to size buttons, say.
anchor	NULL or integer. For box containers. The anchor argument is used to position the child within the parent when there is more space allocated than the child requests. This is specified with a Cartesian pair in -1,0,1 x -1, 0, 1.
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
value	value to assign for selection or property

gtoolkit

Which toolkit are we using?

Description

Which toolkit are we using?

Usage

```
gtoolkit()
```

Value

string of toolkit (RGtk2, tcltk, Qt, ???)

gtree

*constructor for widget to display heirarchical data***Description**

The gtree widget is used to present structured heirarchical data. This data may be specified through a data frame with some accompanying columns by which to split the data, or dynamically through a function (offspring).

generic for toolkit dispatch

For a GTree object, svalue refers to the path specified as a vector of keys or (if INDEX=TRUE) by an integer vector of offspring positions. The drop argument is used to indicate if the terminus of the path is returned or the entire path, defaults=TRUE. To get the data associated with a row, use the [method.

For a GTree object, svalue refers to the path specified as a vector of keys . For the assignment method, one assigns by index. That is svalue(tr, index=TRUE) <- svalue(tr, index=TRUE) should not change the state of the widget. (The index=TRUE argument is the case for setting, but not getting.)

The [method is used to return the data associated with a selected row. The svalue method returns the path or its endpoint, the [method returns the row data associated with the path.

The update method for GTree recomputes the base nodes, then reopens the given node if still available

Usage

```
gtree(x = NULL, INDICES = NULL, offspring = x,
      offspring.data = NULL, chosen.col = 1,
      offspring.col = 2, icon.col = NULL, tooltip.col = NULL,
      multiple = FALSE, handler = NULL, action = NULL,
      container = NULL, ..., toolkit = guiToolkit())

.gtree(toolkit, offspring = NULL, offspring.data = NULL,
        chosen.col = 1, offspring.col = 2, icon.col = NULL,
        tooltip.col = NULL, multiple = FALSE, handler = NULL,
        action = NULL, container = NULL, ...)

## S3 method for class 'GTree'
svalue(obj, index = FALSE, drop = TRUE,
       ...)

## S3 replacement method for class 'GTree'
svalue(obj, index=TRUE, ...) <- value

## S3 method for class 'GTree'
x[i, j, ..., drop = FALSE]
```

```
## S3 method for class 'GTree'
update(object, ...)
```

Arguments

<code>x</code>	Data frame. Optional, if given specify INDICES value to split data into heirarchical data structure
<code>INDICES</code>	Integers or column names, referring to columns of <code>x</code> . Used to form heirarchical structure. Order is important.
<code>offspring</code>	function. A function passed values <code>path</code> and <code>data</code> , the latter from <code>offspring.data</code> . The <code>path</code> is the current position of the parent item using the named keys from the chosen column.
<code>offspring.data</code>	Passed to second argument of <code>offspring</code> function. Used to parameterize a function call.
<code>chosen.col</code>	integer or one of column names of data frame returned by <code>offspring</code> . The chosen column gives the key and value of the path.
<code>offspring.col</code>	integer or column name. Points to column containing logical values indicating if a row has <code>offspring</code> .
<code>icon.col</code>	integer of one of the column names of the data frame. If provided (non-NULL), then this column should provide a stock icon name to be placed in the row for the given data.
<code>tooltip.col</code>	integer or one of the column names of the data frame. If provided (non-NULL), then the row for this item will have a tooltip given by the pointed to value.
<code>multiple</code>	logical. Is multiple selection allowed?
<code>obj</code>	object
<code>index</code>	index
<code>drop</code>	do we return tip or path
<code>value</code>	vector of indices
<code>i</code>	ignored
<code>j</code>	ignored
<code>object</code>	object to update
<code>...</code>	passed to update method
<code>handler</code>	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
<code>action</code>	User supplied data passed to the handler when it is called
<code>container</code>	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
<code>toolkit</code>	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

Details

In the former case, the data frame is split up by the columns specified by INDICES. The first index is used to give the initial branches, the second index the second, etc. The end leaves are the data associated with a given path, with key given by that column specified by chosen.col

For the latter case, the "path" of the current node (the node and its ancestors) is passed to the offspring function which computes the next level in the hierarchy. This level is specified through a data frame. This data frame has special columns. The chosen.col specifies which column is used as the key in the path, the icon.col (when given) points to a stock icon name to decorate the column. Similarly, the tooltip.columns. The fact that a row in the data frame has offspring is specified through the offspring.col column, again specified by index or column name.

Examples

```
#####
## This tree reads a list
offspring <- function(path=character(0), lst, ...) {
  if(length(path))
    obj <- lst[[path]]
  else
    obj <- lst
  nms <- names(obj)
  hasOffspring <- sapply(nms, function(i) {
    newobj <- obj[[i]]
    is.recursive(newobj) && !is.null(names(newobj))
  })
  data.frame(comps=nms, hasOffspring=hasOffspring, ## fred=nms,
             stringsAsFactors=FALSE)
}
l <- list(a="1", b= list(a="21", b="22", c=list(a="231")))

## Not run:
w <- gwindow("Tree test")
t <- gtree(offspring=offspring, offspring.data=l, cont=w)

## End(Not run)

#####
## This tree looks at recursive objects
describe <- function(x) UseMethod("describe")
describe.default <- function(x) sprintf("An object with class %s", class(x)[1])
describe.integer <- function(x) sprintf("An integer with %s value%s", length(x),
  ifelse(length(x) > 1, "s", ""))
describe.numeric <- function(x) sprintf("A numeric with %s value%s", length(x),
  ifelse(length(x) > 1, "s", ""))
describe.factor <- function(x) sprint("A factor with %s level%s", length(levels(x)),
  ifelse(length(levels(x)) > 1, "s", ""))

offspring <- function(path, obj) {
  if(length(path) > 0)
    x <- obj[[path]]
  else
```

```

x <- obj

nms <- names(x)
recursive <- sapply(x, function(i) {
  is.recursive(i) &&
  !is.null(attr(i, "names")) &&
  length(i) > 0
})
descr <- sapply(x, describe)

data.frame(Variable=nms, offspring=recursive, Description=descr, stringsAsFactors=FALSE)
}

l <- lm(mpg ~ wt, mtcars)
## Not run:
w <- gwindow("test")
gtree(offspring=offspring, offspring.data=l, cont=w)

## End(Not run)

```

guiToolkit

set or get the current toolkit for gWidgets

Description

set or get the current toolkit for gWidgets

Usage

```
guiToolkit(name = NULL)
```

Arguments

name name of toolkit (e.g. "tcltk", "RGtk2", "Qt" (not qtbase)). If NULL, then we search for it in a) an inherited toolkit object b) the "guiToolkit" option (which can be set via `options("guiToolkit"="RGtk2")`), say. If that fails, we prompt for a selection for any installed toolkit. In the typical usage, this all happens in the background, except perhaps once.

In design this is to allow different toolkits to be used with different GUIs, but due to differences in event loops, this often leads to lockups, so is not recommended.

Value

an instance of guiWidgetsToolkit sub class.

`guiWidgetsToolkit-class`*A class to record the toolkit a gui object uses*

Description

A class to record the toolkit a gui object uses

An observer can be observed

Handler is a special observer with obj and actino passed as first argument

Observable class sets up objects that can be observed. Inherited by template

This interface is inherited by the base GComponent classes in the toolkit implementations. The methods defined here are referenced by the S3 methods. For exampe, svalue dispatches to `get_value` or `get_index`.

A reference class to create a model that monitors the global workspace. The class has method `update_state` and the "getting" methods `get_by_class`, `get_by_function` (filter), `get_changes`. Use with a `gtimer` instance to keep up to date with changes to the workspace.

Class for commands. Has methods `do`, `redo`, `undo`

Class for multiple commands

A list with `ptr`. delegates call of `do` or `undo` to appropriate command

Class for icons

Usage`Observer(...)``Handler(...)``Observable(...)``BasicToolkitInterface(...)``WSWatcherModel(...)``Command(...)``CommandList(...)``CommandStack(...)``GWidgets2Icons(...)`**Arguments**

... passed to constructor

Details

We combine both widget and container methods here. It isn't perfect, but they do share quite a bit. Perhaps, we could make the container class subclass the basic interface.

gvarbrowser

Constructor for workspace variable browser

Description

A workspace browser widget. The workspace browser displays values in the global environment. Displayed objects are shown in categories.

generic for toolkit dispatch

Return selected objects a string (when drop=TRUE) with recursive values separated by \$, or the objects themselves (when drop=FALSE).

Usage

```
gvarbrowser(handler = NULL, action = "summary",
            container = NULL, ..., toolkit = guiToolkit())

.gvarbrowser(toolkit, handler = NULL, action = "summary",
             container = NULL, ...)

## S3 method for class 'GVarBrowser'
svalue(obj, index = FALSE,
       drop = TRUE, ...)
```

Arguments

handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the <code>add</code> method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.

toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .
obj	object of method call
index	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
drop	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.

Details

For defining the categories, the reference method `set_filter_classes` takes a named list, the names defining the categories, the values being the classes belonging to that category. Non categorized values appear separately. The default is defined in `gWidgets2::gvarbrowser_default_classes`.

The variable browser uses an instance of `WSWatcherModel` to monitor the global workspace. This instance may be useful for other purposes. (For example, one may add an observer that is called to listen for changes to the set of available data frames.). The instance is available through the `ws_model` property.

The `svalue` method returns the selected variable names. If `drop=FALSE` is given, the objects are returned.

The widget should support dragging from without needing to specify a `drag_source`, though this may be overridden.

Use `addHandlerChanged` to listen to activation of a variable (double clicking). Use `addHandlerSelectionChanged` to monitor change of selection.

gwidget	<i>Common parts of a widget</i>
---------	---------------------------------

Description

Used as template for documentation

Usage

```
gwidget(handler = NULL, action = NULL, container = NULL,
        ..., toolkit = guiToolkit())
```

Arguments

handler	A handler assigned to the default change signal. Handlers are called when some event triggers a widget to emit a signal. For each widget some default signal is assumed, and handlers may be assigned to that through <code>addHandlerChanged</code> or at construction time. Handlers are functions whose first argument, <code>h</code> in the documentation, is a list with atleast two components <code>obj</code> , referring to the object emitting the signal and <code>action</code> , which passes in user-specified data to parameterize the function call.
---------	---

action	User supplied data passed to the handler when it is called
container	A parent container. When a widget is created it can be incorporated into the widget heirarchy by passing in a parent container at construction time. (For some toolkits this is not optional, e.g. <code>gWidgets2tcltk</code> or <code>gWidgets2WWW2</code> .)
...	These values are passed to the add method of the parent container, and occasionally have been used to sneak in hidden arguments to toolkit implementations. For example, when using a widget as a menubar object one can specify a parent argument to pass in parent information, similar to how the argument is used with <code>gaction</code> and the dialogs.
toolkit	Each widget constructor is passed in the toolkit it will use. This is typically done using the default, which will lookup the toolkit through <code>guiToolkit</code> .

gwindow

gwindow

Description

top-level window object

S3 generic whose methods are implemented in the toolkit packages

Dispatches on type of child (menubar, toolbar, statusbar, widget)

The dispose method destroys the top-level window and its children.

Usage

```
gwindow(title = "Window", visible = TRUE, name = title,
        width = NULL, height = NULL, parent = NULL,
        handler = NULL, action = NULL, ...,
        toolkit = guiToolkit())
```

```
.gwindow(toolkit, title, visible, name, width, height,
         parent, handler, action, ...)
```

```
## S3 method for class 'GWindow'
add(obj, child, expand = NULL,
    fill = NULL, anchor = NULL, ...)
```

```
## S3 method for class 'GWindow'
dispose(obj, ...)
```

Arguments

`title` title for window's title bar. This is the main property and is accessed via `svalue` or `svalue<-`.

visible	logical. If code TRUE window is drawn when constructed. Otherwise, window can be drawn later using <code>visible<-</code> . This value can default to FALSE by setting the option: <code>options("gWidgets:gwindow-default-visible-is-false"=TRUE)</code> . There are advantages: windows can draw slowly when adding many items. With gWidgets2RGtk2 , the <code>ggraphics</code> widget can like to be added to an undrawn widget as this avoids sizing issue.
name	Name for registry of windows
width	initial width of window
height	initial height of window. This sets height before window manager manages the window
parent	If non-NULL, can be used to suggest default location of window. The argument name was changed from location to parent. This can be a coordinate pair (x,y) with (0,0) the upper left corner, or a gwindow instance. In the latter case the location is suggested by the location of the current window. This is useful for placing dialogs near the parent window.
handler	handler for destroy event
action	action passed t handler
...	ignored
toolkit	toolkit
obj	parent object
child	child widget
expand	NULL or logical. For box containers controls whether a child will expand to fill the allocated space.
fill	NULL or character. For box containers. The value of fill (not always respected) is used to control if expansion happens vertically (y), horizontally (x) or both (both or TRUE). For vertically filled box containers, children always fill horizontally (atleast) and for horizontally filled box containers, children always fill vertically (atleast). This is important to realize when trying to size buttons, say.
anchor	NULL or integer. For box containers. The anchor argument is used to position the child within the parent when there is more space allocated than the child requests. This is specified with a Cartesian pair in -1,0,1 x -1, 0, 1.

Value

a GWindow instance

Author(s)

john verzani

```
installing_gWidgets_toolkits
      blurb about installation
```

Description

put in so can be updated easily

Usage

```
installing_gWidgets_toolkits()
```

```
isExtant      Check if widget is extant.
```

Description

Widgets can be destroyed, but their R object is still present. This is FALSE in that case.
Basic S3 method for isExtant

Usage

```
isExtant(obj)

## Default S3 method:
isExtant(obj)
```

Arguments

```
obj          object
```

```
is_empty      is value missing, null, 0-length or NA length 1
```

Description

is value missing, null, 0-length or NA length 1

Usage

```
is_empty(x)
```

Arguments

x object to test

Value

logical

is_MacOSX *Return logical indicating if we are on a macintosh machine*

Description

Return logical indicating if we are on a macintosh machine

Usage

is_MacOSX()

Value

logical

is_Windows *Return logical indicating if we are on a Windows machine*

Description

Return logical indicating if we are on a Windows machine

Usage

is_Windows()

Value

logical

observer	<i>constructor for handler object</i>
----------	---------------------------------------

Description

constructor for handler object

Usage

```
observer(receiver, handler, action = NULL)
```

Arguments

receiver	object receiving event
handler	function to call
action	used to parametrize handler call not exported, call using :::

redo	<i>Redo past action.</i>
------	--------------------------

Description

Some widgets support redo actions

S3 method.

Usage

```
redo(obj, ...)  
  
## S3 method for class 'GComponent'  
redo(obj, ...)
```

Arguments

obj	object to redo
...	ignored

short_summary	<i>Provide a short summary for an object</i>
---------------	--

Description

Provide a short summary for an object
method for generic
method for generic
method for generic
method for generic
method for generic
method for generic
method for generic
method for generic
method for generic

Usage

```
short_summary(x)

## Default S3 method:
short_summary(x)

## S3 method for class 'numeric'
short_summary(x)

## S3 method for class 'character'
short_summary(x)

## S3 method for class 'logical'
short_summary(x)

## S3 method for class 'data.frame'
short_summary(x)

## S3 method for class 'matrix'
short_summary(x)

## S3 method for class 'list'
short_summary(x)

## S3 method for class 'lm'
short_summary(x)
```

```
## S3 method for class 'function'
short_summary(x)
```

Arguments

x object

size *Return size (width and height) of widget*

Description

Return size (width and height) of widget

S3 method for size

The size is specified in pixels (integers). Some toolkits allow -1 as a default, but not all.

S3 method for size

Usage

```
size(obj)
```

```
## Default S3 method:
size(obj)
```

```
size(obj) <- value
```

```
size(obj) <- value
```

Arguments

obj object

value size in pixels

svalue *svalue*

Description

This returns the "selected" value in a widget (if applicable), or its main property. Selection varies from widget to widget, but should generally be what can be added to the widget by mouse click or typing. For some widgets, the extra argument `index=TRUE` will return the index of the selected value, not the value. For some widget, the argument `drop` is given to either prevent or encourage dropping of information.

Calls `coerce_with` when available. This value is a function and may be set as any property if the constructor does not explicitly provide it.

This method sets the selected value of, or main property of the widget.

Base S3 method

For `gformlayout` the `svalue` assignment method takes a named list and calls `svalue<-` on the children with matching names.

Usage

```
svalue(obj, index = FALSE, drop = NULL, ...)

## Default S3 method:
svalue(obj, index = NULL, drop = NULL,
  ...)

svalue(obj, index=NULL, ...) <- value

svalue(obj, index=NULL, ...) <- value

## S3 replacement method for class 'GFormLayout'
svalue(obj, index=NULL, ...) <-
  value
```

Arguments

<code>obj</code>	object of method call
<code>index</code>	NULL or logical. If TRUE and widget supports it an index, instead of a value will be returned.
<code>drop</code>	NULL or logical. If widget supports it, drop will work as it does in a data frame or perhaps someother means.
<code>...</code>	passed on to call
<code>value</code>	value to assign for selection or property

Value

The return value varies, depending if the widget is a "selection" widget or not. For non-selection widgets, the main property is loosely defined (the title of a window, text of a label or button, spacing of box containers, ...). For selection widgets the return value is the currently selected value. If no selection is made, this will be a 0-length vector with the expected class, if possible. For selection widgets, when `index=TRUE`, the value is an integer, possible 0-length when non selection is made.

tag	<i>get a persistent attribute for an object</i>
-----	---

Description

get a persistent attribute for an object

Basic S3 method

Unlike `attr<-`, this method (essentially) stores the attribute in a reference to the object, not a copy. As such it can be used within function call (handlers) to assign values outside the scope of the function call.

Basic S3 method

Usage

```
tag(obj, key)
```

```
## Default S3 method:
tag(obj, key)
```

```
tag(obj, key) <- value
```

```
tag(obj, key) <- value
```

Arguments

obj	object
key	character. Values are stored by key. If missing, all keys are returned.
value	to assign to key

tooltip	<i>Get a tooltip for the widget</i>
---------	-------------------------------------

Description

Get a tooltip for the widget

Basic S3 method for tooltip<-

Set a tooltip for the widget

Basic S3 method for tooltip<-

Usage

```
tooltip(obj)

## Default S3 method:
tooltip(obj)

tooltip(obj) <- value

tooltip(obj) <- value
```

Arguments

obj	object
value	character tooltip value

undo	<i>Undo past action.</i>
------	--------------------------

Description

Some widgets support undo actions. See reference class method `can_undo` as well.
S3 method.

Usage

```
undo(obj, ...)
```

S3 method for class 'GComponent'
undo(obj, ...)

Arguments

obj	object to call undo on
...	ignored

visible	<i>Controls whether widget is visible or not</i>
---------	--

Description

For most – but not all – widgets, a widget is visible if it is shown. For others, parts of the widget may be controlled by visible. If the former state is desired, simply place widget into a box container.

Basic S3 method

Set visibility of an object

Basic S3 method for visible

Usage

```
visible(obj, ...)
```

```
## Default S3 method:
visible(obj, ...)
```

```
visible(obj) <- value
```

```
visible(obj) <- value
```

Arguments

obj	object
...	ignored
value	logical. Set visible state.

XXX	<i>Functions to message something needs doing. Easy to search for</i>
-----	---

Description

Functions to message something needs doing. Easy to search for

Usage

```
XXX(msg)
```

Arguments

msg	optional message to emit
-----	--------------------------

[.GDefaultWidget *Return items*

Description

Return items

Set object's items

Length of object

set length of object

dimension of object

Names are used in many different contexts.

set names of object

Get dimnames of object

Set dimnames of object

We use the extraction operator, `[`, typically to refer to the underlying items from which a selection can be made. As well, we overload this to containers to refer to the child components.

Return children of a parent container

Set object's items

The update method will cause a widget to recompute itself, if it is necessary.

str method for widgets

The current items for a `gdf` object are both the visible and non-visible items. To retrieve just the currently visible items, use the idiom `obj[visible(obj),]`.

set names for frame

The underlying widget may allow autocompletion, if this is the case then this method is used to set the list of candidates.

Usage

```
## S3 method for class 'GDefaultWidget'
x[i, j, ...]

## S3 replacement method for class 'GDefaultWidget'
x[i, j, ...] <- value

## S3 method for class 'GComponent'
length(x)

## S3 replacement method for class 'GComponent'
length(x) <- value

## S3 method for class 'GComponent'
```

```

dim(x)

## S3 method for class 'GComponent'
names(x)

## S3 replacement method for class 'GComponent'
names(x) <- value

## S3 method for class 'GComponent'
dimnames(x)

## S3 replacement method for class 'GComponent'
dimnames(x) <- value

## S3 method for class 'GComponent'
x[i, j, ..., drop = TRUE]

## S3 method for class 'GContainer'
x[i, j, ..., drop = TRUE]

## S3 replacement method for class 'GComponent'
x[i, j, ...] <- value

## S3 method for class 'GComponent'
update(object, ...)

## S3 method for class 'GComponent'
str(object, ...)

## S3 method for class 'GDf'
x[i, j, ..., drop = TRUE]

## S3 replacement method for class 'GFrame'
names(x) <- value

## S3 method for class 'GEdit'
x[i, j, ..., drop = TRUE]

```

Arguments

x	component
value	value to assign
i	index or row index if applicable
j	column index if applicable
drop	logical. Does return value get "dropped" down to something easier?
...	dots argument
object	object to update

Value

length of object

Index

*Topic **package**

- gWidgets2-package, 3
- .addStockIcons (addStockIcons), 16
- .gaction (gaction), 24
- .galert (galert), 25
- .gbasicdialog (gbasicdialog), 25
- .gbutton (gbutton), 27
- .gcalendar (gcalendar), 29
- .gcheckbox (gcheckbox), 30
- .gcheckboxgroup (gcheckboxgroup), 32
- .gcombobox (gcombobox), 34
- .gconfirm (gconfirm), 36
- .gdf (gdf), 37
- .gdfnotebook (gdfnotebook), 38
- .gdfnotebook.default, 7
- .gedit (gedit), 39
- .getStockIconByName (addStockIcons), 16
- .getStockIcons (addStockIcons), 16
- .gexpandgroup (gexpandgroup), 43
- .gfile (gfile), 44
- .gfilebrowse (gfile), 44
- .gfilter (gfilter), 46
- .gformlayout (gformlayout), 48
- .gframe (gframe), 49
- .ggraphics (ggraphics), 50
- .ggraphicsnotebook (ggraphicsnotebook), 52
- .ggroup (ggroup), 53
- .ghtml (ghtml), 54
- .gimage (gimage), 55
- .ginput (ginput), 56
- .glabel (glabel), 57
- .glayout (glayout), 58
- .gmenu (gmenu), 60
- .gmessage (gmessage), 62
- .gnotebook (gnotebook), 62
- .gpanedgroup (gpanedgroup), 65
- .gprogressbar (gprogressbar), 66
- .gradio (gradio), 67
- .gseparator (gseparator), 69
- .gslider (gslider), 70
- .gspinbutton (gspinbutton), 72
- .gstackwidget (gstackwidget), 73
- .gstatusbar (gstatusbar), 74
- .gtable (gtable), 75
- .gtext (gtext), 78
- .gtimer (gtimer), 80
- .gtoolbar (gtoolbar), 81
- .gtree (gtree), 83
- .gvarbrowser (gvarbrowser), 88
- .gwindow (gwindow), 90
- .make_gcombobox_items (gcombobox), 34
- .stockIconFromClass (addStockIcons), 16
- .stockIconFromObject (addStockIcons), 16
- [.GComponent ([.GDefaultWidget), 101
- [.GContainer ([.GDefaultWidget), 101
- [.GDefaultWidget, 101
- [.GDf ([.GDefaultWidget), 101
- [.GEdit ([.GDefaultWidget), 101
- [.GFilter (gfilter), 46
- [.GLayout (glayout), 58
- [.GTable (gtable), 75
- [.GTree (gtree), 83
- [<- .GCheckbox (gcheckbox), 30
- [<- .GComboBox (gcombobox), 34
- [<- .GComponent ([.GDefaultWidget), 101
- [<- .GDefaultWidget ([.GDefaultWidget), 101
- [<- .GLayout (glayout), 58
- [<- .GRadio (gradio), 67
- add, 6, 8
- add.GMenuBar (gmenu), 60
- add.GNotebook (gnotebook), 62
- add.GToolBar (gtoolbar), 81
- add.GWindow (gwindow), 90
- add3rdmousePopupMenu, 7
- add3rdmousePopupMenu (addHandler), 9
- addDragMotion, 7

- addDragMotion (addHandler), 9
- addDropSource, 7
- addDropSource (addHandler), 9
- addDropTarget, 7
- addDropTarget (addHandler), 9
- addHandler, 7, 9
- addHandlerBlur, 6
- addHandlerBlur (addHandler), 9
- addHandlerChanged, 6
- addHandlerChanged (addHandler), 9
- addHandlerChanged.GButton (gbutton), 27
- addHandlerChanged.GCalendar (gcalendar), 29
- addHandlerChanged.GCheckbox (gcheckbox), 30
- addHandlerChanged.GCheckboxGroup (gcheckboxgroup), 32
- addHandlerChanged.GComboBox (gcombobox), 34
- addHandlerChanged.GDf (gdf), 37
- addHandlerChanged.GEdit (gedit), 39
- addHandlerChanged.GExpandGroup (gexpandgroup), 43
- addHandlerChanged.GNotebook (gnotebook), 62
- addHandlerChanged.GTable (gtable), 75
- addHandlerClicked, 6
- addHandlerClicked (addHandler), 9
- addHandlerColumnClicked, 6
- addHandlerColumnClicked (addHandler), 9
- addHandlerColumnDoubleClicked, 6
- addHandlerColumnDoubleClicked (addHandler), 9
- addHandlerColumnRightClicked, 6
- addHandlerColumnRightClicked (addHandler), 9
- addHandlerDestroy, 6
- addHandlerDestroy (addHandler), 9
- addHandlerDoubleClick, 6
- addHandlerDoubleClick (addHandler), 9
- addHandlerDoubleClick.GTable (gtable), 75
- addHandlerExpose, 7
- addHandlerExpose (addHandler), 9
- addHandlerFocus, 6
- addHandlerFocus (addHandler), 9
- addHandlerIdle, 7
- addHandlerIdle (addHandler), 9
- addHandlerKeystroke, 7
- addHandlerKeystroke (addHandler), 9
- addHandlerMouseMotion, 7
- addHandlerMouseMotion (addHandler), 9
- addHandlerRightclick, 6
- addHandlerRightclick (addHandler), 9
- addHandlerSelect, 6
- addHandlerSelect (addHandler), 9
- addHandlerSelectionChanged (addHandler), 9
- addHandlerUnrealize, 6, 15
- addHandlerUnrealize (addHandler), 9
- addPopupMenu, 7
- addPopupMenu (addHandler), 9
- addSpace (addSpring), 15
- addSpring, 15
- addStockIcons, 16
- BasicToolkitInterface (guiWidgetsToolkit-class), 87
- BasicToolkitInterface-class (guiWidgetsToolkit-class), 87
- blockHandler, 7, 15
- blockHandler (addHandler), 9
- blockHandlers, 7, 15
- blockHandlers (addHandler), 9
- call_meth, 18
- check_deprecated, 19
- check_return_class, 19
- Command (guiWidgetsToolkit-class), 87
- Command-class (guiWidgetsToolkit-class), 87
- CommandList (guiWidgetsToolkit-class), 87
- CommandList-class (guiWidgetsToolkit-class), 87
- CommandStack (guiWidgetsToolkit-class), 87
- CommandStack-class (guiWidgetsToolkit-class), 87
- delete, 6
- delete (add), 8
- dim.GComponent ([.GDefaultWidget), 101
- dimnames.GComponent ([.GDefaultWidget), 101
- dimnames<- .GComponent ([.GDefaultWidget), 101

- dispose, [6](#), [20](#)
- dispose.GBasicDialog (gbasicdialog), [25](#)
- dispose.GNotebook (gnotebook), [62](#)
- dispose.GStackWidget (gnotebook), [62](#)
- dispose.GText (gtext), [78](#)
- dispose.GWindow (gwindow), [90](#)

- editable, [5](#), [20](#)
- editable<-, [5](#)
- editable<- (editable), [20](#)
- enabled, [5](#), [21](#)
- enabled<-, [5](#)
- enabled<- (enabled), [21](#)

- flatten, [22](#)
- focus, [5](#), [22](#)
- focus<-, [5](#)
- focus<- (focus), [22](#)
- font, [5](#), [23](#)
- font<-, [5](#)
- font<- (font), [23](#)

- gaction, [4](#), [24](#)
- galert, [5](#), [25](#)
- gbasicdialog, [5](#), [25](#)
- gbutton, [4](#), [27](#)
- gcalendar, [4](#), [29](#)
- gcheckbox, [4](#), [30](#)
- gcheckboxgroup, [4](#), [32](#)
- gcombobox, [4](#), [34](#)
- gconfirm, [5](#), [36](#)
- gcontainer, [36](#)
- gdf, [4](#), [37](#)
- gdfnotebook, [38](#)
- gdroplist (gcombobox), [34](#)
- gedit, [4](#), [30](#), [39](#)
- get_index_in_list, [42](#)
- get_object_from_string, [42](#)
- getBlock (getWidget.GDefaultWidget), [40](#)
- getStockIconByName (addStockIcons), [16](#)
- getStockIcons (addStockIcons), [16](#)
- getToolkitWidget, [6](#)
- getToolkitWidget (getWidget.GDefaultWidget), [40](#)
- getTopLevel (getWidget.GDefaultWidget), [40](#)
- getWidget (getWidget.GDefaultWidget), [40](#)
- getWidget.GDefaultWidget, [40](#)
- getWithDefault, [41](#)

- gexpandgroup, [5](#), [43](#), [50](#), [54](#)
- gfile, [5](#), [44](#)
- gfilebrowse (gfile), [44](#)
- gfilter, [46](#)
- gformlayout, [48](#), [60](#)
- gframe, [5](#), [44](#), [49](#), [54](#)
- ggraphics, [4](#), [50](#)
- ggraphicsnotebook, [52](#)
- ggroup, [5](#), [44](#), [50](#), [53](#)
- ghtml, [54](#)
- gimage, [4](#), [55](#)
- ginput, [5](#), [56](#)
- glabel, [4](#), [57](#)
- glayout, [5](#), [58](#)
- gmenu, [4](#), [60](#)
- gmessage, [5](#), [62](#)
- gnotebook, [5](#), [62](#)
- gpanedgroup, [5](#), [65](#)
- gprogressbar, [66](#)
- gradio, [4](#), [67](#)
- gseparator, [4](#), [69](#)
- gslider, [4](#), [70](#), [73](#)
- gspinbutton, [4](#), [71](#), [72](#)
- gstackwidget, [5](#), [64](#), [73](#)
- gstatusbar, [4](#), [74](#)
- gtable, [4](#), [75](#)
- gtext, [4](#), [78](#)
- gtimer, [4](#), [7](#), [10](#), [80](#)
- gtoolbar, [4](#), [81](#)
- gtoolkit, [82](#)
- gtree, [4](#), [83](#)
- guiToolkit, [24](#), [28](#), [33](#), [37](#), [45](#), [47](#), [48](#), [51](#), [52](#), [54](#), [55](#), [59](#), [61](#), [64](#), [66–69](#), [71](#), [73–75](#), [77](#), [79](#), [84](#), [86](#), [89](#), [90](#)
- guiWidgetsToolkit-class, [87](#)
- gvarbrowser, [4](#), [88](#)
- gvbox (ggroup), [53](#)
- gwidget, [89](#)
- gWidgets2-package, [3](#)
- GWidgets2Icons (guiWidgetsToolkit-class), [87](#)
- GWidgets2Icons-class (guiWidgetsToolkit-class), [87](#)
- gwindow, [5](#), [90](#)

- Handler (guiWidgetsToolkit-class), [87](#)
- Handler-class (guiWidgetsToolkit-class), [87](#)

- insert (gtext), 78
- installing_gWidgets_toolkits, 92
- is_empty, 92
- is_MacOSX, 93
- is_Windows, 93
- isExtant, 5, 92

- length.GComponent ([.GDefaultWidget), 101
- length<- .GComponent ([.GDefaultWidget), 101

- names.GComponent ([.GDefaultWidget), 101
- names.GNotebook (gnotebook), 62
- names<- .GComponent ([.GDefaultWidget), 101
- names<- .GFrame ([.GDefaultWidget), 101

- Observable (guiWidgetsToolkit-class), 87
- Observable-class (guiWidgetsToolkit-class), 87
- Observer (guiWidgetsToolkit-class), 87
- observer, 94
- Observer-class (guiWidgetsToolkit-class), 87

- redo, 5, 94
- removeHandler, 7, 15
- removeHandler (addHandler), 9

- short_summary, 95
- size, 5, 96
- size<-, 5
- size<- (size), 96
- size<- .GTable (gtable), 75
- stockIconFromClass (addStockIcons), 16
- stockIconFromObject (addStockIcons), 16
- str.GComponent ([.GDefaultWidget), 101
- svalue, 5, 96
- svalue.GButton (gbutton), 27
- svalue.GCalendar (gcalendar), 29
- svalue.GCheckboxGroup (gcheckboxgroup), 32
- svalue.GComboBox (gcombobox), 34
- svalue.GDf (gdf), 37
- svalue.GEdit (gedit), 39
- svalue.GFilter (gfilter), 46
- svalue.GFormLayout (gformlayout), 48
- svalue.GMenuBar (gmenu), 60
- svalue.GRadio (gradio), 67
- svalue.GTable (gtable), 75
- svalue.GText (gtext), 78
- svalue.GTree (gtree), 83
- svalue.GVarBrowser (gvarbrowser), 88
- svalue<-, 5
- svalue<- (svalue), 96
- svalue<- .GCheckbox (gcheckbox), 30
- svalue<- .GGroup (ggroup), 53
- svalue<- .GHtml (ghtml), 54
- svalue<- .GLabel (glabel), 57
- svalue<- .GMenu (gmenu), 60
- svalue<- .GRadio (gradio), 67
- svalue<- .GToolBar (gtoolbar), 81
- svalue<- .GTree (gtree), 83

- tag, 6, 98
- tag<-, 6
- tag<- (tag), 98
- tooltip, 5, 98
- tooltip<- (tooltip), 98

- unblockHandler, 7, 15
- unblockHandler (addHandler), 9
- unblockHandlers, 7, 15
- unblockHandlers (addHandler), 9
- undo, 5, 99
- update.GComponent ([.GDefaultWidget), 101
- update.GTree (gtree), 83

- visible, 5, 100
- visible.GBasicDialog (gbasicdialog), 25
- visible.GTable (gtable), 75
- visible<-, 5
- visible<- (visible), 100
- visible<- .GDf (gdf), 37
- visible<- .GExpandGroup (gexpandgroup), 43

- WSWatcherModel (guiWidgetsToolkit-class), 87
- WSWatcherModel-class (guiWidgetsToolkit-class), 87

- XXX, 100