

Package ‘Rmisc’

August 29, 2016

Type Package

Title Rmisc: Ryan Miscellaneous

Version 1.5

Date 2013-10-21

Author Ryan M. Hope <rmh3093@gmail.com>

Maintainer Ryan M. Hope <rmh3093@gmail.com>

Description The Rmisc library contains many functions useful for data analysis and utility operations.

License GPL-3

Suggests latticeExtra, Hmisc, stats4

Depends lattice, plyr

Collate 'CI.R' 'STDERR.R' 'group.UCL.R' 'group.CI.R' 'group.STDERR.R'
'lr.glover.R' 'multiplot.R' 'panel.circle.R' 'rounder.R'
'rsi.R' 'summarySE.R'

NeedsCompilation no

Repository CRAN

Date/Publication 2013-10-22 00:46:56

R topics documented:

CI	2
group.CI	2
group.STDERR	3
group.UCL	4
lr.glover	4
multiplot	5
normDataWithin	6
panel.circle	7
rounder	7
rsi	8
STDERR	8
summarySE	9
summarySEwithin	10

Index**11**

CI	<i>Confidence Interval</i>
----	----------------------------

Description

Calculates the confidence interval of a vector of data.

Usage

```
CI(x, ci = 0.95)
```

Arguments

x	a vector of data
ci	the confidence interval to be calculated

Value

upper	Upper bound of interval.
mean	Mean of data.
lower	Lower bound of interval.

Examples

```
CI(rnorm(100))
```

group.CI	<i>Group Confidence Interval</i>
----------	----------------------------------

Description

Calculates the confidence interval of grouped data

Usage

```
group.CI(x, data, ci = 0.95)
```

Arguments

x	an 'aggregate' compatible formula
data	a data frame (or list) from which the variables in formula should be taken
ci	the confidence interval to be calculated

Value

A data frame consisting of one column for each grouping factor plus three columns for the upper bound, mean and lower bound of the confidence interval for each level of the grouping factor

Examples

```
require(latticeExtra)
with(group.CI(weight~feed,chickwts),
  segplot(feed~weight.lower+weight.upper,center=weight.mean)
)

require(Hmisc)
with(group.CI(Temp~Month,airquality),
  xYplot(Cbind(Temp.mean,Temp.lower,Temp.upper)~numericScale(Month),type="b",ylim=c(60,90))
)
```

group.STDERR	<i>Group Standard Error Interval</i>
--------------	--------------------------------------

Description

Calculates the standard error interval of grouped data.

Usage

```
group.STDERR(x, data)
```

Arguments

x an ‘aggregate’ compatible formula
data a data frame (or list) from which the variables in formula should be taken.

Value

A data frame consisting of one column for each grouping factor plus three columns for the upper bound, mean and lower bound of the standard error interval for each level of the grouping factor.

Examples

```
require(latticeExtra)
with(group.STDERR(weight~feed,chickwts),
  segplot(feed~weight.lower+weight.upper,center=weight.mean)
)

require(Hmisc)
with(group.STDERR(Temp~Month,airquality),
  xYplot(Cbind(Temp.mean,Temp.lower,Temp.upper)~numericScale(Month),type="b",ylim=c(60,90))
)
```

group.UCL	<i>Group Upper-Center-Lower</i>
-----------	---------------------------------

Description

Applies a function which calculates a parameter with lower/uper bounds to groups of data.

Usage

```
group.UCL(x, data, FUN, ...)
```

Arguments

x	an 'aggregate' compatible formula
data	a data frame (or list) from which the variables in formula should be taken.
FUN	the function to apply to each group
...	extra params passed on to aggregate

Value

A data frame consisting of one column for each grouping factor plus three columns for the upper bound, mean and lower bound of the standard error interval for each level of the grouping factor.

Examples

```
require(latticeExtra)
with(group.UCL(weight~feed,chickwts,FUN=CI),
  segplot(feed~weight.lower+weight.upper,center=weight.mean)
)

require(Hmisc)
with(group.UCL(Temp~Month,airquality,FUN=STDERR),
  xYplot(Cbind(Temp.mean,Temp.lower,Temp.upper)~numericScale(Month),type="b",ylim=c(60,90))
)
```

lr.glover	<i>Likelihood Ratio Test</i>
-----------	------------------------------

Description

Computes a likelihood ratio statistic which reflects the relative likelihood of the data given two competing models.

Usage

```
lr.glover(object, ..., name = NULL)
```


Note

If the layout is something like `matrix(c(1,2,3,3), nrow=2, byrow=TRUE)`, then plot 1 will go in the upper left, 2 will go in the upper right, and 3 will go all the way across the bottom.

References

[http://www.cookbook-r.com/Graphs/Multiple_graphs_on_one_page_\(ggplot2\)](http://www.cookbook-r.com/Graphs/Multiple_graphs_on_one_page_(ggplot2))

normDataWithin	<i>Normalize within-group data</i>
----------------	------------------------------------

Description

Norms the data within specified groups in a data frame; it normalizes each subject (identified by `idvar`) so that they have the same mean, within each group specified by `betweenvars`.

Usage

```
normDataWithin(data = NULL, idvar, measurevar,
               betweenvars = NULL, na.rm = FALSE, .drop = TRUE)
```

Arguments

<code>data</code>	a data frame.
<code>idvar</code>	the name of a column that identifies each subject (or matched subjects)
<code>measurevar</code>	the name of a column that contains the variable to be summarized
<code>betweenvars</code>	a vector containing names of columns that are between-subjects variables
<code>na.rm</code>	a boolean that indicates whether to ignore NA's
<code>.drop</code>	should combinations of variables that do not appear in the input data be preserved (FALSE) or dropped (TRUE, default)

Value

a data frame with normalized data

References

[http://www.cookbook-r.com/Graphs/Plotting_means_and_error_bars_\(ggplot2\)](http://www.cookbook-r.com/Graphs/Plotting_means_and_error_bars_(ggplot2))

panel.circle	<i>Circle Drawing</i>
--------------	-----------------------

Description

A panel function for drawing circles.

Usage

```
panel.circle(x, y, r, segments = 50L, groups = NULL, ...)
```

Arguments

x	The x coordinate of the circle center
y	The y coordinate of the circle center
r	The radius of the circle
segments	The number of polygon segments used to create the circle
groups	A factor defining groups
...	Additional arguments passed to panel.polygon

Examples

```
panel.circle(0, 0, 10)
```

rounder	<i>Round to Increment</i>
---------	---------------------------

Description

Rounds a value to nearest increment

Usage

```
rounder(x, inc, fun = "round")
```

Arguments

x	The value to be rounded
inc	The increment to round to
fun	The rounding function. Valid options are 'floor', 'round' and 'ceiling'.

Value

an object of class numeric

Examples

```
rounder(.92, .05)
rounder(.93, .05)
rounder(.93, .05, "floor")
rounder(.93, .05, "ceiling")
```

rsi	<i>Run Start Indices</i>
-----	--------------------------

Description

Find the starting indices of runs in a vector.

Usage

```
rsi(x)
```

Arguments

x a vector of data.

Value

a vector of indices indicating starting points for runs

Examples

```
rsi(c(0,0,0,1,2,2,3,3,3,3,3,4))
```

STDERR	<i>Standard Error</i>
--------	-----------------------

Description

Calculates the standard error interval of a vector of data

Usage

```
STDERR(x)
```

Arguments

x a vector of data.

Value

upper	Upper bound of interval.
mean	Mean of data.
lower	Lower bound of interval.

Examples

```
STDERR(rnorm(100))
```

summarySE	<i>Summarizes data</i>
-----------	------------------------

Description

Gives count, mean, standard deviation, standard error of the mean, and confidence interval (default 95%).

Usage

```
summarySE(data = NULL, measurevar, groupvars = NULL,
           na.rm = FALSE, conf.interval = 0.95, .drop = TRUE)
```

Arguments

data	a data frame
measurevar	the name of a column that contains the variable to be summarized
groupvars	a vector containing names of columns that contain grouping variables
na.rm	a boolean that indicates whether to ignore NA's
conf.interval	the percent range of the confidence interval (default is 95%)
.drop	should combinations of variables that do not appear in the input data be preserved (FALSE) or dropped (TRUE, default)

Value

a data frame with count, mean, standard deviation, standard error of the mean, and confidence interval (default 95%).

References

[http://www.cookbook-r.com/Graphs/Plotting_means_and_error_bars_\(ggplot2\)](http://www.cookbook-r.com/Graphs/Plotting_means_and_error_bars_(ggplot2))

summarySEwithin	<i>Summarize within-subjects data</i>
-----------------	---------------------------------------

Description

Summarizes data, handling within-subjects variables by removing inter-subject variability. It will still work if there are no within-S variables. Gives count, mean, standard deviation, standard error of the mean, and confidence interval (default 95%). If there are within-subject variables, calculate adjusted values using method from Morey (2008).

Usage

```
summarySEwithin(data = NULL, measurevar,
  betweenvars = NULL, withinvars = NULL, idvar = NULL,
  na.rm = FALSE, conf.interval = 0.95, .drop = TRUE)
```

Arguments

data	a data frame
measurevar	the name of a column that contains the variable to be summarized
betweenvars	a vector containing names of columns that are between-subjects variables
withinvars	a vector containing names of columns that are within-subjects variables
idvar	the name of a column that identifies each subject (or matched subjects)
na.rm	a boolean that indicates whether to ignore NA's
conf.interval	the percent range of the confidence interval (default is 95%)
.drop	should combinations of variables that do not appear in the input data be preserved (FALSE) or dropped (TRUE, default)

Value

a data frame with count, mean, standard deviation, standard error of the mean, and confidence interval (default 95%).

References

[http://www.cookbook-r.com/Graphs/Plotting_means_and_error_bars_\(ggplot2\)](http://www.cookbook-r.com/Graphs/Plotting_means_and_error_bars_(ggplot2))

Index

*Topic **multivariate**

group.CI, [2](#)

group.STDERR, [3](#)

group.UCL, [4](#)

*Topic **univar**

CI, [2](#)

STDERR, [8](#)

CI, [2](#)

group.CI, [2](#)

group.STDERR, [3](#)

group.UCL, [4](#)

lr.glover, [4](#)

multiplot, [5](#)

normDataWithin, [6](#)

panel.circle, [7](#)

rounder, [7](#)

rsi, [8](#)

STDERR, [8](#)

summarySE, [9](#)

summarySEwithin, [10](#)