

Package ‘VarianceGamma’

November 26, 2018

Version 0.4-0

Date 2018-11-26

Title The Variance Gamma Distribution

Author David Scott <d.scott@auckland.ac.nz> and
Christine Yang Dong <c.dong@auckland.ac.nz>

Maintainer David Scott <d.scott@auckland.ac.nz>

Depends R (>= 3.0.1),

Imports grDevices, graphics, stats, DistributionUtils,
GeneralizedHyperbolic

Suggests RUnit

Encoding latin1

Description Provides functions for the variance gamma distribution. Density, distribution and quantile functions. Functions for random number generation and fitting of the variance gamma to data. Also, functions for computing moments of the variance gamma distribution of any order about any location. In addition, there are functions for checking the validity of parameters and to interchange different sets of parameterizations for the variance gamma distribution.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2018-11-26 11:50:04 UTC

R topics documented:

| | |
|--|----|
| summary.vgFit | 2 |
| VarianceGammaMean, Variance, Skewness, Kurtosis and Mode | 3 |
| VarianceGammaDistribution | 4 |
| VarianceGammaPlots | 9 |
| vgCalcRange | 11 |

| | |
|------------------------|----|
| vgChangePars | 13 |
| vgCheckPars | 15 |
| vgFit | 16 |
| vgFitStart | 19 |
| vgMom | 20 |
| vgParam | 22 |

| | |
|--------------|-----------|
| Index | 24 |
|--------------|-----------|

| | |
|---------------|--|
| summary.vgFit | <i>Summarizing Variance Gamma Distribution Fit</i> |
|---------------|--|

Description

summary Method for class "vgFit".

Usage

```
## S3 method for class 'vgFit'
summary(object, ...)

## S3 method for class 'summary.vgFit'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

| | |
|--------|--|
| object | An object of class "vgFit", resulting from a call to vgFit . |
| x | An object of class "summary.vgFit", resulting from a call to summary.vgFit . |
| digits | The number of significant digits to use when printing. |
| ... | Further arguments passed to or from other methods. |

Details

summary.vgFit calculates standard errors for the estimates of c , σ , θ , and ν of the variance gamma distribution parameter vector `param` if the Hessian from the call to [optim](#) or [nlm](#) is available. Because the parameters in the call to the optimiser are c , $\log(\sigma)$, θ and $\log(\nu)$, the delta method is used to obtain the standard errors for σ and ν .

Value

If the Hessian is available, `summary.vgFit` computes standard errors for the estimates of c , σ , θ , and ν , and adds them to `object` as `object$sds`. Otherwise, no calculations are performed and the composition of `object` is unaltered.

`summary.vgFit` invisibly returns `x` with class changed to `summary.vgFit`.

See [vgFit](#) for the composition of an object of class `vgFit`.

`print.summary.vgFit` prints a summary in the same format as [print.vgFit](#) when the Hessian is not available from the fit. When the Hessian is available, the standard errors for the parameter

estimates are printed in parentheses beneath the parameter estimates, in the manner of `fitdistr` in the package MASS.

See Also

[vgFit](#), [summary](#).

Examples

```
### Continuing the vgFit(.) example:
param <- c(0,0.5,0,0.5)
dataVector <- rvg(500, param = param)
fit <- vgFit(dataVector)
print(fit)
summary(fit)
```

Variance Gamma Mean, Variance, Skewness, Kurtosis and Mode

Moments and Mode of the Variance Gamma Distribution

Description

Functions to calculate the mean, variance, skewness, kurtosis and mode of a specific variance gamma distribution.

Usage

```
vgMean(vgC = 0, sigma = 1, theta = 0, nu = 1, param = c(vgC,sigma,theta,nu))
vgVar(vgC = 0, sigma = 1, theta = 0, nu = 1, param = c(vgC,sigma,theta,nu))
vgSkew(vgC = 0, sigma = 1, theta = 0, nu = 1, param = c(vgC,sigma,theta,nu))
vgKurt(vgC = 0, sigma = 1, theta = 0, nu = 1, param = c(vgC,sigma,theta,nu))
vgMode(vgC = 0, sigma = 1, theta = 0, nu = 1, param = c(vgC,sigma,theta,nu))
```

Arguments

| | |
|--------------------|--|
| <code>vgC</code> | The location parameter c , default is equal to 0. |
| <code>sigma</code> | The spread parameter σ , default is equal to 1, must be positive. |
| <code>theta</code> | The asymmetry parameter θ , default is equal to 0. |
| <code>nu</code> | The shape parameter ν , default is equal to 1, must be positive. |
| <code>param</code> | Specifying the parameters as a vector which takes the form <code>c(vgC, sigma, theta, nu)</code> . |

Value

`vgMean` gives the mean of the variance gamma distribution, `vgVar` the variance, `vgSkew` the skewness, `vgKurt` the kurtosis, and `vgMode` the mode. The formulae used for the mean and variance are as given in Seneta (2004). If ν is greater than or equal to 2, the mode is equal to the value of the parameter c . Otherwise, it is found by a numerical optimisation using [optim](#).

The parameterisation of the variance gamma distribution used for these functions is the (c, σ, θ, ν) one. See [vgChangePars](#) to transfer between parameterisations.

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Seneta, E. (2004). Fitting the variance-gamma model to financial data. *J. Appl. Prob.*, 41A:177–187. Kotz, S, Kozubowski, T. J., and Podgórski, K. (2001). The Laplace Distribution and Generalizations. *Birkhauser*, Boston, 349 p.

See Also

[dvg](#), [vgChangePars](#), [vgCalcRange](#), [besselK](#).

Examples

```
param <- c(2,2,2,0.5)
vgMean(param = param)
## Or to specify parameter values individually, use:
vgMean (2,2,2,0.5)

vgVar(param = param)
vgSkew(param = param)
vgKurt(param = param)
vgMode(param = param)
maxDens <- dvg(vgMode(param = param), param = param)
vgRange <- vgCalcRange(param = param, tol = 10^(-2)*maxDens)
curve(dvg(x, param = param), vgRange[1], vgRange[2])
abline(v = vgMode(param = param), col = "blue")
abline(v = vgMean(param = param), col = "red")
```

VarianceGammaDistribution

The Variance Gamma Distribution

Description

Density function, distribution function, quantiles and random number generation for the variance gamma distribution with parameters c (location), σ (spread), θ (asymmetry) and ν (shape). Utility routines are included for the derivative of the density function and to find suitable break points for use in determining the distribution function.

Usage

```
dvg(x, vgC = 0, sigma = 1, theta = 0, nu = 1,
    param = c(vgC,sigma,theta,nu), log = FALSE,
    tolerance = .Machine$double.eps ^ 0.5, ...)
pvg(q, vgC = 0, sigma = 1, theta = 0, nu = 1,
    param = c(vgC,sigma,theta,nu), lower.tail = TRUE, log.p = FALSE,
```

```

    small = 10^(-6), tiny = 10^(-10), deriv = 0.3, subdivisions = 100,
    accuracy = FALSE, ...)
qvg(p, vgC = 0, sigma = 1, theta = 0, nu = 1,
    param = c(vgC,sigma,theta,nu), lower.tail = TRUE, log.p = FALSE,
    small = 10^(-6), tiny = 10^(-10), deriv = 0.3, nInterpol = 100,
    subdivisions = 100, ...)
rvvg(n, vgC = 0, sigma = 1, theta = 0, nu = 1,
    param = c(vgC,sigma,theta,nu))
ddvg(x, vgC = 0, sigma = 1, theta = 0, nu = 1,
    param = c(vgC,sigma,theta,nu), log = FALSE,
    tolerance = .Machine$double.eps ^ 0.5, ...)
vgBreaks(vgC = 0, sigma = 1, theta = 0, nu = 1,
    param = c(vgC,sigma,theta,nu), small = 10^(-6), tiny = 10^(-10),
    deriv = 0.3, ...)

```

Arguments

| | |
|--------------|---|
| x, q | Vector of quantiles. |
| p | Vector of probabilities. |
| n | Number of observations to be generated. |
| vgC | The location parameter c , default is 0. |
| sigma | The spread parameter σ , default is 1, must be positive. |
| theta | The asymmetry parameter θ , default is 0. |
| nu | The shape parameter ν , default is 1, must be positive. |
| param | Specifying the parameters as a vector which takes the form $c(vgC, sigma, theta, nu)$. |
| log, log.p | Logical; if TRUE, probabilities p are given as $\log(p)$; not yet implemented. |
| lower.tail | If TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$; not yet implemented. |
| small | Size of a small difference between the distribution function and zero or one. See Details . |
| tiny | Size of a tiny difference between the distribution function and zero or one. See Details . |
| deriv | Value between 0 and 1. Determines the point where the derivative becomes substantial, compared to its maximum value. See Details . |
| accuracy | Uses accuracy calculated by <code>~integrate</code> to try and determine the accuracy of the distribution function calculation. |
| subdivisions | The maximum number of subdivisions used to integrate the density returning the distribution function. |
| nInterpol | The number of points used in qvg for cubic spline interpolation (see <code>splinefun</code>) of the distribution function. |
| tolerance | Size of a machine difference between two values. See Details . |
| ... | Passes arguments to <code>uniroot</code> . See Details . |

Details

Users may either specify the values of the parameters individually or as a vector. If both forms are specified but with different values, then the values specified by vector param will always overwrite the other ones.

The variance gamma distribution has density

$$f(x) = c(c, \sigma, \theta, \nu) \times e^{[\theta(x-c)/\sigma^2]} |x - c|^{1/\nu-1/2} K_{1/\nu-1/2} \left(\frac{|x - c| \sqrt{2\sigma^2/\nu + \theta^2}}{\sigma^2} \right)$$

where $K_\nu(\cdot)$ is the modified Bessel function of the third kind of order ν , and

$$c(c, \sigma, \theta, \nu) = \frac{2}{\sigma \sqrt{2\pi} \nu^{1/\nu} \Gamma(1/\nu)} \left(\frac{1}{\sqrt{2\sigma^2/\nu + \theta^2}} \right)^{1/\nu-1/2}$$

Special cases:

1. If $\nu < 2$ and $x = c$, then the density function is approximate to

$$f(x) = \frac{\Gamma(1/\nu - 1/2)}{\sigma \sqrt{2\pi} \nu^{1/\nu} \Gamma(1/\nu)} \left(\frac{2\sigma^2}{\sqrt{2\sigma^2/\nu + \theta^2}} \right)^{1/\nu-1/2}$$

2. If $\nu \geq 2$ and $x = c$, then the density function is taken the value Inf.

Use `vgChangePars` to convert from the $(\mu, \sigma, \theta, \tau)$, or $(\theta, \sigma, \kappa, \tau)$ parameterisations given in Kotz *et al.* (2001) to the (c, σ, θ, ν) parameterisation used above.

`pvg` breaks the real line into eight regions in order to determine the integral of `dvg`. The break points determining the regions are found by `vgBreaks`, based on the values of `small`, `tiny`, and `deriv`. In the extreme tails of the distribution where the probability is `tiny` according to `vgCalcRange`, the probability is taken to be zero. In the inner part of the distribution, the range is divided in 6 regions, 3 above the mode, and 3 below. On each side of the mode, there are two break points giving the required three regions. The outer break point is where the probability in the tail has the value given by the variable `small`. The inner break point is where the derivative of the density function is `deriv` times the maximum value of the derivative on that side of the mode. In each of the 6 inner regions the numerical integration routine `safeIntegrate` (which is a wrapper for `integrate`) is used to integrate the density `dvg`.

`qvg` uses the breakup of the real line into the same 8 regions as `pvg`. For quantiles which fall in the 2 extreme regions, the quantile is returned as `-Inf` or `Inf` as appropriate. In the 6 inner regions `splinefun` is used to fit values of the distribution function generated by `pvg`. The quantiles are then found using the `uniroot` function.

`pvg` and `qvg` may generally be expected to be accurate to 5 decimal places.

The variance gamma distribution is discussed in Kotz *et al.* (2001). It can be seen to be the weighted difference of two i.i.d. gamma variables shifted by the value of θ . `rvg` uses this representation to generate observations from the variance gamma distribution.

Value

dvg gives the density function, pvrg gives the distribution function, qvrg gives the quantile function and rvrg generates random variates. An estimate of the accuracy of the approximation to the distribution function may be found by setting `accuracy=TRUE` in the call to `pvrg` which then returns a list with components `value` and `error`.

ddvg gives the derivative of `dvg`.

`vgBreaks` returns a list with components:

| | |
|------------------------|--|
| <code>xTiny</code> | Value such that probability to the left is less than <code>tiny</code> . |
| <code>xSmall</code> | Value such that probability to the left is less than <code>small</code> . |
| <code>lowBreak</code> | Point to the left of the mode such that the derivative of the density is <code>deriv</code> times its maximum value on that side of the mode. |
| <code>highBreak</code> | Point to the right of the mode such that the derivative of the density is <code>deriv</code> times its maximum value on that side of the mode. |
| <code>xLarge</code> | Value such that probability to the right is less than <code>small</code> . |
| <code>xHuge</code> | Value such that probability to the right is less than <code>tiny</code> . |
| <code>modeDist</code> | The mode of the given variance gamma distribution. |

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Seneta, E. (2004). Fitting the variance-gamma model to financial data. *J. Appl. Prob.*, 41A:177–187. Kotz, S, Kozubowski, T. J., and Podgórski, K. (2001). The Laplace Distribution and Generalizations. *Birkhauser*, Boston, 349 p.

See Also

[vgChangePars](#), [vgCalcRange](#)

Examples

```
## Use the following rules for vgCalcRange when plotting graphs for dvg,
## ddvg and pvrg.
## if nu < 2, use:
##   maxDens <- dvg(vgMode(param = c(vgC, sigma, theta, nu)),
##   param = c(vgC, sigma, theta, nu), log = FALSE)
##   vgRange <- vgCalcRange(param = c(vgC, sigma, theta, nu),
##   tol = 10^(-2)*maxDens, density = TRUE)

## if nu >= 2 and theta < 0, use:
##   vgRange <- c(vgC-2,vgC+6)
## if nu >= 2 and theta > 0, use:
##   vgRange <- c(vgC-6,vgC+2)
## if nu >= 2 and theta = 0, use:
##   vgRange <- c(vgC-4,vgC+4)
```

```

# Example 1 (nu < 2)
## For dvg and pvg
param <- c(0,0.5,0,0.5)
maxDens <- dvg(vgMode(param = param), param = param, log = FALSE)
## Or to specify parameter values individually, use:
maxDens <- dvg(vgMode(0,0.5,0,0.5), 0,0.5,0,0.5, log = FALSE)

vgRange <- vgCalcRange(param = param, tol = 10^(-2)*maxDens, density = TRUE)
par(mfrow = c(1,2))
curve(dvg(x, param = param), from = vgRange[1], to = vgRange[2], n = 1000)
title("Density of the Variance Gamma Distribution")
curve(pvg(x, param = param), from = vgRange[1], to = vgRange[2], n = 1000)
title("Distribution Function of the Variance Gamma Distribution")

## For rvg
require(DistributionUtils)
dataVector <- rvg(500, param = param)
curve(dvg(x, param = param), range(dataVector)[1], range(dataVector)[2],
      n = 500)
hist(dataVector, freq = FALSE, add = TRUE)
title("Density and Histogram of the Variance Gamma Distribution")
logHist(dataVector, main =
         "Log-Density and Log-Histogram of the Generalized Hyperbolic Distribution")
curve(log(dvg(x, param = param)), add = TRUE,
      range(dataVector)[1], range(dataVector)[2], n = 500)

## For dvg and ddvg
par(mfrow = c(2,1))
curve(dvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
title("Density of the Variance Gamma Distribution")
curve(ddvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
title("Derivative of the Density of the Variance Gamma Distribution")

# Example 2 (nu > 2 and theta = 0)
## For dvg and pvg
param <- c(0,0.5,0,3)
vgRange <- c(0-4,0+4)
par(mfrow = c(1,2))
curve(dvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
title("Density of the Variance Gamma Distribution")
curve(pvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
title("Distribution Function of the Variance Gamma Distribution")

## For rvg
X2 <- rvg(500, param = param)
curve(dvg(x, param = param), min(X2), max(X2), n = 500)
hist(X2, freq = FALSE, add = TRUE)
title("Density and Histogram of the Variance Gamma Distribution")

```



```

DistributionUtils::logHist(X2, main =
  "Log-Density and Log-Histogram of the Generalized Hyperbolic Distribution")
curve(log(dvg(x, param = param)), add = TRUE, min(X2), max(X2), n = 500)

## For dvg and ddvg
par(mfrow = c(2,1))
curve(dvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
title("Density of the Variance Gamma Distribution")
curve(ddvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
title("Derivative of the Density of the Variance Gamma Distribution")

## Use the following rules for vgCalcRange when plotting graphs for vgBreaks.
## if (nu < 2), use:
##   maxDens <- dvg(vgMode(param = c(vgC, sigma, theta, nu))),
##   param = c(vgC, sigma, theta, nu), log = FALSE)
##   vgRange <- vgCalcRange(param = param, tol = 10^(-6)*maxDens, density = TRUE)
## if (nu >= 2) and theta < 0, use:
##   vgRange <- c(vgC-2,vgC+6)
## if (nu >= 2) and theta > 0, use:
##   vgRange <- c(vgC-6,vgC+2)
## if (nu >= 2) and theta = 0, use:
##   vgRange <- c(vgC-4,vgC+4)

## Example 3 (nu < 2)
## For vgBreaks
param <- c(0,0.5,0,0.5)
maxDens <- dvg(vgMode(param = param), param = param, log = FALSE)
vgRange <- vgCalcRange(param = param, tol = 10^(-6)*maxDens, density = TRUE)
curve(dvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
bks <- vgBreaks(param = param)
abline(v = bks)
title("Density of the Variance Gamma Distribution with breaks")

## Example 4 (nu > 2 and theta = 0)
## For vgBreaks
param <- c(0,0.5,0,3)
vgRange <- c(0-4,0+4)
curve(dvg(x, param = param), from = vgRange[1], to = vgRange[2],
      n = 1000)
bks <- vgBreaks(param = param)
abline(v = bks)
title("Density of the Variance Gamma Distribution with breaks")

```

Description

qqvg produces a variance gamma Q-Q plot of the values in y .

ppvg produces a variance gamma P-P (percent-percent) or probability plot of the values in y . Graphical parameters may be given as arguments to qqvg and ppvg.

Usage

```
qqvg(y, vgC = NULL, sigma = NULL, theta = NULL, nu = NULL,
     param = c(vgC, sigma, theta, nu), main = "Variance Gamma Q-Q Plot",
     xlab = "Theoretical Quantiles", ylab = "Sample Quantiles",
     plot.it = TRUE, line = TRUE, ...)
```

```
ppvg(y, vgC = NULL, sigma = NULL, theta = NULL, nu = NULL,
     param = c(vgC, sigma, theta, nu), main = "Variance Gamma P-P Plot",
     xlab = "Uniform Quantiles",
     ylab = "Probability-integral-transformed Data", plot.it = TRUE,
     line = TRUE, ...)
```

Arguments

| | |
|------------|---|
| y | The data sample. |
| vgC | The location parameter c , default is 0. |
| sigma | The spread parameter σ , default is 1, must be positive. |
| theta | The asymmetry parameter θ , default is 0. |
| nu | The shape parameter ν , default is 1, must be positive. |
| param | An optional option, specifying the parameters as a vector which takes the form $c(\text{vgC}, \text{sigma}, \text{theta}, \text{nu})$ if known. |
| main | Plot title. |
| xlab, ylab | Plot labels. |
| plot.it | Logical. Should the result be plotted? |
| line | Add line through origin with unit slope. |
| ... | Further graphical parameters. |

Details

Users may specify the parameter values of the data sample y using argument `param`. If `param` is not specified by users, then the values are estimated from y by `vgFit`. For more details of fitting a variance gamma distribution to data, see `vgFit`.

Value

For qqvg and ppvg, a list with components:

| | |
|-----|---|
| x | The x coordinates of the points that are to be plotted. |
| y | The y coordinates of the points that are to be plotted. |

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Wilk, M. B. and Gnanadesikan, R. (1968) Probability plotting methods for the analysis of data. *Biometrika*. **55**, 1–17.

See Also

[ppoints](#), [dvg](#).

Examples

```
## Example 1: the parameter values are known
par(mfrow = c(1,2))
y <- rvg(200, param = c(2,2,1,2))
qqvg(y, param = c(2,2,1,2), line = FALSE)
abline(0, 1, col = 2)
ppvg(y, param = c(2,2,1,2))

## Example 2: the parameter values are unknown
par(mfrow = c(1,2))
y <- rvg(200, param = c(2,2,1,2))
qqvg(y, line = FALSE)
abline(0, 1, col = 2)
ppvg(y)
```

vgCalcRange

Range of a Variance Gamma Distribution

Description

Given the parameter vector `param` or the individual parameter values (c, σ, θ, ν) of a variance gamma distribution, this function determines the range outside of which the density function is negligible, to a specified tolerance. The parameterization used is the (c, σ, θ, ν) one (see [dvg](#)). To use another parameterization, use [vgChangePars](#).

Usage

```
vgCalcRange(vgC = 0, sigma = 1, theta = 0, nu = 1,
  param = c(vgC, sigma, theta, nu), tol = 10-5, density = TRUE, ...)
```

Arguments

| | |
|---------|--|
| vgC | The location parameter c , default is 0. |
| sigma | The spread parameter σ , default is 1, must be positive. |
| theta | The asymmetry parameter θ , default is 0. |
| nu | The shape parameter ν , default is 1, must be positive. |
| param | Specifying the parameters as a vector which takes the form $c(\text{vgC}, \text{sigma}, \text{theta}, \text{nu})$. |
| tol | Tolerance. |
| density | Logical. If TRUE, the bounds are for the density function. If FALSE, they should be for the probability distribution, but this has not yet been implemented. |
| ... | Extra arguments for calls to uniroot . |

Details

Users may either specify the values of the parameters individually or as a vector. If both forms are specified but with different values, then the values specified by vector `param` will always overwrite the other ones.

The particular variance gamma distribution being considered is specified by the value of the parameter `param`.

If `density = TRUE`, the function gives a range, outside of which the density is less than the given tolerance. Useful for plotting the density. Also used in determining break points for the separate sections over which numerical integration is used to determine the distribution function. The points are found by using [uniroot](#) on the density function.

If `density = FALSE`, the function returns the message: "Distribution function bounds not yet implemented".

Value

A two-component vector giving the lower and upper ends of the range.

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Seneta, E. (2004). Fitting the variance-gamma model to financial data. *J. Appl. Prob.*, 41A:177–187. Kotz, S, Kozubowski, T. J., and Podgórski, K. (2001). The Laplace Distribution and Generalizations. *Birkhauser*, Boston, 349 p.

See Also

[dvg](#), [vgChangePars](#)

Examples

```
## Use the following rules for vgCalcRange when plotting graphs for dvg,
## ddvg and pv.
## if nu < 2, use:
##   maxDens <- dvg(vgMode(param = c(vgC, sigma, theta, nu)),
##   param = c(vgC, sigma, theta, nu), log = FALSE)
##   vgRange <- vgCalcRange(param = c(vgC, sigma, theta, nu),
##   tol = 10^(-2)*maxDens, density = TRUE)

## if nu >= 2 and theta < 0, use:
##   vgRange <- c(vgC-2,vgC+6)
## if nu >= 2 and theta > 0, use:
##   vgRange <- c(vgC-6,vgC+2)
## if nu >= 2 and theta = 0, use:
##   vgRange <- c(vgC-4,vgC+4)

param <- c(0,0.5,0,0.5)
maxDens <- dvg(vgMode(param = param), param = param)
vgRange <- vgCalcRange(param = param, tol = 10^(-2)*maxDens)
vgRange
curve(dvg(x, param = param), vgRange[1], vgRange[2])
curve(ddvg(x, param = param), vgRange[1], vgRange[2])

param <- c(2,2,0,3)
vgRange <- c(2-4,2+4)
vgRange
curve(dvg(x, param = param), vgRange[1], vgRange[2])
## Not run: vgCalcRange(param = param, tol = 10^(-3), density = FALSE)
```

Description

This function interchanges between the following 4 parameterizations of the variance gamma distribution:

1. c, σ, θ, ν
2. $\theta, \sigma, \mu, \tau$
3. $\theta, \sigma, \kappa, \tau$
4. $\lambda, \alpha, \beta, \mu$

The first set of parameterizations is given in Seneta (2004). The second and third ones are the parameterizations given in Kotz *et al.* (2001). The last set takes the form of the generalized hyperbolic distribution parameterization. δ is not included since the variance gamma distribution is a limiting case of generalized hyperbolic distribution with δ always equal to 0.

Usage

```
vgChangePars(from, to, param, noNames = FALSE)
```

Arguments

| | |
|---------|---|
| from | The set of parameters to change from. |
| to | The set of parameters to change to. |
| param | "from" parameter vector consisting of 4 numerical elements. |
| noNames | Logical. When TRUE, suppresses the parameter names in the output. |

Details

In the 3 parameterizations, the following must be positive:

1. σ, ν
2. σ, τ
3. σ, τ
4. λ, α

In addition in the 4th parameterization, the absolute value of β must be less than α .

Value

A numerical vector of length 4 representing param in the to parameterization.

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Seneta, E. (2004). Fitting the variance-gamma model to financial data. *J. Appl. Prob.*, 41A:177–187. Kotz, S, Kozubowski, T. J., and Podgórski, K. (2001). The Laplace Distribution and Generalizations. *Birkhauser*, Boston, 349 p.

See Also

[dvg](#), [vgMom](#)

Examples

```
param1 <- c(2,2,1,3) # Parameterization 1
param2 <- vgChangePars(1, 2, param1) # Convert to parameterization 2
param2 # Parameterization 2
vgChangePars(2, 1, as.numeric(param2)) # Convert back to parameterization 1

param3 <- c(1,2,0,0.5) # Parameterization 3
param1 <- vgChangePars(3, 1, param3) # Convert to parameterization 1
param1 # Parameterization 1
vgChangePars(1, 3, as.numeric(param1)) # Convert back to parameterization 3
```

`vgCheckPars`*Check Parameters of the Variance Gamma Distribution*

Description

Given a putative set of parameters for the variance gamma distribution, the functions checks if the parameters are in the correct range, and if the set has the correct length of 4.

Usage

```
vgCheckPars(param, ...)
```

Arguments

| | |
|--------------------|---|
| <code>param</code> | Numeric. Putative parameter values for a Variance Gamma distribution. |
| <code>...</code> | Further arguments for calls to <code>all.equal</code> . |

Details

The vector `param` takes the form `c(c, sigma, theta, nu)`. If either `sigma` or `nu` is negative, then an error message is returned.

If the vector `param` has a length not equal to 4, then an error message is returned.

Value

A list with components:

| | |
|-------------------------|--|
| <code>case</code> | Whichever of 'error' or 'normal' is identified by the function. |
| <code>errMessage</code> | An appropriate error message if an error was found, the empty string "" otherwise. |

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

See Also

[dvg](#), [vgMom](#)

Examples

```
vgCheckPars(c(0,1,0,1)) # normal
vgCheckPars(c(0,0,0,1)) # error
vgCheckPars(c(0,1,0,-2)) # error
vgCheckPars(c(0,1,0)) # error
```

vgFit

*Fit the Variance Gamma to Data***Description**

Fits a variance gamma distribution to data. Displays the histogram, log-histogram (both with fitted densities), Q-Q plot and P-P plot for the fit which has the maximum likelihood.

Usage

```
vgFit(x, freq = NULL, breaks = NULL, paramStart = NULL,
      startMethod = "Nelder-Mead", startValues = "SL",
      method = "Nelder-Mead", hessian = FALSE,
      plots = FALSE, printOut = FALSE,
      controlBFGS = list(maxit = 200),
      controlNM = list(maxit = 1000), maxitNLM = 1500, ...)

## S3 method for class 'vgFit'
print(x, digits = max(3, getOption("digits") - 3), ...)

## S3 method for class 'vgFit'
plot(x, which = 1:4,
      plotTitles = paste(c("Histogram of ", "Log-Histogram of ",
                          "Q-Q Plot of ", "P-P Plot of "), x$obsName,
                        sep = " "),
      ask = prod(par("mfcol")) < length(which) && dev.interactive(),
      ...)
```

Arguments

| | |
|--------------------------|--|
| <code>x</code> | Data vector for <code>vgFit</code> . Object of class "vgFit" for <code>print.vgFit</code> and <code>plot.vgFit</code> . |
| <code>freq</code> | A vector of weights with length equal to <code>length(x)</code> . |
| <code>breaks</code> | Breaks for histogram, defaults to those generated by <code>hist(x, right = FALSE, plot = FALSE)</code> . |
| <code>paramStart</code> | A user specified starting parameter vector <code>param</code> taking the form <code>c(vgC, sigma, theta, nu)</code> . |
| <code>startMethod</code> | Method used by <code>vgFitStart</code> in calls to <code>optim</code> , default is "Nelder-Mead". See Details . |
| <code>startValues</code> | Code giving the method of determining starting values for finding the maximum likelihood estimate of <code>param</code> , default method is "SL". See Details . |
| <code>method</code> | Different optimisation methods to consider, default is "Nelder-Mead". See Details . |
| <code>hessian</code> | Logical. If TRUE the value of the hessian is returned. |
| <code>plots</code> | Logical. If FALSE suppresses printing of the histogram, log-histogram, Q-Q plot and P-P plot. |

| | |
|-------------|---|
| printOut | Logical. If FALSE suppresses printing of results of fitting. |
| controlBFGS | A list of control parameters for <code>optim</code> when using the "BFGS" optimisation. |
| controlNLM | A list of control parameters for <code>optim</code> when using the "Nelder-Mead" optimisation. |
| maxitNLM | A positive integer specifying the maximum number of iterations when using the "nlm" optimisation. |
| digits | Desired number of digits when the object is printed. |
| which | If a subset of the plots is required, specify a subset of the numbers 1:4. |
| plotTitles | Titles to appear above the plots. |
| ask | Logical. If TRUE, the user is <i>asked</i> before each plot, see <code>par(ask = .)</code> . |
| ... | Passes arguments to <code>par</code> , <code>hist</code> , <code>logHist</code> , <code>qqhyperb</code> and <code>pqhyperb</code> . |

Details

`startMethod` can be either "BFGS" or "Nelder-Mead".

`startValues` can be one of the following:

- "US" User-supplied.
- "SL" Based on a fitted skew-Laplace distribution.
- "MoM" Method of moments.

For the details concerning the use of `paramStart`, `startMethod`, and `startValues`, see [vgFitStart](#).

The three optimisation methods currently available are:

- "BFGS" Uses the quasi-Newton method "BFGS" as documented in [optim](#).
- "Nelder-Mead" Uses an implementation of the Nelder and Mead method as documented in [optim](#).
- "nlm" Uses the `nlm` function in R.

For details of how to pass control information for optimisation using [optim](#) and [nlm](#), see [optim](#) and [nlm](#).

When `method = "Nelder-Mead"` is used, very rarely, it would return an error message of "error in `optim(paramStart,...)`", use `method = "BFGS"` or `method = "nlm"` instead in that case.

When `method = "nlm"` is used, warnings may be produced. These do not appear to be a problem.

Value

A list with components:

| | |
|----------------------|---|
| <code>param</code> | A vector giving the maximum likelihood estimate of <code>param</code> , as <code>(c, sigma, theta, nu)</code> . |
| <code>maxLik</code> | The value of the maximised log-likelihood. |
| <code>hessian</code> | If <code>hessian</code> was set to TRUE, the value of the hessian. Not present otherwise. |
| <code>method</code> | Optimisation method used. |
| <code>conv</code> | Convergence code. See the relevant documentation (either optim or nlm) for details on convergence. |

| | |
|-------------|--|
| iter | Number of iterations of optimisation routine. |
| obs | The data used to fit the hyperbolic distribution. |
| obsName | A character string with the actual obs argument name. |
| paramStart | Starting value of param returned by call to vgFitStart . |
| svName | Descriptive name for the method finding start values. |
| startValues | Acronym for the method of finding start values. |
| breaks | The cell boundaries found by a call to hist . |
| midpoints | The cell midpoints found by a call to hist . |
| empDens | The estimated density found by a call to hist . |

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Seneta, E. (2004). Fitting the variance-gamma model to financial data. *J. Appl. Prob.*, 41A:177–187.

See Also

[optim](#), [nlm](#), [par](#), [hist](#), [logHist](#), [qqvg](#), [ppv](#), [dskewlap](#) and [vgFitStart](#).

Examples

```
param <- c(0,0.5,0,0.5)
dataVector <- rvg(500, param = param)
## See how well vgFit works
vgFit(dataVector)
vgFit(dataVector, plots = TRUE)
fit <- vgFit(dataVector)
par(mfrow = c(1,2))
plot(fit, which = c(1,3))

## Use nlm instead of default
param <- c(0,0.5,0,0.5)
dataVector <- rvg(500, param = param)
vgFit(dataVector, method = "nlm", hessian = TRUE)

## Use BFGS instead of default
param <- c(0,0.5,0,0.5)
dataVector <- rvg(500, param = param)
vgFit(dataVector, method = "BFGS", hessian = TRUE)
```

 vgFitStart

Find Starting Values for Fitting a Variance Gamma Distribution

Description

Finds starting values for input to a maximum likelihood routine for fitting variance gamma distribution to data.

Usage

```
vgFitStart(x, breaks = NULL, startValues = "SL", paramStart = NULL,
           startMethodSL = "Nelder-Mead",
           startMethodMoM = "Nelder-Mead", ...)
vgFitStartMoM(x, startMethodMoM = "Nelder-Mead", ...)
```

Arguments

| | |
|----------------|--|
| x | Data vector. |
| breaks | Breaks for histogram. If missing, defaults to those generated by <code>hist(x, right = FALSE, plot = FALSE)</code> . |
| startValues | Vector of the different starting values to consider. See Details . |
| paramStart | Starting values for param if startValues = "US". |
| startMethodSL | Method used by call to <code>optim</code> in finding skew Laplace estimates. |
| startMethodMoM | Method used by call to <code>optim</code> in finding method of moments estimates. |
| ... | Passes arguments to <code>optim</code> . |

Details

Possible values of the argument `startValues` are the following:

- "US" User-supplied.
- "SL" Based on a fitted skew-Laplace distribution.
- "MoM" Method of moments.

If `startValues = "US"` then a value must be supplied for `paramStart`.

If `startValues = "MoM"`, `vgFitStartMoM` is called. These starting values are based on Barndorff-Nielsen *et al* (1985).

If `startValues = "SL"`, or `startValues = "MoM"` an initial optimisation is needed to find the starting values. These optimisations call `optim`.

Value

vgFitStart returns a list with components:

| | |
|-----------|--|
| vgStart | A vector with elements vgC, lSigma (log of sigma), theta and lNu (log of nu) giving the starting value of param. |
| xName | A character string with the actual x argument name. |
| breaks | The cell boundaries found by a call to hist . |
| midpoints | The cell midpoints found by a call to hist . |
| empDens | The estimated density found by a call to hist . |

vgFitStartMoM returns only the method of moments estimates as a vector with elements vgC, lSigma (log of sigma), theta and lNu (log of nu).

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Seneta, E. (2004). Fitting the variance-gamma model to financial data. *J. Appl. Prob.*, 41A:177–187.

See Also

[dvg](#), [dskewlap](#), [vgFit](#), [hist](#), and [optim](#).

Examples

```
param <- c(0,0.5,0,0.5)
dataVector <- rvg(500, param = param)
vgFitStart(dataVector, startValues="SL")
vgFitStartMoM(dataVector)
vgFitStart(dataVector, startValues="MoM")
```

 vgMom

Calculate Moments of the Variance Gamma Distribution

Description

This function can be used to calculate raw moments, mu moments, central moments and moments about any other given location for the variance gamma (VG) distribution.

Usage

```
vgMom(order, vgC = 0, sigma = 1, theta = 0, nu = 1,
       param = c(vgC,sigma,theta,nu), momType = "raw", about = 0)
```

Arguments

| | |
|---------|---|
| order | Numeric. The order of the moment to be calculated. Not permitted to be a vector. Must be a positive whole number except for moments about zero. |
| vgC | The location parameter c , default is 0. |
| sigma | The spread parameter σ , default is 1, must be positive. |
| theta | The asymmetry parameter θ , default is 0. |
| nu | The shape parameter ν , default is 1, must be positive. |
| param | Specifying the parameters as a vector which takes the form $c(\text{vgC}, \text{sigma}, \text{theta}, \text{nu})$. |
| momType | Common types of moments to be calculated, default is "raw". See Details . |
| about | Numeric. The point around which the moment is to be calculated, default is 0. See Details . |

Details

For the parameters of the variance gamma distribution, users may either specify the values individually or as a vector. If both forms are specified but with different values, then the values specified by vector `param` will always overwrite the other ones. In addition, the parameters values are examined by calling the function `vgCheckPars` to see if they are valid for the VG distribution.

`order` is also checked by calling the function `is.wholenumber` in `DistributionUtils` package to see whether a whole number is given.

`momType` can be either "raw" (moments about zero), "mu" (moments about `vgC`), or "central" (moments about mean). If one of these moment types is specified, then there is no need to specify the `about` value. For moments about any other location, the `about` value must be specified. In the case that both `momType` and `about` are specified and contradicting, the function will always calculate the moments based on `about` rather than `momType`.

To calculate moments of the VG distribution, the function first calculates mu moments by the formula defined below and then transforms mu moments to central moments or raw moments or moments about any other location as required by calling `momChangeAbout` in `DistributionUtils` package.

To calculate mu moments of the variance gamma distribution, the function first transforms the parameterization of c, σ, θ, ν to the generalized hyperbolic distribution's parameterization of $\lambda, \alpha, \beta, \mu$ (see [vgChangePars](#) for details). Then, the mu moments of the variance gamma distribution are given by

$$\sum_{\ell=\lfloor(k+1)/2\rfloor}^k a_{k,\ell} \beta^{2\ell-k} [\Gamma(\lambda + \ell)/\Gamma(\lambda) 2^\ell / (\alpha^2 - \beta^2)^\ell]$$

where $k = \text{order}$ and $k > 0$ and $a_{k,\ell}$ is the recursive coefficient (see [momRecursion](#) for details).

This formula is developed from the mu moments formula of the generalized hyperbolic distribution given in Scott, Würtz and Tran (2008). Note that the part in `[]` of this equation is actually equivalent to the formula of raw moments of the gamma distribution. So the function calls `gammaRawMom` in `GeneralizedHyperbolic` package when implementing the computations.

Value

The moment specified. In the case of raw moments, `Inf` is returned if the moment is infinite.

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

References

Paoella, Marc S. (2007) *Intermediate Probability: A Computational Approach*, Chichester: Wiley
 Scott, D. J., Würtz, D. and Tran, T. T. (2008) Moments of the Generalized Hyperbolic Distribution. Preprint.

See Also

[vgCheckPars](#), [vgChangePars](#), [vgMean](#), [vgVar](#), [vgSkew](#), [vgKurt](#), [is.wholenumber](#), [momRecursion](#), [momChangeAbout](#) and [momIntegrated](#).

Examples

```
### Raw moments of the VG distribution
vgMom(3, param=c(2,1,2,1), momType = "raw")

### Mu moments of the VG distribution
vgMom(2, param=c(2,1,2,1), momType = "mu")

### Central moments of the VG distribution
vgMom(4, param=c(2,1,2,1), momType = "central")

### Moments about any locations
vgMom(4, param=c(2,1,2,1), about = 1)
```

 vgParam

Parameter Sets for Variance Gamma Distribution

Description

These objects store different parameter sets of the Variance Gamma distribution for testing or demonstrating purpose as matrixes. Specifically, the parameter sets `vgSmallShape` and `vgLargeShape` have constant (standard) location and spread parameters of $c=0$ and $\sigma=1$; where asymmetry and shape parameters vary from $\theta=(-2, 0, 2)$ and $\nu=(0.5, 1, 2)$ for `vgSmallShape` and $\theta=(-4, -2, 0, 2, 4)$ and $\nu=(0.25, 0.5, 1, 2, 4)$ for `vgLargeShape`.

The parameter sets `vgSmallParam` and `vgLargeParam` have varied values of all 4 parameters. `vgSmallParam` contains all of the parameter combinations from $c=(-2, 0, 2)$, $\sigma=(0.5, 1, 2)$, $\theta=(-2, 0, 2)$ and $\nu=(0.5, 1, 2)$. `vgLargeParam` contains all of the parameter combinations from $c=(-4, -2, 0, 2, 4)$, $\sigma=(0.25, 0.5, 1, 2, 4)$, $\theta=(-4, -2, 0, 2, 4)$ and $\nu=(0.25, 0.5, 1, 2, 4)$.

Usage

```
vgSmallShape
vgLargeShape
vgSmallParam
vgLargeParam
```

Format

vgSmallShape: a 9 by 4 matrix; vgLargeShape: a 25 by 4 matrix; vgSmallParam: a 81 by 4 matrix; vgLargeParam: a 625 by 4 matrix.

Author(s)

David Scott <d.scott@auckland.ac.nz>, Christine Yang Dong <c.dong@auckland.ac.nz>

Examples

```
data(vgParam)
## Testing the accuracy of vgMean
for (i in 1:nrow(vgSmallParam)) {
  param <- vgSmallParam[i,]
  x <- rvg(10000,param = param)
  sampleMean <- mean(x)
  funMean <- vgMean(param = param)
  difference <- abs(sampleMean - funMean)
  print(difference)
}
```

Index

*Topic **distribution**

- vgCheckPars, 15
- vgMom, 20

- besselK, 4

- ddvg (VarianceGammaDistribution), 4
- dskewlap, 18, 20
- dvg, 4, 11, 12, 14, 15, 20
- dvg (VarianceGammaDistribution), 4

- hist, 18, 20

- integrate, 5, 6
- is.wholenumber, 22

- logHist, 18

- momChangeAbout, 22
- momIntegrated, 22
- momRecursion, 21, 22

- nlm, 2, 17, 18

- optim, 2, 3, 16–20

- par, 17, 18
- plot.vgFit (vgFit), 16
- ppoints, 11
- ppv, 18
- ppv (VarianceGammaPlots), 9
- print.summary.vgFit (summary.vgFit), 2
- print.vgFit, 2
- print.vgFit (vgFit), 16
- pvg (VarianceGammaDistribution), 4

- qqvg, 18
- qqvg (VarianceGammaPlots), 9
- qvg (VarianceGammaDistribution), 4

- rv (VarianceGammaDistribution), 4

- safeIntegrate, 6
- summary, 3
- summary.vgFit, 2, 2

- uniroot, 12

- Variance Gamma Mean, Variance, Skewness, Kurtosis and Mode, 3
- VarianceGammaDistribution, 4
- VarianceGammaPlots, 9
- vgBreaks (VarianceGammaDistribution), 4
- vgCalcRange, 4, 7, 11
- vgChangePars, 3, 4, 7, 11, 12, 13, 21, 22
- vgCheckPars, 15, 22
- vgFit, 2, 3, 10, 16, 20
- vgFitStart, 17, 18, 19
- vgFitStartMoM (vgFitStart), 19
- vgKurt, 22
- vgKurt (Variance Gamma Mean, Variance, Skewness, Kurtosis and Mode), 3
- vgLargeParam (vgParam), 22
- vgLargeShape (vgParam), 22
- vgMean, 22
- vgMean (Variance Gamma Mean, Variance, Skewness, Kurtosis and Mode), 3
- vgMode (Variance Gamma Mean, Variance, Skewness, Kurtosis and Mode), 3
- vgMom, 14, 15, 20
- vgParam, 22
- vgSkew, 22
- vgSkew (Variance Gamma Mean, Variance, Skewness, Kurtosis and Mode), 3
- vgSmallParam (vgParam), 22
- vgSmallShape (vgParam), 22
- vgVar, 22
- vgVar (Variance Gamma Mean, Variance, Skewness, Kurtosis and Mode), 3