

Package ‘neatStats’

October 8, 2020

Title Neat and Painless Statistical Reporting

Version 1.5.1

Date 2020-09-27

Description User-friendly, clear and simple statistics, primarily for publication in psychological science. The main functions are wrappers for other packages, but there are various additions as well. Every relevant step from data aggregation to reportable printed statistics is covered for basic experimental designs.

URL <https://github.com/gaspar1/neatstats>

Depends R (>= 3.6.0)

Imports PowerR, plyr, bayestestR, pROC, MBESS, car, ez, BayesFactor, Exact, ggplot2, ggpubr, logspline, grDevices, stats, graphics

Suggests rstudioapi

License BSD_2_clause + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

NeedsCompilation no

Author Gáspár Lukács [aut, cre] (<<https://orcid.org/0000-0001-9401-4830>>),
Bennett Kleinberg [ctb] (<<https://orcid.org/0000-0003-1658-9086>>),
Johnny van Doorn [ctb] (<<https://orcid.org/0000-0003-0270-096X>>)

Maintainer Gáspár Lukács <lkcs gaspar@gmail.com>

Repository CRAN

Date/Publication 2020-10-08 08:30:02 UTC

R topics documented:

aggr_neat	2
anova_neat	5
ci_from_p	13

corr_neat	14
dems_neat	16
enum	19
excl_neat	20
mean_ci	21
mon_conv	22
mon_neat	23
norm_tests	24
path_neat	25
peek_neat	26
plot_neat	28
props_neat	36
rbind_loop	38
read_dir	40
ro	42
roc_neat	43
se	44
table_neat	45
t_neat	47
var_tests	51

Index	54
--------------	-----------

aggr_neat	<i>Aggregation, descriptives</i>
-----------	----------------------------------

Description

Returns aggregated values per group for given variable. Serves as argument in the [table_neat](#) function.

Usage

```
aggr_neat(
  dat,
  values,
  method = mean,
  group_by = NULL,
  filt = NULL,
  sep = "_",
  prefix = NULL,
  new_name = NULL,
  round_to = 2
)
```

Arguments

<code>dat</code>	Data frame (or name of data frame as string).
<code>values</code>	The vector of numbers from which the statistics are to be calculated, or the name of the column in the <code>dat</code> data frame, that contains the vector.
<code>method</code>	Function of string. If function, uses the values to calculate the returned value for the given function (e.g. means, as per default, using the mean function). Such a function may return a vector of results as well; see Examples. If string, one of two internal functions will be used. If the string end with "+sd", e.g., "mean+sd", the function preceding the "+" sign will be calculated along with the standard deviation, displayed in a single column, rounded as set in the <code>round_to</code> argument. (This is primarily for use in the <code>table_neat</code> function for summary tables.) If the string does not end with "+sd", a ratio for the occurrences of given elements will be calculated. Multiple elements can be given as a vector of strings. The number of occurrences of these elements will be the numerator (dividend), while the entire column length (i.e., number of all elements) will be the denominator (divisor). For example, if a column contains elements "correct", "incorrent", "tooslow", the ratio of "correct" to all other elements (i.e., including elements "correct", "incorrent", and "tooslow") can be written simply as <code>method = "correct"</code> . The complementary ratio, of "incorrent" and "tooslow", can be written as <code>method = "incorrent, tooslow"</code> . (Hint: filter to get ratios of subgroups, e.g. to include only "correct" and "incorrent" elements, and calculate their ratio; see below.)
<code>group_by</code>	String, or vector of strings: the name(s) of the column(s) in the <code>dat</code> data frame, containing the vector(s) of factors by which the statistics are grouped.
<code>filt</code>	An expression to filter, by column values, the entire <code>dat</code> data frame before performing the aggregation. The expression should use column names alone; see Examples.
<code>sep</code>	String (underscore "_" by default) for separating group names (and prefix, if given).
<code>prefix</code>	NULL (default) or string. String specifies a prefix for each group type under the group column.
<code>new_name</code>	NULL (default) or string. String specifies new name for the variable to be used as column title. If NULL, the name will be "aggr_value" (or, if used with <code>table_neat</code> , the input variable name is used).
<code>round_to</code>	Number of digits after the decimal point to round to, when using "+sd" in method.

Value

A data frame with the statistics per group, with a single column ("aggr_group") indicating the grouping.

See Also

`table_neat` to create full tables using multiple variables

Examples

```
data("mtcars") # load base R example dataset

# overall means and SDs for wt (Weight)
aggr_neat(mtcars, wt)

# rename column
aggr_neat(mtcars, wt, new_name = 'weight')

# grouped by cyl (Number of cylinders)
aggr_neat(mtcars, wt, group_by = 'cyl')

# grouped by cyl and gear
aggr_neat(mtcars, wt, group_by = c('cyl', 'gear'))

# prefix for group names
aggr_neat(mtcars, wt, group_by = 'cyl', prefix = 'cyl')

# filter to only have cyl larger than 4
aggr_neat(mtcars, wt, group_by = 'cyl', filt = cyl > 4)

# filter to only have hp (Gross horsepower) smaller than 200
aggr_neat(mtcars, wt, group_by = 'cyl', filt = hp < 200)

# combine two filters above, and add prefix
aggr_neat(
  mtcars,
  wt,
  group_by = 'cyl',
  filt = (hp < 200 & cyl > 4),
  prefix = 'filtered'
)

# add SD (and round output numbers to 2)
aggr_neat(mtcars,
  wt,
  group_by = 'cyl',
  method = 'mean+sd',
  round_to = 2)

# now medians instead of means
aggr_neat(mtcars, wt, group_by = 'cyl', method = median)

# with SD
aggr_neat(mtcars,
  wt,
  group_by = 'cyl',
  method = 'median+sd',
  round_to = 1)

# overall ratio of gear 4 (Number of gears)
aggr_neat(mtcars, gear, method = '4')
```

```
# overall ratio of gear 4 and 5
aggr_neat(mtcars, gear, method = '4, 5')

# same ratio calculated per each cyl
aggr_neat(mtcars, gear, group_by = 'cyl', method = '4, 5')

# per each cyl and per vs (engine type)
aggr_neat(mtcars,
          gear,
          group_by = c('cyl', 'vs'),
          method = '4, 5')

# ratio of gear 3 per gear 3 and 5
aggr_neat(
  mtcars,
  gear,
  group_by = 'cyl',
  method = '3',
  filt = gear %in% c(3, 5)
)

# both mean and median
aggr_neat(
  mtcars,
  gear,
  group_by = 'cyl',
  method = function(v) {
    c(my_mean = mean(v), my_median = median(v))
  }
)

# mean, median, and count
aggr_neat(
  mtcars,
  gear,
  group_by = 'cyl',
  method = function(v) {
    c(mean = mean(v),
      median = median(v),
      count = length(v))
  }
)
```

anova_neat

Comparison of Multiple Means: ANOVA

Description

[Analysis of variance](#) (ANOVA) F-test results with appropriate [Welch's](#) and epsilon corrections where applicable (unless specified otherwise), including partial eta squared effect sizes with con-

fidence intervals (CIs), generalized eta squared, and [inclusion Bayes factor based on matched models](#) (BFs).

Usage

```
anova_neat(
  data_per_subject,
  values,
  within_ids = NULL,
  between_vars = NULL,
  ci = 0.9,
  norm_tests = "none",
  norm_plots = FALSE,
  var_tests = FALSE,
  bf_added = FALSE,
  bf_sample = 10000,
  test_title = "--- neat ANOVA ---",
  welch = TRUE,
  e_correction = NULL,
  type = 2,
  white.adjust = FALSE,
  hush = FALSE,
  plot_means = FALSE,
  ...
)
```

Arguments

<code>data_per_subject</code>	Data frame. Should contain all values (measurements/observations) in a single row per each subject.
<code>values</code>	Vector of strings; column name(s) in the <code>data_per_subject</code> data frame. Each column should contain a single dependent variable: thus, to test repeated (within-subject) measurements, each specified column should contain one measurement.
<code>within_ids</code>	NULL (default), string, or named list. In case of no within-subject factors, leave as NULL. In case of a single within subject factor, a single string may be given to optionally provide custom name for the within-subject factor (note: this is a programming variable name, so it should not contain spaces, etc.); otherwise (if left NULL) this one within-subject factor will always just be named "within_factor". In case of multiple within-subject factors, each factor must be specified as a named list element, each with a vector of strings that distinguish the levels within that factors. The column names given as values should always contain one (and only one) of these strings within each within-subject factor, and thus they will be assigned the appropriate level. For example, <code>values = 'rt_s1_neg,rt_s1_pos,rt_s2_neg,rt_s2_pos'</code> could have <code>within_ids = list(session = c('s1', 's2'), valence = c('pos', 'neg'))</code> . (Note: the strings for distinguishing must be unambiguous. E.g., for values <code>apple_a</code> and <code>apple_b</code> , do not set levels <code>c('a', 'b')</code> , because 'a' is also found in <code>apple_b</code> . In this

	case, you could choose levels <code>c('_a', '_b')</code> to make sure the values are correctly distinguished.) See also Examples.
<code>between_vars</code>	NULL (default; in case of no between-subject factors) or vector of strings; column name(s) in the <code>data_per_subject</code> data frame. Each column should contain a single between-subject independent variable (representing between-subject factors).
<code>ci</code>	Numeric; confidence level for returned CIs. (Default: <code>.9</code> ; Lakens, 2014; Steiger, 2004.)
<code>norm_tests</code>	Normality tests for the pooled ANOVA residuals ("none" by default, giving no tests). Any or all of the following character input is accepted (as a single string or a character vector; case-insensitive): "W" (Shapiro-Wilk), "K2" (D'Agostino-Pearson), "A2" (Anderson-Darling), "JB" (Jarque-Bera); see norm_tests . The option "all" selects all four previous tests at the same time.
<code>norm_plots</code>	If TRUE and <code>norm_tests</code> is not "none", displays density, histogram, and Q-Q plots (and scatter plots for paired tests) for the pooled residuals.#'
<code>var_tests</code>	Logical, FALSE by default. If TRUE (and there are any between-subject factors), runs variance equality tests via var_tests for all combinations of the between-subject factors within each level of within-subject factor combinations; see Details.
<code>bf_added</code>	Logical. If TRUE (default), inclusion Bayes factor is calculated and displayed. (Note: with multiple factors and/or larger dataset, the calculation can take considerable time.)
<code>bf_sample</code>	Number of samples used to estimate Bayes factor (10000 by default).
<code>test_title</code>	String, "---neat ANOVA ---" by default. Simply displayed in printing preceding the statistics.
<code>welch</code>	If TRUE (default), calculates Welch's ANOVA via stats::oneway.test in case of a single factor (one-way) between-subject design. If FALSE, calculates via ez::ezANOVA in such cases too (i.e., same as in case of every other design).
<code>e_correction</code>	NULL (default) or one of the following strings: 'gg', 'hf', or 'none'. If set to 'gg', Greenhouse-Geisser correction is applied in case of repeated measures (regardless of violation of sphericity). If set to 'hf', Huynh-Feldt correction is applied. If set to 'none', no correction is applied. If NULL, Greenhouse-Geisser correction is applied when Mauchly's sphericity test is significant and the Greenhouse-Geisser epsilon is not larger than <code>.75</code> , while Huynh-Feldt correction is applied when Mauchly's sphericity test is significant and the Greenhouse-Geisser epsilon is larger than <code>.75</code> (see Girden, 1992).
<code>type</code>	Sum of squares type specified as a number: 1, 2, or 3. Set to 2 by default (which is generally recommended, see e.g. Navarro, 2019, Chapter 16).
<code>white.adjust</code>	If not FALSE (default) uses a heteroscedasticity-corrected coefficient covariance matrix; the various values of the argument specify different corrections ("hc0", "hc1", "hc2", "hc3", or "hc4"). See the documentation for car::hccm for details. If set to TRUE then the "hc3" correction is selected.
<code>hush</code>	Logical. If TRUE, prevents printing any details to console.
<code>plot_means</code>	Logical (FALSE by default). If TRUE, creates plots of means by factor, by passing data and factor information to plot_neat .
<code>...</code>	Any additional arguments will be passed on to plot_neat .

Details

The Bayes factor (BF) is always calculated with the default `rscaleFixed` of 0.5 ("medium") and `rscaleRandom` of 1 ("nuisance"). BF supporting null hypothesis is denoted as BF01, while that supporting alternative hypothesis is denoted as BF10. When the BF is smaller than 1 (i.e., supports null hypothesis), the reciprocal is calculated (hence, BF10 = BF, but BF01 = 1/BF). When the BF is greater than or equal to 10000, scientific (exponential) form is reported for readability. (The original full BF number is available in the returned named vector as `bf`.)

Mauchly's sphericity test is returned for repeated measures with more than two levels. If Mauchly's test is significant, epsilon correction may be applied (see the `e_correction` parameter).

Variance equality tests (if `var_tests` is TRUE): Brown-Forsythe and Fligner-Killeen tests are performed for each within-subject factor level (or, in case of several factors, each combination) via `var_tests`. Note that variance testing is generally not recommended (see e.g., Zimmerman, 2004). In case of a one-way between-subject ANOVA, Welch-corrected results are reported by default, which corrects for unequal variances. In case of multiple between-subject factors, the `white.adjust` parameter can be set to TRUE (or "hc3") to apply "hc3" correction for unequal variances. In case of a mixed ANOVA (both between-subject and within-subject factors), if the tests are significant and the data is unbalanced (unequal group sample sizes), you should either consider the results respectively or choose a different test.

In case of multiple values (column names) that match identical levels for all factors, the given columns will be merged into a single column taking the mean value of all these columns. (This is to simplify "dropping" a within-subject factor and retesting the remaining factors.) Explicit warning messages are shown in each such case.

Value

Prints ANOVA statistics (including, for each model, F-test with partial eta squared and its CI, generalized eta squared, and BF, as specified via the corresponding parameters) in APA style. Furthermore, when assigned, returns a list with up to four elements. First, `'stat_list'`, a list of named vectors per each effect (main or interaction). Each vector contains the following elements: F (F value), p (p value), `petas` (partial eta squared), `getas` (generalized eta squared), `epsilon` (epsilon used for correction), and `bf` (inclusion BF; when `bf_added` is not FALSE). Second, a dataframe with mean and SD per each condition (i.e., per each level per each factor). Third, the `ezANOVA` object, named `ez_anova` (calculated even when `oneway.test` is printed). Fourth, when `bf_added` is not FALSE, the `anovaBF` object, named `bf_models`; including all models on which the inclusion BFs are based.

Note

The F-tests are calculated via `ez::ezANOVA`, including Mauchly's sphericity test. (But Welch's ANOVA is calculated in case of one-way between-subject designs via `stats::oneway.test`, unless the `welch` parameter is set to FALSE.)

Confidence intervals are calculated, using the F value, via `MBESS::conf.limits.ncf`, converting noncentrality parameters to partial eta squared as $ncp / (ncp + df_{nom} + df_{denom} + 1)$ (Smithson, 2003).

Generalized eta squared is to facilitate potential subsequent meta-analytical comparisons (see Lakens, 2013).

The inclusion Bayes factor based on matched models is calculated via `bayestestR::bayesfactor_inclusion`, (with `match_models = TRUE`, and using an `BayesFactor::anovaBF` object for `models` input).

References

- Girden, E. (1992). ANOVA: Repeated measures. Newbury Park, CA: Sage.
- Kelley, K. (2007). Methods for the behavioral, educational, and social sciences: An R package. *Behavior Research Methods*, 39(4), 979-984. doi: [10.3758/BF03192993](https://doi.org/10.3758/BF03192993)
- Lakens, D. (2013). Calculating and reporting effect sizes to facilitate cumulative science: A practical primer for t-tests and ANOVAs. *Frontiers in Psychology*, 4. <https://doi.org/10.3389/fpsyg.2013.00863>
- Lakens, D. (2014). Calculating confidence intervals for Cohen's d and eta-squared using SPSS, R, and Stata [Blog post]. Retrieved from <http://daniellakens.blogspot.com/2014/06/calculating-confidence-intervals.html>
- Mathot, S. (2017). Bayes like a Baws: Interpreting Bayesian Repeated Measures in JASP [Blog post]. Retrieved from <https://www.cogsci.nl/blog/interpreting-bayesian-repeated-measures-in-jasp>
- McDonald, J. H. 2015. Handbook of Biological Statistics (3rd ed.). Sparky House Publishing, Baltimore, Maryland. Retrieved from <http://www.biostathandbook.com>
- Moder, K. (2010). Alternatives to F-test in one way ANOVA in case of heterogeneity of variances (a simulation study). *Psychological Test and Assessment Modeling*, 52(4), 343-353.
- Navarro, D. (2019). Learning Statistics with R: A Tutorial for Psychology Students and Other Beginners (Version 0.6.1). Retrieved from <https://learningstatisticswithr.com/>
- Smithson, M. (2003). Confidence intervals. Thousand Oaks, Calif: Sage Publications.
- Steiger, J. H. (2004). Beyond the F test: effect size confidence intervals and tests of close fit in the analysis of variance and contrast analysis. *Psychological Methods*, 9(2), 164-182. doi: [10.1037/1082989X.9.2.164](https://doi.org/10.1037/1082989X.9.2.164)
- Zimmerman, D. W. (2004). A note on preliminary tests of equality of variances. *British Journal of Mathematical and Statistical Psychology*, 57(1), 173–181. <https://doi.org/10.1348/000711004849222>

See Also

[plot_neat](#), [t_neat](#)

Examples

```
# assign random data in a data frame for illustration
# (note that the 'subject' is only for illustration; since each row contains the
# data of a single subject, no additional subject id is needed)
dat_1 = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  grouping1 = c(1, 1, 1, 1, 2, 2, 2, 2, 2, 2),
  grouping2 = c(1, 2, 1, 2, 2, 1, 1, 1, 2, 1),
  value_1_a = c(36.2, 45.2, 41, 24.6, 30.5, 28.2, 40.9, 45.1, 31, 16.9),
  value_2_a = c(-14.1, 58.5, -25.5, 42.2, -13, 4.4, 55.5, -28.5, 25.6, -37.1),
  value_1_b = c(83, 71, 111, 70, 92, 75, 110, 111, 110, 85),
  value_2_b = c(8.024, -14.162, 3.1, -2.1, -1.5, 0.91, 11.53, 18.37, 0.3, -0.59),
  value_1_c = c(27.4, -17.6, -32.7, 0.4, 37.2, 1.7, 18.2, 8.9, 1.9, 0.4),
  value_2_c = c(7.7, -0.8, 2.2, 14.1, 22.1, -47.7, -4.8, 8.6, 6.2, 18.2)
```

```

)
head(dat_1) # see what we have

# For example, numbers '1' and '2' in the variable names of the values can
# denote sessions in an experiment, such as '_1' for first session, and '_2' for
# second session'. The letters '_a', '_b', '_c' could denote three different
# types of techniques used within each session, to be compared to each other.
# See further below for a more verbose but more meaningful example data.

# get the between-subject effect of 'grouping1'
anova_neat(dat_1, values = 'value_1_a', between_vars = 'grouping1')

# main effects of 'grouping1', 'grouping2', and their interactions
anova_neat(dat_1,
            values = 'value_1_a',
            between_vars = c('grouping1', 'grouping2'))

# repeated measures:
# get the within-subject effect for 'value_1_a' vs. 'value_1_b'
anova_neat(dat_1, values = c('value_1_a', 'value_1_b'))

# same, but give the factor a custom variable name, and omit BF for speed
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b'),
  within_ids = 'a_vs_b',
  bf_added = FALSE
)
# or
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b'),
  within_ids = 'letters',
  bf_added = FALSE
)

# within-subject effect for 'value_1_a' vs. 'value_1_b' vs. 'value_1_c'
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b', 'value_1_c'),
  bf_added = FALSE
)

# within-subject main effect for 'value_1_a' vs. 'value_1_b' vs. 'value_1_c',
# between-subject main effect 'grouping1', and the interaction of these two main
# effects
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b', 'value_1_c'),
  between_vars = 'grouping1',
  bf_added = FALSE
)

```

```

# within-subject 'number' main effect for variables with number '1' vs. number
# '2' ('value_1_a' and 'value_1_b' vs. 'value_2_a' and 'value_2_b'), 'letter'
# main effect for variables with final letter 'a' vs. final letter 'b'
# ('value_1_a' and 'value_2_a' vs. 'value_1_b' and 'value_2_b'), and the
# 'letter' x 'number' interaction
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_2_a', 'value_1_b', 'value_2_b'),
  within_ids = list(
    letters = c('_a', '_b'),
    numbers = c('_1', '_2')
  ),
  bf_added = FALSE
)

# same as above, but now including between-subject main effect 'grouping2' and
# its interactions
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_2_a', 'value_1_b', 'value_2_b'),
  within_ids = list(
    letters = c('_a', '_b'),
    numbers = c('_1', '_2')
  ),
  between_vars = 'grouping2',
  bf_added = FALSE
)

# same as above, but now creating a plot of means
# y_title passed add an example title (label) for the Y axis
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_2_a', 'value_1_b', 'value_2_b'),
  within_ids = list(
    letters = c('_a', '_b'),
    numbers = c('_1', '_2')
  ),
  between_vars = 'grouping2',
  bf_added = FALSE,
  plot_means = TRUE,
  y_title = 'Example Y Title'
)

# same as above, but collapsing means over the removed "numbers" factor
anova_neat(
  dat_1,
  values = c('value_1_a', 'value_2_a', 'value_1_b', 'value_2_b'),
  within_ids = list(
    letters = c('_a', '_b')
  ),
  between_vars = 'grouping2',
  bf_added = FALSE,
  plot_means = TRUE,

```

```

    y_title = 'Example Y Title'
  )

# In real datasets, these could of course be more meaningful. For example, let's
# say participants rated the attractiveness of pictures with low or high levels
# of frightening and low or high levels of disgusting qualities. So there are
# four types of ratings:
# 'low disgusting, low frightening' pictures
# 'low disgusting, high frightening' pictures
# 'high disgusting, low frightening' pictures
# 'high disgusting, high frightening' pictures

# this could be meaningfully assigned e.g. as below
pic_ratings = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  rating_fright_low_disgust_low = c(36.2,45.2,41,24.6,30.5,28.2,40.9,45.1,31,16.9),
  rating_fright_high_disgust_low = c(-14.1,58.5,-25.5,42.2,-13,4.4,55.5,-28.5,25.6,-37.1),
  rating_fright_low_disgust_high = c(83,71,111,70,92,75,110,111,110,85),
  rating_fright_high_disgust_high = c(8.024,-14.162,3.1,-2.1,-1.5,0.91,11.53,18.37,0.3,-0.59)
)
head(pic_ratings) # see what we have

# the same logic applies as for the examples above, but now the
# within-subject differences can be more meaningfully specified, e.g.
# 'disgust_low' vs. 'disgust_high' for levels of disgustingness, while
# 'fright_low' vs. 'fright_high' for levels of frighteningness
anova_neat(
  pic_ratings,
  values = c(
    'rating_fright_low_disgust_low',
    'rating_fright_high_disgust_low',
    'rating_fright_low_disgust_high',
    'rating_fright_high_disgust_high'
  ),
  within_ids = list(
    disgustingness = c('disgust_low', 'disgust_high'),
    frighteningness = c('fright_low', 'fright_high')
  ),
  bf_added = FALSE
)

# the results are the same as for the analogous test for the 'dat_1' data, only
# with different names

# now let's say the ratings were done in two separate groups
pic_ratings = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  group_id = c(1, 2, 1, 2, 2, 1, 1, 1, 2, 1),
  rating_fright_low_disgust_low = c(36.2,45.2,41,24.6,30.5,28.2,40.9,45.1,31,16.9),
  rating_fright_high_disgust_low = c(-14.1,58.5,-25.5,42.2,-13,4.4,55.5,-28.5,25.6,-37.1),
  rating_fright_low_disgust_high = c(83,71,111,70,92,75,110,111,110,85),
  rating_fright_high_disgust_high = c(8.024,-14.162,3.1,-2.1,-1.5,0.91,11.53,18.37,0.3,-0.59)
)

```

```

# now test the effect and interactions of 'group_id'
anova_neat(
  pic_ratings,
  values = c(
    'rating_fright_low_disgust_low',
    'rating_fright_high_disgust_low',
    'rating_fright_low_disgust_high',
    'rating_fright_high_disgust_high'
  ),
  within_ids = list(
    disgustingness = c('disgust_low', 'disgust_high'),
    frighteningness = c('fright_low', 'fright_high')
  ),
  between_vars = 'group_id',
  bf_added = FALSE
)

# again, same results as with 'dat_1' (using 'grouping2' as group_id)

```

ci_from_p

CI from p value

Description

Calculates approximate confidence interval (CI) for any given difference, based on the difference value and p value, according to Altman & Bland (2011).

Usage

```
ci_from_p(diff, p_value, ci = 0.95)
```

Arguments

diff	Difference (number) around which the CI is to be calculated.
p_value	The p value for CI calculation.
ci	Numeric; confidence level for the returned CIs (.95 per default).

Value

CI limits as named numeric vector with two elements.

Note

Check the Altman & Bland (2011) paper for details! (The calculation for proportions is not implemented here.)

References

Altman, D. G., & Bland, J. M. (2011). How to obtain the confidence interval from a P value. *Bmj*, 343(d2090). doi: [10.1136/bmj.d2090](https://doi.org/10.1136/bmj.d2090)

Examples

```
# Example 1
# calculate proportion difference test
proptest_stat = prop.test(x = c(49, 40), n = c(50, 50))

# calculate proportion difference
my_diff = 49/50-40/50

# calculate approximate CI
ci_from_p(my_diff, proptest_stat$p.value)

# returned CI should be very similar to the actual CI
proptest_stat$conf.int

# Example 2
# generate random data
v1 = stats::rnorm(190, 40, 60)
v2 = stats::rnorm(170, 50, 45)

# calculate t-test
ttest_stat = stats::t.test(v1, v2)

# calculate mean difference
my_diff = mean(v1) - mean(v2)

# calculate approximate CI
ci_from_p(my_diff, ttest_stat$p.value)

# returned CI should be similar to the actual CI
ttest_stat$conf.int
```

corr_neat

Correlation Statistics

Description

[Pearson correlation](#) results including confidence interval (CI) and correlation [Bayes factor](#) (BF). For non-parametric version, Spearman's [rank correlation](#) results along with corresponding rank-based BFs (as per van Doorn et al., 2020).

Usage

```
corr_neat(
  var1,
  var2,
  nonparametric = FALSE,
  ci = 0.95,
  bf_added = FALSE,
  direction = NULL,
  round_r = 3,
  for_table = FALSE,
  sb_correction = FALSE,
  hush = FALSE
)
```

Arguments

var1	Numeric vector; numbers of the first variable.
var2	Numeric vector; numbers of the second variable.
nonparametric	Logical (FALSE by default). If TRUE, uses nonparametric tests (Spearman's rank correlation, including BFs; see Details).
ci	Numeric; confidence level for the returned CI, as implemented in cor.test .
bf_added	Logical. If TRUE (default), Bayes factor is calculated and displayed.
direction	NULL or string; optionally specifies one-sided test: either "negative" (negative correlation expected) or "positive" (positive correlation expected). (Short forms also work, e.g. "p", "pos", "neg", etc.) If NULL (default), the test is two-sided.
round_r	Number to round to the correlation and its CI.
for_table	Logical. If TRUE, omits the confidence level display from the printed text.
sb_correction	Logical. If TRUE, applies Spearman-Brown correction ($2 * r / (1+r)$) to the correlation (including CI).
hush	Logical. If TRUE, prevents printing any details to console.

Details

The Bayes factor (BF) is calculated with the default r-scale of 1/3 for parametric test, and with the default r-scale of 1 for nonparametric test. BF supporting null hypothesis is denoted as BF01, while that supporting alternative hypothesis is denoted as BF10. When the BF is smaller than 1 (i.e., supports null hypothesis), the reciprocal is calculated (hence, BF10 = BF, but BF01 = 1/BF). When the BF is greater than or equal to 10000, scientific (exponential) form is reported for readability. (The original full BF number is available in the returned named vector as bf.)#'

Value

Prints correlation statistics (including CI and BF) in APA style. Furthermore, when assigned, returns a named vector with the following elements: r (Pearson correlation), p (p value), bf (Bayes factor).

Note

The correlation and CI is calculated via `stats::cor.test`.

The parametric Bayes factor is calculated via `BayesFactor::correlationBF`. The nonparametric (rank-based) Bayes factor is a contribution by Johnny van Doorn; the original source code is available via <https://osf.io/gny35/>.

References

- Brown, W. (1910). Some experimental results in the correlation of mental abilities. *British Journal of Psychology*, 1904-1920, 3(3), 296-322. doi: [10.1111/j.20448295.1910.tb00207.x](https://doi.org/10.1111/j.20448295.1910.tb00207.x)
- Eisinga, R., Grotenhuis, M. te, & Pelzer, B. (2013). The reliability of a two-item scale: Pearson, Cronbach, or Spearman-Brown? *International Journal of Public Health*, 58(4), 637-642. doi: [10.1007/s0003801204163](https://doi.org/10.1007/s0003801204163)
- Spearman, C. (1910). Correlation calculated from faulty data. *British Journal of Psychology*, 1904-1920, 3(3), 271-295. doi: [10.1111/j.20448295.1910.tb00206.x](https://doi.org/10.1111/j.20448295.1910.tb00206.x)
- van Doorn, J., Ly, A., Marsman, M., & Wagenmakers, E.-J. (2020). Bayesian rank-based hypothesis testing for the rank sum test, the signed rank test, and Spearman's rho. *Journal of Applied Statistics*, 1–23. doi: [10.1080/02664763.2019.1709053](https://doi.org/10.1080/02664763.2019.1709053)

See Also

[t_neat](#)

Examples

```
# assign two variables
v1 = c(11, 15, 19, 43, 53, -4, 34, 8, 33, -1, 54 )
v2 = c(4, -2, 23, 13, 32, 16, 3, 29, 37, -4, 65 )

corr_neat(v1, v2) # prints statistics

# one-sided, and omitting the "95% CI" part
corr_neat(v1, v2, direction = 'pos', for_table = TRUE)

# print statistics and assign main results
results = corr_neat(v1, v2, direction = 'pos')

results['p'] # get precise p value
```

dems_neat

Demographics

Description

Prints participant count, age mean and SD, and gender ratio, from given dataset.

Usage

```
dems_neat(
  data_per_subject,
  group_by = NULL,
  gender_col = NULL,
  age_col = NULL,
  percent = FALSE,
  round_perc = 0,
  show_fem = NULL
)
```

Arguments

data_per_subject	Data frame from which demographics are to be calculated. Should contain columns named as "age" and as "gender" (or, alternatively, "sex"). Alternatively, these columns can be specified via the gender_col and age_col parameters. The age column must contain only numbers or NA, while gender column must contain only 1 (= male) or 2 (= female), either as numbers or as strings, or NA. Alternatively, male can be indicated, instead of 1, with the string male (or its abbreviations, e.g. m), while in that case female can be indicated, instead of 2, with the string female (or its abbreviations, e.g. f or fem). (Lettercases do not matter, e.g. Male or MALE are both evaluated same as male.)
group_by	Optionally the name(s) of column(s) from the data frame provided as data_per_subject to group by.
gender_col	Optionally the name of column from the data frame that contains the gender (sex) information.
age_col	Optionally the name of column from the data frame that contains the age information.
percent	Logical. If TRUE, gender ratios (and the "unknown" ratios based on NA values) are presented as percentage. If FALSE, they are presented as counts (i.e., numbers of subjects).
round_perc	Number to round to, when using percentages.
show_fem	Logical or NULL. If TRUE, the numbers of both male and female are displayed. If FALSE, only the number of males is displayed. If NULL (default), only the number of males is displayed when there are no unknown cases, but both numbers are displayed when there are any unknown cases.

Details

If gender_col and/or age_col are not specified, the function will first look for columns named precisely "age" and as "gender". If either is not found, the function looks for the same names but with any lettercase (e.g. "AGE" or "Gender"). If still no "gender" column is found, the function looks for "sex" column in the same manner. If no column is found for either, all related values will be counted as "unknown" (NA).

If NA values are found in either the age or gender column, the ratio (or count) of unknown cases will be displayed everywhere. Otherwise it will simply not be displayed anywhere.

Examples

```

# below is an illustrative example dataset
# (the "subject" and "measure_x" columns are not used in the function)
dat = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  conditions = c('x', 'y', 'x', 'y', 'y', 'x', 'x', 'x', 'y', 'x'),
  gender = c(2, 2, 1, 2, 1, 2, 2, 2, 1, 1),
  age = c(6, 7, 8.5, 6, 5, 16, 17, 16, 45, 77),
  measure_x = c(83, 71, 111, 70, 92, 75, 110, 111, 110, 85),
  stringsAsFactors = TRUE
)

# print demographics (age and gender) per "conditions":
dems_neat(dat, group_by = 'conditions')

# another dataset, with some missing values
dat = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  conditions = c('x', 'y', 'x', 'y', 'y', 'x', 'x', 'x', 'y', 'x'),
  gender = c(2, 2, NA, NA, 1, 1, 1, 2, NA, NA),
  age = c(6, 7, 8.5, 6, 5, 16, NA, 16, 45, 77),
  measure_x = c(83, 71, 111, 70, 92, 75, 110, 111, 110, 85),
  stringsAsFactors = TRUE
)

# again print demographics per "conditions":
dems_neat(dat, group_by = 'conditions')

# another dataset, with no "age"/"gender" columns
dat = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  conditions = c('x', 'y', 'x', 'y', 'y', 'x', 'x', 'x', 'y', 'x'),
  geschlecht = c(2, 2, NA, NA, 1, 1, 1, 2, NA, NA),
  alter = c(6, 7, 8.5, 6, 5, 16, NA, 16, 45, 77),
  measure_y = c(83, 71, 111, 70, 92, 75, 110, 111, 110, 85),
  stringsAsFactors = TRUE
)

# the following will return "unknowns"
dems_neat(dat, group_by = 'conditions')

# age column specified
dems_neat(dat, group_by = 'conditions', gender_col = 'geschlecht')

# both columns specified
dems_neat(dat,
  group_by = 'conditions',
  age_col = 'alter',
  gender_col = 'geschlecht')

```

enum

Enumerate

Description

Aids enumeration and merging (via [rbind_loop](#)) in loops: adds numbers to a vector input, and indicates loop start for [rbind_loop](#).

Usage

```
enum(items, hush = FALSE, enumerate = TRUE)
```

Arguments

<code>items</code>	The items to be enumerated in the loop.
<code>hush</code>	Logical. If TRUE (default), prints "Loop started." when executed.
<code>enumerate</code>	Logical. If TRUE (default), adds numbering to the input vector (in item pairs, see Examples). If FALSE, returns the original input.

Value

Vector with numbers added (if so set).

See Also

[rbind_loop](#)

Examples

```
my_vector = c('aa', 'bb', 'xyz', 'last')

for (item in enum(my_vector)) {
  print(item)
}

# just to show what enum() returns
enum(my_vector)
```

excl_neat

*Exclusion***Description**

Filters dataset by rows (normally: subjects, observations) and prints the numbers of excluded rows and remaining rows. Returns the filtered dataset and (optionally) also the excluded rows.

Usage

```
excl_neat(
  dat,
  filt,
  excluded = FALSE,
  group_by = NULL,
  sort_by = "exclusion",
  hush = FALSE
)
```

Arguments

dat	Data frame to be filtered.
filt	An expression to use for filtering, by column values, the dat data frame. (Only the rows for which the filter expression is TRUE will be kept.)
excluded	Logical; FALSE by default. If TRUE, the function returns not only the filtered data frame, but also a data frame containing the excluded rows. The returned object in this case will be a list with two elements: (1) the filtered data frame named <code>filtered</code> , and (2) the data frame with excluded rows named <code>excluded</code> (see Examples).
group_by	String, or vector of strings: the name(s) of the column(s) in the dat data frame, containing the vector(s) of factors by which the printed counts are grouped.
sort_by	String; specifies whether the printed counts should be sorted by exclusion (default; "exclusion" or its short forms, e.g. "excl"), or by the factors given for group_by (for this, give any other string, e.g. "conditions"). If NULL (default).
hush	Logical. If TRUE, prevents printing counts to console.

Value

A data frame with the rows for which the `filt` expression is TRUE, or, optionally, a list with this data frame plus a data frame with the excluded rows. At the same time, prints, by default, the count of remaining and excluded rows.

See Also

[aggr_neat](#)

Examples

```

data("mtcars") # load base R example dataset

# filter mtcars for mpg > 20
excl_neat(mtcars, mpg > 20)

# assign the same
mtcars_filtered = excl_neat(mtcars, mpg > 20)
# (mtcars_filtered now contains the filtered subset)

# return and assign excluded rows too
mtcars_filtered_plus_excluded = excl_neat(mtcars, mpg > 20, excluded = TRUE)

# print filtered data frame
print(mtcars_filtered_plus_excluded$filtered)

# print data frame with excluded rows
print(mtcars_filtered_plus_excluded$excluded)

# group printed count by cyl
excl_neat(mtcars, mpg > 20, group_by = 'cyl')

# sort output by grouping
excl_neat(mtcars, mpg > 20, group_by = 'cyl', sort_by = 'group')

# group by cyl and carb
excl_neat(mtcars, mpg > 15, group_by = c('cyl', 'carb'))

# longer filter expression
excl_neat(mtcars, mpg > 15 & gear == 4, group_by = 'cyl',)

```

mean_ci

Confidence Interval of Mean limits

Description

Calculates confidence interval of a vector of numbers.

Usage

```
mean_ci(x, distance_only = TRUE, ci = 0.95)
```

Arguments

x Numeric vector.

distance_only Logical. If TRUE (default), the function returns only the distance between the mean and either confidence interval limit. Otherwise returns the confidence interval (i.e., both limits).

ci Numeric; confidence level for returned CI.

Value

Distance of limit or confidence interval (as named vector).

See Also

[se](#), [plot_neat](#)

Examples

```
mean_ci( c(11, 15, 19, 43, 53, -4, 34, 8, 33, -1, 54 ), FALSE )
mean_ci( c(11, 15, 19, 43, 53, -4, 34, 8, 33, -1, 54 ), FALSE, ci = .80 )
mean_ci( c(11, 15, 19, 43, 53, -4, 34, 8, 33, -1, 54 ), ci = .80 )
```

mon_conv

Monitor Screen Unit Conversion

Description

Given a specific monitor object, converts specified screen units to other specified units. The possible units to convert from and to: "cm" (centimeters), "pix" (pixels), or "deg" (degrees of visual angle).

Usage

```
mon_conv(mon_obj, value, from, to)
```

Arguments

mon_obj	Monitor object, as assigned with mon_neat .
value	Number; value (magnitude) of the given unit to convert from. (Can be vector as well.)
from	String; unit ("cm", "pix", or "deg") to convert from.
to	String; unit ("cm", "pix", or "deg") to convert to.

Value

Number (magnitude) in the given output (to) unit.

See Also

[mon_neat](#)

Examples

```
# assign monitor with 50 cm distance, screen width 52 cm and 1920 pixels
my_mon = mon_neat(distance = 50, mon_width_cm = 52, mon_width_pixel = 1920)

# convert 30.4 pixels to degrees of visual angle, for the specified monitor
mon_conv(my_mon, 30.4, 'pix', 'deg') # returns 0.9434492 (degrees)

# convert 0.94 degrees of visual angle to pixels
mon_conv(my_mon, 0.94, 'deg', 'pix') # returns 30.28885 (pixels)

# convert 10 degrees of visual angle to cm
mon_conv(my_mon, 10, from = 'deg', to = 'cm')

# convert 8.748866 cm to pixels
mon_conv(my_mon, 8.748866, from = 'cm', to = 'pix')
```

mon_neat	<i>Monitor Object</i>
----------	-----------------------

Description

Assigns a monitor object, storing distance and width parameters.

Usage

```
mon_neat(distance, mon_width_cm, mon_width_pixel)
```

Arguments

distance	Viewing distance in cm (from eyes to screen).
mon_width_cm	Monitor screen width in cm.
mon_width_pixel	Monitor screen width in pixels.

Value

A monitor object with the specified parameters, to be used in the [mon_conv](#) function.

See Also

[mon_conv](#)

Examples

```
# assign monitor with 57 cm viewing distance, screen width 52 cm and 1920 pixels
my_mon = mon_neat(distance = 57, mon_width_cm = 52, mon_width_pixel = 1920)
```

norm_tests

*Normality Tests and Plots***Description**

Performs normality tests and creates related plots (histogram, density, Q-Q). This is primarily a sub-function of `t_neat` and `anova_neat`, but here it is available separately for other potential purposes.

Usage

```
norm_tests(
  var1,
  var2 = NULL,
  pair = FALSE,
  norm_tests = "all",
  alpha = 0.05,
  plots = FALSE,
  aspect_ratio = 1,
  hush = FALSE
)
```

Arguments

<code>var1</code>	Numeric vector; numbers of any given variable.
<code>var2</code>	Optional numeric vector (or NULL); numbers of a second variable.
<code>pair</code>	Logical; only matters if <code>var2</code> is not null. In that case, if TRUE each normality test is performed for the difference values between the two variables in case of paired samples, or, if FALSE, separately for each of the two variables for unpaired samples.
<code>norm_tests</code>	Normality tests. Any or all of the following character input is accepted (as a single string or a character vector; case-insensitive): "W" (Shapiro-Wilk), "K2" (D'Agostino-Pearson), "A2" (Anderson-Darling), "JB" (Jarque-Bera); see Notes. The option "all" (default value) selects all four previous tests at the same time.
<code>alpha</code>	Numeric (.05 by default), alpha level: if any p value is below this alpha level, the function returns TRUE, otherwise FALSE.
<code>plots</code>	Logical: if TRUE adds histogram, density, and Q-Q plots. (Note: in case of paired samples, Q-Q plots are plotted on a separate figure. In RStudio, press on "Previous plot" under "Plots" to see these Q-Q plots.)
<code>aspect_ratio</code>	Aspect ratio of the plots: 1 (1/1) by default. (Set to NULL for dynamic aspect ratio.)
<code>hush</code>	Logical. If TRUE, prevents printing any details to console.

Value

Prints normality tests, and displays plots if so specified. Returns TRUE if any of the specified tests has p value below the specified alpha, otherwise returns FALSE.

Note

#Normality tests are all calculated via `Power::statcompute`, selected based on the recommendation of Lakens (2015), quoting Yap and Sim (2011, p. 2153): "If the distribution is symmetric with low kurtosis values (i.e. symmetric short-tailed distribution), then the D'Agostino-Pearson and Shapiro-Wilkes tests have good power. For symmetric distribution with high sample kurtosis (symmetric long-tailed), the researcher can use the JB, Shapiro-Wilkes, or Anderson-Darling test." See url<https://github.com/Lakens/perfect-t-test> for more details.

References

Lakens, D. (2015). The perfect t-test (version 1.0.0). Retrieved from <https://github.com/Lakens/perfect-t-test>. doi: [10.5281/zenodo.17603](https://doi.org/10.5281/zenodo.17603)

Yap, B. W., & Sim, C. H. (2011). Comparisons of various types of normality tests. *Journal of Statistical Computation and Simulation*, 81(12), 2141–2155. doi: [10.1080/00949655.2010.520163](https://doi.org/10.1080/00949655.2010.520163)

See Also

[t_neat](#)

Examples

```
norm_tests(stats::rnorm(100))
# should be normal...
```

path_neat

Script Path

Description

Gives, in RStudio, the path to the script file in which it is executed.

Usage

```
path_neat(subdir = "")
```

Arguments

subdir String, optional. Subdirectory relative to the script's path.

Value

Script file's path as string. If `subdir` is given, it is appended to the original path.

Examples

```
# assuming the given script is at path "C:/script_folder/"
path_neat('') # returns "C:/script_folder/"
path_neat('my_subdir/misc/') # returns "C:/script_folder/my_subdir/misc/"

# Note: the returned string can be used as argument for base::setwd()
# e.g. setwd( path_neat() ) # sets working directory to the script's path
```

 peek_neat

Cursory Summaries and Plots per Group

Description

Cursory summaries and plots per group.

Usage

```
peek_neat(
  dat,
  values,
  group_by = NULL,
  filt = NULL,
  sep = ", ",
  collapse = NULL,
  f_print = NULL,
  f_plot = NULL,
  iqr_times = 3,
  round_to = 4,
  group_n = TRUE,
  ...
)
```

Arguments

<code>dat</code>	Data frame (or name of data frame as string).
<code>values</code>	String, or vector of strings: the name(s) of the column(s) in the <code>dat</code> data frame, containing the vector(s) of values.
<code>group_by</code>	String, or vector of strings: the name(s) of the column(s) in the <code>dat</code> data frame, containing the vector(s) of factors by which the statistics are grouped.

<code>filt</code>	An expression to filter, by column values, the entire data frame before performing the aggregation. The expression should use column names alone; see Examples.
<code>sep</code>	String (comma by default) for separating group names.
<code>collapse</code>	Decides how to handle multiple columns of values. If NULL (default), displays each column of values as separate groups. Alternatively, any function can be given using which the columns are collapsed into a single column. For example, if mean is given for this parameter, a single column will be calculated based on the means of all given values columns. (NA is always ignored.)
<code>f_print</code>	Printing function; see details.
<code>f_plot</code>	Plotting function; see details. (Provide string to skip plotting.)
<code>iqr_times</code>	The multiplication of IQR to calculate Tukey's fences, when using default <code>f_print</code> (NULL); see Details. The default is 3 to spot Tukey's "far outliers" (e.g. by comparing the fences with min and max values). (Note that the usual fences, e.g. for box plots, use 1.5).
<code>round_to</code>	Number of significant fractional digits to round to , when using default <code>f_print</code> (NULL).
<code>group_n</code>	Logical. If TRUE, adds sample sizes (n) per group to plots when using default <code>f_plot</code> (NULL).
<code>...</code>	Any arguments to be passed to the <code>f_plot</code> function.

Details

Prints, by default, the following data (per group): mean; 95 mean as `ci_low` and `ci_upp`; sd; median; `quantile_1st` and `quantile_3rd` (first and third quantiles); "Tukey's fences" as `fence_low` and `fence_upp`; minimum and maximum values (`min`, `max`); number of NAs (`na`). Tukey's fences are the upper and lower limits with distances of X times the IQR from the actual IQR, where X is specified via the `iqr_times` parameter. Returns (invisibly) the same values, unrounded, via a data frame. If alternative `f_print` is given, prints whatever value is returned from the given function (and attempts, if possible, to create a data frame).

Creates and displays box plot(s) (per group) by default, along with overlaid violin plot (densities proportionate to sample sizes). If alternative `f_plot` is given, the first argument will be the values per group, and all plots will be [arranged](#) into a single plot and displayed together. To skip plotting, just give any character as argument (e.g. "none" or just "").

Value

Data frame with the printed values (if possible).

Examples

```
data("mtcars") # load base R example dataset

# overall info for wt (Weight)
peek_neat(mtcars, 'wt')
#'
```

```

# now grouped by cyl (Number of cylinders)
peek_neat(mtcars, 'wt', group_by = 'cyl')

# grouped by cyl and gear
peek_neat(mtcars, 'wt', group_by = c('cyl', 'gear'))

# filter to only have cyl larger than 4
peek_neat(mtcars, 'wt', group_by = 'cyl', filt = cyl > 4)

# without plots
peek_neat(mtcars, 'wt', group_by = 'cyl', f_plot = "")

# with histograms etc, using plot_neat
peek_neat(mtcars, 'wt', group_by = 'cyl', f_plot = plot_neat)

# with Q-Q plots, via ggpubr
peek_neat(mtcars, 'wt', group_by = 'cyl',
          f_plot = ggpubr::ggqqplot)

# skewness and kurtosis data via psych
## Not run:
info_df = peek_neat(
  mtcars,
  'wt',
  group_by = 'cyl',
  f_print = psych::describe,
  f_plot = ""
)
info_df # contains all data returns by psych::describe

## End(Not run)

```

plot_neat

Plots of Means and of Dispersion

Description

Primarily for line and bar [plots](#) for factorial designs. Otherwise (if no `data_per_subject` is given) descriptive dispersion plots (histogram, density, or box plots) for a continuous variable. (For the latter, only the parameters `values`, `parts`, `part_colors`, and `binwidth` are used, the rest are ignored.)

Usage

```

plot_neat(
  data_per_subject = NULL,
  values = NULL,
  within_ids = NULL,

```

```

between_vars = NULL,
factor_names = NULL,
value_names = NULL,
y_title = NULL,
reverse = FALSE,
panels = NULL,
type = "line",
dodge = NULL,
bar_colors = c("#333333", "#AAAAAA"),
line_colors = c("#555555", "#000000"),
row_number = 1,
method = mean,
eb_method = neatStats::mean_ci,
numerics = FALSE,
hush = FALSE,
parts = c("h", "d", "n", "b"),
part_colors = NULL,
binwidth = NULL
)

```

Arguments

data_per_subject	Data frame containing all values (measurements/observations for a factorial design) in a single row per each subject. Otherwise, if no data frame is given (default: NULL), histogram, density, or box plots will be returned for a continuous variable (numeric vector).
values	For plots of means (factorial designs): vector of strings; column name(s) in the data_per_subject data frame. Each column should contain a single dependent variable: thus, to plot repeated (within-subject) measurements, each specified column should contain one measurement. For descriptive dispersion plots (if data_per_subject is NULL), a numeric vector is expected.
within_ids	NULL (default), string, or named list. In case of no within-subject factors, leave as NULL. In case of a single within subject factor, a single string may be given to optionally provide custom name for the within-subject factor (note: this is a programming variable name, so it should not contain spaces, etc.); otherwise (if left NULL) this one within-subject factor will always just be named "within_factor". In case of multiple within-subject factors, each factor must be specified as a named list element, each with a vector of strings that distinguish the levels within that factors. The column names given as values should always contain one (and only one) of these strings within each within-subject factor, and thus they will be assigned the appropriate level. For example, values = 'rt_s1_neg,rt_s1_pos,rt_s2_neg,rt_s2_pos' could have within_ids = list(session = c('s1', 's2'), valence = c('pos', 'neg')). (Note: the strings for distinguishing must be unambiguous. E.g., for values apple_a and apple_b, do not set levels c('a', 'b'), because 'a' is also found in apple_b. In this case, you could choose levels c('_a', '_b') to make sure the values are correctly distinguished.) See also Examples.

between_vars	NULL (default; in case of no between-subject factors) or vector of strings; column name(s) in the data_per_subject data frame. Each column should contain a single between-subject independent variable (representing between-subject factors).
factor_names	NULL or named vector. In a named vector, factor names (either within or between) can be given a different name for display, in a dictionary style, using original factor name as the name of a vector element, and the element's value (as string) for the new name. For example, to change a factor named "condition" to "High vs. low arousal", the vector may be given (in this case with a single element) as factor_names = c(condition = "High vs. low arousal").
value_names	NULL or named vector. Same as factor_names, but regarding the factor values. For example, to change values "high_a" and "low_a" to "High" and "Low" for display, the vector may be given as value_names = c(high_a = "High", low_a = "Low").
y_title	NULL (default) or string. Optionally given title for the y axis.
reverse	Logical (default: FALSE). If TRUE, reverses the default grouping of variables within the figure, or within each panel, in case of multiple panels. (The default grouping is decided automatically by given factor order, but always starting, when applicable, with within-subject factors: first factor is split to adjacent bars, or vertically aligned dots in case of line plot.)
panels	NULL or string. Optionally gives the factor name by which the plot is to be split into different panels, in case of three factors. (By default, the third given factor is used.)
type	Strong: "line" (default) or "bar". The former gives line plot, the latter gives bar plot.
dodge	Number. Specifies the amount by which the adjacent bars or dots 'dodge' each other (i.e., are displaced compared to each other). (Default is 0.1 for line plots, and 0.9 for bar plots.)
bar_colors	Vector of strings, specifying colors from which all colors for any number of differing adjacent bars are interpolated. (If the number of given colors equal the number of different bars, the precise colors will correspond to each bar.) The default c('#333333', '#AAAAAA') gives a color gradient from dark gray to light gray. (In case of a single factor, the first given colors is taken.)
line_colors	Vector of strings, specifying colors from which all colors for any number of differing vertically aligned dots and corresponding lines are interpolated. The default c('#555555', '#000000') gives a color gradient from dark gray to black. (In case of a single factor, the first given colors is taken.)
row_number	Number. In case of multiple panels, the number of rows in which the panels should be arranged. For example, with the default row_number = 1, all panels will be displayed in one vertically aligned row.
method	A function (default: mean) for the calculation of the main statistics (bar or dot heights).
eb_method	A function (default: mean_ci for 95 the calculation of the error bar size (as a single value used for both directions of the error bar). If set to NULL, no error bar is displayed.#'

numerics	If FALSE (default), returns <code>ggplot</code> object. If set to TRUE, returns only the numeric aggregated data per grouping factors, as specified by <code>method</code> and <code>eb_method</code> functions. If set to any string (e.g. "both"), returns the numeric aggregated data and at the same time <code>draws</code> the plot.
hush	Logical. If TRUE, prevents printing aggregated values.
parts	For dispersion plots only (if no <code>data_per_subject</code> is given). A vector of characters that specify which types of overlaid types to plot: "h" for histogram, "d" for density, "n" normally distributed density (using the mean and standard deviation of the given variable), "b" for boxplot. (All are included by default: <code>parts = c("h", "d", "n", "b")</code>).
part_colors	For dispersion plots only (if no <code>data_per_subject</code> is given). A named that can specify and thereby override default colors and alpha (transparency) of each plot type. Colors can be given by adding "c" to the plot type letter, e.g. <code>c(hc = "blue")</code> for blue histogram. Alpha can be given by adding "a" to the plot type letter, e.g. <code>c(ha = 0)</code> for completely transparent histogram. Any number may be given: e.g. a dark red transparent histogram with green boxplot would be <code>part_colors = c(hc = "#cc0000", ha = 0.1, bc = "green")</code> .
binwidth	For dispersion plots only (if no <code>data_per_subject</code> is given). Binwidth for histograms. If NULL (default), Freedman–Diaconis rule is used if it produces at least 10 bins – otherwise <code>bandwidth</code> is calculated for 10 bins.

Value

By default, a `ggplot` plot object. (This object may be further modified or adjusted via regular `ggplot` methods.) If so set (`numerics`), aggregated values as specified by the methods.

Note

More than three factors is not allowed: it would make little sense and it would be difficult to clearly depict in a simple figure. (However, you can build an appropriate graph using `ggplot` directly; but you can also just divide the data to produce several three-factor plots, after which you can use e.g. `ggpubr`'s `ggarrange` to easily collate the plots.)

See Also

[anova_neat](#), [mean_ci](#), [se](#)

Examples

```
# assign random data in a data frame for illustration
# (note that the 'subject' is only for illustration; since each row contains the
# data of a single subject, no additional subject id is needed)
dat_1 = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14),
  grouping1 = c(1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2),
  grouping2 = c(1, 2, 1, 2, 2, 1, 2, 1, 2, 1, 1, 1, 2, 1),
  value_1_a = c(36.2, 45.2, 41, 24.6, 30.5, 28.2, 40.9, 45.1,
                31, 16.9, 40.1, 42.1, 41, 12.9),
```

```

value_2_a = c(-14.1, 58.5,-25.5, 42.2,-13, 4.4, 55.5,-28.5,
              25.6,-37.1, 55.1,-38.5, 28.6,-34.1),
value_1_b = c(83, 71, 111, 70, 92, 75, 110, 111, 110, 85,
              132, 121, 151, 95),
value_2_b = c(8.024,-14.162, 3.1,-2.1,-1.5, 0.91, 11.53,
              18.37, 0.3,-0.59, 12.53, 13.37, 2.3,-3),
value_1_c = c(27.4, -17.6, -32.7, 0.4, 37.2, 1.7, 18.2, 8.9,
              1.9, 0.4, 2.7, 14.2, 3.9, 4.9),
value_2_c = c(7.7,-0.8, 2.2, 14.1, 22.1,-47.7,-4.8, 8.6,
              6.2, 18.2,-6.8, 5.6, 7.2, 13.2)
)
head(dat_1) # see what we have

# plot for factors 'grouping1', 'grouping2'
plot_neat(
  data_per_subject = dat_1,
  values = 'value_1_a',
  between_vars = c('grouping1', 'grouping2')
)

# same as above, but with bars and renamed factors
plot_neat(
  data_per_subject = dat_1,
  values = 'value_1_a',
  between_vars = c('grouping1', 'grouping2'),
  type = 'bar',
  factor_names = c(grouping1 = 'experimental condition', grouping2 = 'gender')
)

# same, but with different (lighter) gray scale bars
plot_neat(
  dat_1,
  values = 'value_1_a',
  between_vars = c('grouping1', 'grouping2'),
  type = 'bar',
  factor_names = c(grouping1 = 'experimental condition', grouping2 = 'gender'),
  bar_colors = c('#555555', '#BBBBBB')
)

# same, but with red and blue bars
plot_neat(
  dat_1,
  values = 'value_1_a',
  between_vars = c('grouping1', 'grouping2'),
  type = 'bar',
  factor_names = c(grouping1 = 'experimental condition', grouping2 = 'gender'),
  bar_colors = c('red', 'blue') # equals c('#FF0000', '#0000FF')
)

# within-subject factor for 'value_1_a' vs. 'value_1_b' vs. 'value_1_c'
# (automatically named 'within_factor'), between-subject factor 'grouping1'
plot_neat(
  dat_1,

```



```

    values = c('value_1_a', 'value_1_b', 'value_1_c'),
    between_vars = c('grouping1', 'grouping2')
  )

# same, but panelled by 'within_factor'
plot_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b', 'value_1_c'),
  between_vars = c('grouping1', 'grouping2'),
  panels = 'within_factor'
)

# same, but SE for error bars instead of (default) SD
plot_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b', 'value_1_c'),
  between_vars = c('grouping1', 'grouping2'),
  panels = 'within_factor',
  eb_method = se
)

# same, but 95% CI for error bars instead of SE
# (arguably more meaningful than SEs)
plot_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b', 'value_1_c'),
  between_vars = c('grouping1', 'grouping2'),
  panels = 'within_factor',
  eb_method = mean_ci
)

# same, but using medians and Median Absolute Deviations
plot_neat(
  dat_1,
  values = c('value_1_a', 'value_1_b', 'value_1_c'),
  between_vars = c('grouping1', 'grouping2'),
  panels = 'within_factor',
  method = stats::median,
  eb_method = stats::mad
)

# within-subject factor 'number' for variables with number '1' vs. number '2'
# ('value_1_a' and 'value_1_b' vs. 'value_2_a' and 'value_2_b'), factor 'letter'
# for variables with final letter 'a' vs. final letter 'b' ('value_1_a' and
# 'value_2_a' vs. 'value_1_b' and 'value_2_b')
plot_neat(
  dat_1,
  values = c('value_1_a', 'value_2_a', 'value_1_b', 'value_2_b'),
  within_ids = list(
    letters = c('_a', '_b'),
    numbers = c('_1', '_2')
  )
)

```

```

# same as above, but now including between-subject factor 'grouping2'
plot_neat(
  dat_1,
  values = c('value_1_a', 'value_2_a', 'value_1_b', 'value_2_b'),
  within_ids = list(
    letters = c('_a', '_b'),
    numbers = c('_1', '_2')
  ),
  between_vars = 'grouping2'
)

# same as above, but renaming factors and values for display
plot_neat(
  dat_1,
  values = c('value_1_a', 'value_2_a', 'value_1_b', 'value_2_b'),
  within_ids = list(
    letters = c('_a', '_b'),
    numbers = c('_1', '_2')
  ),
  between_vars = 'grouping2',
  factor_names = c(numbers = 'session (first vs. second)'),
  value_names = c(
    '_1' = 'first',
    '_2' = 'second',
    '1' = 'group 1',
    '2' = 'group 2'
  )
)

# In real datasets, these could of course be more meaningful. For example, let's
# say participants rated the attractiveness of pictures with low or high levels
# of frightening and low or high levels of disgusting qualities. So there are
# four types of ratings:
# 'low disgusting, low frightening' pictures
# 'low disgusting, high frightening' pictures
# 'high disgusting, low frightening' pictures
# 'high disgusting, high frightening' pictures

# this could be meaningfully assigned e.g. as below
pic_ratings = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  rating_fright_low_disgust_low = c(36.2, 45.2, 41, 24.6, 30.5, 28.2, 40.9, 45.1, 31, 16.9),
  rating_fright_high_disgust_low = c(-14.1, 58.5, -25.5, 42.2, -13, 4.4, 55.5, -28.5, 25.6, -37.1),
  rating_fright_low_disgust_high = c(83, 71, 111, 70, 92, 75, 110, 111, 110, 85),
  rating_fright_high_disgust_high = c(8.024, -14.162, 3.1, -2.1, -1.5, 0.91, 11.53, 18.37, 0.3, -0.59)
)
head(pic_ratings) # see what we have

# the same logic applies as for the examples above, but now the
# within-subject differences can be more meaningfully specified, e.g.
# 'disgust_low' vs. 'disgust_high' for levels of disgustingness, while
# 'fright_low' vs. 'fright_high' for levels of frighteningness

```

```

plot_neat(
  pic_ratings,
  values = c(
    'rating_fright_low_disgust_low',
    'rating_fright_high_disgust_low',
    'rating_fright_low_disgust_high',
    'rating_fright_high_disgust_high'
  ),
  within_ids = list(
    disgustingness = c('disgust_low', 'disgust_high'),
    frighteningness = c('fright_low', 'fright_high')
  )
)

# now let's say the ratings were done in two separate groups
pic_ratings = data.frame(
  subject = c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10),
  group_id = c(1, 2, 1, 2, 2, 1, 1, 1, 2, 1),
  rating_fright_low_disgust_low = c(36.2, 45.2, 41, 24.6, 30.5, 28.2, 40.9, 45.1, 31, 16.9),
  rating_fright_high_disgust_low = c(-14.1, 58.5, -25.5, 42.2, -13, 4.4, 55.5, -28.5, 25.6, -37.1),
  rating_fright_low_disgust_high = c(83, 71, 111, 70, 92, 75, 110, 111, 110, 85),
  rating_fright_high_disgust_high = c(8.024, -14.162, 3.1, -2.1, -1.5, 0.91, 11.53, 18.37, 0.3, -0.59)
)

# now include the 'group_id' factor in the plot
plot_neat(
  pic_ratings,
  values = c(
    'rating_fright_low_disgust_low',
    'rating_fright_high_disgust_low',
    'rating_fright_low_disgust_high',
    'rating_fright_high_disgust_high'
  ),
  within_ids = list(
    disgustingness = c('disgust_low', 'disgust_high'),
    frighteningness = c('fright_low', 'fright_high')
  ),
  between_vars = 'group_id'
)

## DISPERSION PLOTS

plot_neat(values = rnorm(100))

# with smaller binwidth (hence more bins)
plot_neat(values = rnorm(100), binwidth = 0.2)

# without normal distribution line
plot_neat(values = rnorm(100), parts = c('h', 'd', 'b'))

# without histogram
plot_neat(values = rnorm(100), parts = c('d', 'n', 'b'))

```

```
# blue density, fully opaque histogram
plot_neat(values = rnorm(100),
          part_colors = c(dc = 'blue', ha = 1))
```

 props_neat

Difference of Two Proportions

Description

[Unconditional exact test](#) results for the comparison of two independent proportions, including confidence interval (CI) for the proportion difference, and corresponding [independent multinomial contingency table Bayes factor](#) (BF). Cohen's h and its CI are also calculated.

Usage

```
props_neat(
  case1,
  case2,
  n1,
  n2,
  greater = NULL,
  ci = NULL,
  bf_added = FALSE,
  h_added = FALSE,
  for_table = FALSE,
  hush = FALSE
)
```

Arguments

case1	Number of 'cases' (as opposed to 'controls'; e.g. positive outcomes vs. negative outcomes) in 'group 1'.
case2	Number of 'cases' in 'group 2'.
n1	Number; sample size of 'group 1'.
n2	Number; sample size of 'group 2'.
greater	NULL or string (or number); optionally specifies one-sided exact test: either "1" (case1/n1 proportion expected to be greater than case2/n2 proportion) or "2" (case2/n2 proportion expected to be greater than case1/n1 proportion). If NULL (default), the test is two-sided.
ci	Numeric; confidence level for the returned CIs (proportion difference and Cohen's h).
bf_added	Logical. If TRUE (default), Bayes factor is calculated and displayed. (Always two-sided.)

h_added	Logical. If TRUE, Cohen's h and its CI are calculated and displayed. (FALSE by default.)
for_table	Logical. If TRUE, omits the confidence level display from the printed text.
hush	Logical. If TRUE, prevents printing any details to console.

Details

The Bayes factor (BF) is always calculated with the default r-scale of 0.707. BF supporting null hypothesis is denoted as BF01, while that supporting alternative hypothesis is denoted as BF10. When the BF is smaller than 1 (i.e., supports null hypothesis), the reciprocal is calculated (hence, BF10 = BF, but BF01 = 1/BF). When the BF is greater than or equal to 10000, scientific (exponential) form is reported for readability. (The original full BF number is available in the returned named vector as bf.)

Value

Prints exact test statistics (including proportion difference with CI, and BF) in APA style. Furthermore, when assigned, returns a named vector with the following elements: z (Z), p (p value), prop_diff (raw proportion difference), h (Cohen's h), bf (Bayes factor).

Note

Barnard's unconditional exact test is calculated via `Exact::exact.test` ("z-pooled").

The CIs for the proportion difference is calculated based on the p value, as described by Altman and Bland (2011).

The Bayes factor is calculated via `BayesFactor::contingencyTableBF`, with `sampleType = "indepMulti"`, as appropriate when both sample sizes (n1 and n2) are known in advance (as it normally happens). (For details, see `contingencyTableBF`, or e.g. 'Chapter 17 Bayesian statistics' in Navarro, 2019.)

References

- Altman, D. G., & Bland, J. M. (2011). How to obtain the confidence interval from a P value. *Bmj*, 343(d2090). doi: [10.1136/bmj.d2090](https://doi.org/10.1136/bmj.d2090)
- Barnard, G. A. (1947). Significance tests for 2x2 tables. *Biometrika*, 34(1/2), 123-138. doi: [10.1093/biomet/34.12.123](https://doi.org/10.1093/biomet/34.12.123)
- Lydersen, S., Fagerland, M. W., & Laake, P. (2009). Recommended tests for association in 2x2 tables. *Statistics in medicine*, 28(7), 1159-1175. doi: [10.1002/sim.3531](https://doi.org/10.1002/sim.3531)
- Navarro, D. (2019). Learning statistics with R. <https://learningstatisticswithr.com/>
- Suissa, S., & Shuster, J. J. (1985). Exact unconditional sample sizes for the 2 times 2 binomial trial. *Journal of the Royal Statistical Society: Series A (General)*, 148(4), 317-327. doi: [10.2307/2981892](https://doi.org/10.2307/2981892)

Examples

```
props_neat(
  case1 = 35,
  case2 = 48,
```

```

    n1 = 80,
    n2 = 77,
    h_added = TRUE
  )

  props_neat(
    case1 = 35,
    case2 = 48,
    n1 = 80,
    n2 = 77,
    greater = "2"
  )

```

rbind_loop

Merge by Columns in Loops

Description

Merges rows by columns in a loop using the `enum` function. On first iteration, indicated by `enum`, initiates a new data frame with the data to merge as first row. On all following iterations, adds data to merge as subsequent rows (using `plyr:rbind.fill`).

Usage

```
rbind_loop(merged, ..., hush = FALSE, nameless = FALSE)
```

Arguments

<code>merged</code>	The name of the data frame for the merged data (without quotes).
<code>...</code>	Any number of data to be merged. Each argument must be one of the following: a data frame with either single row or two column; a named vector or a named list (with single elements); or a single value with parameter name (e.g. <code>date = 1989</code> or <code>id = "jdoe"</code>). Data with two columns will be transposed using first column as column names and second column as corresponding values. See Details, Examples.
<code>hush</code>	Logical. If TRUE (default), prints message when the data frame for merging is initiated.
<code>nameless</code>	Logical. If FALSE (default), unnamed vectors or list elements are not allowed. If set to TRUE, unnamed elements will be named automatically (e.g. <code>X.value</code>).

Details

In each call, all data passed to the function (via `...`) will be merged into a single row, and that single row will be added to the merged data frame

See an extensive example via <https://github.com/gasparl/neatstats>.

See Also[enum](#)**Examples**

```

my_vector = c('aa', 'bb', 'cxyz', 'last')
for (elem in enum(my_vector)) {
  cat(elem, fill = TRUE)
  rbind_loop(
    merged_data, # data frame name for merging
    item = elem[2],
    number = elem[1],
    whatever = paste0('number (', elem[1], ')')
  )
}
# merged_data now contains all merged rows
print(merged_data)
# item number  whatever
# 1 aa      1 number (1)
# 2 bb      2 number (2)
# 3 cxyz    3 number (3)
# 4 last    4 number (4)

# example with other data types
for (elem in enum(my_vector)) {
  cat(elem, fill = TRUE)
  dframe1 = data.frame(item = elem[2],
                      number = elem[1])

  print(elem[1])
  asnum = as.numeric(elem[1])
  dframe2 = data.frame(
    my_cols = c('index', 'squared', 'multiple'),
    my_vals = c(elem[1], asnum ** 2, asnum * 10)
  )
  my_list = list(ls_item = elem[2], ls_num = elem[1])
  my_vec = c(v_item = elem[2], v_num = elem[1])
  rbind_loop(
    merged_data,
    dframe1, # data frame with single row
    dframe2, # data frame with two columns
    my_list, # named list
    my_vec, # named vector
    single_val = elem[2], # single element
    constant = "whatever" # other single element
  )
}

# again merged_data contains all merged rows
# (previous content, if any, were removed)
print(merged_data)

```

```
# example with differring columns
for (elem in enum(my_vector)) {
  cat(elem, fill = TRUE)
  dframe = data.frame(item = elem[2],
                      number = elem[1])
  asnum = as.numeric(elem[1])
  if (asnum %% 2 == 0) {
    dframe$sqr = asnum ** 2
  }
  rbind_loop(merged_data,
            dframe)
}

# merged_data contains all new merged rows
# with NAs where sqr was not added
print(merged_data)

# an extensive example to show how to collect and aggregate raw data is
# available via the README file at the repository:
# https://github.com/gaspar1/neatstats
```

read_dir

Read and Merge Files from Directory

Description

Reads data files from any given directory as data frames and merges them into a single data frame (using `plyr:rbind.fill`).

Usage

```
read_dir(
  pattern = "*[.]",
  path = ".",
  reader_function = utils::read.table,
  ...,
  subdirs = FALSE,
  filt = NULL,
  hush = FALSE
)
```

Arguments

`pattern` Regular expression ("regex"; as string or NULL) for selecting files (passed to the `list.files` function). The default NULL means that all files at the specified path will be read in. To select, for example, a specific extension like ".txt", the

pattern can be given as "\\ .txt\$" (for CSV files, "\\ .csv\$", etc.). Files ending with e.g. "group2.txt" can be specified as "group2\\.txt\$". Files starting with "exp3" can be specified as "^exp3". Files starting with "exp3" AND ending with ".txt" extension can be specified as "^exp3.*\\.txt\$". To read in a single file, specify the full filename (e.g. "exp3_subject46_group2.txt"). (See `?regex` for more details.)

path	Path to the directory from which the files should be selected and read. The default "." means the current working directory (as returned by <code>getwd()</code>). Either specify correct working directory in advance (see <code>setwd</code> , <code>path_neat</code>), or otherwise enter relative or full paths (e.g. "C:/research" or "/home/projects", etc.).
reader_function	A function to be used for reading the files, <code>utils::read.table</code> by default.
...	Any arguments to be passed on to the chosen reader_function.
subdirs	Logical (FALSE by default). If TRUE, searches files in subdirectories as well (relative to the given path).
filt	An expression to filter, by column values, each data file after it is read and before it is merged with the other data. (The expression should use column names alone; see Examples.)
hush	Logical. If FALSE (default), prints lists all data file names as they are being read (along with related warnings).

Note

This function is very similar to the `readbulk::read_bulk` function. One important difference however is the possibility of pre-filtering by file (see `filt`). Data files could include significant amount of unnecessary data, and filtering prevents these to be merged. Another important difference is the possibility of file selection based on any regex pattern.

See Also

[plyr::rbind.fill](#)

Examples

```
# first, set current working directory
# e.g. to script's path with setwd(path_neat())

# read all text files in current working directory
merged_df = read_dir("\\.txt$")
# merged_df now has all data

# some advisable options passed to read.table
merged_df = read_dir(
  '\\.txt$',
  header = TRUE,
  fill = TRUE,
```

```

    quote = "\"",
    stringsAsFactors = FALSE
  )

```

ro

*Neat rounding***Description**

Rounds a given number to given number of digits after the decimal point, returning it as string, with trailing zeros when applicable.

Usage

```
ro(num, round_to = 2, leading_zero = TRUE, signi = FALSE)
```

Arguments

num	Number to be rounded.
round_to	Number of fractional digits (i.e., digits after the decimal point), to round to.
leading_zero	Logical, TRUE by default. If FALSE, omits leading zero (e.g. returns ".17" instead of "0.17").
signi	Logical, FALSE by default. If TRUE, rounds to a fractional digit that allows at least the first N non-zero digits displayed in all numbers, where N is specified by the round_to parameter. (See base:formatC)

Value

Number as string: num rounded to round_to digits, with trailing zeros when applicable.

Examples

```

ro( 1.2345 ) # returns "1.23"

ro( 0.12345, 1 ) # returns "0.1"

ro( 12.3, 4 ) # returns "12.3000"

# examples with vectors
to_round = c(1000, 100, 0.1, 0.01, 0.001, 0.0001)
ro(to_round)
ro(to_round, 3)
ro(to_round, 3, leading_zero = FALSE)
ro(to_round, 3, signi = TRUE)
to_round2 = c(1230.000, 100, 0.012, 0.01, 0.123, 0.012340)
ro(to_round2, 3)

```

```

ro(to_round2, 3, signi = TRUE)
ro(to_round2, 2, signi = TRUE)
ro(to_round2, 1, signi = TRUE)
ro(to_round2, 9, signi = TRUE)

```

roc_neat

Difference of Two Areas Under the Curves

Description

Comparison of two [areas under the receiver operating characteristic curves](#) (AUCs).

Usage

```
roc_neat(roc1, roc2, pair = FALSE, greater = NULL, ci = NULL, hush = FALSE)
```

Arguments

roc1	Receiver operating characteristic (ROC) object .
roc2	Receiver operating characteristic (ROC) object .
pair	Logical. If TRUE, the test is conducted for paired samples. Otherwise (default) for independent samples.
greater	NULL or string (or number); optionally specifies one-sided test: either "1" (roc1 AUC expected to be greater than roc2 AUC) or "2" (roc2 AUC expected to be greater than roc2 AUC). If NULL (default), the test is two-sided.
ci	Numeric; confidence level for the returned CIs (raw difference).
hush	Logical. If TRUE, prevents printing any details to console.

Value

Prints DeLong's test results for the comparison of the two given AUCs in APA style, as well as corresponding CI for the AUC difference. Furthermore, when assigned, returns a named vector with the following two elements: stat (D value), p (p value).

Note

The test statistics are calculated via [pROC::roc.test](#) as DeLong's test (for both paired and unpaired). The roc_neat function merely prints it in APA style.

The ROC object may be calculated via [t_neat](#), or directly with [pROC::roc](#).

References

- Altman, D. G., & Bland, J. M. (2011). How to obtain the confidence interval from a P value. *Bmj*, 343(d2090). doi: [10.1136/bmj.d2090](https://doi.org/10.1136/bmj.d2090)
- DeLong, E. R., DeLong, D. M., & Clarke-Pearson, D. L. (1988). Comparing the areas under two or more correlated receiver operating characteristic curves: a nonparametric approach. *Biometrics*, 44(3), 837-845. doi: [10.2307/2531595](https://doi.org/10.2307/2531595)
- Robin, X., Turck, N., Hainard, A., Tiberti, N., Lisacek, F., Sanchez, J. C., & Muller, M. (2011). pROC: an open-source package for R and S+ to analyze and compare ROC curves. *BMC bioinformatics*, 12(1), 77. doi: [10.1186/147121051277](https://doi.org/10.1186/147121051277)

See Also

[t_neat](#)

Examples

```
# calculate first AUC (from v1 and v2)
v1 = c(191, 115, 129, 43, 523,-4, 34, 28, 33,-1, 54)
v2 = c(4,-2, 23, 13, 32, 16, 3, 29, 37,-4, 65)
results1 = t_neat(v1, v2, auc_added = TRUE)

# calculate second AUC (from v3 and v4)
v3 = c(14.1, 58.5, 25.5, 42.2, 13, 4.4, 55.5, 28.5, 25.6, 37.1)
v4 = c(36.2, 45.2, 41, 24.6, 30.5, 28.2, 40.9, 45.1, 31, 16.9)
results2 = t_neat(v3, v4, auc_added = TRUE)

# one-sided comparison of the two AUCs
roc_neat(results1$roc_obj, results2$roc_obj, greater = "1")
```

se

Standard Error of Mean

Description

Simply calculates the standard error of a vector of numbers.

Usage

```
se(x)
```

Arguments

x Numeric vector.

Value

Standard error.

See Also[mean_ci](#), [plot_neat](#)**Examples**

```
se( c(11, 15, 19, 43, 53, -4, 34, 8, 33, -1, 54 ) )
```

table_neat	<i>Table, descriptives</i>
------------	----------------------------

Description

Creates a neat means (or similar descriptives) and standard deviations table, using [aggr_neat](#) functions as arguments. Alternatively, merges and transposes data frames into rows.

Usage

```
table_neat(
  values_list,
  group_by = NULL,
  group_per = "rows",
  to_clipboard = FALSE,
  method = "mean+sd",
  transpose = FALSE
)
```

Arguments

values_list	Data frames as returned from the aggr_neat function: variables from which the statistics for the table are to be calculated. The group_by, method, and prefix parameters are ignored when they are given in the table_neat function; see Details and also an extensive example via https://github.com/gasparl/neatstats .
group_by	String, or vector of strings: the name(s) of the column(s) in the dat given data frame, containing the vector(s) of factors by which the statistics are grouped. (Overwrites group_by in aggr_neat ; see Details.)
group_per	String, "rows" or "columns". If set to "columns" (or just "c" or "col", etc.), each column contains statistics for one group. Otherwise (default), each row contains statistics for one group.
to_clipboard	Logical. If TRUE, the table is copied to the clipboard (default: FALSE).
method	Function or string; overwrites the method argument in aggr_neat when used within this function. See method in the aggr_neat function for details. Default value: "mean+sd" (to calculate means and standard deviations table).

transpose Logical (default: FALSE) or string. If TRUE or string, ignores all other parameters (except `values_list`), but merges all values from given list of data frames (as returned from the `aggr_neat`) and transposes them into a single row, using, by default, the "aggr_group" column values for new headers (corresponding to the output of `aggr_neat`; see Examples). However, a string given as argument for the transpose parameter can also specify a custom column name.

Details

The `values`, `round_to`, and `new_name` arguments given in the `aggr_neat` function are always applied. However, the `prefix` parameter will be overwritten as NULL. If `new_name` in `aggr_neat` is NULL, the given input variable names will be used instead of "aggr_value". Furthermore, the `group_by` or `method` given in the `aggr_neat` function are only applied when no arguments are given in the `table_neat` function for the identical parameters (`group_by` or `medians`). If either parameter is given in the `table_neat` function, all separately given respective argument(s) in the `aggr_neat` function(s) are ignored.

Value

Returns a data frame with means or medians and SDs per variable and per group.

See Also

[aggr_neat](#) for more related details

Examples

```
data("mtcars") # load base R example dataset

# overall means and SDs table for disp (Displacement) and hp (Gross horsepower)
table_neat(list(aggr_neat(mtcars, disp),
                aggr_neat(mtcars, hp)))

# means and SDs table for mpg (Miles/(US) gallon), wt (Weight), and hp (Gross horsepower)
# grouped by cyl (Number of cylinders)
# each measure rounded to respective optimal number of digits
# wt renamed to weight (for the column title)
table_neat(list(
  aggr_neat(mtcars, mpg, round_to = 1),
  aggr_neat(mtcars, wt, new_name = 'weight', round_to = 2),
  aggr_neat(mtcars, hp, round_to = 0)
),
group_by = 'cyl')

# same as above, but with medians, and with groups per columns
table_neat(
  list(
    aggr_neat(mtcars, mpg, round_to = 1),
    aggr_neat(mtcars, wt, new_name = 'weight', round_to = 2),
    aggr_neat(mtcars, hp, round_to = 0)
  ),
)
```

```

    group_by = 'cyl',
    method = 'median+sd',
    group_per = 'columns'
  )

# an extensive example to show how to collect and aggregate raw data is
# available via the README file at the repository:
# https://github.com/gasparl/neatstats

```

t_neat

Difference of Two Means and Area Under the Curve

Description

Welch's **t-test** results including Cohen's *d* with confidence interval (CI), **Bayes factor** (BF), and **area under the receiver operating characteristic curve** (AUC). For non-parametric version, **Wilcoxon test** results (Mann–Whitney U test, aka "Wilcoxon rank-sum test", for independent samples; Wilcoxon signed-rank test for paired samples; along with corresponding rank-based BFs as per van Doorn et al., 2020).

Usage

```

t_neat(
  var1,
  var2,
  pair = FALSE,
  nonparametric = FALSE,
  greater = NULL,
  norm_tests = "latent",
  norm_plots = FALSE,
  ci = NULL,
  bf_added = FALSE,
  bf_rscale = sqrt(0.5),
  bf_sample = 1000,
  auc_added = FALSE,
  r_added = TRUE,
  for_table = FALSE,
  test_title = "Descriptives:",
  round_descr = 2,
  round_auc = 3,
  auc_greater = "1",
  hush = FALSE,
  plots = FALSE,
  rug_size = 4,
  aspect_ratio = 1,
  y_label = "density estimate",
  x_label = "\nvalues",

```

```

    factor_name = NULL,
    var_names = c("1", "2"),
    reverse = FALSE
  )

```

Arguments

var1	Numeric vector; numbers of the first variable.
var2	Numeric vector; numbers of the second variable.
pair	Logical. If TRUE, all tests (t, BF, AUC) are conducted for paired samples. If FALSE (default) for independent samples.
nonparametric	Logical (FALSE by default). If TRUE, uses nonparametric (rank-based, "Wilcoxon") t-tests (including BFs; see Notes).
greater	NULL or string (or number); optionally specifies one-sided tests (t and BF): either "1" (var1 mean expected to be greater than var2 mean) or "2" (var2 mean expected to be greater than var1 mean). If NULL (default), the test is two-sided.
norm_tests	Normality tests. Any or all of the following character input is accepted (as a single string or a character vector; case-insensitive): "W" (Shapiro-Wilk), "K2" (D'Agostino-Pearson), "A2" (Anderson-Darling), "JB" (Jarque-Bera); see Notes. Two other options are "all" (to choose all four previous tests at the same time) or "latent" (default value; prints all tests only if nonparametric is set to FALSE and any of the four tests gives a p value below .05). Each normality test is performed for the difference values between the two variables in case of paired samples, or for each of the two variables for unpaired samples. Set to "none" to disable (i.e., not to perform any normality tests).
norm_plots	If TRUE and norm_tests is not "none", displays density, histogram, and Q-Q plots (and scatter plots for paired tests) for each of the two variable (and differences for pairwise observations, in case of paired samples).
ci	Numeric; confidence level for returned CIs for Cohen's d and AUC.
bf_added	Logical. If TRUE (default), Bayes factor is calculated and displayed.
bf_rscale	The scale of the prior distribution (0.707 by default).
bf_sample	Number of samples used to estimate Bayes factor (1000 by default). More samples (e.g. 10000) take longer time but give more stable BF.
auc_added	Logical (FALSE by default). If TRUE, AUC is calculated and displayed (including TPR and TNR, i.e., true positive and true negative rates, i.e. sensitivity and specificity, using an optimal cutoff value, i.e. threshold, that provides maximal TPR and TNR).
r_added	Logical. If TRUE (default), Pearson correlation is calculated and displayed in case of paired comparison.
for_table	Logical. If TRUE, omits the confidence level display from the printed text.
test_title	String, "Descriptives:" by default. Simply displayed in printing preceding the descriptive statistics. (Useful e.g. to distinguish several different comparisons inside a function or a for loop.)
round_descr	Number to round to the descriptive statistics (means and SDs).

round_auc	Number to round to the AUC and its CI.
auc_greater	String (or number); specifies which variable is expected to have greater values for 'cases' as opposed to 'controls': "1" (default; var1 expected to be greater for 'cases' than var2 mean) or "2" (var2 expected to be greater for 'cases' than var1). Not to be confused with one-sided tests; see Details .
hush	Logical. If TRUE, prevents printing any details to console.
plots	Logical (or NULL). If TRUE, creates a combined density plot (i.e., Gaussian kernel density estimates) from the two variables. Includes dashed vertical lines to indicate means of each of the two variables. If nonparametric is set to TRUE, medians are calculated for these dashed lines instead of means. When auc_added is TRUE (and the AUC is at least .5), the best threshold value for classification (maximal differentiation accuracy using Youden's index) is added to the plot as solid vertical line. (In case of multiple best thresholds with identical overall accuracy, all are added.) If NULL, same as if TRUE except that histogram is added to the background.
rug_size	Numeric (4 by default): size of the rug ticks below the density plot. Set to 0 (zero) to omit rug plotting.
aspect_ratio	Aspect ratio of the plots: 1 (1/1) by default. (Set to NULL for dynamic aspect ratio.)
y_label	String or NULL; the label for the y axis. (Default: "density estimate".)
x_label	String or NULL; the label for the x axis. (Default: "values".)
factor_name	String or NULL; factor legend title. (Default: NULL.)
var_names	A vector of two strings; the variable names to be displayed in the legend. (Default: c("1", "2").)
reverse	Logical. If TRUE, reverses the order of variable names displayed in the legend.

Details

The Bayes factor (BF) supporting null hypothesis is denoted as BF01, while that supporting alternative hypothesis is denoted as BF10. When the BF is smaller than 1 (i.e., supports null hypothesis), the reciprocal is calculated (hence, BF10 = BF, but BF01 = 1/BF). When the BF is greater than or equal to 10000, scientific (exponential) form is reported for readability. (The original full BF number is available in the returned named vector as bf.)

For simplicity, Cohen's d is reported for nonparametric tests too: you may however want to consider reporting alternative effect sizes in this case.

The original `pROC::auc` function, by default, always returns an AUC greater than (or equal to) .5, assuming that the prediction based on values in the expected direction work correctly at least at chance level. This however may be confusing. Consider an example where we measure the heights of persons in a specific small sample and expect that greater height predicts masculine gender. The results are, say, 169, 175, 167, 164 (cm) for one gender, and 176, 182, 179, 165 for the other. If the expectation is correct (the second, greater values are for males), the AUC is .812. However, if in this particular population females are actually taller than males, the AUC is in fact .188. To keep things clear, the `t_neat` function always makes an assumption about which variable is expected to be greater for correct classification ("1" by default; i.e., var1; to be specified as `auc_greater = "2"` for var2 to be expected as greater). For this example, if the first (smaller) variables are given

as var1 for females, and second (larger), variables are given as var2 for males, we have to specify `auc_greater = "2"` to indicate the expectation of larger values for males. (Or, easier, just add the expected larger values as var1.)

Value

Prints t-test statistics (including Cohen's d with CI, BF, and AUC, as specified via the corresponding parameters) in APA style. Furthermore, when assigned, returns a list, that contains a named vector 'stats' with the following elements: t (t value), p (p value), d (Cohen's d), bf (Bayes factor), auc (AUC), accuracy (overall accuracy using the most optimal classification threshold), and youden (Youden's index: specificity + sensitivity - 1). The latter three are NULL when `auc_added` is FALSE. When `auc_added` is TRUE, there are also two additional elements of the list. One is 'roc_obj', which is a `roc` object, to be used e.g. with the `roc_neat` function. The other is 'best_thresholds', which contains the best threshold value(s) for classification, along with corresponding specificity and sensitivity. Finally, if `plots` is TRUE (or NULL), the plot is displayed as well as returned as a `ggplot` object, named `t_plot`.

Note

The Welch's t-test is calculated via `stats::t.test`.

#Normality tests are all calculated via `Power::statcompute`, selected based on the recommendation of Lakens (2015), quoting Yap and Sim (2011, p. 2153): "If the distribution is symmetric with low kurtosis values (i.e. symmetric short-tailed distribution), then the D'Agostino-Pearson and Shapiro-Wilkes tests have good power. For symmetric distribution with high sample kurtosis (symmetric long-tailed), the researcher can use the JB, Shapiro-Wilkes, or Anderson-Darling test." See [urlhttps://github.com/Lakens/perfect-t-test](https://github.com/Lakens/perfect-t-test) for more details.

Cohen's d and its confidence interval are calculated, using the t value, via `MBESS::ci.smd` for independent samples (as standardized mean difference) and via `MBESS::ci.sm` for paired samples (as standardized mean).

The parametric Bayes factor is calculated via `BayesFactor::ttestBF`. The nonparametric (rank-based) Bayes factor is a contribution by Johnny van Doorn; the original source code is available via <https://osf.io/gny35/>.

The correlation and its CI are calculated via `stats::cor.test`, and is always two-sided, always with 95 percent CI. For more, use `corr_neat`.

The AUC and its CI are calculated via `pROC::auc`, and the accuracy at most optimal threshold via `pROC::coords` (`x = "best"`); both using the object `pROC::roc`.

References

- Delacre, M., Lakens, D., & Leys, C. (2017). Why psychologists should by default use Welch's t-test instead of Student's t-test. *International Review of Social Psychology*, 30(1). doi: [10.5334/irsp.82](https://doi.org/10.5334/irsp.82)
- Kelley, K. (2007). Methods for the behavioral, educational, and social sciences: An R package. *Behavior Research Methods*, 39(4), 979-984. doi: [10.3758/BF03192993](https://doi.org/10.3758/BF03192993)
- Lafaye de Micheaux, P., & Tran, V. A. (2016). PowerR: A Reproducible Research Tool to Ease Monte Carlo Power Simulation Studies for Goodness-of-fit Tests in R. *Journal of Statistical Software*, 69(3). doi: [10.18637/jss.v069.i03](https://doi.org/10.18637/jss.v069.i03)

Lakens, D. (2015). The perfect t-test (version 1.0.0). Retrieved from <https://github.com/Lakens/perfect-t-test>. doi: [10.5281/zenodo.17603](https://doi.org/10.5281/zenodo.17603)

Robin, X., Turck, N., Hainard, A., Tiberti, N., Lisacek, F., Sanchez, J. C., & Muller, M. (2011). pROC: an open-source package for R and S+ to analyze and compare ROC curves. *BMC bioinformatics*, 12(1), 77. doi: [10.1186/147121051277](https://doi.org/10.1186/147121051277)

van Doorn, J., Ly, A., Marsman, M., & Wagenmakers, E.-J. (2020). Bayesian rank-based hypothesis testing for the rank sum test, the signed rank test, and Spearman's rho. *Journal of Applied Statistics*, 1–23. doi: [10.1080/02664763.2019.1709053](https://doi.org/10.1080/02664763.2019.1709053)

Yap, B. W., & Sim, C. H. (2011). Comparisons of various types of normality tests. *Journal of Statistical Computation and Simulation*, 81(12), 2141–2155. doi: [10.1080/00949655.2010.520163](https://doi.org/10.1080/00949655.2010.520163)

See Also

[corr_neat](#), [roc_neat](#)

Examples

```
# assign two variables (numeric vectors)
v1 = c(191, 115, 129, 43, 523,-4, 34, 28, 33,-1, 54)
v2 = c(4,-2, 23, 13, 32, 16, 3, 29, 37,-4, 65)

t_neat(v1, v2) # prints results as independent samples
t_neat(v1, v2, pair = TRUE) # as paired samples (r added by default)
t_neat(v1, v2, pair = TRUE, greater = "1") # one-sided
t_neat(v1, v2, pair = TRUE, auc_added = TRUE ) # AUC included

# print results and assign returned list
results = t_neat(v1, v2, pair = TRUE)

results$stats['bf'] # get precise BF value
```

var_tests

Variance Equality Tests

Description

Displayed sample sizes and SDs and performs Brown-Forsythe and Fligner-Killeen variance equality tests (tests of homogeneity of variances) per group combinations. This is primarily a subfunction of [anova_neat](#), but here it is available separately for other potential purposes.

Usage

```
var_tests(xvar, group_by, dat = NULL, hush = FALSE, sep = ", ")
```

Arguments

xvar	Either a numeric vector (numbers of any given variable), or, if dat is given, a column name specifying the variable in the given data frame.
group_by	Either a vector of factors with which to group the xvar values, or, if dat is given, one or more column names specifying the columns in the given data frame.
dat	Either NULL or a data frame from which the respective column names should be selected for xvar and group.
hush	Logical. If TRUE, prevents printing any details to console.
sep	String (underscore "_" by default) for separating group names.

Value

Prints test results.

Note

Brown-Forsythe test (i.e., Levene's test using medians) is calculated via `car::leveneTest`. Fligner-Killeen test, which may be more robust (i.e., less affected by non-normal distribution), is calculated via `stats::fligner.test`. (See also Conover et al., 1981, p. 360.)

References

- Brown, M. B. & Forsythe, A. B. (1974), Journal of the American Statistical Association, 69, pp. 364-367.
- Conover W. J., Johnson M. E., & Johnson M. M. (1981) A comparative study of tests for homogeneity of variances, with applications to the outer continental shelf bidding data. *Technometrics*, 23, 351–361.
- Fligner, M. A. & Killeen, T. J. (1976). Distribution-free two-sample tests for scale. 'Journal of the American Statistical Association.' 71(353), 210-213.
- Fox, J. & Weisberg, S. (2019) *An R Companion to Applied Regression*, Third Edition, Sage.
- Levene, H. (1960). Robust tests for equality of variances. In I. Olkin, H. Hotelling, et al. (eds.). *Contributions to Probability and Statistics: Essays in Honor of Harold Hotelling*. Stanford University Press. pp. 278–292.

See Also

[anova_neat](#)

Examples

```
data("ToothGrowth") # load base R example dataset

# the statistics of the four functions below should match
var_tests(ToothGrowth$len, ToothGrowth$supp)
var_tests('len', 'supp', ToothGrowth)
car::leveneTest(len ~ supp, data = ToothGrowth)
```

```
stats::fligner.test(len ~ supp, ToothGrowth)

# again the results below should match each other
var_tests(ToothGrowth$len,
          interaction(ToothGrowth$supp, ToothGrowth$dose))
var_tests('len', c('supp', 'dose'), ToothGrowth)
car::leveneTest(len ~ supp * as.factor(dose), data = ToothGrowth)
stats::fligner.test(len ~ interaction(supp, dose), ToothGrowth)
```

Index

- object, [43](#)
- Unconditional exact test, [36](#)

- aggr_neat, [2](#), [20](#), [45](#), [46](#)
- Analysis of variance, [5](#)
- anova_neat, [5](#), [24](#), [31](#), [51](#), [52](#)
- anovaBF, [8](#)
- area under the receiver operating characteristic curve, [47](#)
- areas under the receiver operating characteristic curves, [43](#)
- arranged, [27](#)

- base:formatC, [42](#)
- Bayes factor, [14](#), [47](#)
- BayesFactor::anovaBF, [9](#)
- BayesFactor::contingencyTableBF, [37](#)
- BayesFactor::correlationBF, [16](#)
- BayesFactor::ttestBF, [50](#)
- bayestestR::bayesfactor_inclusion, [9](#)

- car::hccm, [7](#)
- car::leveneTest, [52](#)
- ci_from_p, [13](#)
- contingencyTableBF, [37](#)
- cor.test, [15](#)
- corr_neat, [14](#), [50](#), [51](#)

- dems_neat, [16](#)
- dodge, [30](#)
- draws, [31](#)

- enum, [19](#), [38](#), [39](#)
- Exact::exact.test, [37](#)
- excl_neat, [20](#)
- ez::ezANOVA, [7](#), [8](#)
- ezANOVA, [8](#)

- Gaussian kernel density estimates, [49](#)
- getwd, [41](#)
- ggplot, [31](#), [50](#)

- inclusion Bayes factor based on matched models, [6](#)
- independent multinomial contingency table Bayes factor, [36](#)
- IQR, [27](#)

- list.files, [40](#)

- MBESS::ci.sm, [50](#)
- MBESS::ci.smd, [50](#)
- MBESS::conf.limits.ncf, [8](#)
- mean_ci, [21](#), [30](#), [31](#), [45](#)
- mon_conv, [22](#), [23](#)
- mon_neat, [22](#), [23](#)

- norm_tests, [7](#), [24](#)

- oneway.test, [8](#)

- path_neat, [25](#), [41](#)
- Pearson correlation, [14](#)
- peek_neat, [26](#)
- plot_neat, [7](#), [9](#), [22](#), [28](#), [45](#)
- plots, [28](#)
- plyr:rbind.fill, [38](#), [40](#), [41](#)
- Power::statcompute, [25](#), [50](#)
- pROC::auc, [49](#), [50](#)
- pROC::coords, [50](#)
- pROC::roc, [43](#), [50](#)
- pROC::roc.test, [43](#)
- props_neat, [36](#)

- rank correlation, [14](#)
- rbind_loop, [19](#), [38](#)
- read_dir, [40](#)
- ro, [42](#)
- roc, [50](#)
- roc_neat, [43](#), [50](#), [51](#)

- se, [22](#), [31](#), [44](#)
- setwd, [41](#)

significant fractional digits to round
to, [27](#)

stats::cor.test, [16](#), [50](#)

stats::fligner.test, [52](#)

stats::oneway.test, [7](#), [8](#)

stats::t.test, [50](#)

t_neat, [9](#), [16](#), [24](#), [25](#), [43](#), [44](#), [47](#)

table_neat, [2](#), [3](#), [45](#), [45](#), [46](#)

to round, [15](#), [17](#), [48](#), [49](#)

utils::read.table, [41](#)

var_tests, [7](#), [8](#), [51](#)

Welch, [5](#)

Wilcoxon test, [47](#)