

Package ‘orders’

September 24, 2020

Type Package

Title Sampling from Order Statistics of New Families of Distributions

Version 0.1.4

Author Carlos Alberto Cardozo Delgado

Maintainer Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>

Description Set of tools to generate samples of order statistics and others quantities of interest from new families of distributions.

The main references for this package are: Gentle, J. (2009), Computational Statistics, Springer-Verlag;

Naradajah, S. and Rocha, R. (2016), <DOI:10.18637/jss.v069.i10> and

Stasinopoulos, M. and Rigby, R. (2015), <DOI:10.1111/j.1467-9876.2005.00510.x>.

The families of distributions are: Marshall Olkin G distributions, exponentiated G distributions, beta G distributions, gamma G distributions, Kumaraswamy G distributions, generalized beta G distributions,

beta extended G distributions, gamma G distributions, gamma uniform G distributions, beta exponential G distributions, Weibull G distributions, log gamma G I distributions, log gamma G II distributions,

exponentiated generalized G distributions, exponentiated Kumaraswamy G distributions, geometric exponential Poisson G distributions, truncated-exponential skew-symmetric G distributions, modified beta G distributions,

and exponentiated exponential Poisson G distributions, Poisson-inverse gaussian distribution, Skew normal type 1 distributions, Skew student t distribution, Sinh-Arcsinh distribution, Sichel distribution and Zero inflated Poisson.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports Newdistns, gamlss.dist

NeedsCompilation no

Repository CRAN

Date/Publication 2020-09-24 12:00:06 UTC

R topics documented:

| | |
|------------------|----|
| order_beg | 2 |
| order_betaexp | 3 |
| order_betag | 5 |
| order_eepg | 6 |
| order_eg | 7 |
| order_exp | 8 |
| order_expkumg | 9 |
| order_gammag | 10 |
| order_gammag1 | 11 |
| order_gammag2 | 12 |
| order_gbg | 13 |
| order_kumg | 14 |
| order_loggammag1 | 16 |
| order_loggammag2 | 17 |
| order_mbetag | 18 |
| order_mog | 19 |
| order_pig | 20 |
| order_sichel | 21 |
| order_sinharsinh | 22 |
| order_snormal1 | 23 |
| order_sstudentt | 24 |
| order_tessg | 25 |
| order_weibullg | 26 |
| order_zip | 27 |

| | |
|--------------|-----------|
| Index | 29 |
|--------------|-----------|

| | |
|-----------|--|
| order_beg | <i>Random Sampling of Order Statistics from a Beta Extended G Distribution</i> |
|-----------|--|

Description

order_beg is used to obtain a random sample of order statistics from a Beta Extended G Distribution.

Usage

```
order_beg(size, spec, alpha, a, b, k, n, ...)
```

Arguments

| | |
|-------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| alpha | numeric, represents the scale parameter. Default value is 1. |

| | |
|-----|---|
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the second shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Beta Extended G Distribution and the value of its joint probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Exponential Distribution
order_beg(10, "exp", 1, 1, 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Normal Distribution
order_beg(10, "norm", 1, 1, 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Log-normal Distribution
order_beg(10, "lnorm", 1, 1, 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Beta Extended Chis-square Distribution
order_beg(10, "chisq", 1, 1, 1, k=3, 50, df=3)
```

| | |
|----------------|---|
| order_betaexpG | <i>Random Sampling of Order Statistics from a Beta Exponential G Distribution</i> |
|----------------|---|

Description

order_betaexpG is used to obtain a random sample of order statistics from a Beta Exponential G Distribution.

Usage

```
order_betaexpG(size, spec, lambda, a, b, k, n, ...)
```

Arguments

| | |
|--------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| lambda | numeric, represents the first shape parameter. Default value is 1. |
| a | numeric, represents the second shape parameter. Default value is 1. |
| b | numeric, represents the third shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Beta Exponential G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdists: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Exponential Distribution
order_betaexpG(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Normal Distribution
order_betaexpG(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Log-normal Distribution
order_betaexpG(10,"lnorm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Beta Exponential Chi-square Distribution
order_betaexpG(10,"chisq",1,1,1,k=3,50,df=3)
```

order_betag *Random Sampling of Order Statistics from a Beta G Distribution*

Description

order_betag is used to obtain a random sample of order statistics from a Beta G Distribution.

Usage

```
order_betag(size, spec, a, b, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the first shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Beta G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Beta Exponential Distribution
order_betag(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Beta Normal Distribution
order_betag(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Beta Log-normal Distribution
order_betag(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Beta Chis-square Distribution
order_betag(10,"chisq",1,1,k=3,50,df=3)
```

| | |
|------------|--|
| order_eepg | <i>Random Sampling of Order Statistics from a Exponentiated Exponential Poisson G Distribution</i> |
|------------|--|

Description

order_eepg is used to obtain a random sample of order statistics from a Exponentiated Exponential Poisson G Distribution.

Usage

```
order_eepg(size, spec, lambda, a, k, n, ...)
```

Arguments

| | |
|--------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| lambda | numeric, represents a scale parameter. Default value is 1. |
| a | numeric, represents the shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Exponentiated Exponential Poisson G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Exponential Distribution
order_eepg(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Normal Distribution
```

```

order_eepg(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Log-normal Distribution
order_eepg(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Exponential Poisson Chi-square Distribution
order_eepg(10,"chisq",1,1,k=3,50,df=3)

```

| | |
|----------|--|
| order_eg | <i>Random Sampling of Order Statistics from a Exponentiated Generalized G Distribution</i> |
|----------|--|

Description

order_eg is used to obtain a random sample of order statistics from a Exponentiated Generalized G Distribution.

Usage

```
order_eg(size, spec, a, b, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the second shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Exponentiated Generalized G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```

library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Exponential Distribution
order_eg(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Normal Distribution
order_eg(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Log-normal Distribution
order_eg(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Generalized Chi-square Distribution
order_eg(10,"chisq",1,1,k=3,50,df=3)

```

| | |
|------------|--|
| order_expg | <i>Random Sampling of Order Statistics from a Exponentiated G Distribution</i> |
|------------|--|

Description

order_expg is used to obtain a random sample of order statistics from a Exponentiated G Distribution.

Usage

```
order_expg(size, spec, a, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Exponentiated G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Exponential Distribution
order_exp(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Normal Distribution
order_exp(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Log-normal Distribution
order_exp(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Exponentiated Chi-square Distribution
order_exp(10,"chisq",1,k=3,50,df=3)
```

| | |
|---------------|--|
| order_expkung | <i>Random Sampling of Order Statistics from a Exponentiated Kumaraswamy G Distribution</i> |
|---------------|--|

Description

order_expkung is used to obtain a random sample of order statistics from a Exponentiated Kumaraswamy G Distribution.

Usage

```
order_expkung(size, spec, a, b, c, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp","lnorm","chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the second shape parameter. Default value is 1. |
| c | numeric, represents the third shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Exponentiated Kumaraswamy G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Exponential Distribution
order_expkumg(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Normal Distribution
order_expkumg(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Log-normal Distribution
order_expkumg(10,"lnorm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Exponentiated Kumaraswamy Chi-square Distribution
order_expkumg(10,"chisq",1,1,1,k=3,50,df=3)
```

order_gammag

Random Sampling of Order Statistics from a Gamma Uniform G Distribution

Description

order_gammag is used to obtain a random sample of order statistics from a Gamma Uniform G Distribution.

Usage

```
order_gammag(size, spec, a, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Gamma Uniform G Distribution and the value of its joint probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdists: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Exponential Distribution
order_gammag(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Normal Distribution
order_gammag(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Log-normal Distribution
order_gammag(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Uniform Chi-square Distribution
order_gammag(10,"chisq",1,k=3,50,df=3)
```

order_gammag1

Random Sampling of Order Statistics from a Gamma G I Distribution

Description

order_gammag1 is used to obtain a random sample of order statistics from a Gamma G I Distribution.

Usage

```
order_gammag1(size, spec, a, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Gamma G I Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Gamma Exponential I Distribution
order_gammag1(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Normal I Distribution
order_gammag1(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Log-normal I Distribution
order_gammag1(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from a Gamma Chi-square I Distribution
order_gammag1(10,"chisq",1,k=3,50,df=3)
```

order_gammag2

Random Sampling of Order Statistics from a Gamma G II Distribution

Description

order_gammag2 is used to obtain a random sample of order statistics from a Gamma G II Distribution.

Usage

```
order_gammag2(size, spec, a, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Gamma G II Distribution and the value of its joint probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdists: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Gamma Exponential II Distribution
order_gammag2(10, "exp", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Gamma Normal II Distribution
order_gammag2(10, "norm", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Gamma Log-normal II Distribution
order_gammag2(10, "lnorm", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from a Gamma Chi-square II Distribution
order_gammag2(10, "chisq", 1, k=3, 50, df=3)
```

| | |
|-----------|---|
| order_gbg | <i>Random Sampling of Order Statistics from a Generalized Beta G Distribution</i> |
|-----------|---|

Description

order_gbg is used to obtain a random sample of order statistics from a Generalized Beta G Distribution.

Usage

```
order_gbg(size, spec, a, b, c, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the second shape parameter. Default value is 1. |
| c | numeric, represents the third shape parameter. Default value is 1. |

k numeric, represents the Kth smallest value from a sample.
n numeric, represents the size of the sample to compute the order statistic from.
... represents others parameters of the G distribution.

Value

A list with a random sample of order statistics from a Generalized Beta G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Exponential Distribution
order_gbg(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Normal Distribution
order_gbg(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Log-normal Distribution
order_gbg(10,"lnorm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Generalized Beta Chi-square Distribution
order_gbg(10,"chisq",1,1,1,k=3,50,df=3)
```

| | |
|------------|--|
| order_kumg | <i>Random Sampling of Order Statistics from a Kumaraswamy G Distribution</i> |
|------------|--|

Description

order_expkumg is used to obtain a random sample of order statistics from a Kumaraswamy G Distribution.

Usage

```
order_kumg(size, spec, a, b, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the second shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Kumaraswamy G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Exponential Distribution
order_kumg(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Normal Distribution
order_kumg(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Log-normal Distribution
order_kumg(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Kumaraswamy Chi-square Distribution
order_kumg(10,"chisq",1,1,k=3,50,df=3)
```

| | |
|------------------|--|
| order_loggammag1 | <i>Random Sampling of Order Statistics from a Log Gamma G I Distribution</i> |
|------------------|--|

Description

order_loggammag1 is used to obtain a random sample of order statistics from a Log Gamma G I Distribution.

Usage

```
order_loggammag1(size, spec, a, b, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the second shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Log Gamma G I Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Exponential I Distribution
order_loggammag1(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Normal I Distribution
```



```

order_loggammag1(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Log-normal I Distribution
order_loggammag1(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Chi-square I Distribution
order_loggammag1(10,"chisq",1,1,k=3,50,df=3)

```

| | |
|------------------|---|
| order_loggammag2 | <i>Random Sampling of Order Statistics from a Log Gamma G II Distribution</i> |
|------------------|---|

Description

order_loggammag2 is used to obtain a random sample of order statistics from a Log Gamma G II Distribution.

Usage

```
order_loggammag2(size, spec, a, b, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| a | numeric, represents the first shape parameter. Default value is 1. |
| b | numeric, represents the second shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Log Gamma G II Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
 Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```

library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Exponential II Distribution
order_loggammag2(10,"exp",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Normal II Distribution
order_loggammag2(10,"norm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Log-normal II Distribution
order_loggammag2(10,"lnorm",1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Log Gamma Chi-square II Distribution
order_loggammag2(10,"chisq",1,1,k=3,50,df=3)

```

| | |
|--------------|--|
| order_mbetag | <i>Random Sampling of Order Statistics from a Modified Beta G Distribution</i> |
|--------------|--|

Description

order_mbetag is used to obtain a random sample of order statistics from a Modified Beta G Distribution.

Usage

```
order_mbetag(size, spec, beta, a, b, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| beta | numeric, represents the scale parameter. Default value is 1. |
| a | numeric, represents a shape parameter must be positive. Default value is 1. |
| b | numeric, represents a shape parameter must be positive. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Modified Beta G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Modified Beta Exponential Distribution
order_mbetag(10,"exp",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Modified Beta Normal Distribution
order_mbetag(10,"norm",1,1,1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Modified Beta Log-normal Distribution
order_mbetag(10,"lnorm",1,1,1,k=3,50)
```

| | |
|-----------|---|
| order_mog | <i>Random Sampling of Order Statistics from a Marshall Olkin G Distribution</i> |
|-----------|---|

Description

order_mog is used to obtain a random sample of order statistics from a Marshall Olkin G Distribution.

Usage

```
order_mog(size, spec, beta, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| beta | numeric, represents the scale parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Marshall Olkin G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Marshall Olkin Exponential Distribution
order_mog(10, "exp", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from
# a Marshall Olkin Normal Distribution
order_mog(10, "norm", 1, k=3, 50)
# A sample of size 10 of the 3-th order statistics from
# a Marshall Olkin Log-normal Distribution
order_mog(10, "lnorm", 1, k=3, 50)
```

order_pig

Random Sampling of Order Statistics from a Poisson-inverse Gaussian Distribution

Description

order_pig is used to obtain a random sample of order statistics from a Poisson-inverse Gaussian Distribution.

Usage

```
order_pig(size, k, mu, sigma, n, ...)
```

Arguments

| | |
|-------|---|
| size | numeric, represents the size of the sample. |
| k | numeric, represents the Kth smallest value from a sample. |
| mu | numeric, represents the location parameter values. |
| sigma | numeric, represents scale parameter values. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of a Poisson-inverse Gaussian distribution. |

Value

A list with a random sample of order statistics from a Poisson-inverse Gaussian Distribution and the value of its joint probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Ribgy, R. and Stasinopoulos, M. (2005) Generalized Additive Models for Location Scale and Shape, Journal of the Royal Statistical Society. Applied Statistics, Series C.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Poisson-inverse Gaussian Distribution
order_pig(size=10,k=3,mu=6,sigma=1,n=30)
```

order_sichel

Random Sampling of Order Statistics from a Sichel Distribution

Description

order_sichel is used to obtain a random sample of order statistics from a Sichel Distribution.

Usage

```
order_sichel(size, k, mu, sigma, nu, n, ...)
```

Arguments

| | |
|-------|---|
| size | numeric, represents the size of the sample. |
| k | numeric, represents the Kth smallest value from a sample. |
| mu | numeric, represents the location parameter values. |
| sigma | numeric, represents scale parameter values. |
| nu | numeric, represents skewness parameter values |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of a Skew normal type 1 distribution. |

Value

A list with a random sample of order statistics from a Sichel Distribution and the value of its joint probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Ribgy, R. and Stasinopoulos, M. (2005) Generalized Additive Models for Location Scale and Shape, Journal of the Royal Statistical Society. Applied Statistics, Series C.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Sichel Distribution
order_sichel(size=10,k=3,mu=5,sigma=1,nu=1,n=30)
```

| | |
|-------------------|---|
| order_sinharcsinh | <i>Random Sampling of Order Statistics from a Sinh-Arcsinh Distribution</i> |
|-------------------|---|

Description

order_sinharcsinh is used to obtain a random sample of order statistics from a Sinh-Arcsinh Distribution.

Usage

```
order_sinharcsinh(size, k, mu, sigma, nu, tau, n, ...)
```

Arguments

| | |
|-------|---|
| size | numeric, represents the size of the sample. |
| k | numeric, represents the Kth smallest value from a sample. |
| mu | numeric, represents the location parameter values. |
| sigma | numeric, represents scale parameter values. |
| nu | numeric, represents skewness parameter values |
| tau | numeric, represents kurtosis tau parameter values. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of a Sinh-Arcsinh distribution. |

Value

A list with a random sample of order statistics from a Sinh-Arcsinh Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Ribgy, R. and Stasinopoulos, M. (2005) Generalized Additive Models for Location Scale and Shape, Journal of the Royal Statistical Society. Applied Statistics, Series C.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Sinh-Arcsinh Distribution
order_sinharcsinh(size=10,k=3,mu=0,sigma=1,nu=1,tau=2,n=30)
```

| | |
|----------------|---|
| order_snormal1 | <i>Random Sampling of Order Statistics from a Skew normal type 1 Distribution</i> |
|----------------|---|

Description

order_snormal1 is used to obtain a random sample of order statistics from a Skew normal type 1 Distribution.

Usage

```
order_snormal1(size, k, mu, sigma, nu, tau, n, ...)
```

Arguments

| | |
|-------|---|
| size | numeric, represents the size of the sample. |
| k | numeric, represents the Kth smallest value from a sample. |
| mu | numeric, represents the location parameter values. |
| sigma | numeric, represents scale parameter values. |
| nu | numeric, represents skewness parameter values |
| tau | numeric, represents kurtosis tau parameter values. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of a Skew normal type 1 distribution. |

Value

A list with a random sample of order statistics from a Skew normal type 1 Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Ribgy, R. and Stasinopoulos, M. (2005) Generalized Additive Models for Location Scale and Shape, Journal of the Royal Statistical Society. Applied Statistics, Series C.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Skew normal type 1 Distribution
order_snormal1(size=10,mu=0,sigma=1,nu=0,tau=2,k=3,n=50)
```

| | |
|-----------------|---|
| order_sstudentt | <i>Random Sampling of Order Statistics from a Skew student t Distribution</i> |
|-----------------|---|

Description

order_sstudentt is used to obtain a random sample of order statistics from a Skew student t Distribution.

Usage

```
order_sstudentt(size, k, mu, sigma, nu, tau, n, ...)
```

Arguments

| | |
|-------|---|
| size | numeric, represents the size of the sample. |
| k | numeric, represents the Kth smallest value from a sample. |
| mu | numeric, represents the location parameter values. |
| sigma | numeric, represents scale parameter values. |
| nu | numeric, represents skewness parameter values |
| tau | numeric, represents kurtosis tau parameter values. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of a Skew student t distribution. |

Value

A list with a random sample of order statistics from a Skew student t Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

- Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
- Ribgy, R. and Stasinopoulos, M. (2005) Generalized Additive Models for Location Scale and Shape, Journal of the Royal Statistical Society: Applied Statistics.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Skew student t Distribution
order_sstudentt(size=10,k=3,mu=0,sigma=1,nu=0,tau=2,n=30)
```

| | |
|-------------|---|
| order_tessg | <i>Random Sampling of Order Statistics from a Truncated-Exponential Skew-Symmetric G Distribution</i> |
|-------------|---|

Description

order_tessg is used to obtain a random sample of order statistics from a Truncated-Exponential Skew-Symmetric G Distribution.

Usage

```
order_tessg(size, spec, lambda, k, n, ...)
```

Arguments

| | |
|--------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| lambda | numeric, represents the skewness parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Truncated-Exponential Skew-Symmetric G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

- Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.
- Naradajah, S. and Rocha, R. (2016) Newdistns: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```

library(orders)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Exponential Distribution
order_tessg(10,"exp",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Normal Distribution
order_tessg(10,"norm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Log-normal Distribution
order_tessg(10,"lnorm",1,k=3,50)
# A sample of size 10 of the 3-th order statistics from
# a Truncated-Exponential Skew-Symmetric Chi-square Distribution
order_tessg(10,"chisq",1,k=3,50,df=3)

```

| | |
|----------------|--|
| order_weibullg | <i>Random Sampling of Order Statistics from a Weibull G Distribution</i> |
|----------------|--|

Description

order_weibullg is used to obtain a random sample of order statistics from a Weibull G Distribution.

Usage

```
order_weibullg(size, spec, beta, c, k, n, ...)
```

Arguments

| | |
|------|--|
| size | numeric, represents the size of the sample. |
| spec | character, represents an specific G distribution. Possible values "norm", "exp", "lnorm", "chisq". |
| beta | numeric, represents the scale parameter. Default value is 1. |
| c | numeric, represents the shape parameter. Default value is 1. |
| k | numeric, represents the Kth smallest value from a sample. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of the G distribution. |

Value

A list with a random sample of order statistics from a Weibull G Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Naradajah, S. and Rocha, R. (2016) Newdistsn: An R Package for New Families of Distributions, Journal of Statistical Software.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Weibull Exponential Distribution
order_weibullg(10,"exp",beta=1,c=1,k=3,n=50)
# A sample of size 10 of the 3-th order statistics from a Weibull Normal Distribution
order_weibullg(10,"norm",beta=1,c=1,k=3,n=50)
# A sample of size 10 of the 3-th order statistics from a Weibull Log-normal Distribution
order_weibullg(10,"lnorm",beta=1,c=1,k=3,n=50)
# A sample of size 10 of the 3-th order statistics from a Weibull Chi-square Distribution
order_weibullg(10,"chisq",beta=1,c=1,k=3,n=50,df=3)
```

| | |
|-----------|--|
| order_zip | <i>Random Sampling of Order Statistics from a Zero Inflated Poisson Distribution</i> |
|-----------|--|

Description

order_zip is used to obtain a random sample of order statistics from a Zero Inflated Poisson Distribution.

Usage

```
order_zip(size, k, mu, sigma, n, ...)
```

Arguments

| | |
|-------|---|
| size | numeric, represents the size of the sample. |
| k | numeric, represents the Kth smallest value from a sample. |
| mu | numeric, represents the location parameter values. |
| sigma | numeric, represents scale parameter values. |
| n | numeric, represents the size of the sample to compute the order statistic from. |
| ... | represents others parameters of a Zero Inflated Poisson distribution. |

Value

A list with a random sample of order statistics from a Zero Inflated Poisson Distribution and the value of its join probability density function evaluated in the random sample.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Gentle, J, Computational Statistics, First Edition. Springer - Verlag, 2009.

Ribgy, R. and Stasinopoulos, M. (2005) Generalized Additive Models for Location Scale and Shape, Journal of the Royal Statistical Society. Applied Statistics, Series C.

Examples

```
library(orders)
# A sample of size 10 of the 3-th order statistics from a Zero Inflated Poisson Distribution
order_zip(size=10,k=3,mu=5,sigma=0.1,n=30)
```

Index

order_beg, 2
order_betaexp, 3
order_betag, 5
order_eepg, 6
order_eg, 7
order_exp, 8
order_expkung, 9
order_gammag, 10
order_gammag1, 11
order_gammag2, 12
order_gbg, 13
order_kung, 14
order_loggammag1, 16
order_loggammag2, 17
order_mbetag, 18
order_mog, 19
order_pig, 20
order_sichel, 21
order_sinharcsinh, 22
order_snormal1, 23
order_sstudentt, 24
order_tessg, 25
order_weibullg, 26
order_zip, 27