

Package ‘princurve’

August 25, 2020

Version 2.1.5

Title Fit a Principal Curve in Arbitrary Dimension

Description Fitting a principal curve to a data matrix in arbitrary dimensions.
Hastie and Stuetzle (1989) <doi:10.2307/2289936>.

License GPL-2

Encoding UTF-8

Depends R (>= 3.0)

Imports stats, graphics, grDevices, Rcpp

Suggests devtools, testthat

LinkingTo Rcpp

NeedsCompilation yes

RoxygenNote 7.1.1

URL <https://github.com/rcannood/princurve>

BugReports <https://github.com/rcannood/princurve/issues>

Collate 'RcppExports.R' 'bias_correct_curve.R' 'deprecated.R'
'package.R' 'periodic_lowess.R' 'smoother_functions.R'
'principal_curve.R' 'start_circle.R'

Author Trevor Hastie [aut],
Andreas Weingessel [aut],
Kurt Hornik [aut] (<<https://orcid.org/0000-0003-4198-9911>>),
Henrik Bengtsson [ctb] (HenrikBengtsson),
Robrecht Cannoodt [aut, cre] (<<https://orcid.org/0000-0003-3641-729X>>,
rcannood)

Maintainer Robrecht Cannoodt <rcannood@gmail.com>

Repository CRAN

Date/Publication 2020-08-25 06:40:08 UTC

R topics documented:

princurve-package	2
principal.curve	2
principal_curve	3
project_to_curve	5
smoother_functions	6
start_circle	6

Index	8
--------------	----------

princurve-package	<i>Fit a Principal Curve in Arbitrary Dimension</i>
-------------------	---

Description

Fit a principal curve which describes a smooth curve that passes through the middle of the data x in an orthogonal sense. This curve is a non-parametric generalization of a linear principal component. If a closed curve is fit (using `smoother = "periodic_lowess"`) then the starting curve defaults to a circle, and each fit is followed by a bias correction suggested by Jeff Banfield.

References

Hastie, T. and Stuetzle, W., [Principal Curves](#), JASA, Vol. 84, No. 406 (Jun., 1989), pp. 502-516, DOI: [10.2307/2289936](#) (PDF).

See also Banfield and Raftery (JASA, 1992).

See Also

[principal_curve](#), [project_to_curve](#)

principal.curve	<i>Deprecated functions</i>
-----------------	-----------------------------

Description

This function is deprecated, please use [principal_curve](#) and [project_to_curve](#) instead.

Usage

```
principal_curve(...)

## S3 method for class 'principal_curve'
lines(...)

## S3 method for class 'principal_curve'
plot(...)

## S3 method for class 'principal_curve'
points(...)

get.lam(...)
```

Arguments

```
...          Catch-all for old parameters.
```

```
principal_curve          Fit a Principal Curve
```

Description

Fit a principal curve which describes a smooth curve that passes through the middle of the data x in an orthogonal sense. This curve is a non-parametric generalization of a linear principal component. If a closed curve is fit (using `smoother = "periodic_lowess"`) then the starting curve defaults to a circle, and each fit is followed by a bias correction suggested by Jeff Banfield.

Usage

```
principal_curve(
  x,
  start = NULL,
  thresh = 0.001,
  maxit = 10,
  stretch = 2,
  smoother = c("smooth_spline", "lowess", "periodic_lowess"),
  approx_points = FALSE,
  trace = FALSE,
  plot_iterations = FALSE,
  ...
)

## S3 method for class 'principal_curve'
lines(x, ...)

## S3 method for class 'principal_curve'
```

```

plot(x, ...)

## S3 method for class 'principal_curve'
points(x, ...)

whiskers(x, s, ...)

```

Arguments

<code>x</code>	a matrix of points in arbitrary dimension.
<code>start</code>	either a previously fit principal curve, or else a matrix of points that in row order define a starting curve. If missing or NULL, then the first principal component is used. If the smoother is "periodic_lowess", then a circle is used as the start.
<code>thresh</code>	convergence threshold on shortest distances to the curve.
<code>maxit</code>	maximum number of iterations.
<code>stretch</code>	A stretch factor for the endpoints of the curve, allowing the curve to grow to avoid bunching at the end. Must be a numeric value between 0 and 2.
<code>smoother</code>	choice of smoother. The default is "smooth_spline", and other choices are "lowess" and "periodic_lowess". The latter allows one to fit closed curves. Beware, you may want to use <code>iter = 0</code> with <code>lowess()</code> .
<code>approx_points</code>	Approximate curve after smoothing to reduce computational time. If FALSE, no approximation of the curve occurs. Otherwise, <code>approx_points</code> must be equal to the number of points the curve gets approximated to; preferably about 100.
<code>trace</code>	If TRUE, the iteration information is printed
<code>plot_iterations</code>	If TRUE the iterations are plotted.
<code>...</code>	additional arguments to the smoothers
<code>s</code>	a parametrized curve, represented by a polygon.

Value

An object of class "principal_curve" is returned. For this object the following generic methods are currently available: `plot`, `points`, `lines`.

It has components:

<code>s</code>	a matrix corresponding to <code>x</code> , giving their projections onto the curve.
<code>ord</code>	an index, such that <code>s[order,]</code> is smooth.
<code>lambda</code>	for each point, its arc-length from the beginning of the curve. The curve is parametrized approximately by arc-length, and hence is unit-speed.
<code>dist</code>	the sum-of-squared distances from the points to their projections.
<code>converged</code>	A logical indicating whether the algorithm converged or not.
<code>num_iterations</code>	Number of iterations completed before returning.
<code>call</code>	the call that created this object; allows it to be updated().

References

Hastie, T. and Stuetzle, W., **Principal Curves**, JASA, Vol. 84, No. 406 (Jun., 1989), pp. 502-516, DOI: [10.2307/2289936](https://doi.org/10.2307/2289936) (PDF).

See Also

[project_to_curve](#)

Examples

```
x <- runif(100,-1,1)
x <- cbind(x, x ^ 2 + rnorm(100, sd = 0.1))
fit <- principal_curve(x)
plot(fit)
lines(fit)
points(fit)
whiskers(x, fit$s)
```

project_to_curve	<i>Project a set of points to the closest point on a curve</i>
------------------	--

Description

Finds the projection index for a matrix of points x , when projected onto a curve s . The curve need not be of the same length as the number of points.

Usage

```
project_to_curve(x, s, stretch = 2)
```

Arguments

x	a matrix of data points.
s	a parametrized curve, represented by a polygon.
stretch	A stretch factor for the endpoints of the curve, allowing the curve to grow to avoid bunching at the end. Must be a numeric value between 0 and 2.

Value

A structure is returned which represents a fitted curve. It has components

s	The fitted points on the curve corresponding to each point x
ord	the order of the fitted points
lambda	The projection index for each point
dist	The total squared distance from the curve
dist_ind	The squared distances from the curve to each of the respective points

See Also[principal_curve](#)

smoother_functions	<i>Smoother functions</i>
--------------------	---------------------------

Description

Each of these functions have an interface `function(lambda, xj, ...)`, and return smoothed values for `xj`. The output is expected to be ordered along an ordered `lambda`. This means that the following is true:

```
x <- runif(100)
y <- runif(100)
ord <- sample.int(100)
sfun <- smoother_functions[[1]]
all(sfun(x, y) == sfun(x[ord], y[ord]))
```

Usage

```
smoother_functions
```

Format

An object of class `list` of length 3.

start_circle	<i>Generate circle as initial curve</i>
--------------	---

Description

The starting circle is defined in the first two dimensions, and has zero values in all other dimensions.

Usage

```
start_circle(x)
```

Arguments

`x` The data for which to generate the initial circle

Examples

```
## Not run:  
x <- cbind(  
  rnorm(100, 1, .2),  
  rnorm(100, -5, .2),  
  runif(100, 1.9, 2.1),  
  runif(100, 2.9, 3.1)  
)  
circ <- start_circle(x)  
plot(x)  
lines(circ)  
  
## End(Not run)
```

Index

- * **datasets**
 - smoother_functions, 6
- * **nonparametric**
 - principal_curve, 3
 - princurve-package, 2
 - project_to_curve, 5
- * **regression**
 - principal_curve, 3
 - princurve-package, 2
 - project_to_curve, 5
- * **smooth**
 - principal_curve, 3
 - princurve-package, 2
 - project_to_curve, 5

get.lam (principal_curve), 2

lines.principal_curve
(principal_curve), 2

lines.principal_curve
(principal_curve), 3

plot.principal_curve (principal_curve),
2

plot.principal_curve (principal_curve),
3

points.principal_curve
(principal_curve), 2

points.principal_curve
(principal_curve), 3

principal_curve, 2

principal_curve, 2, 3, 6

princurve (princurve-package), 2

princurve-package, 2

project_to_curve, 2, 5, 5

smoother_functions, 6

start_circle, 6

whiskers (principal_curve), 3