

# Package ‘vein’

October 14, 2020

**Type** Package

**Title** Vehicular Emissions Inventories

**Version** 0.9.0.1

**Date** 2020-09-23

**Description** Elaboration of vehicular emissions inventories, consisting in four stages, pre-processing activity data, preparing emissions factors, estimating the emissions and post-processing of emissions in maps and databases. More details in Ibarra-Espinosa et al (2018) <doi:10.5194/gmd-11-2209-2018>.

Before using VEIN you need to know the vehicular composition of your study area, in other words, the combination of of type of vehicles, size and fuel of the fleet. Then, it is recommended to start with the project to download a template to create a structure of directories and scripts.

**License** MIT + file LICENSE

**URL** <https://gitlab.com/ibarraespinosa/vein>

**BugReports** <https://gitlab.com/ibarraespinosa/vein/-/issues>

**LazyData** no

**Depends** R (>= 3.5.0)

**Imports** sf, data.table, units, graphics, stats

**Suggests** knitr, rmarkdown, testthat, covr, lwgeom, cptcity

**RoxygenNote** 7.1.1

**Encoding** UTF-8

**NeedsCompilation** yes

**Config/testthat/parallel** true

**VignetteBuilder** knitr

**Author** Sergio Ibarra-Espinosa [aut, cre, wdc]  
(<<https://orcid.org/0000-0002-3162-1905>>)

**Maintainer** Sergio Ibarra-Espinosa <[sergio.ibarra@usp.br](mailto:sergio.ibarra@usp.br)>

**Repository** CRAN

**Date/Publication** 2020-10-13 23:50:02 UTC

**R topics documented:**

add_lkm . . . . .	3
add_polid . . . . .	4
adt . . . . .	5
age . . . . .	6
age_hdv . . . . .	8
age_ldv . . . . .	10
age_moto . . . . .	11
aw . . . . .	13
celsius . . . . .	14
cold_mileage . . . . .	15
colplot . . . . .	16
ef_cetesb . . . . .	17
ef_china . . . . .	21
ef_evap . . . . .	24
ef_fun . . . . .	27
ef_hdv_scaled . . . . .	28
ef_hdv_speed . . . . .	29
ef_im . . . . .	32
ef_ive . . . . .	33
ef_ldv_cold . . . . .	35
ef_ldv_cold_list . . . . .	36
ef_ldv_scaled . . . . .	38
ef_ldv_speed . . . . .	39
ef_local . . . . .	44
ef_nitro . . . . .	45
ef_wear . . . . .	46
ef_whe . . . . .	47
emis . . . . .	48
EmissionFactors . . . . .	52
EmissionFactorsList . . . . .	53
Emissions . . . . .	54
EmissionsArray . . . . .	55
emis_chem . . . . .	56
emis_cold . . . . .	58
emis_cold_td . . . . .	60
emis_det . . . . .	62
emis_dist . . . . .	64
emis_evap . . . . .	65
emis_evap2 . . . . .	67
emis_grid . . . . .	69
emis_hot_td . . . . .	71
emis_merge . . . . .	75
emis_order . . . . .	76
emis_paved . . . . .	78
emis_post . . . . .	80
emis_source . . . . .	82

emis_to_streets . . . . .	83
emis_wear . . . . .	84
fe2015 . . . . .	85
fkm . . . . .	86
fuel_corr . . . . .	87
get_project . . . . .	88
GriddedEmissionsArray . . . . .	89
grid_emis . . . . .	90
invcop . . . . .	92
inventory . . . . .	93
long_to_wide . . . . .	95
make_grid . . . . .	96
my_age . . . . .	97
net . . . . .	98
netspeed . . . . .	99
pc_cold . . . . .	100
pc_profile . . . . .	101
pollutants . . . . .	101
profiles . . . . .	102
remove_units . . . . .	103
speciate . . . . .	104
Speed . . . . .	106
split_emis . . . . .	107
temp_fact . . . . .	108
to_latex . . . . .	108
Vehicles . . . . .	109
vein_notes . . . . .	110
vkm . . . . .	112
wide_to_long . . . . .	113

**Index****114**


---

add_lkm	<i>Construction function to add unit km</i>
---------	---

---

**Description**

add\_lkm just add unit 'km' to different R objects

**Usage**

```
add_lkm(x)
```

**Arguments**

x	Object with class "data.frame", "matrix", "numeric" or "integer"
---	--

**Value**

Objects of class "data.frame" or "units"

**Examples**

```
## Not run:
a <- add_lkm(rnorm(100)*10)
plot(a)
b <- add_lkm(matrix(rnorm(100)*10, ncol = 10))
print(head(b))

## End(Not run)
```

---

add\_polid

*Add polygon id to lines road network*

---

**Description**

Sometimes you need to add polygon id into your streets road network. [add\\_polid](#) add add\_polid id into your road network cropping your network by.

For instance, you have open street maps road network the you have the polygon of your regions. This function adds the id of your polygon as a new column in the streets network.

**Usage**

```
add_polid(polyg, street, by)
```

**Arguments**

polyg	sf object POLYGON or sp
street	streets road network class sf or sp
by	Character indicating the column with the id in polyg

**See Also**

[emis\\_to\\_streets](#)

**Examples**

```
## Not run:
data(net)
nets <- sf::st_as_sf(net)
bb <- sf::st_as_sf(sf::st_as_sfc(sf::st_bbox(nets)))
bb$id <- "a"
a <- add_polid(polyg = bb, street = nets, by = "id")

## End(Not run)
```

---

adt *Average daily traffic (ADT) from hourly traffic data.*

---

### Description

adt calculates ADT based on hourly traffic data.

### Usage

```
adt(
  pc,
  lcv,
  hgv,
  bus,
  mc,
  p_pc,
  p_lcv,
  p_hgv,
  p_bus,
  p_mc,
  feq_pc = 1,
  feq_lcv = 1.5,
  feq_hgv = 2,
  feq_bus = 2,
  feq_mc = 0.5
)
```

### Arguments

pc	numeric vector for passenger cars
lcv	numeric vector for light commercial vehicles
hgv	numeric vector for heavy good vehicles or trucks
bus	numeric vector for bus
mc	numeric vector for motorcycles
p_pc	data-frame profile for passenger cars, 24 hours only.
p_lcv	data-frame profile for light commercial vehicles, 24 hours only.
p_hgv	data-frame profile for heavy good vehicles or trucks, 24 hours only.
p_bus	data-frame profile for bus, 24 hours only.
p_mc	data-frame profile for motorcycles, 24 hours only.
feq_pc	Numeric, factor equivalence
feq_lcv	Numeric, factor equivalence
feq_hgv	Numeric, factor equivalence
feq_bus	Numeric, factor equivalence
feq_mc	Numeric, factor equivalence

**Value**

numeric vector of total volume of traffic per link as ADT

**Examples**

```
## Not run:
data(net)
data(pc_profile)
p1 <- pc_profile[, 1]
adt1 <- adt(pc = net$ldv*0.75,
           lcv = net$ldv*0.1,
           hgv = net$hdv,
           bus = net$hdv*0.1,
           mc = net$ldv*0.15,
           p_pc = p1,
           p_lcv = p1,
           p_hgv = p1,
           p_bus = p1,
           p_mc = p1)

head(adt1)

## End(Not run)
```

---

age

*Applies a survival rate to numeric new vehicles*

---

**Description**

`age` returns survived vehicles

**Usage**

```
age(x, type = "weibull", a = 14.46, b = 4.79, agemax, verbose = FALSE)
```

**Arguments**

x	Numeric; numerical vector of sales or registrations for each year
type	Character; any of "gompertz", "double_logistic", "weibull" and "weibull2"
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemax	Integer; age of oldest vehicles for that category
verbose	Logical; message with average age and total number of vehicles regions or streets.

**Value**

dataframe of age distribution of vehicles

## Note

The functions `age*` produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use, use: `my_age` 2. If you know the sales of vehicles, or the registry of new vehicles, use `age` to apply a survival function. 3. If you know the theoretical shape of the circulating fleet and you can use `age_ldv`, `age_hdv` or `age_moto`. For instance, you don't know the sales or registry of vehicles, but somehow you know the shape of this curve. 4. You can use/merge/transform/dapt any of these functions.

**gompertz:**  $1 - \exp(-\exp(a + b \cdot \text{time}))$ , defaults PC:  $b = -0.137$ ,  $a = 1.798$ , LCV:  $b = -0.141$ ,  $a = 1.618$  MCT (2006). de Gases de Efeito Estufa-Emissões de Gases de Efeito Estufa por Fontes Moveis, no Setor Energético. Ministerio da Ciencia e Tecnologia. This curve is also used by Guo and Wang (2012, 2015) in the form:  $V \cdot \exp(\alpha \cdot \exp(\beta \cdot E))$  where V is the saturation car ownership level and E GDP per capita Huo, H., & Wang, M. (2012). Modeling future vehicle sales and stock in China. Energy Policy, 43, 17–29. doi:10.1016/j.enpol.2011.09.063 Huo, Hong, et al. "Vehicular air pollutant emissions in China: evaluation of past control policies and future perspectives." Mitigation and Adaptation Strategies for Global Change 20.5 (2015): 719-733.

**double\_logistic:**  $1/(1 + \exp(a \cdot (\text{time} + b))) + 1/(1 + \exp(a \cdot (\text{time} - b)))$ , defaults PC:  $b = 21$ ,  $a = 0.19$ , LCV:  $b = 15.3$ ,  $a = 0.17$ , HGV:  $b = 17$ ,  $a = 0.1$ , BUS:  $b = 19.1$ ,  $a = 0.16$  MCT (2006). de Gases de Efeito Estufa-Emissões de Gases de Efeito Estufa por Fontes Moveis, no Setor Energético. Ministerio da Ciencia e Tecnologia.

**weibull:**  $\exp(-(\text{time}/a)^b)$ , defaults PC:  $b = 4.79$ ,  $a = 14.46$ , Taxi:  $b = +\text{inf}$ ,  $a = 5$ , Government and business:  $b = 5.33$ ,  $a = 13.11$  Non-operating vehicles:  $b = 5.08$ ,  $a = 11.53$  Bus:  $b = +\text{inf}$ ,  $a = 9$ , non-transit bus:  $b = +\text{inf}$ ,  $a = 5.5$  Heavy HGV:  $b = 5.58$ ,  $a = 12.8$ , Medium HGV:  $b = 5.58$ ,  $a = 10.09$ , Light HGV:  $b = 5.58$ ,  $a = 8.02$  Hao, H., Wang, H., Ouyang, M., & Cheng, F. (2011). Vehicle survival patterns in China. Science China Technological Sciences, 54(3), 625-629.

**weibull2:**  $\exp(-((\text{time} + b)/a)^b)$ , defaults  $b = 11$ ,  $a = 26$  Zachariadis, T., Samaras, Z., Zierock, K. H. (1995). Dynamic modeling of vehicle populations: an engineering approach for emissions calculations. Technological Forecasting and Social Change, 50(2), 135-149. Cited by Huo and Wang (2012)

## See Also

Other age: `age_hdv()`, `age_ldv()`, `age_moto()`

## Examples

```
## Not run:
vehLIA <- rep(1, 25)
PV_Minia <- age(x = vehLIA)
PV_Minib <- age(x = vehLIA, type = "weibull2", b = 11, a = 26)
PV_Minic <- age(x = vehLIA, type = "double_logistic", b = 21, a = 0.19)
PV_Minid <- age(x = vehLIA, type = "gompertz", b = -0.137, a = 1.798)
plot(PV_Minia, type = "b", pch = 16)
lines(PV_Minib, type = "b", pch = 16, col = "red")
lines(PV_Minic, type = "b", pch = 16, col = "blue")
lines(PV_Minid, type = "b", pch = 16, col = "green")
legend(x = 20, y = 0.85,
       legend = c("weibull", "weibull2", "double_logistic", "gompertz"),
```

```

    col = c("black", "red", "blue", "green"),
    lty=c(1,1),
    lwd=c(2.5, 2.5, 2.5, 2.5))
  #lets put some numbers
vehLIA <- c(65400, 79100, 80700, 85300, 86700, 82000, 74500, 67700, 60600, 62500,
84700, 62600, 47900, 63900, 41800, 37492, 34243, 30995, 27747, 24499, 21250,
18002, 14754, 11506, 8257)
PV_Minia <- age(x = vehLIA)
PV_Minib <- age(x = vehLIA, type = "weibull2", b = 11, a = 26)
PV_Minic <- age(x = vehLIA, type = "double_logistic", b = 21, a = 0.19)
PV_Minid <- age(x = vehLIA, type = "gompertz", b = -0.137, a = 1.798)
plot(PV_Minia, type = "b", pch = 16)
lines(PV_Minib, type = "b", pch = 16, col = "red")
lines(PV_Minic, type = "b", pch = 16, col = "blue")
lines(PV_Minid, type = "b", pch = 16, col = "green")
legend(x = 20, y = 80000,
      legend = c("weibull", "weibull2", "double_logistic", "gompertz"),
      col = c("black", "red", "blue", "green"),
      lty=c(1,1),
      lwd=c(2.5, 2.5, 2.5, 2.5))

## End(Not run)

```

---

age\_hdv

*Returns amount of vehicles at each age*

---

## Description

[age\\_hdv](#) returns amount of vehicles at each age

## Usage

```

age_hdv(
  x,
  name = "age",
  a = 0.2,
  b = 17,
  agemin = 1,
  agemax = 50,
  k = 1,
  bystreet = F,
  net,
  verbose = FALSE,
  namerows,
  time
)

```



**Arguments**

x	Numeric; numerical vector of vehicles with length equal to lines features of road network
name	Character; of vehicle assigned to columns of dataframe
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemin	Integer; age of newest vehicles for that category
agemax	Integer; age of oldest vehicles for that category
k	Numeric; multiplication factor. If its length is > 1, it must match the length of x
bystreet	Logical; when TRUE it is expecting that 'a' and 'b' are numeric vectors with length equal to x
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total number of vehicles
namerows	Any vector to be change row.names. For instance, name of regions or streets.
time	Character to be the time units as denominator, eg "1/h"

**Value**

dataframe of age distribution of vehicles at each street

**Note**

The functions `age*` produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use, use: `my_age` 2. If you know the sales of vehicles, or the registry of new vehicles, use `age` to apply a survival function. 3. If you know the theoretical shape of the circulating fleet and you can use `age_ldv`, `age_hdv` or `age_moto`. For instance, you don't know the sales or registry of vehicles, but somehow you know the shape of this curve. 4. You can use/merge/transform/adapt any of these functions.

**See Also**

Other age: `age_ldv()`, `age_moto()`, `age()`

**Examples**

```
## Not run:
data(net)
LT_B5 <- age_hdv(x = net$hdv, name = "LT_B5")
plot(LT_B5)
LT_B5 <- age_hdv(x = net$hdv, name = "LT_B5", net = net)
plot(LT_B5)

## End(Not run)
```

---

age\_ldv *Returns amount of vehicles at each age*

---

### Description

`age_ldv` returns amount of vehicles at each age

### Usage

```
age_ldv(
  x,
  name = "age",
  a = 1.698,
  b = -0.2,
  agemin = 1,
  agemax = 50,
  k = 1,
  bystreet = F,
  net,
  verbose = FALSE,
  namerows,
  time
)
```

### Arguments

x	Numeric; numerical vector of vehicles with length equal to lines features of road network
name	Character; of vehicle assigned to columns of dataframe
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemin	Integer; age of newest vehicles for that category
agemax	Integer; age of oldest vehicles for that category
k	Numeric; multiplication factor. If its length is > 1, it must match the length of x
bystreet	Logical; when TRUE it is expecting that 'a' and 'b' are numeric vectors with length equal to x
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total number of vehicles
namerows	Any vector to be change row.names. For instance, name of regions or streets.
time	Character to be the time units as denominator, eg "1/h"

### Value

dataframe of age distribution of vehicles

**Note**

The functions `age*` produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use, use: `my_age`
2. If you know the sales of vehicles, or the registry of new vehicles, use `age` to apply a survival function.
3. If you know the theoretical shape of the circulating fleet and you can use `age_ldv`, `age_hdv` or `age_moto`. For instance, you don't know the sales or registry of vehicles, but somehow you know the shape of this curve.
4. You can use/merge/transform/adapt any of these functions.

It consists in a Gompertz equation with default parameters from 1 national emissions inventory for green housegases in Brazil, MCT 2006

**See Also**

Other age: `age_hdv()`, `age_moto()`, `age()`

**Examples**

```
## Not run:
data(net)
PC_E25_1400 <- age_ldv(x = net$ldv, name = "PC_E25_1400")
plot(PC_E25_1400)
PC_E25_1400 <- age_ldv(x = net$ldv, name = "PC_E25_1400", net = net)
plot(PC_E25_1400)

## End(Not run)
```

---

age\_moto

*Returns amount of vehicles at each age*

---

**Description**

`age_moto` returns amount of vehicles at each age

**Usage**

```
age_moto(
  x,
  name = "age",
  a = 0.2,
  b = 17,
  agemin = 1,
  agemax = 50,
  k = 1,
  bystreet = FALSE,
  net,
  verbose = FALSE,
  namerows,
```

```
    time
  )
```

### Arguments

x	Numeric; numerical vector of vehicles with length equal to lines features of road network
name	Character; of vehicle assigned to columns of dataframe
a	Numeric; parameter of survival equation
b	Numeric; parameter of survival equation
agemin	Integer; age of newest vehicles for that category
agemax	Integer; age of oldest vehicles for that category
k	Numeric; multiplication factor. If its length is > 1, it must match the length of x
bystreet	Logical; when TRUE it is expecting that 'a' and 'b' are numeric vectors with length equal to x
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total numer of vehicles
namerows	Any vector to be change row.names. For instance, name of regions or streets.
time	Character to be the time units as denominator, eg "1/h"

### Value

dataframe of age distrubution of vehicles

### Note

The functions age\* produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use , use: [my\\_age](#)
2. If you know the sales of vehicles, or the registry of new vehicles, use [age](#) to apply a survival function.
3. If you know the theoretical shape of the circulating fleet and you can use [age\\_ldv](#), [age\\_hdv](#) or [age\\_moto](#). For instance, you dont know the sales or registry of vehicles, but somehow you know the shape of this curve.
4. You can use/merge/transform/adapt any of these functions.

### See Also

Other age: [age\\_hdv\(\)](#), [age\\_ldv\(\)](#), [age\(\)](#)

### Examples

```
## Not run:
data(net)
MOTO_E25_500 <- age_moto(x = net$ldv, name = "M_E25_500", k = 0.4)
plot(MOTO_E25_500)
MOTO_E25_500 <- age_moto(x = net$ldv, name = "M_E25_500", k = 0.4, net = net)
plot(MOTO_E25_500)

## End(Not run)
```

aw

*Average Weight for hourly traffic data.***Description**

aw average weight form traffic.

**Usage**

```
aw(
  pc,
  lcv,
  hgv,
  bus,
  mc,
  p_pc,
  p_lcv,
  p_hgv,
  p_bus,
  p_mc,
  w_pc = 1,
  w_lcv = 3.5,
  w_hgv = 20,
  w_bus = 20,
  w_mc = 0.5,
  net
)
```

**Arguments**

pc	numeric vector for passenger cars
lcv	numeric vector for light commercial vehicles
hgv	numeric vector for heavy good vehicles or trucks
bus	numeric vector for bus
mc	numeric vector for motorcycles
p_pc	data-frame profile for passenger cars, 24 hours only.
p_lcv	data-frame profile for light commercial vehicles, 24 hours only.
p_hgv	data-frame profile for heavy good vehicles or trucks, 24 hours only.
p_bus	data-frame profile for bus, 24 hours only.
p_mc	data-frame profile for motorcycles, 24 hours only.
w_pc	Numeric, factor equivalence
w_lcv	Numeric, factor equivalence
w_hgv	Numeric, factor equivalence

w_bus	Numeric, factor equivalence
w_mc	Numeric, factor equivalence
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"

**Value**

data.frame with with average weight

**Examples**

```
## Not run:
data(net)
data(pc_profile)
p1 <- pc_profile[, 1]
aw1 <- aw(pc = net$ldv*0.75,
          lcv = net$ldv*0.1,
          hgv = net$hdv,
          bus = net$hdv*0.1,
          mc = net$ldv*0.15,
          p_pc = p1,
          p_lcv = p1,
          p_hgv = p1,
          p_bus = p1,
          p_mc = p1)

head(aw1)

## End(Not run)
```

---

celsius

*Construction function for Celsius temperature*


---

**Description**

celsius just add unit celsius to different R objects

**Usage**

```
celsius(x)
```

**Arguments**

x                    Object with class "data.frame", "matrix", "numeric" or "integer"

**Value**

Objects of class "data.frame" or "units"

**Examples**

```
## Not run:
a <- celsius(rnorm(100)*10)
plot(a)
b <- celsius(matrix(rnorm(100)*10, ncol = 10))
print(head(b))

## End(Not run)
```

---

cold_mileage	<i>Fraction of mileage driven with a cold engine or catalizer below normal temperature</i>
--------------	--

---

**Description**

This function depends length of trip and on ambient temperature. From the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

**Usage**

```
cold_mileage(ltrip, ta)
```

**Arguments**

ltrip	Numeric; Length of trip. It must be in 'units' km.
ta	Numeric or data.frame; average monthly temperature Celsius. If it is a data.frame, it is convenient that each column is each month.

**Note**

This function is set so that values vaires between 0 and 1.

**Examples**

```
## Not run:
lkm <- units::set_units(1:10, km)
ta <- celsius(matrix(0:9, ncol = 12, nrow = 10))
a <- cold_mileage(lkm, rbind(ta, ta))
(a)
filled.contour(as.matrix(a), col = cptcity::lucky(n = 16))

## End(Not run)
```

colplot

*Function to plot columns of data.frames***Description**

`colplot` plots columns of data.frame

**Usage**

```
colplot(
  df,
  cols = names(df),
  xlab = "",
  ylab = "",
  main = NULL,
  theme = "black",
  col = cptcity::cpt(pal = cptcity::find_cpt("pastel")[4], n = length(names(df))),
  type = "b",
  lwd = 2,
  pch = 1:ncol(df),
  familyfont = "",
  spl = 5,
  all_values = FALSE
)
```

**Arguments**

<code>df</code>	data.frame.
<code>cols</code>	Character, columns of data.frame.
<code>xlab</code>	a label for the x axis, defaults to a description of x.
<code>ylab</code>	a label for the x axis, defaults to a description of x.
<code>main</code>	Character, a main title for the plot, see also <a href="#">title</a> .
<code>theme</code>	Character; "black", "dark", "clean", "ink"
<code>col</code>	The colors for lines and points. Multiple colors can be specified so that each point can be given its own color. If there are fewer colors than points they are recycled in the standard fashion. Default are cptcity colour palette "kst_18_pastels"
<code>type</code>	1-character string giving the type of plot desired. The following values are possible, for details, see plot: "p" for points, "l" for lines, "b" for both points and lines, "c" for empty points joined by lines, "o" for overplotted points and lines, "s" and "S" for stair steps and "h" for histogram-like vertical lines. Finally, "n" does not produce any points or lines.
<code>lwd</code>	a vector of line widths, see <a href="#">par</a> .



pch	plotting ‘character’, i.e., symbol to use. This can either be a single character or an integer code for one of a set of graphics symbols. The full set of S symbols is available with pch = 0:18, see the examples below. (NB: R uses circles instead of the octagons used in S.). Value pch = "." (equivalently pch = 46) is handled specially. It is a rectangle of side 0.01 inch (scaled by cex). In addition, if cex = 1 (the default), each side is at least one pixel (1/72 inch on the pdf, postscript and xfig devices). For other text symbols, cex = 1 corresponds to the default fontsize of the device, often specified by an argument pointsize. For pch in 0:25 the default size is about 75 the character height (see par("cin")).
familyfont	"Character" to specify font, default is "", options "serif", "sans", "mono" or more according device
spl	numer to control space for legend, default is 5.
all_values	logical, if FALSE shows only positive > 0 values

**Value**

a nice plot

**Note**

This plot shows values > 0 by default. To plot all values, use all\_values = TRUE

**See Also**

[par](#)

**Examples**

```
## Not run:
a <- ef_cetesb("CO", c("PC_G", "PC_FE", "PC_FG"), agemax = 20)
colplot(df = a, ylab = "CO [g/km]", theme = "dark", pch = NULL, type = "l")
#colplot(df = a, cols = "PC_FG", main = "EF", ylab = "CO [g/km]")
#colplot(df = a, ylab = "CO [g/km]", theme = "clean")

## End(Not run)
```

---

 ef\_cetesb

*Emissions factors for Environment Company of Sao Paulo, Brazil  
(CETESB) 2017*

---

**Description**

[ef\\_cetesb](#) returns a vector or data.frame of Brazilian emission factors.

**Usage**

```
ef_cetesb(
  p,
  veh,
  year = 2017,
  agemax = 40,
  scale = "default",
  sppm,
  full = FALSE,
  project = "constant",
  verbose = FALSE,
  csv
)
```

**Arguments**

p	Character; Pollutants: "CO", "HC", "NMHC", "CH4", "NOx", "CO2", "RCHO" (aldehydes + formaldehyde), "ETOH", "PM", "N2O", "KML", "FC", "NO2", "NO", "gD/KWH", "gCO2/KWH", "RCHO_0km" (aldehydes + formaldehyde), "CO_0km", "HC_0km", "NMHC_0km", "NOx_0km", "NO2_0km", "NO_0km", "RCHO_0km" and "ETOH_0km", "FS" (fuel sales) (g/km). If scale = "tunnel" is used, there is also "ALD" for aldehydes and "HCHO" for formaldehydes Evaporative emissions at average temperature ranges: "D_20_35", "S_20_35", "R_20_35", "D_10_25", "S_10_25", "R_10_25", "D_0_15", "S_0_15" and "R_0_15" where D means diurnal (g/day), S hot/warm soak (g/trip) and R hot/warm running losses (g/trip).
veh	Character; Vehicle categories: "PC_G", "PC_FG", "PC_FE", "PC_E", "LCV_G", "LCV_FG", "LCV_FE", "LCV_E", "LCV_D", "TRUCKS_SL", "TRUCKS_L", "TRUCKS_M", "TRUCKS_SH", "TRUCKS_H", "BUS_URBAN", "BUS_MICRO", "BUS_COACH", "BUS_ARTIC", "MC_G_150", "MC_G_150_500", "MC_G_500", "MC_FG_150", "MC_FG_150_500", "MC_FG_500", "MC_FE_150", "MC_FE_150_500", "MC_FE_500" "CICLOMOTOR", "GNV"
year	Numeric; Filter the emission factor to start from a specific base year. If project is 'constant' values above 2017 and below 1980 will be repeated
agemax	Integer; age of oldest vehicles for that category
scale	Character; values "default" or "tunnel". If "tunnel", emission factors are scaled to represent EF measurements in tunnels in Sao Paulo
sppm	Numeric, sulfur (sulphur) in ppm in fuel.
full	Logical; To return a data.frame instead or a vector adding Age, Year, Brazilian emissions standards and its euro equivalent.
project	Character showing the method for projecting emission factors in future. Currently the only value is "constant"
verbose	Logical; To show more information
csv	String with the path to download the ef in a .csv file. For instance, ef.csv

**Value**

A vector of Emission Factor or a data.frame

**Note**

The new convention for vehicles names are translated from CETESB report:

veh	description
PC_G	Passenger Car Gasohol (Gasoline + 27perc of anhydrous ethanol)
PC_E	Passenger Car Ethanol (hydrous ethanol)
PC_FG	Passenger Car Flex Gasohol (Gasoline + 27perc of anhydrous ethanol)
PC_FE	Passenger Car Flex Ethanol (hydrous ethanol)
LCV_G	Light Commercial Vehicle Gasohol (Gasoline + 27perc of anhydrous ethanol)
LCV_E	Light Commercial Vehicle Ethanol (hydrous ethanol)
LCV_FG	Light Commercial Vehicle Flex Gasohol (Gasoline + 27perc of anhydrous ethanol)
LCV_FE	Light Commercial Vehicle Flex Ethanol (hydrous ethanol)
LCV_D	Light Commercial Vehicle Diesel (5perc bio-diesel)
TRUCKS_SL_D	Trucks Semi Light Diesel (5perc bio-diesel)
TRUCKS_L_D	Trucks Light Diesel (5perc bio-diesel)
TRUCKS_M_D	Trucks Medium Diesel (5perc bio-diesel)
TRUCKS_SH_D	Trucks Semi Heavy Diesel (5perc bio-diesel)
TRUCKS_H_D	Trucks Heavy Diesel (5perc bio-diesel)
BUS_URBAN_D	Urban Bus Diesel (5perc bio-diesel)
BUS_MICRO_D	Micro Urban Bus Diesel (5perc bio-diesel)
BUS_COACH_D	Coach (inter-state) Bus Diesel (5perc bio-diesel)
BUS_ARTIC_D	Articulated Urban Bus Diesel (5perc bio-diesel)
MC_150_G	Motorcycle engine less than 150cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_500_G	Motorcycle engine 150-500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_500_G	Motorcycle greater than 500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_FG	Flex Motorcycle engine less than 150cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_500_FG	Flex Motorcycle engine 150-500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_500_FG	Flex Motorcycle greater than 500cc Gasohol (Gasoline + 27perc of anhydrous ethanol)
MC_150_FE	Flex Motorcycle engine less than 150cc Ethanol (hydrous ethanol)
MC_150_500_FE	Flex Motorcycle engine 150-500cc Ethanol (hydrous ethanol)
MC_500_FE	Flex Motorcycle greater than 500cc Ethanol (hydrous ethanol)

The percentage varies of bioduels varies by law.

This emission factors are not exactly the same as the report of CETESB.

- 1) In this emission factors, there is also NO and NO<sub>2</sub> based on split by published in the EMEP/EEA air pollutant emission inventory guidebook.
- 2) Also, the emission factors were extended till 50 years of use, repeating the oldest value.
- 3) CNG emission factors were expanded to other pollutants by comparison of US.EPA-AP42 emission factor: Section 1.4 Natural Gas Combustion.

In the previous versions I used the letter 'd' for deteriorated. I removed the letter 'd' internally to not break older code.

If by mistake, the user inputs one of veh names from the old convention, they are internally changed to the new convention: "SLT", "LT", "MT", "SHT", "HT", "UB", "SUB", "COACH", "ARTIC", "M\_G\_150", "M\_G\_150\_500", "M\_G\_500", "M\_FG\_150", "M\_FG\_150\_500", "M\_FG\_500", "M\_FE\_150", "M\_FE\_150\_500", "M\_FE\_500",

If pollutant is "SO2", it needs ppm. It is designed when veh has length 1, if it has length 2 or more, it will show a warning

**Emission factor for vehicles older than the reported by CETESB were filled as the moving average of 2:**

- Range EF from PC and LCV otto: 2018 - 1982. EF for 1981 and older as movign average.
- Range LCV diesel : 2018 - 2006. EF for 2005 and older as movign average.
- Range Trucks and Buse: 2018 - 1998. EF for 1997 and older as movign average.
- Range MC Gasoline: 2018 - 2003. EF for 2002 and older as movign average.
- Range MC Flex 150-500cc and >500cc: 2018 - 2012. EF for 2011 and older as movign average.

Currently, 2020, there are not any system for recovery of fuel vapors in Brazil. Hence, the FS takes into account the vapour that comes from the fuel tank inside the car and released into the atmosphere when injecting new fuel. There are discussions about incrementing implementing stage I and II and/or ORVR thesedays. The ef FS is calculated by transforming g FC/km into (L/KM)\*g/L with g/L 1.14 fgor gasoline and 0.37 for ethanol (CETESB, 2016). The density considered is 0.75425 for gasoline and 0.809 for ethanol (t/m<sup>3</sup>)

CETESB emission factors did not cover evaporative emissions from motorcycles, which occure. Therefore, in the absence of better data, it was assumed the same ratio from passenger cars.

Li, Lan, et al. "Exhaust and evaporative emissions from motorcycles fueled with ethanol gasoline blends." *Science of the Total Environment* 502 (2015): 627-631.

If scale is used with tunnel, the references are:

- Pérez-Martinez, P. J., Miranda, R. M., Nogueira, T., Guardani, M. L., Fornaro, A., Ynoue, R., and Andrade, M. F. (2014). Emission factors of air pollutants from vehicles measured inside road tunnels in Sao Paulo: case study comparison. *International Journal of Environmental Science and Technology*, 11(8), 2155-2168.
- Nogueira, T., de Souza, K. F., Fornaro, A., de Fatima Andrade, M., and de Carvalho, L. R. F. (2015). On-road emissions of carbonyls from vehicles powered by biofuel blends in traffic tunnels in the Metropolitan Area of Sao Paulo, Brazil. *Atmospheric Environment*, 108, 88-97.

## References

Emissoes Veiculares no Estado de Sao Paulo 2016. Technical Report. url: <https://cetesb.sp.gov.br/veicular/relatorios-e-publicacoes/>.

## Examples

```
## Not run:
a <- ef_cetesb("CO", "PC_G")
a <- ef_cetesb("R_10_25", "PC_G")
a <- ef_cetesb("CO", c("PC_G", "PC_FE"))
```

```

ef_cetesb(p = "CO", veh = "PC_G", year = 1970, agemax = 40)
ef_cetesb(p = "CO", veh = "PC_G", year = 2030, agemax = 40)
ef_cetesb(p = "CO", veh = "TRUCKS_L_D", year = 2018)
ef_cetesb(p = "CO", veh = "SLT", year = 2018) # olds names
ef_cetesb(p = "SO2", veh = "PC_G", year = 2030, agemax = 40, sppm = 300)
ef_cetesb(p = "SO2", veh = "PC_FE", year = 2030, agemax = 40, sppm = 300)
a <- ef_cetesb(p = "NMHC", veh = c("PC_G", "PC_FG", "PC_FE", "PC_E"), year = 2018, agemax = 20)
colplot(a, main = "NMHC EF", ylab = "[g/km]", xlab = "Years of use")

## End(Not run)

```

---

ef\_china

*Emissions factors from Chinese emissions guidelines*


---

## Description

`ef_china` returns emission factors as vector or data.frames. The emission factors comes from the chinese emission guidelines (v3) from the Chinese Ministry of Ecology and Environment <http://www.mee.gov.cn/gkml/hbb/bj>

## Usage

```

ef_china(
  v = "PV",
  t = "Small",
  f = "G",
  standard,
  p,
  k = 1,
  ta = celsius(15),
  humidity = 0.5,
  altitude = 1000,
  speed = Speed(30),
  baseyear_det = 2016,
  sulphur = 50,
  load_factor = 0.5,
  details = FALSE,
  correction_only = FALSE
)

```

## Arguments

v	Character; category vehicle: "PV" for Passenger Vehicles or 'Trucks"
t	Character; sub-category of of vehicle: PV Gasoline: "Mini", "Small", "Medium", "Large", "Taxi", "Motorcycles", "Moped", PV Diesel: "Mediumbus", "Largebus", "3-Wheel". Trucks: "Mini", "Light" , "Medium", "Heavy"
f	Character;fuel: "G", "D"

standard	Character or data.frame; "PRE", "I", "II", "III", "IV", "V". When it is a data.frame, it each row is a different region and ta, humidity, altitude, speed, sulphur and load_factor lengths have the same as the number of rows.
p	Character; pollutant: "CO", "NOx", "HC", "PM", "Evaporative_driving" or "Evaporative_parking"
k	Numeric; multiplication factor
ta	Numeric; temperature of ambient in celcius degrees. When standard is a data.frame, the length must be equal to the number of rows of standard.
humidity	Numeric; relative humidity. When standard is a data.frame, the length must be equal to the number of rows of standard.
altitude	Numeric; altitude in meters. When standard is a data.frame, the length must be equal to the number of rows of standard.
speed	Numeric; altitude in km/h When standard is a data.frame, the length must be equal to the number of rows of standard.
baseyear_det	Integer; any of 2014, 2015, 2016, 2017, 2018
sulphur	Numeric; sulphur in ppm. When standard is a data.frame, the length must be equal to the number of rows of standard.
load_factor	Numeric; When standard is a data.frame, the length must be equal to the number of rows of standard.
details	Logical; When TRUE, it shows a description of the vehicle in chinese and english. Only when length standard is 1.
correction_only	Logical; When TRUE, return only correction factors.

**Value**

An emission factor

**Note**

Combination of vehicles:

v	t	f
PV	Mini	G
PV	Small	G
PV	Medium	G
PV	Large	G
PV	Taxi	G
PV	Bus	G
PV	Motorcycles	G
PV	Moped	G
PV	Mini	D
PV	Small	D
PV	Mediumbus	D
PV	Largebus	D
PV	Bus	D

PV	3-Wheel	D
PV	Small	ALL
PV	Mediumbus	ALL
PV	Largebus	ALL
PV	Taxi	ALL
PV	Bus	ALL
Trucks	Bus	G
Trucks	Light	G
Trucks	Medium	G
Trucks	Heavy	G
Trucks	Light	D
Trucks	Medium	D
Trucks	Heavy	D
Trucks	Low Speed	D
Trucks	Mini	D

**See Also**

[ef\\_ldv\\_speed emis\\_hot\\_td](#)

**Examples**

```
## Not run:
# when standard is 'character'
# Checking
df_st <- rev(c(as.character(as.roman(5:1)), "PRE"))
ef_china(t = "Mini", f = "G", standard = df_st, p = "CO")
ef_china(t = "Mini", f = "G", standard = df_st, p = "HC")
ef_china(t = "Mini", f = "G", standard = df_st, p = "NOx")
ef_china(t = "Mini", f = "G", standard = df_st, p = "PM2.5")
ef_china(t = "Mini", f = "G", standard = df_st, p = "PM10")

ef_china(t = "Small", f = "G", standard = df_st, p = "CO")
ef_china(t = "Small", f = "G", standard = df_st, p = "HC")
ef_china(t = "Small", f = "G", standard = df_st, p = "NOx")
ef_china(t = "Small", f = "G", standard = df_st, p = "PM2.5")
ef_china(t = "Small", f = "G", standard = df_st, p = "PM10")

ef_china(t = "Mini",
         standard = c("PRE"),
         p = "CO",
         k = 1,
         ta = celsius(15),
         humidity = 0.5,
         altitude = 1000,
         speed = Speed(30),
         baseyear_det = 2014,
         sulphur = 50,
         load_factor = 0.5,
```

```

      details = FALSE)
ef_china(standard = c("PRE", "I"), p = "CO", correction_only = TRUE)

# when standard is 'data.frame'
df_st <- matrix(c("V", "IV", "III", "III", "II", "I", "PRE"), nrow = 2, ncol = 7, byrow = TRUE)
df_st <- as.data.frame(df_st)
a <- ef_china(standard = df_st,
             p = "PM10",
             ta = rep(celsius(15), 2),
             altitude = rep(1000, 2),
             speed = rep(Speed(30), 2),
             sulphur = rep(50, 2))

dim(a)
dim(df_st)
ef_china(standard = df_st, p = "PM2.5", ta = rep(celsius(20), 2),
         altitude = rep(1501, 2), speed = rep(Speed(29), 2), sulphur = rep(50, 2))
a

# when standard, temperature and humidity are data.frames
# assuming 10 regions
df_st <- matrix(c("V", "IV", "III", "III", "II", "I", "PRE"), nrow = 10, ncol = 7, byrow = TRUE)
df_st <- as.data.frame(df_st)
df_t <- matrix(21:30, nrow = 10, ncol = 12, byrow = TRUE)
df_t <- as.data.frame(df_t)
for(i in 1:12) df_t[, i] <- celsius(df_t[, i])

# assuming 10 regions
df_h <- matrix(seq(0.4, 0.5, 0.05), nrow = 10, ncol = 12, byrow = TRUE)
df_h <- as.data.frame(df_h)
a <- ef_china(standard = df_st, p = "CO", ta = df_t, humidity = df_h,
             altitude = rep(1501, 10), speed = rep(Speed(29), 10), sulphur = rep(50, 10))
a
a <- ef_china(standard = df_st, p = "PM2.5", ta = df_t, humidity = df_h,
             altitude = rep(1501, 10), speed = rep(Speed(29), 10), sulphur = rep(50, 10))
a
a <- ef_china(standard = df_st, p = "PM10", ta = df_t, humidity = df_h,
             altitude = rep(1501, 10), speed = rep(Speed(29), 10), sulphur = rep(50, 10))
a
dim(a)

## End(Not run)

```

---

 ef\_evap

*Evaporative emission factor*


---

## Description

[ef\\_evap](#) is a lookup table with tier 2 evaporative emission factors from EMEP/EEA emission guidelines



**Usage**

```
ef_evap(
  ef,
  v,
  cc,
  dt,
  ca,
  pollutant = "NMHC",
  k = 1,
  ltrip,
  kmday,
  show = FALSE,
  verbose = FALSE
)
```

**Arguments**

ef	Name of evaporative emission factor as *eshotc*: mean hot-soak with carburetor, *eswarmc*: mean cold and warm-soak with carburetor, eshotfi: mean hot-soak with fuel injection, *erhotc*: mean hot running losses with carburetor, *erwarmc* mean cold and warm running losses, *erhotfi* mean hot running losses with fuel injection. Length of ef 1.
v	Type of vehicles, "PC", "Motorcycle", "Motorcycle_2S" and "Moped"
cc	Size of engine in cc. PC "<=1400", "1400_2000" and ">2000" Motorcycle_2S: "<=50". Motorcycles: ">50", "<=250", "250_750" and ">750". Only engines of >750 has canister.
dt	Character or Numeric: Average monthly temperature variation: "-5_10", "0_15", "10_25" and "20_35". This argument can vector with several elements. dt can also be data.frame, but it is recommended that the number of columns are each month. So that dt varies in each row and each column.
ca	Size of canister: "no" meaning no canister, "small", "medium" and "large".
pollutant	Character indicating any of the covered pollutants: "NMHC", "ethane", "propane", "i-butane", "n-butane", "i-pentane", "n-pentane", "2-methylpentane", "3-methylpentane", "n-hexane", "n-heptane", "propene", "trans-2-butene", "isobutene", "cis-2-butene", "1,3-butadiene", "trans-2-pentene", "cis-2-pentene", "isoprene", "propyne", "acetylene", "benzene", "toluene", "ethylbenzene", "m-xylene", "o-xylene", "1,2,4-trimethylbenzene" and "1,3,5-trimethylbenzene". Default is "NMHC"
k	multiplication factor
ltrip	Numeric; Length of trip. Experimental feature to conter g/trip and g/proced (assuming proced similar to trip) in g/km.
kmday	Numeric; average daily mileage. Experimental option to convert g/day in g/km. it is an information more solid than to know the average number of trips per day.
show	when TRUE shows row of table with respective emission factor.
verbose	Logical; To show more information

**Value**

emission factors in `g/trip` or `g/proced`. The object has class `(g)` but in order to know it is `g/trip` or `g/proceed` the argument `show` must be `T`

**Note**

Diurnal losses occur with daily temperature variations. Running losses occur during vehicles use. Hot soak emission occur following vehicles use.

**References**

Mellios G and Ntziachristos 2016. Gasoline evaporation. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2009

**Examples**

```
## Not run:
# Do not run
a <- ef_evap(ef = "eshotc", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
pollutant = "cis-2-pentene")
a <- ef_evap(ef = "ed", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
show = TRUE)
a <- ef_evap(ef = c("erhotc", "erhotc"), v = "PC", cc = "<=1400",
dt = "0_15", ca = "no",
show = TRUE)
a <- ef_evap(ef = c("erhotc", "erhotc"), v = "PC", cc = "<=1400",
dt = "0_15", ca = "no",
show = FALSE)
a <- ef_evap(ef = "eshotc", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
show = TRUE)
ef_evap(ef = "erhotc", v = "PC", cc = "<=1400", dt = "0_15", ca = "no",
show = TRUE)
temps <- 10:20
a <- ef_evap(ef = "erhotc", v = "PC", cc = "<=1400", dt = temps, ca = "no",
show = TRUE)
dt <- matrix(rep(1:24,5), ncol = 12) # 12 months
dt <- celsius(dt)
a <- ef_evap(ef = "erhotc", v = "PC", cc = "<=1400",
dt = dt, ca = "no")
lkm <- units::set_units(10, km)
a <- ef_evap(ef = "erhotc", v = "PC", cc = "<=1400", ltrip = lkm,
dt = dt, ca = "no")

## End(Not run)
```

---

`ef_fun`*Experimental: Returns a function of Emission Factor by age of use*

---

## Description

`ef_fun` returns amount of vehicles at each age

## Usage

```
ef_fun(  
  ef,  
  type = "logistic",  
  x = 1:length(ef),  
  x0 = mean(ef),  
  k = 1/4,  
  L = max(ef)  
)
```

## Arguments

<code>ef</code>	Numeric; numeric vector of emission factors.
<code>type</code>	Character; "logistic" by default so far.
<code>x</code>	Numeric; vector for ages of use.
<code>x0</code>	Numeric; the x-value of the sigmoid's midpoint,
<code>k</code>	Numeric; the steepness of the curve.
<code>L</code>	Integer; the curve's maximum value.

## Value

dataframe of age distribution of vehicles at each street.

## References

[https://en.wikipedia.org/wiki/Logistic\\_function](https://en.wikipedia.org/wiki/Logistic_function)

## Examples

```
## Not run:  
data(fe2015)  
CO <- vein::EmissionFactors(fe2015[fe2015$Pollutant == "CO", "PC_G"])  
ef_logit <- ef_fun(ef = CO, x0 = 27, k = 0.4, L = 33)  
plot(ef_logit, type = "b", pch = 16)  
lines(ef_logit, pch = 16, col = "blue")  
  
## End(Not run)
```

---

ef_hdv_scaled	<i>Scaling constant with speed emission factors of Heavy Duty Vehicles</i>
---------------	--

---

## Description

`ef_hdv_scaled` creates a list of scaled functions of emission factors. A scaled emission factor which at a speed of the driving cycle (SDC) gives a desired value. This function needs a dataframe with local emission factors with a column with the name "Euro\_HDV" indicating the Euro equivalence standard, assuming that there are available local emission factors for several consecutive years.

## Usage

```
ef_hdv_scaled(df, dfcol, SDC = 34.12, v, t, g, eu, gr = 0, l = 0.5, p)
```

## Arguments

df	deprecated
dfcol	Column of the dataframe with the local emission factors eg df\$dfcol
SDC	Speed of the driving cycle
v	Category vehicle: "Coach", "Trucks" or "Ubus"
t	Sub-category of of vehicle: "3Axes", "Artic", "Midi", "RT", "Std" and "TT"
g	Gross weight of each category: "<=18", ">18", "<=15", ">15 & <=18", "<=7.5", ">7.5 & <=12", ">12 & <=14", ">14 & <=20", ">20 & <=26", ">26 & <=28", ">28 & <=32", ">32", ">20 & <=28", ">28 & <=34", ">34 & <=40", ">40 & <=50" or ">50 & <=60"
eu	Euro emission standard: "PRE", "I", "II", "III", "IV" and "V"
gr	Gradient or slope of road: -0.06, -0.04, -0.02, 0.00, 0.02, 0.04 or 0.06
l	Load of the vehicle: 0.0, 0.5 or 1.0
p	Pollutant: "CO", "FC", "NOx" or "HC"

## Value

A list of scaled emission factors g/km

## Note

The length of the list should be equal to the name of the age categories of a specific type of vehicle

**Examples**

```
## Not run:
# Do not run
data(fe2015)
co1 <- fe2015[fe2015$Pollutant=="CO",]
lef <- ef_hdv_scaled(dfcol = co1$LT, v = "Trucks", t = "RT",
g = "<=7.5", eu = co1$Euro_HDV, gr = 0, l = 0.5, p = "CO")
length(lef)
plot(x = 0:150, y = lef[[36]](0:150), col = "red", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of oldest vehicle")
plot(x = 0:150, y = lef[[1]](0:150), col = "blue", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of newest vehicle")

## End(Not run)
```

---

ef\_hdv\_speed

*Emissions factors for Heavy Duty Vehicles based on average speed*


---

**Description**

This function returns speed dependent emission factors. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

**Usage**

```
ef_hdv_speed(
  v,
  t,
  g,
  eu,
  x,
  gr = 0,
  l = 0.5,
  p,
  k = 1,
  show.equation = FALSE,
  speed,
  fcorr = rep(1, 8)
)
```

**Arguments**

v                   Category vehicle: "Coach", "Trucks" or "Ubus"  
t                    Sub-category of of vehicle: "3Axes", "Artic", "Midi", "RT", "Std" and "TT"

g	Gross weight of each category: "<=18", ">18", "<=15", ">15 & <=18", "<=7.5", ">7.5 & <=12", ">12 & <=14", ">14 & <=20", ">20 & <=26", ">26 & <=28", ">28 & <=32", ">32", ">20 & <=28", ">28 & <=34", ">34 & <=40", ">40 & <=50" or ">50 & <=60"
eu	Euro emission standard: "PRE", "I", "II", "III", "IV", "V". Also "II+CRDPF", "III+CRDPF", "IV+CRDPF", "II+SCR", "III+SCR" and "V+SCR" for pollutants Number of particles and Active Surface.
x	Numeric; if pollutant is "SO2", it is sulphur in fuel in ppm, if is "Pb", Lead in fuel in ppm.
gr	Gradient or slope of road: -0.06, -0.04, -0.02, 0.00, 0.02, 0.04 or 0.06
l	Load of the vehicle: 0.0, 0.5 or 1.0
p	Character; pollutant: "CO", "FC", "NOx", "NO", "NO2", "HC", "PM", "NMHC", "CH4", "CO2", "SO2" or "Pb". Only when p is "SO2" or "Pb" x is needed. Also polycyclic aromatic hydrocarbons (PAHs), persistent organi pollutants (POPs), and Number of particles and Active Surface.
k	Multiplication factor
show.equation	Option to see or not the equation parameters
speed	Numeric; Speed to return Number of emission factor and not a function. It needs units in km/h
fcorr	Numeric; Correction by fuel properties by euro technology. See <a href="#">fuel_corr</a> . The order from first to last is "PRE", "I", "II", "III", "IV", "V", VI, "VIc". Default is 1

### Value

an emission factor function which depends of the average speed V g/km

### Note

**Pollutants (g/km):** "CO", "NOx", "HC", "PM", "CH4", "NMHC", "CO2", "SO2", "Pb".

**Black Carbon and Organic Matter (g/km):** "BC", "OM"

**PAH and POP (g/km):** "indeno(1,2,3-cd)pyrene", "benzo(k)fluoranthene", "benzo(ghi)perylene", "fluoranthene", "benzo(a)pyrene", "pyrene", "perylene", "anthanthrene", "benzo(b)fluorene", "benzo(e)pyrene", "triphenylene", "3,6-dimethyl-phenanthrene", "benzo(a)anthracene", "phenanthrene", "naphthalene", "anthracene"

**Dioxins and furans (g equivalent toxicity / km):** "PCDD", "PCDF" and "PCB".

**Metals (g/km):** "As", "Cd", "Cr", "Cu", "Hg", "Ni", "Pb", "Se", "Zn" (g/km). **NMHC (g/km):**

*ALKANES (g/km):* "ethane", "propane", "butane", "isobutane", "pentane", "isopentane", "heptane", "octane", "2-methylhexane", "nonane", "2-methylheptane", "2-methylhexane", "decane", "3-methylheptane", "alkanes\_C10\_C12"

*CYCLOALKANES (g/km):* "cycloalkanes".

*ALKENES (g/km):* "ethylene", "propylene", "isobutene", "2-butene", "1,3-butadiene"

*ALKYNES (g/km):* "acetylene".

*ALDEHYDES (g/km)*: "formaldehyde", "acetaldehyde", "acrolein", "benzaldehyde", "crotonaldehyde", "methacrolein", "butyraldehyde", "propionaldehyde", "i-valeraldehyde"

*KETONES (g/km)*: "acetone"

*AROMATICS (g/km)*: "toluene", "ethylbenzene", "m-xylene", "p-xylene", "o-xylene", "1,2,3-trimethylbenzene", "1,2,4-trimethylbenzene", "1,3,5-trimethylbenzene", "styrene", "benzene", "C9".

*Active Surface (cm<sup>2</sup>/km) (gr = 0 and l = 0.5)*: "AS\_urban", "AS\_rural", "AS\_highway"

*Total Number of particles (N/km) (gr = 0 and l = 0.5)*: "N\_urban", "N\_rural", "N\_highway", "N\_50nm\_urban", "N\_50\_100nm\_rural", "N\_100\_1000nm\_highway".

The available standards for Active Surface or number of particles are: Euro II and III Euro II and III + CRDPF Euro II and III + SCR Euro IV + CRDPF Euro V + SCR

The categories Pre Euro and Euro I were assigned with the factors of Euro II and Euro III The categories euro IV and euro V were assigned with euro III + SCR

## See Also

[fuel\\_corr emis ef\\_ldv\\_cold](#)

## Examples

```
## Not run:
# Quick view
pol <- c("CO", "NOx", "HC", "NMHC", "CH4", "FC", "PM", "CO2", "SO2",
"AS_urban", "AS_rural", "AS_highway",
"N_urban", "N_rural", "N_highway",
"N_50nm_urban", "N_50_100nm_rural", "N_100_1000nm_highway")
f <- sapply(1:length(pol), function(i){
print(pol[i])
ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
l = 0.5, p = pol[i], x = 10)(30)
})
f
# PAH POP
ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
l = 0.5, p = "naphthalene", x = 10)(30)
ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
l = 0.5, p = "fluoranthene", x = 10)(30)

# Dioxins and Furans
ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
l = 0.5, p = "PCB", x = 10)(30)

# NMHC
ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
l = 0.5, p = "heptane", x = 10)(30)

V <- 0:130
ef1 <- ef_hdv_speed(v = "Trucks", t = "RT", g = "<=7.5", e = "II", gr = 0,
l = 0.5, p = "HC")
plot(1:130, ef1(1:130), pch = 16, type = "b")
euro <- c(rep("V", 5), rep("IV", 5), rep("III", 5), rep("II", 5),
```

```

      rep("I", 5), rep("PRE", 15))
lef <- lapply(1:30, function(i) {
ef_hdv_speed(v = "Trucks", t = "RT", g = ">32", gr = 0,
eu = euro[i], l = 0.5, p = "NOx",
show.equation = FALSE)(25) })
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")
a <- ef_hdv_speed(v = "Trucks", t = "RT", g = ">32", gr = 0,
eu = euro, l = 0.5, p = "NOx", speed = Speed(0:125))
a$speed <- NULL
filled.contour(as.matrix(a), col = cptcity::lucky(n = 24),
xlab = "Speed", ylab = "Age")
persp(x = as.matrix(a), theta = 35, xlab = "Speed", ylab = "Age",
zlab = "NOx [g/km]", col = cptcity::lucky(), phi = 25)
aa <- ef_hdv_speed(v = "Trucks", t = "RT", g = ">32", gr = 0,
eu = rbind(euro, euro), l = 0.5, p = "NOx", speed = Speed(0:125))

## End(Not run)

```

---

ef\_im

*Emission factors depending on accumulated mileage*


---

## Description

`ef_im` calculate the theoretical emission factors of vehicles. The approach is different from including deterioration factors (`emis_det`) but similar, because they represent how much emits a vehicle with a normal deterioration, but that it will pass the Inspection and Maintenance program.

## Usage

```
ef_im(ef, tc, amileage, max_amileage, max_ef, verbose = TRUE)
```

## Arguments

<code>ef</code>	Numeric; emission factors of vehicles with <b>0 mileage</b> (new vehicles).
<code>tc</code>	Numeric; rate of growth of emissions by year of use.
<code>amileage</code>	Numeric; Accumulated mileage by age of use.
<code>max_amileage</code>	Numeric; Max accumulated mileage. This means that after this value, mileage is constant.
<code>max_ef</code>	Numeric; Max ef. This means that after this value, ef is constant.
<code>verbose</code>	Logical; if you want detailed description.

## Value

An emission factor of a deteriorated vehicle under normal conditions which would be approved in a inspection and maintenance program.



## Examples

```
## Not run:
# Do not run
# Passenger Cars PC
data(fkm)
# cumulative mileage from 1 to 50 years of use, 40:50
mil <- cumsum(fkm$KM_PC_E25(1:10))
ef_im(ef = seq(0.1, 2, 0.2), seq(0.1, 1, 0.1), mil)

## End(Not run)
```

---

ef_ive	<i>Base emissions factors from International Vehicle Emissions (IVE) model</i>
--------	--

---

## Description

`ef_ive` returns the base emission factors from the the IVE model. This function depend on vectorized mileage, which means your can enter with the mileage by age of use and the name of the pollutant.

## Usage

```
ef_ive(
  description = "Auto/Sml Truck",
  fuel = "Petrol",
  weight = "Light",
  air_fuel_control = "Carburetor",
  exhaust = "None",
  evaporative = "PCV",
  mileage,
  pol,
  details = FALSE
)
```

## Arguments

description	Character; "Auto/Sml Truck" "Truck/Bus" or "Sml Engine".
fuel	Character; "Petrol", "NG Retrofit", "Natural Gas", "Prop Retro.", "Propane", "EthOH Retrofit", "OEM Ethanol", "Diesel", "Ethanol" or "CNG/LPG".
weight	Character; "Light", "Medium", "Heavy", "Lt", "Med" or "Hvy"
air_fuel_control	Character; One of the following characters: "Carburetor", "Single-Pt FI", "Multi-Pt FI", "Carb/Mixer", "FI", "Pre-Chamber Inject.", "Direct Injection", "2-Cycle", "2-Cycle, FI", "4-Cycle, Carb", "4-Cycle, FI" "4-Cycle"

exhaust	Character: "None", "2-Way", "2-Way/EGR", "3-Way", "3-Way/EGR", "None/EGR", "LEV", "ULEV", "SULEV", "EuroI", "EuroII", "EuroIII", "EuroIV", "Hybrid", "Improved", "EGR+Improv", "Particulate", "Particulate/NOx", "EuroV", "High Tech" or "Catalyst"			
evaporative	Character: "PCV", "PCV/Tank" or "None".			
mileage	Numeric; mileage of vehicle by age of use km.			
pol	Character; One of the following characters: "Carburetor", "Single-Pt FI", "Multi-Pt FI", "Carb/Mixer", "FI", "Pre-Chamber Inject.", "Direct Injection", "2-Cycle", "2-Cycle, FI", "4-Cycle, Carb", "4-Cycle, FI" "4-Cycle" #'			
"VOC_gkm"	"CO_gkm"	"NOx_gkm"	"PM_gkm"	
"Pb_gkm"	"SO2_gkm"	"NH3_gkm"	"1,3-butadiene_gkm"	
"formaldehyde_gkm"	"acetaldehyde_gkm"	"benzene_gkm"	"EVAP_gkm"	
"CO2_gkm"	"N2O_gkm"	"CH4_gkm"	"VOC_gstart"	
"CO_gstart"	"NOx_gstart"	"PM_gstart"	"Pb_gstart"	
"SO2_gstart"	"NH3_gstart"	"1,3-butadiene_gstart"	"formaldehyde_gstart"	
"acetaldehyde_gstart"	"benzene_gstart"	"EVAP_gstart"	"CO2_gstart"	
"N2O_gstart"	"CH4_gstart"			
details	Logical; option to see or not more information about vehicle.			

## Value

An emission factor by annual mileage.

## References

Nicole Davis, James Lents, Mauricio Osses, Nick Nikkila, Matthew Barth. 2005. Development and Application of an International Vehicle Emissions Model. Transportation Research Board, 81st Annual Meeting, January 2005, Washington, D.C.

## Examples

```
## Not run:
# Do not run
# Passenger Cars PC
data(fkm)
# cumulative mileage from 1 to 50 years of use, 40:50
mil <- cumsum(fkm$KM_PC_E25(1:50))
ef_ive("Truck/Bus", mileage = mil, pol = "CO_gkm")
ef_ive(mileage = mil, pol = "CO_gkm", details = TRUE)

## End(Not run)
```

**Description**

`ef_ldv_cold` returns speed functions or data.frames which depends on ambient temperature average speed. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

**Usage**

```
ef_ldv_cold(
  v = "LDV",
  ta,
  cc,
  f,
  eu,
  p,
  k = 1,
  show.equation = FALSE,
  speed,
  fcorr = rep(1, 8)
)
```

**Arguments**

v	Character; Category vehicle: "LDV"
ta	Numeric vector or data.frame; Ambient temperature. Monthly mean can be used. When ta is a data.frame, one option is that the number of rows should be the number of rows of your Vehicles data.frame. This is convenient for top-down approach when each simple feature can be a polygon, with a monthly average temperature for each simple feature. In this case, the number of columns can be the 12 months.
cc	Character; Size of engine in cc: "<=1400", "1400_2000" or ">2000"
f	Character; Type of fuel: "G", "D" or "LPG"
eu	Character or data.frame of Characters; Euro standard: "PRE", "I", "II", "III", "IV", "V", "VI" or "VIc". When 'eu' is a data.frame and 'ta' is also a data.frame both has to have the same number of rows. For instance, When you want that each simple feature or region has a different emission standard.
p	Character; Pollutant: "CO", "FC", "NOx", "HC" or "PM"
k	Numeric; Multiplication factor
show.equation	Option to see or not the equation parameters
speed	Numeric; Speed to return Number of emission factor and not a function.

`fcorr` Numeric; Correction by fuel properties by euro technology. See [fuel\\_corr](#). The order from first to last is "PRE", "I", "II", "III", "IV", "V", VI, "VIc". Default is 1

### Value

an emission factor function which depends of the average speed `V` and ambient temperature. `g/km`

### See Also

[fuel\\_corr](#)

### Examples

```
## Not run:
ef1 <- ef_ldv_cold(ta = 15, cc = "<=1400", f = "G", eu = "PRE", p = "CO",
  show.equation = TRUE)
ef1(10)
speed <- Speed(10)
ef_ldv_cold(ta = 15, cc = "<=1400", f = "G", eu = "PRE", p = "CO", speed = speed)
# lets create a matrix of ef cold at different speeds and temperatures
te <- -50:50
lf <- sapply(1:length(te), function(i){
  ef_ldv_cold(ta = te[i], cc = "<=1400", f = "G", eu = "I", p = "CO", speed = Speed(0:120))
})
filled.contour(lf, col= cptcity::lucky())
euros <- c("V", "V", "IV", "III", "II", "I", "PRE", "PRE")
ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(0))
lf <- ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(0:120))
dt <- matrix(rep(2:25,5), ncol = 12) # 12 months
ef_ldv_cold(ta = dt, cc = "<=1400", f = "G", eu = "I", p = "CO", speed = Speed(0))
ef_ldv_cold(ta = dt, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(34))
euros2 <- c("V", "V", "V", "IV", "IV", "IV", "III", "III")
dfe <- rbind(euros, euros2)
ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = dfe, p = "CO", speed = Speed(0))

ef_ldv_cold(ta = dt[1:2,], cc = "<=1400", f = "G", eu = dfe, p = "CO", speed = Speed(0))
# Fuel corrections
fcorr <- c(0.5,1,1,1,0.9,0.9,0.9,0.9)
ef1 <- ef_ldv_cold(ta = 15, cc = "<=1400", f = "G", eu = "PRE", p = "CO",
  show.equation = TRUE, fcorr = fcorr)
ef_ldv_cold(ta = 10, cc = "<=1400", f = "G", eu = dfe, p = "CO", speed = Speed(0),
  fcorr = fcorr)

## End(Not run)
```

**Description**

This function creates a list of functions of cold start emission factors considering different euro emission standard to the elements of the list.

**Usage**

```
ef_ldv_cold_list(df, v = "LDV", ta, cc, f, eu, p)
```

**Arguments**

df	Dataframe with local emission factor
v	Category vehicle: "LDV"
ta	ambient temperature. Montly average van be used
cc	Size of engine in cc: <=1400", "1400_2000" and ">2000"
f	Type of fuel: "G" or "D"
eu	character vector of euro standards: "PRE", "I", "II", "III", "IV", "V", "VI" or "VIc".
p	Pollutant: "CO", "FC", "NOx", "HC" or "PM"

**Value**

A list of cold start emission factors g/km

**Note**

The length of the list should be equal to the name of the age categories of a specific type of vehicle

**Examples**

```
## Not run:
# Do not run
df <- data.frame(age1 = c(1,1), age2 = c(2,2))
eu = c("I", "PRE")
l <- ef_ldv_cold(t = 17, cc = "<=1400", f = "G",
eu = "I", p = "CO")
l_cold <- ef_ldv_cold_list(df, t = 17, cc = "<=1400", f = "G",
eu = eu, p = "CO")
length(l_cold)

## End(Not run)
```

---

 ef\_ldv\_scaled

*Scaling constant with speed emission factors of Light Duty Vehicles*


---

### Description

This function creates a list of scaled functions of emission factors. A scaled emission factor which at a speed of the driving cycle (SDC) gives a desired value.

### Usage

```
ef_ldv_scaled(df, dfcol, SDC = 34.12, v, t = "4S", cc, f, eu, p)
```

### Arguments

df	deprecated
dfcol	Column of the dataframe with the local emission factors eg df\$dfcol
SDC	Speed of the driving cycle
v	Category vehicle: "PC", "LCV", "Motorcycle" or "Moped"
t	Sub-category of of vehicle: PC: "ECE_1501", "ECE_1502", "ECE_1503", "ECE_1504", "IMPROVED_CONVENTIONAL", "OPEN_LOOP", "ALL", "2S" or "4S". LCV: "4S", Motorcycle: "2S" or "4S". Moped: "2S" or "4S"
cc	Size of engine in cc: PC: "<=1400", ">1400", "1400_2000", ">2000", "<=800", "<=2000". Motorcycle: ">=50" (for "2S"), "<=250", "250_750", ">=750". Moped: "<=50". LCV : "<3.5" for gross weight.
f	Type of fuel: "G", "D", "LPG" or "FH" (Full Hybrid: starts by electric motor)
eu	Euro standard: "PRE", "I", "II", "III", "III+DPF", "IV", "V", "VI", "VIc"
p	Pollutant: "CO", "FC", "NOx", "HC" or "PM". If your pollutant dfcol is based on fuel, use "FC", if it is based on "HC", use "HC".

### Details

This function calls "ef\_ldv\_speed" and calculate the specific k value, dividing the local emission factor by the respective speed emissions factor at the speed representative of the local emission factor, e.g. If the local emission factors were tested with the FTP-75 test procedure, SDC = 34.12 km/h.

### Value

A list of scaled emission factors g/km

### Note

The length of the list should be equal to the name of the age categories of a specific type of vehicle. Thanks to Glauber Camponogara for the help.

**See Also**

ef\_ldv\_seed

**Examples**

```
## Not run:
data(fe2015)
co1 <- fe2015[fe2015$Pollutant=="CO", ]
lef <- ef_ldv_scaled(dfcol = co1$PC_G, v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = co1$Euro_LDV, p = "CO")
length(lef)
lef[[1]](40) # First element of the list of speed functions at 40 km/h
lef[[36]](50) # 36th element of the list of speed functions at 50 km/h
plot(x = 0:150, y = lef[[36]](0:150), col = "red", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of oldest vehicle")
plot(x = 0:150, y = lef[[1]](0:150), col = "blue", type = "b", ylab = "[g/km]",
pch = 16, xlab = "[km/h]",
main = "Variation of emissions with speed of newest vehicle")

## End(Not run)
```

---

ef\_ldv\_speed

*Emissions factors for Light Duty Vehicles and Motorcycles*


---

**Description**

[ef\\_ldv\\_speed](#) returns speed dependent emission factors, data.frames or list of emission factors. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

**Usage**

```
ef_ldv_speed(
  v,
  t = "4S",
  cc,
  f,
  eu,
  p,
  x,
  k = 1,
  speed,
  show.equation = FALSE,
  fcorr = rep(1, 8)
)
```

**Arguments**

v	Character; category vehicle: "PC", "LCV", "Motorcycle" or "Moped"
t	Character; sub-category of of vehicle: PC: "ECE_1501", "ECE_1502", "ECE_1503", "ECE_1504", "IMPROVED_CONVENTIONAL", "OPEN_LOOP", "ALL", "2S" or "4S". LCV: "4S", Motorcycle: "2S" or "4S". Moped: "2S" or "4S"
cc	Character; size of engine in cc: PC: "<=1400", ">1400", "1400_2000", ">2000", "<=800", "<=2000". Motorcycle: ">=50" (for "2S"), "<=250", "250_750", ">=750". Moped: "<=50". LCV : "<3.5" for gross weight.
f	Character; type of fuel: "G", "D", "LPG" or "FH" (Gasoline Full Hybrid). Full hybrid vehicles cannot be charged from the grid and recharge; only its own engine may recharge tis batteries.
eu	Character or data.frame of characters; euro standard: "PRE", "I", "II", "III", "III+DPF", "IV", "V", "VI" or "VIc". When the pollutant is active surface or number of particles, eu can also be "III+DISI"
p	Character; pollutant: "CO", "FC", "NOx", "NO", "NO2", "HC", "PM", "NMHC", "CH4", "CO2", "SO2" or "Pb". Only when p is "SO2" pr "Pb" x is needed. Also polycyclic aromatic hydrocarbons (PAHs), persistent organi pollutants (POPs), and Number of particles and Active Surface.
x	Numeric; if pollutant is "SO2", it is sulphur in fuel in ppm, if is "Pb", Lead in fuel in ppm.
k	Numeric; multiplication factor
speed	Numeric; Speed to return Number of emission factor and not a function.
show.equation	Logical; option to see or not the equation parameters.
fcorr	Numeric; Correction by fuel properties by euro technology. See <a href="#">fuel_corr</a> . The order from first to last is "PRE", "I", "II", "III", "IV", "V", VI, "VIc". Default is 1

**Details**

The argument of this functions have several options which results in different combinations that returns emission factors. If a combination of any option is wrong it will return an empty value. Therefore, it is important ti know the combinations.

**Value**

An emission factor function which depends of the average speed V g/km

**Note**

t = "ALL" and cc == "ALL" works for several pollutants because emission fators are the same. Some exceptions are with NOx and FC because size of engine.

**Hybrid cars:** the only cover "PC" and according to EMEP/EEA air pollutant emission inventory guidebook 2016 (Ntziachristos and Samaras, 2016) only for euro IV. When new literature is available, I will update these factors.

**Pollutants (g/km):** "CO", "NOx", "HC", "PM", "CH4", "NMHC", "CO2", "SO2", "Pb", "FC".



**Black Carbon and Organic Matter (g/km):** "BC", "OM"

**PAH and POP (g/km):** "indeno(1,2,3-cd)pyrene", "benzo(k)fluoranthene", "benzo(b)fluoranthene", "benzo(ghi)perylene", "fluoranthene", "benzo(a)pyrene", "pyrene", "perylene", "anthanthrene", "benzo(b)fluorene", "benzo(e)pyrene", "triphenylene", "benzo(j)fluoranthene", "dibenzo(a,j)anthracene", "dibenzo(a,l)pyrene", "3,6-dimethyl-phenanthrene", "benzo(a)anthracene", "acenaphthylene", "acenaphthene", "chrysene", "phenanthrene", "naphthalene", "anthracene", "coronene", "dibenzo(ah)anthracene".

**Dioxins and furans(g equivalent toxicity / km):** "PCDD", "PCDF" and "PCB".

**Metals (g/km):** "As", "Cd", "Cr", "Cu", "Hg", "Ni", "Pb", "Se", "Zn".

**NMHC (g/km):**

*ALKANES (g/km):* "ethane", "propane", "butane", "isobutane", "pentane", "isopentane", "hexane", "heptane", "octane", "2-methylhexane", "nonane", "2-methylheptane", "3-methylhexane", "decane", "3-methylheptane", "alkanes\_C10\_C12", "alkanes\_C13".

*CYCLOALKANES (g/km):* "cycloalkanes".

*ALKENES (g/km):* "ethylene", "propylene", "propadiene", "1-butene", "isobutene", "2-butene", "1,3-butadiene", "1-pentene", "2-pentene", "1-hexene", "dimethylhexene".

*ALKYNES (g/km):* "1-butyne", "propyne", "acetylene".

*ALDEHYDES (g/km):* "formaldehyde", "acetaldehyde", "acrolein", "benzaldehyde", "crotonaldehyde", "methacrolein", "butyraldehyde", "isobutanaldehyde", "propionaldehyde", "hexanal", "i-valeraldehyde", "valeraldehyde", "o-tolualdehyde", "m-tolualdehyde", "p-tolualdehyde".

*KETONES (g/km):* "acetone", "methylethylketone".

*AROMATICS (g/km):* "toluene", "ethylbenzene", "m-xylene", "p-xylene", "o-xylene", "1,2,3-trimethylbenzene", "1,2,4-trimethylbenzene", "1,3,5-trimethylbenzene", "styrene", "benzene", "C9", "C10", "C13".

*Active Surface (cm<sup>2</sup>/km):* "AS\_urban", "AS\_rural", "AS\_highway"

*Total Number of particles (N/km):* "N\_urban", "N\_rural", "N\_highway", "N\_50nm\_urban", "N\_50\_100nm\_rural", "N\_100\_1000nm\_highway".

The available standards for Active Surface or number of particles are Euro I, II, III, III+DPF for diesle and III+DISI for gasoline. Pre euro vehicles has the value of Euro I and euro IV, V, VI and VIc the value of euro III.

## See Also

[fuel\\_corr emis ef\\_ldv\\_cold](#)

## Examples

```
## Not run:
# Passenger Cars PC
# Emission factor function
V <- 0:150
ef1 <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "CO")
efs <- EmissionFactors(ef1(1:150))
plot(Speed(1:150), efs, xlab = "speed[km/h]", type = "b", pch = 16, col = "blue")

# Quick view
```

```

pol <- c("CO", "NOx", "HC", "NMHC", "CH4", "FC", "PM", "CO2", "SO2",
"1-butyne", "propyne")
f <- sapply(1:length(pol), function(i){
ef_ldv_speed("PC", "4S", "<=1400", "G", "PRE", pol[i], x = 10)(30)
})
f
# PM Characteristics
pol <- c("AS_urban", "AS_rural", "AS_highway",
"N_urban", "N_rural", "N_highway",
"N_50nm_urban", "N_50_100nm_rural", "N_100_1000nm_highway")
f <- sapply(1:length(pol), function(i){
ef_ldv_speed("PC", "4S", "<=1400", "D", "PRE", pol[i], x = 10)(30)
})
f
# PAH POP
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "indeno(1,2,3-cd)pyrene")(10)
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "naphthalene")(10)

# Dioxins and Furans
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "PCB")(10)

# NMHC
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G", eu = "PRE",
p = "hexane")(10)

# List of Copert emission factors for 40 years fleet of Passenger Cars.
# Assuming a euro distribution of euro V, IV, III, II, and I of
# 5 years each and the rest 15 as PRE euro:
euro <- c(rep("V", 5), rep("IV", 5), rep("III", 5), rep("II", 5),
rep("I", 5), rep("PRE", 15))
speed <- 25
lef <- lapply(1:40, function(i) {
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euro[i], p = "CO")
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euro[i], p = "CO", show.equation = FALSE)(25) })
# to check the emission factor with a plot
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")
euros <- c("VI", "V", "IV", "III", "II")
ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euros, p = "CO")
a <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = euros, p = "CO", speed = Speed(0:120))
head(a)
filled.contour(as.matrix(a)[1:10, 1:length(euros)], col = cptcity::cpt(n = 18))
filled.contour(as.matrix(a)[110:120, 1:length(euros)], col = cptcity::cpt(n = 16))
filled.contour(as.matrix(a)[, 1:length(euros)], col = cptcity::cpt(n = 21))
filled.contour(as.matrix(a)[, 1:length(euros)],

```

```

col = cptcity::cpt("mpl_viridis", n = 21))
filled.contour(as.matrix(a)[, 1:length(euros)],
col = cptcity::cpt("mpl_magma", n = 21))
persp(as.matrix(a)[, 1:length(euros)], phi = 0, theta = 0)
persp(as.matrix(a)[, 1:length(euros)], phi = 25, theta = 45)
persp(as.matrix(a)[, 1:length(euros)], phi = 0, theta = 90)
persp(as.matrix(a)[, 1:length(euros)], phi = 25, theta = 90+45)
persp(as.matrix(a)[, 1:length(euros)], phi = 0, theta = 180)
new_euro <- c("VI", "VI", "V", "V", "V")
euro <- c("V", "V", "IV", "III", "II")
old_euro <- c("III", "II", "I", "PRE", "PRE")
meuros <- rbind(new_euro, euro, old_euro)
aa <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
eu = meuros, p = "CO", speed = Speed(10:11))
# Light Commercial Vehicles
V <- 0:150
ef1 <- ef_ldv_speed(v = "LCV", t = "4S", cc = "<3.5", f = "G", eu = "PRE",
p = "CO")
efs <- EmissionFactors(ef1(1:150))
plot(Speed(1:150), efs, xlab = "speed[km/h]")
lef <- lapply(1:5, function(i) {
ef_ldv_speed(v = "LCV", t = "4S", cc = "<3.5", f = "G",
eu = euro[i], p = "CO", show.equation = FALSE)(25) })
# to check the emission factor with a plot
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")

# Motorcycles
V <- 0:150
ef1 <- ef_ldv_speed(v = "Motorcycle", t = "4S", cc = "<=250", f = "G",
eu = "PRE", p = "CO", show.equation = TRUE)
efs <- EmissionFactors(ef1(1:150))
plot(Speed(1:150), efs, xlab = "speed[km/h]")
# euro for motorcycles
eurom <- c(rep("III", 5), rep("II", 5), rep("I", 5), rep("PRE", 25))
lef <- lapply(1:30, function(i) {
ef_ldv_speed(v = "Motorcycle", t = "4S", cc = "<=250", f = "G",
eu = eurom[i], p = "CO",
show.equation = FALSE)(25) })
efs <- EmissionFactors(unlist(lef)) #returns 'units'
plot(efs, xlab = "age")
lines(efs, type = "l")
a <- ef_ldv_speed(v = "Motorcycle", t = "4S", cc = "<=250", f = "G",
eu = eurom, p = "CO", speed = Speed(0:125))
a$speed <- NULL
filled.contour(as.matrix(a), col = cptcity::lucky(),
xlab = "Speed", ylab = "Age")
persp(x = as.matrix(a), theta = 35, xlab = "Speed", ylab = "Euros",
zlab = "CO [g/km]", col = cptcity::lucky(), phi = 25)

## End(Not run)

```

---

ef\_local                      *Local Emissions factors*

---

### Description

`ef_local` process an data.frame delivered by the user, but adding similar functionality and arguments as `ef_cetesb`, which are classification, filtering and projections

### Usage

```
ef_local(
  p,
  veh,
  year = 2017,
  agemax = 40,
  ef,
  full = FALSE,
  project = "constant",
  verbose = TRUE
)
```

### Arguments

p	Character; pollutant delivered by the user. the name of the column of the data.frame must be <b>Pollutant</b> .
veh	Character; Vehicle categories available in the data.frame provided by the user
year	Numeric; Filter the emission factor to start from a specific base year. If project is 'constant' values above 2017 and below 1980 will be repeated
agemax	Integer; age of oldest vehicles for that category
ef	data.frame, for local the emission factors. The names of the ef must be 'Age' 'Year' 'Pollutant' and all the vehicle categories...
full	Logical; To return a data.frame instead or a vector adding Age, Year, Brazilian emissions standards and its euro equivalents.
project	Character showing the method for projecting emission factors in future. Currently the only value is "constant"
verbose	Logical; To show more information

### Details

returns a vector or data.frame of Brazilian emission factors.

### Value

A vector of Emission Factor or a data.frame

**Note**

The names of the ef must be 'Age' 'Year' 'Pollutant' and all the vehicle categories...

**See Also**

[ef\\_cetesb](#)

**Examples**

```
## Not run:
#do not run

## End(Not run)
```

---

 ef\_nitro

*Emissions factors of N2O and NH3*


---

**Description**

[ef\\_nitro](#) returns emission factors as a functions of acondumulated mileage. The emission factors comes from the guidelines EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emep-eea-air-pollutant-emission-inventory-guidebook>

**Usage**

```
ef_nitro(
  v,
  t = "Hot",
  cond = "Urban",
  cc,
  f,
  eu,
  p = "NH3",
  S = 10,
  cumileage,
  k = 1,
  show.equation = FALSE,
  fcorr = rep(1, 8)
)
```

**Arguments**

v	Category vehicle: "PC", "LCV", "Motorcycles_2S", "Motorcycles", "Trucks", "Trucks-A", "Coach" and "BUS"
t	Type: "Cold" or "Hot"
cond	"Urban", "Rural", "Highway"

cc	PC: "<=1400", "1400_2000", ">2000". LCV: "<3.5". Motorcycles: ">=50", Motorcycles_2S, "<50", ">=50". Trucks: ">3.5", "7.5_12", "12_28", "28_34". Trucks_A: ">34". BUS: "<=15", ">15 & <= 18". Coach: "<=18", ">18"
f	Type of fuel: "G", "D" or "LPG"
eu	Euro standard: "PRE", "I", "II", "III", "IV", "V", "VI", "VIc"
p	Pollutant: "N2O", "NH3"
S	Sulphur (ppm). Number.
cumileage	Numeric; Acondumulated mileage to return number of emission factor and not a function.
k	Multiplication factor
show.equation	Option to see or not the equation parameters
fcorr	Numeric; Correction by by euro technology.

**Value**

an emission factor function which depends on the acondumulated mileage, or an EmissionFactor

**Note**

if length of eu is bigger than 1, cumileage can have values of length 1 or length equal to length of eu

**Examples**

```
## Not run:
efe10 <- ef_nitro(v = "PC", t = "Hot", cond = "Urban", f = "G", cc = "<=1400",
eu = "III", p = "NH3", S = 10,
show.equation = FALSE)
efe50 <- ef_nitro(v = "PC", t = "Hot", cond = "Urban", f = "G", cc = "<=1400",
eu = "III", p = "NH3", S = 50,
show.equation = TRUE)
efe10(10)
efe50(10)
efe10 <- ef_nitro(v = "PC", t = "Hot", cond = "Urban", f = "G", cc = "<=1400",
eu = "III", p = "NH3", S = 10, cumileage = units::set_units(25000, "km"))

## End(Not run)
```

---

 ef\_wear

*Emissions factors from tyre, break and road surface wear*


---

**Description**

[ef\\_wear](#) estimates wear emissions. The sources are tyres, breaks and road surface.

**Usage**

```
ef_wear(wear, type, pol = "TSP", speed, load = 0.5, axle = 2)
```

**Arguments**

wear	Character; type of wear: "tyre", "break" and "road"
type	Character; type of vehicle: "2W", "PC", "LCV", "HDV"
pol	Character; pollutant: "TSP", "PM10", "PM2.5", "PM1" and "PM0.1"
speed	Data.frame of speeds
load	Load of the HDV
axle	Number of axle of the HDV

**Value**

emission factors grams/km

**References**

Ntziachristos and Boulter 2016. Automobile tyre and break wear and road abrasion. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

**Examples**

```
## Not run:
data(net)
data(pc_profile)
pc_week <- temp_fact(net$lhv+net$hdv, pc_profile)
df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
ef <- ef_wear(wear = "tyre", type = "PC", pol = "PM10", speed = df)

## End(Not run)
```

---

 ef\_whe

*Emission factor that incorporates the effect of high emitters*

---

**Description**

`ef_whe` return weighted emission factors of vehicles considering that one part of the fleet has a normal deterioration and another has a deteriorated fleet that would be rejected in a inspection and maintenance program but it is still in circulation. This emission factor might be applicable in cities without a inspection and maintenance program and with Weighted emission factors considering that part of the fleet are high emitters.

**Usage**

```
ef_whe(efhe, phe, ef)
```

**Arguments**

efhe	Numeric; Emission factors of high emitters vehicles. This vehicles would be rejected in a inspection and mantainence program.
phe	Numeric; Percentage of high emitters.
ef	Numeric; Emission factors deteriorated vehicles under normal conditions. These vehicles would be approved in a inspection and mantainence program.

**Value**

An emission factor by annual mileage.

**Examples**

```
## Not run:
# Do not run
# Let's say high emitter is 5 times the normal ef.
co_efhe <- ef_cetesb(p = "COd", "PC_G") * 5
# Let's say that the perfil of high emitters increases linearly
# till 30 years and after that percentage is constant
perc <- c(seq(0.01, 0.3, 0.01), rep(0.3, 20))
# Now, lets use our ef with normal deterioration
co_ef_normal <- ef_cetesb(p = "COd", "PC_G")
efd <- ef_whe(efhe = co_efhe, phe = perc, ef = co_ef_normal)
# now, we can plot the three ef
plot(co_efhe)
lines(co_ef_normal, pch = 16, col = "red" )
lines(efd, pch = 16, col = "blue")

## End(Not run)
```

---

emis

*Estimation of emissions*


---

**Description**

`emis` estimates vehicular emissions as the product of the vehicles on a road, length of the road, emission factor avaliated at the respective speed.  $E = VEH * LENGTH * EF(speed)$

**Usage**

```
emis(
  veh,
  lkm,
  ef,
  speed,
  agemax = ifelse(is.data.frame(veh), ncol(veh), ncol(veh[[1]])),
  profile,
```



```

    simplify = FALSE,
    fortran = FALSE,
    hour = nrow(profile),
    day = ncol(profile),
    verbose = FALSE
)

```

### Arguments

veh	"Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that type of vehicle. The number of rows is equal to the number of streets link. If this is a list, the length of the list is the vehicles for each hour.
lkm	Length of each link in km
ef	List of functions of emission factors
speed	Speed data-frame with number of columns as hours. The default value is 34km/h
agemax	Age of oldest vehicles for that category
profile	Dataframe or Matrix with nrow equal to 24 and ncol 7 day of the week
simplify	Logical; to determine if EmissionsArray should les dimensions, being streets, vehicle categories and hours or default (streets, vehicle categories, hours and days). Default is FALSE to avoid break old code, but the recommendation is that new estimations use this parameter as TRUE
fortran	Logical; to try the fortran calculation when speed is not used. I will add fortran for EmissionFactorsList soon.
hour	Number of considered hours in estimation. Default value is number of rows of argument profile
day	Number of considered days in estimation
verbose	Logical; To show more information

### Value

If the user applies a top-down approach, the resulting units will be according its own data. For instance, if the vehicles are veh/day, the units of the emissions implicitly will be g/day.

### Note

Hour and day will be deprecated because they can be inferred from the profile matrix.

### Examples

```

## Not run:
# Do not run
data(net)
data(pc_profile)
data(profiles)
data(fe2015)
data(fkm)

```

```

PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
        133833,138441,142682,171029,151048,115228,98664,126444,101027,
        84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
        1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")

# Estimation for morning rush hour and local emission factors and speed
speed <- data.frame(S8 = net$ps)
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G", agemax = ncol(pc1)))
system.time(E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed))
system.time(E_CO_2 <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, simplify = TRUE))
identical(E_CO, E_CO_2)

# Estimation for morning rush hour and local emission factors without speed
lef <- ef_cetesb("CO", "PC_G", agemax = ncol(pc1))
system.time(E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef))
system.time(E_CO_2 <- emis(veh = pc1,lkm = net$lkm, ef = lef, fortran = TRUE))
identical(E_CO, E_CO_2)

# Estimation for 168 hour and local factors and speed
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G", agemax = ncol(pc1)))
system.time(
E_CO <- emis(veh = pc1,
            lkm = net$lkm,
            ef = lef,
            speed = speed,
            profile = profiles$PC_JUNE_2014))
system.time(
E_CO_2 <- emis(veh = pc1,
            lkm = net$lkm,
            ef = lef,
            speed = speed,
            profile = profiles$PC_JUNE_2014,
            simplify = TRUE))

# Estimation for 168 hour and local factors and without speed
lef <- ef_cetesb("CO", "PC_G", agemax = ncol(pc1))
system.time(
E_CO <- emis(veh = pc1,
            lkm = net$lkm,
            ef = lef,
            profile = profiles$PC_JUNE_2014)) ; sum(E_CO)
system.time(
E_CO_2 <- emis(veh = pc1,
            lkm = net$lkm,
            ef = lef,
            profile = profiles$PC_JUNE_2014,
            fortran = TRUE)) ; sum(E_CO)
system.time(
E_CO_3 <- emis(veh = pc1,
            lkm = net$lkm,

```

```

        ef = lef,
        profile = profiles$PC_JUNE_2014,
        simplify = TRUE)) ; sum(E_CO)
system.time(
E_CO_4 <- emis(veh = pc1,
              lkm = net$lkm,
              ef = lef,
              profile = profiles$PC_JUNE_2014,
              simplify = TRUE,
              fortran = TRUE)) ; sum(E_CO)
identical(round(E_CO, 2), round(E_CO_2, 2))
identical(round(E_CO_3, 2), round(E_CO_4, 2))
identical(round(E_CO_3[, ,1], 2), round(E_CO_4[, ,1], 2))
dim(E_CO_3)
dim(E_CO_4)
# but
a <- unlist(lapply(1:41, function(i){
  unlist(lapply(1:168, function(j) {
    identical(E_CO_3[, i, j], E_CO_4[, i, j])
  })))
unique(a)

#Estimation with list of vehicles
lpc <- list(pc1, pc1)
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G", agemax = ncol(pc1)))
E_COv2 <- emis(veh = lpc, lkm = net$lkm, ef = lef, speed = speed)

# top down
veh <- age_ldv(x = net$ldv[1:4], name = "PC_E25_1400", agemax = 4)
mil <- fkm$KM_PC_E25(1:4)
ef <- ef_cetesb("COd", "PC_G")[1:4]
emis(veh, units::set_units(mil, "km"), ef)

# group online
bus1 <- age_hdv(30, agemax = 4)
veh = bus1
lkm = units::set_units(400, "km")
speed = 40
efco <- ef_cetesb("COd", "UB", agemax = 4)
lef <- ef_hdv_scaled(dfcol = as.numeric(efco),
                   v = "Ubus",
                   t = "Std",
                   g = ">15 & <=18",
                   eu = rep("IV", 4),
                   gr = 0,
                   l = 0.5,
                   p = "CO")
for(i in 1:length(lef)) print(lef[[i]](10))
(a <- emis(veh = bus1, lkm = lkm, ef = efco, verbose = TRUE))
(b <- emis(veh = bus1, lkm = lkm, ef = efco, verbose = TRUE, fortran = TRUE))

## End(Not run)

```

---

EmissionFactors      *Construction function for class "EmissionFactors"*

---

### Description

EmissionFactors returns a tranformed object with class "EmissionFactors" and units g/km.

### Usage

```
EmissionFactors(x, ...)  
  
## S3 method for class 'EmissionFactors'  
print(x, ...)  
  
## S3 method for class 'EmissionFactors'  
summary(object, ...)  
  
## S3 method for class 'EmissionFactors'  
plot(x, ...)
```

### Arguments

x	Object with class "data.frame", "matrix" or "numeric"
...	ignored
object	Object with class "EmissionFactors"

### Value

Objects of class "EmissionFactors" or "units"

### Examples

```
## Not run:  
data(fe2015)  
names(fe2015)  
class(fe2015)  
df <- fe2015[fe2015$Pollutant=="CO", c(ncol(fe2015)-1,ncol(fe2015))]  
ef1 <- EmissionFactors(df)  
class(ef1)  
summary(ef1)  
plot(ef1)  
print(ef1)  
  
## End(Not run)
```

---

EmissionFactorsList    *Construction function for class "EmissionFactorsList"*

---

### Description

EmissionFactorsList returns a tranformed object with class"EmissionsFactorsList".

### Usage

```
EmissionFactorsList(x, ...)

## S3 method for class 'EmissionFactorsList'
print(x, ..., default = FALSE)

## S3 method for class 'EmissionFactorsList'
summary(object, ...)

## S3 method for class 'EmissionFactorsList'
plot(x, ...)
```

### Arguments

x	Object with class "list"
...	ignored
default	Logical value. When TRUE prints default list, when FALSE prints messages with description of list
object	Object with class "EmissionFactorsList"

### Value

Objects of class "EmissionFactorsList"

### Examples

```
## Not run:
data(fe2015)
names(fe2015)
class(fe2015)
df <- fe2015[fe2015$Pollutant=="CO", c(ncol(fe2015)-1,ncol(fe2015))]
ef1 <- EmissionFactorsList(df)
class(ef1)
length(ef1)
length(ef1[[1]])
summary(ef1)
ef1

## End(Not run)
```

Emissions

*Construction function for class "Emissions"***Description**

Emissions returns a tranformed object with class "Emissions". The type of objects supported are of classes "matrix", "data.frame" and "numeric". If the class of the object is "matrix" this function returns a dataframe.

**Usage**

```
Emissions(x, time, ...)

## S3 method for class 'Emissions'
print(x, ...)

## S3 method for class 'Emissions'
summary(object, ...)

## S3 method for class 'Emissions'
plot(x, ...)
```

**Arguments**

x	Object with class "data.frame", "matrix" or "numeric"
time	Character to be the time units as denominator, eg "1/h"
...	ignored
object	object with class "Emissions"

**Value**

Objects of class "Emissions" or "units"

**Examples**

```
## Not run:
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491, 22340, 24818, 31808, 46458, 28574, 24856, 28972, 37818, 49050, 87923,
         133833, 138441, 142682, 171029, 151048, 115228, 98664, 126444, 101027,
         84771, 55864, 36306, 21079, 20138, 17439, 7854, 2215, 656, 1262, 476, 512,
         1181, 4991, 3711, 5653, 7039, 5839, 4257, 3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
```

```

speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::as_units(fkm[[1]](1:24), "km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", cc = "<=1400",
                    f = "G", p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile)
dim(E_CO) # streets x vehicle categories x hours x days
class(E_CO)
plot(E_CO)
####
Emissions(1, time = "1/h")

## End(Not run)

```

---

EmissionsArray

*Construction function for class "EmissionsArray"*


---

## Description

EmissionsArray returns a tranformed object with class "EmissionsArray" with 4 dimensios.

## Usage

```

EmissionsArray(x, ...)

## S3 method for class 'EmissionsArray'
print(x, ...)

## S3 method for class 'EmissionsArray'
summary(object, ...)

## S3 method for class 'EmissionsArray'
plot(x, ...)

```

## Arguments

x	Object with class "data.frame", "matrix" or "numeric"
...	ignored
object	object with class "EmissionsArray"

## Value

Objects of class "EmissionsArray"

**Note**

Future version of this function will return an Array of 3 dimensions.

**Examples**

```
## Not run:
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
          133833,138441,142682,171029,151048,115228,98664,126444,101027,
          84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
          1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24), "km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", cc = "<=1400",
                    f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile, simplify = TRUE)
class(E_CO)
summary(E_CO)
E_CO
plot(E_CO)
lpc <- list(pc1, pc1)
E_COv2 <- emis(veh = lpc,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
              profile = pc_profile, hour = 2, day = 1)

## End(Not run)
```

emis\_chem

*Aggregate emissions by lumped groups in chemical mechanism***Description**

[emis\\_chem](#) aggregates emissions by chemical mechanism and convert grams to mol. This function reads all hydrocarbos and respective criteria pollutants specified in [ef\\_ldv\\_speed](#) and [ef\\_hdv\\_speed](#).

**Usage**

```
emis_chem(dfe, mechanism, colby, long = FALSE)
```



**Arguments**

dfc	data.frame with column 'emissions' in grams and 'pollutant' in long format. It is supposed that each line is the pollution of some region. Then the 'coldby' argument is for include the name of the region.
mechanism	Character, "RADM2_SORG", "CBMZ_MOSAIC", "CPTEC", "GOCART_CPTEC", "MOZEM", "MOZCEM", "CAMMAM", "MOZMEM", "MOZC_T1_EM", "CB05_OPT1" or "CB05_OPT2"
colby	Character indicating column name for aggregating extra column. For instance, region or province.
long	Logical. Do you want data in long format?

**Value**

data.frame with lumped groups by chemical mechanism. It transform emissions in grams to mol.

**Note**

This feature is experimental and the mapping of pollutants and lumped species may change in future. This function is converting the initial data.frame input into data.table. To have a comprehensive speciation is necessary enter with a data.frame with column 'emission' in long format including another column named 'pollutant' with species of NMHC, CO, NO, NO2, NH3, SO2, PM2.5 and coarse PM10.

Groups derived from gases has units 'mol' and from aerosols 'g'. The aerosol units for WRF-Chem are  $\mu\text{g}/\text{m}^2/\text{s}$  while for CMAQ and CAMx are g/s. So, leaving the units just in g, allow to make further change while providing flexibility for several models. TODO: Enter with wide data.frame, with each line as a each street, each column for pollutant

**See Also**

[ef\\_ldv\\_speed](#) [ef\\_hdv\\_speed](#) [speciate](#) [ef\\_evap](#)

**Examples**

```
## Not run:
# CO
df <- data.frame(emission = Emissions(1:10))
df$pollutant = "CO"
emis_chem(df, "CBMZ_MOSAIC")
# hexanal
df$pollutant = "hexanal"
emis_chem(df, "CBMZ_MOSAIC")
# propadiene and NO2
df2 <- df1 <- df
df1$pollutant = "propadiene"
df2$pollutant = "NO2"
(dfc <- rbind(df1, df2))
emis_chem(dfc, "CBMZ_MOSAIC")
dfe$region <- rep(letters[1:2], 10)
emis_chem(dfe, "CBMZ_MOSAIC", "region")
```

```
emis_chem(dfe, "CBMZ_MOSAIC", "region", TRUE)

## End(Not run)
```

---

emis\_cold

*Estimation of cold start emissions hourly for the of the week*


---

## Description

emis\_cold emissions are estimated as the product of the vehicles on a road, length of the road, emission factor avaliated at the respective speed.The estimation considers beta parameter, the fraction of mileage driven

## Usage

```
emis_cold(
  veh,
  lkm,
  ef,
  efcold,
  beta,
  speed = 34,
  agemax = if (!inherits(x = veh, what = "list")) { ncol(veh) } else {
    ncol(veh[[1]]) },
  profile,
  simplify = FALSE,
  hour = nrow(profile),
  day = ncol(profile),
  array = TRUE,
  verbose = FALSE
)
```

## Arguments

veh	"Vehicles" data-frame or list of "Vehicles" data-frame. Each data-frame as number of columns matching the age distribution of that type of vehicle. The number of rows is equal to the number of streets link
lkm	Length of each link
ef	List of functions of emission factors of vehicular categories
efcold	List of functions of cold start emission factors of vehicular categories
beta	Datraframe with the hourly cold-start distribution to each day of the period. Number of rows are hours and columns are days
speed	Speed data-frame with number of columns as hours
agemax	Age of oldest vehicles for that category
profile	Numerical or dataframe with nrows equal to 24 and ncol 7 day of the week

simplify	Logical; to determine if EmissionsArray should les dimensions, being streets, vehicle categories and hours or default (streets, vehicle categories, hours and days). Default is FALSE to avoid break old code, but the recommendation is that new estimations use this parameter as TRUE
hour	Number of considered hours in estimation
day	Number of considered days in estimation
array	Deprecated! <code>emis_cold</code> returns only arrays. When TRUE and veh is not a list, expects a profile as a dataframe producing an array with dimensions (streets x columns x hours x days)
verbose	Logical; To show more information

### Value

EmissionsArray g/h

### Examples

```
## Not run:
# Do not run
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
data(pc_cold)
pcf <- as.data.frame(cbind(pc_cold,pc_cold,pc_cold,pc_cold,pc_cold,pc_cold,
pc_cold))
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
133833,138441,142682,171029,151048,115228,98664,126444,101027,
84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24), "km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", cc = "<=1400",
f = "G",p = "CO", eu=co1$Euro_LDV)
# Mohtly average temperature 18 Celcius degrees
lefec <- ef_ldv_cold_list(df = co1, ta = 18, cc = "<=1400", f = "G",
eu = co1$Euro_LDV, p = "CO" )
lefec <- c(lefec,lefec[length(lefec)], lefec[length(lefec)],
lefec[length(lefec)], lefec[length(lefec)],
lefec[length(lefec)])
length(lefec) == ncol(pc1)
#emis change length of 'ef' to match ncol of 'veh'
class(lefec)
```

```

PC_CO_COLD <- emis_cold(veh = pc1,
                       lkm = net$lkm,
                       ef = lef,
                       efcold = lefec,
                       beta = pcf,
                       speed = speed,
                       profile = pc_profile)

class(PC_CO_COLD)
plot(PC_CO_COLD)
lpc <- list(pc1, pc1)
PC_CO_COLDv2 <- emis_cold(veh = pc1,
                         lkm = net$lkm,
                         ef = lef,
                         efcold = lefec,
                         beta = pcf,
                         speed = speed,
                         profile = pc_profile,
                         hour = 2,
                         day = 1)

## End(Not run)

```

---

emis\_cold\_td

*Estimation of cold start emissions with top-down approach*


---

## Description

[emis\\_cold\\_td](#) estimates cold start emissions with a top-down approach. This is, annual or monthly emissions or region. Specifically, the emissions are estimated for row of the simple feature (row of the spatial feature).

In general was designed so that each simple feature is a region with different average monthly temperature. This function, as other in this package, adapts to the class of the input data. providing flexibility to the user.

## Usage

```

emis_cold_td(
  veh,
  lkm,
  ef,
  efcold,
  beta,
  pro_month,
  params,
  verbose = FALSE,
  fortran = FALSE
)

```

**Arguments**

veh	"Vehicles" data-frame or spatial feature, where columns are the age distribution of that vehicle. and rows each simple feature or region. The number of rows is equal to the number of streets link
lkm	Numeric; mileage by the age of use of each vehicle.
ef	Numeric; emission factor with
efcold	Data.frame. When it is a data.frame, each column is for each type of vehicle by age of use, rows are each simple feature. When you have emission factors for each month, the order should be a data.frame in a long format, as returned by <a href="#">ef_ldv_cold</a> .
beta	Data.frame with the fraction of cold starts. The rows are the fraction for each spatial feature or subregion, the columns are the age of use of vehicle.
pro_month	Numeric; monthly profile to distribute annual mileage in each month.
params	List of parameters; Add columns with information to returning data.frame
verbose	Logical; To show more information
fortran	Logical; to try the fortran calculation.

**Value**

Emissions data.frame

**See Also**

[ef\\_ldv\\_cold](#)

**Examples**

```
## Not run:
# Do not run
veh <- age_ldv(1:10, agemax = 8)
euros <- c("V", "V", "IV", "III", "II", "I", "PRE", "PRE")
dt <- matrix(rep(2:25,5), ncol = 12, nrow = 10) # 12 months, 10 rows
row.names(dt) <- paste0("Simple_Feature_", 1:10)
efc <- ef_ldv_cold(ta = dt, cc = "<=1400", f = "G", eu = euros, p = "CO", speed = Speed(34))
efh <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
                  eu = euros, p = "CO", speed = Speed(runif(nrow(veh), 15, 40)))
lkm <- units::as_units(18:11, "km")*1000
cold_lkm <- cold_mileage(ltrip = units::as_units(20, "km"), ta = celsius(dt))
names(cold_lkm) <- paste0("Month_", 1:12)
veh_month <- c(rep(8, 1), rep(10, 5), 9, rep(10, 5))
system.time(
a <- emis_cold_td(veh = veh,
                 lkm = lkm,
                 ef = efh[1, ],
                 efcold = efc[1:10, ],
                 beta = cold_lkm[,1],
                 verbose = TRUE))
system.time(
```

```

a2 <- emis_cold_td(veh = veh,
                  lkm = lkm,
                  ef = efh[1, ],
                  efcold = efc[1:10, ],
                  beta = cold_lkm[,1],
                  verbose = TRUE,
                  fortran = TRUE) # emistd2coldf.f95
a$emissions <- round(a$emissions, 8)
a2$emissions <- round(a2$emissions, 8)
identical(a, a2)

# Adding parameters
emis_cold_td(veh = veh,
             lkm = lkm,
             ef = efh[1, ],
             efcold = efc[1:10, ],
             beta = cold_lkm[,1],
             verbose = TRUE,
             params = list(paste0("data_", 1:10),
                           "moredata"))

system.time(
aa <- emis_cold_td(veh = veh,
                  lkm = lkm,
                  ef = efh,
                  efcold = efc,
                  beta = cold_lkm,
                  pro_month = veh_month,
                  verbose = TRUE))

system.time(
aa2 <- emis_cold_td(veh = veh,
                   lkm = lkm,
                   ef = efh,
                   efcold = efc,
                   beta = cold_lkm,
                   pro_month = veh_month,
                   verbose = TRUE,
                   fortran = TRUE) # emistd5coldf.f95
aa$emissions <- round(aa$emissions, 8)
aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)

## End(Not run)

```

---

emis\_det

*Determine deterioration factors for urban conditions*


---

### Description

`emis_det` returns deterioration factors. The emission factors comes from the guidelines for developing emission factors of the EMEP/EEA air pollutant emission inventory guidebook <http://www.eea.europa.eu/themes/air/emeip>

eea-air-pollutant-emission-inventory-guidebook This function subset an internal database of emission factors with each argument

### Usage

```
emis_det(
  po,
  cc,
  eu,
  speed = Speed(18.9),
  km,
  verbose = FALSE,
  show.equation = FALSE
)
```

### Arguments

po	Character; Pollutant "CO", "NOx" or "HC"
cc	Character; Size of engine in cc converin "<=1400", "1400_2000" or ">2000"
eu	Character; Euro standard: "I", "II", "III", "III", "IV", "V", "VI", "VIc"
speed	Numeric; Speed to return Number of emission factor and not a function. It needs units in km/h
km	Numeric; accumulated mileage in km.
verbose	Logical; To show more information
show.equation	Option to see or not the equation parameters

### Value

It returns a numeric vector representing the increase in emissions due to normal deterioring

### Note

The deterioration factors functions are available for technologies euro "II", "III" and "IV". In order to cover all euro technologies, this function assumes that the deterioration function of "III" and "IV" applies for "V", "VI" and "VIc". However, as these technologies are relative new, accumulated milage is low and hence, deteeriation factors small.

### Examples

```
## Not run:
data(fkm)
pckm <- fkm[[1]](1:24); pckma <- cumsum(pckm)
km <- units::set_units(pckma[1:11], km)
# length eu = length km = 1
emis_det(po = "CO", cc = "<=1400", eu = "III", km = km[5], show.equation = TRUE)
# length eu = length km = 1, length speed > 1
emis_det(po = "CO", cc = "<=1400", eu = "III", km = km[5], speed = Speed(1:10))
# length km != length eu error
# (cod1 <- emis_det(po = "CO", cc = "<=1400", eu = c("III", "IV"), speed = Speed(30),
```

```

# km = km[4]))
# length eu = 1 length km > 1
emis_det(po = "CO", cc = "<=1400", eu = "III", km = km)
# length eu = 2, length km = 2 (if different length, error!)
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = c("III", "IV"), km = km[4:5]))
# length eu = 2, length km = 2, length speed > 1
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = c("III", "IV"), speed = Speed(0:130),
km = km[4:5]))
euros <- c("V","V","V", "IV", "IV", "IV", "III", "III", "III", "III")
# length eu = 2, length km = 2, length speed > 1
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = euros, speed = Speed(1:100),
km = km[1:10]))
cod1 <- as.matrix(cod1[, 1:11])
filled.contour(cod1, col = cptcity::cpt(6277, n = 20))
filled.contour(cod1, col = cptcity::lucky(n = 19))
euro <- c(rep("V", 5), rep("IV", 5), "III")
euros <- rbind(euro, euro)
(cod1 <- emis_det(po = "CO", cc = "<=1400", eu = euros, km = km))

## End(Not run)

```

emis\_dist

*Allocate emissions into spatial objects (street emis to grid)*

## Description

`emis_dist` allocates emissions proportionally to each feature. "Spatial" objects are converted to "sf" objects. Currently, 'LINESTRING' or 'MULTILINESTRING' supported. The emissions are distributed in each street.

## Usage

```
emis_dist(gy, spobj, pro, osm, verbose = FALSE)
```

## Arguments

gy	Numeric; a unique total (top-down)
spobj	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf".
pro	Matrix or data-frame profiles, for instance, <code>pc_profile</code> .
osm	Numeric; vector of length 5, for instance, <code>c(5, 3, 2, 1, 1)</code> . The first element covers 'motorway' and 'motorway_link'. The second element covers 'trunk' and 'trunk_link'. The third element covers 'primary' and 'primary_link'. The fourth element covers 'secondary' and 'secondary_link'. The fifth element covers 'tertiary' and 'tertiary_link'.
verbose	Logical; to show more info.



**Note**

When spobj is a 'Spatial' object (class of sp), they are converted into 'sf'.

**Examples**

```
## Not run:
data(net)
data(pc_profile)
po <- 1000
t1 <- emis_dist(gy = po, spobj = net)
head(t1)
sum(t1$gy)
#t1 <- emis_dist(gy = po, spobj = net, osm = c(5, 3, 2, 1, 1) )
t1 <- emis_dist(gy = po, spobj = net, pro = pc_profile)

## End(Not run)
```

emis\_evap

*Estimation of evaporative emissions***Description**

[emis\\_evap](#) estimates evaporative emissions from EMEP/EEA emisison guidelines

**Usage**

```
emis_evap(
  veh,
  x,
  ed,
  hotfi,
  hotc,
  warmc,
  carb = 0,
  p,
  params,
  pro_month,
  verbose = FALSE
)
```

**Arguments**

veh	Numeric or data.frame of Vehicles with untis 'veh'.
x	Numeric which can be either, daily mileage by age of use with units 'lkm', number of trips or number of proc. When it has units 'lkm', all the emission factors must be in 'g/km'. When ed is in g/day, x it is the number of days (without units). When hotfi, hotc or warmc are in g/trip, x it is the number of trips (without units). When hotfi, hotc or warmc are in g/proced, x it is the number of proced (without units).

ed	average daily evaporative emisisions. If x has units 'lkm', the units of ed must be 'g/km', other case, this are simply g/day (without units).
hotfi	average hot running losses or soak evaporative factor for vehicles with fuel injection and returnless fuel systems. If x has units 'lkm', the units of ed must be 'g/km', other case, this are simply g/trip or g/proced
hotc	average running losses or soak evaporative factor for vehicles with carburator or fuel return system for vehicles with fuel injection and returnless fuel systems. If x has units 'lkm', the units of ed must be 'g/km',
warmc	average cold and warm running losses or soak evaporative factor for vehicles with carburator or fuel return system for vehicles with fuel injection and returnless fuel systems. If x has units 'lkm', the units of ed must be 'g/km',
carb	fraction of gasoline vehicles with carburator or fuel return system.
p	Fraction of trips finished with hot engine
params	Character; Add columns with information to returning data.frame
pro_month	Numeric; montly profile to distribute annual mileage in each month.
verbose	Logical; To show more information

**Value**

numeric vector of emission estimation in grams

**Note**

When veh is a "Vehicles" data.frame, emission factors are evaluated till the number of columns of veh. For instance, if the length of the emission factor is 20 but the number of columns of veh is 10, the 10 first emission factors are used.

**References**

Mellios G and Ntziachristos 2016. Gasoline evaporation. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2009

**See Also**

[ef\\_evap](#)

**Examples**

```
## Not run:
(a <- Vehicles(1:10))
(lkm <- units::as_units(1:10, "km"))
(ef <- EmissionFactors(1:10))
(ev <- emis_evap(veh = a, x = lkm, hotfi = ef))

## End(Not run)
```

emis\_evap2

*Estimation of evaporative emissions 2***Description**

emis\_evap performs the estimation of evaporative emissions from EMEP/EEA emission guidelines with Tier 2.

**Usage**

```
emis_evap2(
  veh,
  name,
  size,
  fuel,
  aged,
  nd4,
  nd3,
  nd2,
  nd1,
  hs_nd4,
  hs_nd3,
  hs_nd2,
  hs_nd1,
  r1_nd4,
  r1_nd3,
  r1_nd2,
  r1_nd1,
  d_nd4,
  d_nd3,
  d_nd2,
  d_nd1
)
```

**Arguments**

veh	Total number of vehicles by age of use. If is a list of 'Vehicles' data-frames, it will sum the columns of the eight element of the list representing the 8th hour. It was chosen this hour because it is morning rush hour but the user can adapt the data to this function
name	Character of type of vehicle
size	Character of size of vehicle
fuel	Character of fuel of vehicle
aged	Age distribution vector. E.g.: 1:40
nd4	Number of days with temperature between 20 and 35 celcius degrees

nd3	Number of days with temperature between 10 and 25 celcius degrees
nd2	Number of days with temperature between 0 and 15 celcius degrees
nd1	Number of days with temperature between -5 and 10 celcius degrees
hs_nd4	average daily hot-soak evaporative emissions for days with temperature between 20 and 35 celcius degrees
hs_nd3	average daily hot-soak evaporative emissions for days with temperature between 10 and 25 celcius degrees
hs_nd2	average daily hot-soak evaporative emissions for days with temperature between 0 and 15 celcius degrees
hs_nd1	average daily hot-soak evaporative emissions for days with temperature between -5 and 10 celcius degrees
r1_nd4	average daily running losses evaporative emissions for days with temperature between 20 and 35 celcius degrees
r1_nd3	average daily running losses evaporative emissions for days with temperature between 10 and 25 celcius degrees
r1_nd2	average daily running losses evaporative emissions for days with temperature between 0 and 15 celcius degrees
r1_nd1	average daily running losses evaporative emissions for days with temperature between -5 and 10 celcius degrees
d_nd4	average daily diurnal evaporative emissions for days with temperature between 20 and 35 celcius degrees
d_nd3	average daily diurnal evaporative emissions for days with temperature between 10 and 25 celcius degrees
d_nd2	average daily diurnal evaporative emissions for days with temperature between 0 and 15 celcius degrees
d_nd1	average daily diurnal evaporative emissions for days with temperature between -5 and 10 celcius degrees

**Value**

dataframe of emission estimation in grams/days

**References**

Mellios G and Ntziachristos 2016. Gasoline evaporation. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2009

**Examples**

```
## Not run:
data(net)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
133833,138441,142682,171029,151048,115228,98664,126444,101027,
84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
```

```

veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
ef1 <- ef_evap(ef = "erhotc", v = "PC", cc = "<=1400", dt = "0_15", ca = "no")
dfe <- emis_evap2(veh = pc1,
  name = "PC",
  size = "<=1400",
  fuel = "G",
  aged = 1:ncol(pc1),
  nd4 = 10,
  nd3 = 4,
  nd2 = 2,
  nd1 = 1,
  hs_nd4 = ef1*1:ncol(pc1),
  hs_nd3 = ef1*1:ncol(pc1),
  hs_nd2 = ef1*1:ncol(pc1),
  hs_nd1 = ef1*1:ncol(pc1),
  d_nd4 = ef1*1:ncol(pc1),
  d_nd3 = ef1*1:ncol(pc1),
  d_nd2 = ef1*1:ncol(pc1),
  d_nd1 = ef1*1:ncol(pc1),
  r1_nd4 = ef1*1:ncol(pc1),
  r1_nd3 = ef1*1:ncol(pc1),
  r1_nd2 = ef1*1:ncol(pc1),
  r1_nd1 = ef1*1:ncol(pc1))
lpc <- list(pc1, pc1, pc1, pc1,
  pc1, pc1, pc1, pc1)
dfe <- emis_evap2(veh = lpc,
  name = "PC",
  size = "<=1400",
  fuel = "G",
  aged = 1:ncol(pc1),
  nd4 = 10,
  nd3 = 4,
  nd2 = 2,
  nd1 = 1,
  hs_nd4 = ef1*1:ncol(pc1),
  hs_nd3 = ef1*1:ncol(pc1),
  hs_nd2 = ef1*1:ncol(pc1),
  hs_nd1 = ef1*1:ncol(pc1),
  d_nd4 = ef1*1:ncol(pc1),
  d_nd3 = ef1*1:ncol(pc1),
  d_nd2 = ef1*1:ncol(pc1),
  d_nd1 = ef1*1:ncol(pc1),
  r1_nd4 = ef1*1:ncol(pc1),
  r1_nd3 = ef1*1:ncol(pc1),
  r1_nd2 = ef1*1:ncol(pc1),
  r1_nd1 = ef1*1:ncol(pc1))

## End(Not run)

```

## Description

`emis_grid` allocates emissions proportionally to each grid cell. The process is performed by intersection between geometries and the grid. It means that requires "sr" according with your location for the projection. It is assumed that `spobj` is a `Spatial*DataFrame` or an "sf" with the pollutants in data. This function returns an object of class "sf".

It is

## Usage

```
emis_grid(spobj = net, g, sr, type = "lines", FN = "sum", flux = TRUE, k = 1)
```

## Arguments

<code>spobj</code>	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf".
<code>g</code>	A grid with class "SpatialPolygonsDataFrame" or "sf".
<code>sr</code>	Spatial reference e.g: 31983. It is required if <code>spobj</code> and <code>g</code> are not projected. Please, see <a href="http://spatialreference.org/">http://spatialreference.org/</a> .
<code>type</code>	type of geometry: "lines", "points" or "polygons".
<code>FN</code>	Character indicating the function. Default is "sum"
<code>flux</code>	Logical, if TRUE, it return flux (mass / area / time (implicit)) in a polygon grid, if false, mass / time (implicit) as points, in a similar fashion as EDGAR provide data.
<code>k</code>	Numeric to multiply emissions

## Note

- 1) If `flux = TRUE` (default), emissions are flux = mass / area / time (implicit), as polygons. If `flux = FALSE`, emissions are mass / time (implicit), as points. Time units are not displayed because each use can have different time units for instance, year, month, hour second, etc.**
- 2) Therefore, it is good practice to have time units in 'spobj'. This implies that spobj MUST include units!.**
- 3) In order to check the sum of the emissions, you must calculate the grid-area in km<sup>2</sup> and multiply by each column of the resulting emissions grid, and then sum.**

## Examples

```
## Not run:
data(net)
g <- make_grid(net, 1/102.47/2) #500m in degrees
names(net)
netsf <- sf::st_as_sf(net)
netg <- emis_grid(spobj = netsf[, c("ldv", "hdv")], g = g, sr= 31983)
plot(netg["ldv"], axes = TRUE)
plot(netg["hdv"], axes = TRUE)
netg <- emis_grid(spobj = netsf[, c("ldv", "hdv")], g = g, sr= 31983, FN = "mean")
plot(netg["ldv"], axes = TRUE)
```

```

plot(netg["hdv"], axes = TRUE)
netg <- emis_grid(spobj = netsf[, c("ldv", "hdv")], g = g, sr= 31983, flux = FALSE)
plot(netg["ldv"], axes = TRUE, pch = 16,
pal = cptcity::cpt(colorRampPalette= TRUE, rev = TRUE), cex = 3)

## End(Not run)

```

emis\_hot\_td

*Estimation of hot exhaust emissions with top-down approach*

## Description

`emis_hot_td` estimates old start emissions with a top-down approach. This is, annual or monthly emissions or region. Specifically, the emissions are estimated for row of the simple feature (row of the spatial feature).

In general was designed so that each simple feature is a region with different average monthly temperature. This function, as other in this package, adapts to the class of the input data. providing flexibility to the user.

## Usage

```
emis_hot_td(veh, lkm, ef, pro_month, params, verbose = FALSE, fortran = FALSE)
```

## Arguments

veh	"Vehicles" data-frame or spatial feature, where columns are the age distribution of that vehicle. and rows each simple feature or region.
lkm	Numeric; mileage by the age of use of each vehicle.
ef	Numeric or data.frame; emission factors. When it is a data.frame number of rows can be for each region, or also, each region repeated along 12 months. For instance, if you have 10 regions the number of rows of ef can also be 120 (10 * 120). when you have emission factors that varies with month, see <a href="#">ef_china</a> .
pro_month	Numeric or data.frame; montly profile to distribute annual mileage in each month. When it is a data.frame, each region (row) can have a different monthly profile.
params	List of parameters; Add columns with information to returning data.frame
verbose	Logical; To show more information
fortran	Logical; to try the fortran calculation.

## Details

List to make easier to use this function.

1. 'pro\_month' is data.frame AND rows of 'ef' and 'veh' are equal.
2. 'pro\_month' is numeric AND rows of 'ef' and 'veh' are equal.

3. 'pro\_month' is data.frame AND rows of 'ef' is 12X rows of 'veh'.
4. 'pro\_month' is numeric AND rows of 'ef' is 12X rows of 'veh'.
5. 'pro\_month' is data.frame AND class of 'ef' is 'units'.
6. 'pro\_month' is numeric AND class of 'ef' is 'units'.
7. NO 'pro\_month' AND class of 'ef' is 'units'.
8. NO 'pro\_month' AND 'ef' is data.frame.
9. 'pro\_month' is numeric AND rows of 'ef' is 12 (monthly 'ef').

### Value

Emissions data.frame

### See Also

[ef\\_ldv\\_speed](#) [ef\\_china](#)

### Examples

```
## Not run:
# Do not run
euros <- c("V", "V", "IV", "III", "II", "I", "PRE", "PRE")
efh <- ef_ldv_speed(v = "PC", t = "4S", cc = "<=1400", f = "G",
  eu = euros, p = "CO", speed = Speed(34))
lkm <- units::as_units(c(20:13), "km")*1000
veh <- age_ldv(1:10, agemax = 8)
system.time(
a <- emis_hot_td(veh = veh,
  lkm = lkm,
  ef = EmissionFactors(as.numeric(efh[, 1:8])),
  verbose = TRUE))

system.time(
a2 <- emis_hot_td(veh = veh,
  lkm = lkm,
  ef = EmissionFactors(as.numeric(efh[, 1:8])),
  verbose = TRUE,
  fortran = TRUE)) #emistd7f.f95

identical(a, a2)

# adding columns
emis_hot_td(veh = veh,
  lkm = lkm,
  ef = EmissionFactors(as.numeric(efh[, 1:8])),
  verbose = TRUE,
  params = list(paste0("data_", 1:10), "moredata"))

# monthly profile (numeric) with numeric ef
veh_month <- c(rep(8, 1), rep(10, 5), 9, rep(10, 5))
system.time(
aa <- emis_hot_td(veh = veh,
  lkm = lkm,
```



```

        ef = EmissionFactors(as.numeric(efh[, 1:8])),
        pro_month = veh_month,
        verbose = TRUE))

system.time(
aa2 <- emis_hot_td(veh = veh,
                  lkm = lkm,
                  ef = EmissionFactors(as.numeric(efh[, 1:8])),
                  pro_month = veh_month,
                  verbose = TRUE,
                  fortran = TRUE)) #emistd5f.f95
aa$emissions <- round(aa$emissions, 8)
aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)

# monthly profile (numeric) with data.frame ef
veh_month <- c(rep(8, 1), rep(10, 5), 9, rep(10, 5))
def <- matrix(EmissionFactors(as.numeric(efh[, 1:8])),
              nrow = nrow(veh), ncol = ncol(veh), byrow = TRUE)
def <- EmissionFactors(def)
system.time(
aa <- emis_hot_td(veh = veh,
                  lkm = lkm,
                  ef = def,
                  pro_month = veh_month,
                  verbose = TRUE))

system.time(
aa2 <- emis_hot_td(veh = veh,
                  lkm = lkm,
                  ef = def,
                  pro_month = veh_month,
                  verbose = TRUE,
                  fortran = TRUE)) #emistd1f.f95
aa$emissions <- round(aa$emissions, 8)
aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)

# monthly profile (data.frame)
dfm <- matrix(c(rep(8, 1), rep(10, 5), 9, rep(10, 5)), nrow = 10, ncol = 12,
              byrow = TRUE)
system.time(
aa <- emis_hot_td(veh = veh,
                  lkm = lkm,
                  ef = EmissionFactors(as.numeric(efh[, 1:8])),
                  pro_month = dfm,
                  verbose = TRUE))

system.time(
aa2 <- emis_hot_td(veh = veh,
                  lkm = lkm,
                  ef = EmissionFactors(as.numeric(efh[, 1:8])),
                  pro_month = dfm,
                  verbose = TRUE,
                  fortran = TRUE)) # emistd6f.f95
aa$emissions <- round(aa$emissions, 2)

```

```

aa2$emissions <- round(aa2$emissions, 2)
identical(aa, aa2)

# Suppose that we have a EmissionsFactor data.frame with number of rows for each month
# number of rows are 10 regions
# number of columns are 12 months
tem <- runif(n = 6*10, min = -10, max = 35)
temp <- c(rev(tem[order(tem)]), tem[order(tem)])
plot(temp)
dftemp <- celsius(matrix(temp, ncol = 12))
dfef <- ef_evap(ef = c(rep("eshotfi", 8)),
               v = "PC",
               cc = "<=1400",
               dt = dftemp,
               show = F,
               ca = "small",
               ltrip = units::set_units(10, km),
               pollutant = "NMHC")
dim(dfef) # 120 rows and 9 columns, 8 ef (g/km) and 1 for month
system.time(
aa <- emis_hot_td(veh = veh,
                 lkm = lkm,
                 ef = dfef,
                 pro_month = veh_month,
                 verbose = TRUE))

system.time(
aa2 <- emis_hot_td(veh = veh,
                  lkm = lkm,
                  ef = dfef,
                  pro_month = veh_month,
                  verbose = TRUE,
                  fortran = TRUE)) #emistd3f.f95
aa$emissions <- round(aa$emissions, 2)
aa2$emissions <- round(aa2$emissions, 2)
identical(aa, aa2)
plot(aggregate(aa$emissions, by = list(aa$month), sum)$x)

# Suppose that we have a EmissionsFactor data.frame with number of rows for each month
# monthly profile (data.frame)
system.time(
aa <- emis_hot_td(veh = veh,
                 lkm = lkm,
                 ef = dfef,
                 pro_month = dfm,
                 verbose = TRUE))

system.time(
aa2 <- emis_hot_td(veh = veh,
                  lkm = lkm,
                  ef = dfef,
                  pro_month = dfm,
                  verbose = TRUE,
                  fortran = TRUE)) #emistd4f.f95
aa$emissions <- round(aa$emissions, 8)

```

```

aa2$emissions <- round(aa2$emissions, 8)
identical(aa, aa2)
plot(aggregate(aa$emissions, by = list(aa$month), sum)$x)

## End(Not run)

```

emis\_merge

*Merge several emissions files returning data-frames or 'sf' of lines***Description**

`emis_merge` reads rds files and returns a data-frame or an object of 'spatial feature' of streets, merging several files.

**Usage**

```

emis_merge(
  pol = "CO",
  what = "STREETS.rds",
  streets = T,
  net,
  FN = "sum",
  ignore,
  path = "emi",
  crs,
  under = "after",
  as_list = FALSE,
  k = 1,
  verbose = TRUE
)

```

**Arguments**

<code>pol</code>	Character. Pollutant.
<code>what</code>	Character. Word to search the emissions names, "STREETS", "DF" or whatever name. It is important to include the extension '.rds'. For instance, If you have several files "XX_CO_STREETS.rds", what should be "STREETS.rds"
<code>streets</code>	Logical. If true, <code>emis_merge</code> will read the street emissions created with <code>emis_post</code> by "streets_wide", returning an object with class 'sf'. If false, it will read the emissions data-frame and rbind them.
<code>net</code>	'Spatial feature' or 'SpatialLinesDataFrame' with the streets. It is expected # that the number of rows is equal to the number of rows of street emissions. If # not, the function will stop.
<code>FN</code>	Character indicating the function. Default is "sum"
<code>ignore</code>	Character; Which pollutants or other charavter would you like to remove?
<code>path</code>	Character. Path where emissions are located

crs	coordinate reference system in numeric format from <a href="http://spatialreference.org/">http://spatialreference.org/</a> to transform/project spatial data using <code>sf::st_transform</code>
under	"Character"; "after" when you stored your pollutant x as ' <code>X_</code> ' "before" when ' <code>_X</code> ' and "none" for merging directly the files.
as_list	"Logical"; for returning the results as list or not.
k	factor
verbose	Logical to display more information or not. Default is TRUE

**Value**

'Spatial feature' of lines or a dataframe of emissions

**Examples**

```
## Not run:
# Do not run

## End(Not run)
```

---

emis\_order

*Re-order the emission to match specific hours and days*


---

**Description**

Emissions are usually estimated for a year, 24 hours or one week from monday to sunday (with 168 hours). This depends on the availability of traffic data. When an air quality simulation is going to be done, they cover specific periods of time. For instance, WRF Chem emissions files supports periods of time, or two emissions sets for a representative day (0-12z 12-0z). Also a WRF Chem simulation scan starts a thursday at 00:00 UTC, cover 271 hours of simulations, but hour emissions are in local time and cover only 168 hours starting on monday. This function tries to transform our emissions in local time to the desired utc time, by recycling the local emissions.

**Usage**

```
emis_order(
  x,
  lt_emissions,
  start_utc_time,
  desired_length,
  tz_lt = Sys.timezone(),
  seconds = 0,
  k = 1,
  net,
  verbose = TRUE
)
```

**Arguments**

x	one of the following: <ul style="list-style-type: none"> <li>• Spatial object of class "Spatial". Columns are hourly emissions.</li> <li>• Spatial Object of class "sf". Columns are hourly emissions.</li> <li>• "data.frame", "matrix" or "Emissions".</li> </ul> In all cases, columns are hourly emissions.
lt_emissions	Local time of the emissions at first hour. It must be the <b>before</b> time of start_utc_time. For instance, if start_utc_time is 2020-02-02 00:00, and your emissions starts monday at 00:00, your lt_emissions must be 2020-01-27 00:00. The argument tz_lt will detect your current local time zone and do the rest for you.
start_utc_time	UTC time for the desired first hour. For instance, the first hour of the namelist.input for WRF.
desired_length	Integer; length to recycle or subset local emissions. For instance, the length of the WRF Chem simulations, states at namelist.input.
tz_lt	Character, Time zone of the local emissions. Default value is derived from Sys.timezone(), however, it accepts any other. If you enter a wrong tz, this function will show you a menu to choose one of the 697 time zones available.
seconds	Number of seconds to add
k	Numeric, factor.
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING".
verbose	Logical, to show more information, default is TRUE.

**Value**

sf or data.frame

**See Also**

[GriddedEmissionsArray](#)

**Examples**

```
## Not run:
#do not run
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
         133833,138441,142682,171029,151048,115228,98664,126444,101027,
         84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
         1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
```

```

pckm <- units::set_units(fkm[[1]](1:24), "km")
pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", t = "4S", cc = "<=1400",
                    f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile, simplify = TRUE)
class(E_CO)
E_CO_STREETS <- emis_post(arra = E_CO, pollutant = "CO", by = "streets", net = net)
g <- make_grid(net, 1/102.47/2, 1/102.47/2) #500m in degrees
E_CO_g <- emis_grid(spobj = E_CO_STREETS, g = g, sr= 31983)
head(E_CO_g) #class sf
gr <- GriddedEmissionsArray(E_CO_g, rows = 19, cols = 23, times = 168, T)
wCO <- emis_order(x = E_CO_g,
                  lt_emissions = "2020-02-19 00:00",
                  start_utc_time = "2020-02-20 00:00",
                  desired_length = 241)

## End(Not run)

```

emis\_paved

*Estimation of resuspension emissions from paved roads***Description**

emis\_paved estimates vehicular emissions from paved roads. The vehicular emissions are estimated as the product of the vehicles on a road, length of the road, emission factor from AP42 13.2.1 Paved roads. It is assumed dry hours and annual aggregation should consider moisture factor. It depends on Average Daily Traffic (ADT)

**Usage**

```

emis_paved(
  veh,
  adt,
  lkm,
  k = 0.62,
  sL1 = 0.6,
  sL2 = 0.2,
  sL3 = 0.06,
  sL4 = 0.03,
  W,
  net = net
)

```

**Arguments**

veh	Numeric vector with length of elements equals to number of streets It is an array with dimensions number of streets x hours of day x days of week
adt	Numeric vector of with Average Daily Traffic (ADT)
lkm	Length of each link
k	K_PM30 = 3.23 (g/vkm), K_PM15 = 0.77 (g/vkm), K_PM10 = 0.62 (g/vkm) and K_PM2.5 = 0.15 (g/vkm).
sL1	Silt loading (g/m2) for roads with ADT <= 500
sL2	Silt loading (g/m2) for roads with ADT > 500 and <= 5000
sL3	Silt loading (g/m2) for roads with ADT > 5000 and <= 1000
sL4	Silt loading (g/m2) for roads with ADT > 10000
W	array of dimensions of veh. It consists in the hourly averaged weight of traffic fleet in each road
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"

**Value**

emission estimation g/h

**Note**

silt values can vary a lot. For comparison:

ADT	US-EPA g/m2	CENMA (Chile) g/m2
< 500	0.6	2.4
500-5000	0.2	0.7
5000-1000	0.06	0.6
>10000	0.03	0.3

**References**

EPA, 2016. Emission factor documentation for AP-42. Section 13.2.1, Paved Roads. <https://www3.epa.gov/ttn/chief/ap42/ch>

CENMA Chile: Actualizacion de inventario de emisiones de contaminantes atmosfericos RM 2020 Universidad de Chile#'

**Examples**

```
## Not run:
# Do not run
veh <- matrix(1000, nrow = 10, ncol = 10)
W <- veh*1.5
lkm <- 1:10
ADT <- 1000:1010
emi <- emis_paved(veh = veh, adt = ADT, lkm = lkm, k = 0.65, W = W)
class(emi)
```

```
head(emi)

## End(Not run)
```

---

emis_post	<i>Post emissions</i>
-----------	-----------------------

---

### Description

emis\_post simplify emissions estimated as total per type category of vehicle or by street. It reads EmissionsArray and Emissions classes. It can return an dataframe with hourly emissions at each street, or a data base with emissions by vehicular category, hour, including size, fuel and other characteristics.

### Usage

```
emis_post(arr, veh, size, fuel, pollutant, by = "veh", net, type_emi, k = 1)
```

### Arguments

arr	Array of emissions 4d: streets x category of vehicles x hours x days or 3d: streets x category of vehicles x hours
veh	Character, type of vehicle
size	Character, size or weight
fuel	Character, fuel
pollutant	Pollutant
by	Type of output, "veh" for total vehicular category , "streets_narrow" or "streets". "streets" returns a dataframe with rows as number of streets and columns the hours as days*hours considered, e.g. 168 columns as the hours of a whole week and "streets repeats the row number of streets by hour and day of the week
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING". Only when by = 'streets_wide'
type_emi	Character, type of emissions(exhaust, evaporative, etc)
k	Numeric, factor

### Note

This function depends on EmissionsArray objects which currently has 4 dimensions. However, a future version of VEIN will produce EmissionsArray with 3 dimensiones and his fungeorge soros drugsectio also will change. This change will be made in order to not produce inconsistencies with previous versions, therefore, if the user count with an EmissionsArry with 4 dimension, it will be able to use this function.



## Examples

```

## Not run:
# Do not run
data(net)
data(pc_profile)
data(fe2015)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
          133833,138441,142682,171029,151048,115228,98664,126444,101027,
          84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
          1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
# Estimation for morning rush hour and local emission factors
speed <- data.frame(S8 = net$ps)
p1h <- matrix(1)
lef <- EmissionFactorsList(fe2015[fe2015$Pollutant=="CO", "PC_G"])
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed,
            profile = p1h)
E_CO_STREETS <- emis_post(arr = E_CO, pollutant = "CO", by = "streets_wide")
summary(E_CO_STREETS)
E_CO_STREETSsf <- emis_post(arr = E_CO, pollutant = "CO",
                           by = "streets", net = net)
summary(E_CO_STREETSsf)
plot(E_CO_STREETSsf, main = "CO emissions (g/h)")
# arguments required: arr, veh, size, fuel, pollutant ad by
E_CO_DF <- emis_post(arr = E_CO, veh = "PC", size = "<1400", fuel = "G",
                    pollutant = "CO", by = "veh")
# Estimation 168 hours
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24),"km"); pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckm[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckm[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(dfcol = cod, v = "PC", cc = "<=1400",
                   f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile)
# arguments required: arr, pollutant ad by
E_CO_STREETS <- emis_post(arr = E_CO, pollutant = "CO", by = "streets")
summary(E_CO_STREETS)
# arguments required: arr, veh, size, fuel, pollutant ad by
E_CO_DF <- emis_post(arr = E_CO, veh = "PC", size = "<1400", fuel = "G",
                    pollutant = "CO", by = "veh")
head(E_CO_DF)
# recreating 24 profile
lpc <-list(pc1*0.2, pc1*0.1, pc1*0.1, pc1*0.2, pc1*0.5, pc1*0.8,
          pc1, pc1*1.1, pc1,
          pc1*0.8, pc1*0.5, pc1*0.5,

```

```

pc1*0.5, pc1*0.5, pc1*0.5, pc1*0.8,
pc1, pc1*1.1, pc1,
pc1*0.8, pc1*0.5, pc1*0.3, pc1*0.2, pc1*0.1)
E_COv2 <- emis(veh = lpc, lkm = net$lkm, ef = lef, speed = speed[, 1:24],
             agemax = 41, hour = 24, day = 1)
plot(E_COv2)
E_CO_DFv2 <- emis_post(arr = E_COv2,
                     veh = "PC",
                     size = "<1400",
                     fuel = "G",
                     type_emi = "Exhaust",
                     pollutant = "CO", by = "veh")

head(E_CO_DFv2)

## End(Not run)

```

---

emis\_source

*A function to source vein scripts*


---

## Description

[emis\\_source](#) source vein scripts

## Usage

```

emis_source(
  path = "est",
  pattern = ".R",
  ignore = "~",
  first,
  ask = TRUE,
  recursive = TRUE,
  full.names = TRUE,
  echo = FALSE
)

```

## Arguments

path	Character; path to source scripts. Default is "est".
pattern	Character; extensions of R scripts. Default is ".R".
ignore	Character; character to be excluded. Default is "~". Sometimes, the OS creates automatic back-ups, for instance "run.R~", the idea is to avoid sourcing these files.
first	Character; first script.
ask	Logical; Check inputs or not. Default is "FALSE". It allows to stop inputs
recursive	Logical; recursive or not. Default is "TRUE"
full.names	Logical; full.names or not. Default is "TRUE".
echo	Source with echo?

**Examples**

```
## Not run:
# Do not run

## End(Not run)
```

---

emis_to_streets	<i>Emis to streets distribute top-down emissions into streets</i>
-----------------	---

---

**Description**

`emis_to_streets` allocates emissions proportionally to each feature. "Spatial" objects are converted to "sf" objects. Currently, 'LINESTRING' or 'MULTILINESTRING' supported. The emissions are distributed in each street.

**Usage**

```
emis_to_streets(streets, dfemis, by = "ID", stpro, verbose = TRUE)
```

**Arguments**

streets	sf object with geometry 'LINESTRING' or 'MULTILINESTRING'. Or SpatialLinesDataFrame
dfemis	data.frame with emissions
by	Character indicating the columns that must be present in both 'street' and 'dfemis'
stpro	data.frame with two columns, category of streets and value. The name of the first column must be "stpro" and the sf streets must also have a column with the name "stpro" indicating the category of streets. The second column must have the name "VAL" indicating the associated values to each category of street
verbose	Logical; to show more info.

**Note**

When `spobj` is a 'Spatial' object (class of `sp`), they are converted into 'sf'.

**See Also**

[add\\_polid](#)

**Examples**

```
## Not run:
data(net)
stpro = data.frame(stpro = as.character(unique(net$street)),
                  VAL = 1:9)
dnet <- net["ldv"]
dnet$stpro <- as.character(net$street)
```

```

dnet$ID <- "A"
df2 <- data.frame(BC = 10, CO = 20, ID = "A")
ste <- emis_to_streets(streets = dnet, dfemis = df2)
sum(ste$ldv)
sum(net$ldv)
sum(ste$BC)
sum(df2$BC)
ste2 <- emis_to_streets(streets = dnet, dfemis = df2, stpro = stpro)
sum(ste2$ldv)
sum(net$ldv)
sum(ste2$BC)
sum(df2$BC)

## End(Not run)

```

emis\_wear

*Emission estimation from tyre, break and road surface wear***Description**

emis\_wear estimates wear emissions. The sources are tyres, breaks and road surface.

**Usage**

```

emis_wear(
  veh,
  lkm,
  ef,
  what = "tyre",
  speed,
  agemax = ncol(veh),
  profile,
  hour = nrow(profile),
  day = ncol(profile)
)

```

**Arguments**

veh	Object of class "Vehicles"
lkm	Length of the road in km.
ef	list of emission factor functions class "EmissionFactorsList", length equals to hours.
what	Character for indicating "tyre", "break" or "road"
speed	Speed data-frame with number of columns as hours
agemax	Age of oldest vehicles for that category
profile	Numerical or dataframe with nrow equal to 24 and ncol 7 day of the week
hour	Number of considered hours in estimation
day	Number of considered days in estimation

**Value**

emission estimation g/h

**References**

Ntziachristos and Boulter 2016. Automobile tyre and break wear and road abrasion. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

**Examples**

```
## Not run:
data(net)
data(pc_profile)
pc_week <- temp_fact(net$ldv[1:10] + net$hdv[1:10], pc_profile[, 1])
df <- netspeed(pc_week, net$ps[1:10], net$ffs[1:10],
              net$capacity[1:10], net$lkm[1:10], alpha = 1)
ef <- ef_wear(wear = "tyre", type = "PC", pol = "PM10", speed = df)
emi <- emis_wear(veh = age_ldv(net$ldv[1:10], name = "VEH"),
               lkm = net$lkm[1:10], ef = ef, speed = df,
               profile = pc_profile[, 1])

emi

## End(Not run)
```

fe2015

*Emission factors from Environmental Agency of Sao Paulo CETESB***Description**

A dataset containing emission factors from CETESB and its equivalency with EURO

**Usage**

```
data(fe2015)
```

**Format**

A data frame with 288 rows and 12 variables:

**Age** Age of use

**Year** Year of emission factor

**Pollutant** Pollutants included: "CH4", "CO", "CO2", "HC", "N2O", "NMHC", "NOx", and "PM"

**Proconve\_LDV** Proconve emission standard: "PP", "L1", "L2", "L3", "L4", "L5", "L6"

**t\_Euro\_LDV** Euro emission standard equivalence: "PRE\_ECE", "I", "II", "III", "IV", "V"

**Euro\_LDV** Euro emission standard equivalence: "PRE\_ECE", "I", "II", "III", "IV", "V"

**Proconve\_HDV** Proconve emission standard: "PP", "P1", "P2", "P3", "P4", "P5", "P7"

**Euro\_HDV** Euro emission standard equivalence: "PRE", "I", "II", "III", "V"

**PC\_G** CETESB emission standard for Passenger Cars with Gasoline (g/km)

**LT** CETESB emission standard for Light Trucks with Diesel (g/km)

### Source

CETESB

---

fkm

*List of functions of mileage in km fro Brazilian fleet*

---

### Description

Functions from CETESB: Antonio de Castro Bruni and Marcelo Pereira Bales. 2013. Curvas de intensidade de uso por tipo de veiculo automotor da frota da cidade de Sao Paulo This functions depends on the age of use of the vehicle

### Usage

data(fkm)

### Format

A data frame with 288 rows and 12 variables:

**KM\_PC\_E25** Mileage in km of Passenger Cars using Gasoline with 25% Ethanol

**KM\_PC\_E100** Mileage in km of Passenger Cars using Ethanol 100%

**KM\_PC\_FLEX** Mileage in km of Passenger Cars using Flex engines

**KM\_LCV\_E25** Mileage in km of Light Commercial Vehicles using Gasoline with 25% Ethanol

**KM\_LCV\_FLEX** Mileage in km of Light Commercial Vehicles using Flex

**KM\_PC\_B5** Mileage in km of Passenger Cars using Diesel with 5% biodiesel

**KM\_TRUCKS\_B5** Mileage in km of Trucks using Diesel with 5% biodiesel

**KM\_BUS\_B5** Mileage in km of Bus using Diesel with 5% biodiesel

**KM\_LCV\_B5** Mileage in km of Light Commercial Vehicles using Diesel with 5% biodiesel

**KM\_SBUS\_B5** Mileage in km of Small Bus using Diesel with 5% biodiesel

**KM\_ATRUCKS\_B5** Mileage in km of Articulated Trucks using Diesel with 5% biodiesel

**KM\_MOTO\_E25** Mileage in km of Motorcycles using Gasoline with 25% Ethanol

**KM\_LDV\_GNV** Mileage in km of Light Duty Vehicles using Natural Gas

### Source

CETESB

---

fuel_corr	<i>Correction due Fuel effects</i>
-----------	------------------------------------

---

**Description**

Take into account the effect of better fuels on vehicles with older technology. If the ratio is less than 1, return 1. It means that it is not a degradation function.

**Usage**

```
fuel_corr(
  euro,
  g = c(e100 = 52, aro = 39, o2 = 0.4, e150 = 86, olefin = 10, s = 165),
  d = c(den = 840, pah = 9, cn = 51, t95 = 350, s = 400)
)
```

**Arguments**

euro	Character; Euro standards ("PRE", "I", "II", "III", "IV", "V", VI, "VIc")
g	Numeric; vector with parameters of gasoline with the names: e100(vol. sulphur, ppm)
d	Numeric; vector with parameters for diesel with the names: den (density at 15 celcius degrees kg/m3), pah (Back end distillation in Celcius degrees) and s (sulphur, ppm)

**Value**

A list with the correction of emission factors.

**Note**

This function cannot be used to account for deterioration, therefore, it is restricted to values between 0 and 1. Parameters for gasoline (g):

O2 = Oxygenates in

S = Sulphur content in ppm

ARO = Aromatics content in

OLEFIN = Olefins content in

E100 = Mid range volatility in

E150 = Tail-end volatility in

Parameters for diesel (d):

DEN = Density at 15 C (kg/m3)

S = Sulphur content in ppm

PAH = Aromatics content in

CN = Cetane number

T95 = Back-end distillation in o C.

**Examples**

```
## Not run:
f <- fuel_corr(euro = "I")
names(f)

## End(Not run)
```

---

<code>get_project</code>	<i>Download vein project</i>
--------------------------	------------------------------

---

**Description**

`get_project` downloads a project for running vein. The projects are available on [Github.com/atmoschem/vein/projects](https://github.com/atmoschem/vein/projects)

**Usage**

```
get_project(directory, case = "brasil")
```

**Arguments**

`directory` Character; Path to an existing or a new directory to be created. It needs absolute path.

`case` Character; One of of the following:

<b>case</b>	<b>Description</b>	<b>EF</b>	<b>Outputs</b>
brazil or brazil_bu or brasil or brasil_bu	Bottom-up	CETESB	.rds
emislacovid	Bottom-up March 2020	CETESB	.rds
brazil_bu_csvgz	Bottom-up	CETESB	.csv.gz
brazil_bu_csv	Bottom-up. Faster but heavier	CETESB	.csv
brazil_bu_cb05	Bottom-up CB05	CETESB	.rds

**Note**

default case can be any of "brasil", "brazil", "brazil\_bu", "brasil\_bu", they are the same

**Examples**

```
## Not run:
#do not run
get_project("awesomecity")

## End(Not run)
```



---

GriddedEmissionsArray *Construction function for class "GriddedEmissionsArray"*

---

### Description

GriddedEmissionsArray returns a tranformed object with class "EmissionsArray" with 4 dimen-  
sions.

### Usage

```
GriddedEmissionsArray(x, ..., cols, rows, times = ncol(x), rotate, flip = TRUE)
```

```
## S3 method for class 'GriddedEmissionsArray'  
print(x, ...)
```

```
## S3 method for class 'GriddedEmissionsArray'  
summary(object, ...)
```

```
## S3 method for class 'GriddedEmissionsArray'  
plot(x, ..., times = 1)
```

### Arguments

x	Object with class "SpatialPolygonDataFrame", "sf" "data.frame" or "matrix"
...	ignored
cols	Number of columns
rows	Number of rows
times	Number of times
rotate	Character, rotate array to "left" or "right"
flip	Logical, To flip vertically the array or not
object	object with class "EmissionsArray"

### Value

Objects of class "GriddedEmissionsArray"

### Examples

```
## Not run:  
data(net)  
data(pc_profile)  
data(fe2015)  
data(fkm)  
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,  
133833,138441,142682,171029,151048,115228,98664,126444,101027,  
84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
```

```

      1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
veh <- data.frame(PC_G = PC_G)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
pcw <- temp_fact(net$ldv+net$hdv, pc_profile)
speed <- netspeed(pcw, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
pckm <- units::set_units(fkm[[1]](1:24), "km")
pckma <- cumsum(pckm)
cod1 <- emis_det(po = "CO", cc = 1000, eu = "III", km = pckma[1:11])
cod2 <- emis_det(po = "CO", cc = 1000, eu = "I", km = pckma[12:24])
#vehicles newer than pre-euro
co1 <- fe2015[fe2015$Pollutant=="CO", ] #24 obs!!!
cod <- c(co1$PC_G[1:24]*c(cod1,cod2),co1$PC_G[25:nrow(co1)])
lef <- ef_ldv_scaled(co1, cod, v = "PC", t = "4S", cc = "<=1400",
                    f = "G",p = "CO", eu=co1$Euro_LDV)
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef, speed = speed, agemax = 41,
            profile = pc_profile, simplify = TRUE)
class(E_CO)
E_CO_STREETS <- emis_post(arras = E_CO, pollutant = "CO", by = "streets",
                        net = net, k = units::set_units(1, "1/h"))
g <- make_grid(net, 1/102.47/2, 1/102.47/2) #500m in degrees
E_CO_g <- emis_grid(spobj = E_CO_STREETS, g = g, sr= 31983)
plot(E_CO_g["V9"])
gr <- GriddedEmissionsArray(E_CO_g, rows = 19, cols = 23, times = 168, flip = FALSE)
plot(gr)
# For some cptcity color gradients:
plot(gr, col = cptcity::lucky())

## End(Not run)

```

---

grid\_emis

*Allocate emissions gridded emissions into streets (grid to emis street)*


---

## Description

`grid_emis` it is sort of the opposite of `emis_grid`. It allocates gridded emissions into streets. This function applies `emis_dist` into each grid cell using `lapply`. This function is in development and pull request are welcome.

## Usage

```
grid_emis(spobj, g, top_down = FALSE, sr, pro, char, verbose = FALSE)
```

## Arguments

spobj	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf".
g	A grid with class "SpatialPolygonsDataFrame" or "sf". This grid includes the total emissions with the column "emission". If profile is going to be used, the column 'emission' must include the sum of the emissions for each profile. For

	instance, if profile covers the hourly emissions, the column 'emission' must be the sum of the hourly emissions.
top_down	Logical; requires emissions named 'emissions' and allows to apply profile factors. If your data is hourly emissions or a spatial grid with several emissions at different hours, being each hour a column, it is better to use top_down = FALSE. In this way all the hourly emissions are considered, however, each hourly emissions has to have the name "V" and the number of the hour like "V1"
sr	Spatial reference e.g: 31983. It is required if spobj and g are not projected. Please, see <a href="http://spatialreference.org/">http://spatialreference.org/</a> .
pro	Numeric, Matrix or data-frame profiles, for instance, pc_profile.
char	Character, name of the first letter of hourly emissions. New variables in R start with letter "V", for your hourly emissions might start with letter "h". This option applies when top_down is FALSE. For instance, if your hourly emissions are: "h1", "h2", "h3"... 'char' can be "h"
verbose	Logical; to show more info.

### Note

**Your gridded emissions might have flux units (mass / area / time(implicit)) You must multiply your emissions with the area to return to the original units.**

### Examples

```
## Not run:
data(net)
data(pc_profile)
data(fkm)
PC_G <- c(33491,22340,24818,31808,46458,28574,24856,28972,37818,49050,87923,
133833,138441,142682,171029,151048,115228,98664,126444,101027,
84771,55864,36306,21079,20138,17439, 7854,2215,656,1262,476,512,
1181, 4991, 3711, 5653, 7039, 5839, 4257,3824, 3068)
pc1 <- my_age(x = net$ldv, y = PC_G, name = "PC")
# Estimation for morning rush hour and local emission factors
lef <- EmissionFactorsList(ef_cetesb("CO", "PC_G"))
E_CO <- emis(veh = pc1,lkm = net$lkm, ef = lef,
profile = 1, speed = Speed(1))
E_CO_STREETS <- emis_post(arrs = E_CO, by = "streets", net = net)

g <- make_grid(net, 1/102.47/2) #500m in degrees

gCO <- emis_grid(spobj = E_CO_STREETS, g = g)
gCO$emission <- gCO$V1
area <- sf::st_area(gCO)
area <- units::set_units(area, "km^2") #Check units!
gCO$emission <- gCO$emission*area
#
\dontrun{
#do not run
library(osmdata)
library(sf)
```

```

osm <- osmdata_sf(
  add_osm_feature(
    opq(bbox = st_bbox(gCO)),
    key = 'highway')$osm_lines[, c("highway")]
st <- c("motorway", "motorway_link", "trunk", "trunk_link",
"primary", "primary_link", "secondary", "secondary_link",
"tertiary", "tertiary_link")
osm <- osm[osm$highway %in% st, ]
plot(osm, axes = T)
# top_down requires name `emissions` into gCO`
xnet <- grid_emis(osm, gCO, top_down = TRUE)
plot(xnet, axes = T)
# bottom_up requires that emissions are named `V` plus the hour like `V1`
xnet <- grid_emis(osm, gCO, top_down= FALSE)
plot(xnet["V1"], axes = T)
}

## End(Not run)

```

---

invcop

*Helper function to copy and zip projects*


---

## Description

invcop help to copy and zip projects

## Usage

```

invcop(
  in_name = getwd(),
  out_name,
  all = FALSE,
  main = TRUE,
  ef = TRUE,
  est = TRUE,
  network = TRUE,
  veh_rds = FALSE,
  veh_csv = TRUE,
  zip = TRUE
)

```

## Arguments

in_name	Character; Name of current project.
out_name	Character; Name of output project.
all	Logical; copy ALL (and for once) or not.
main	Logical; copy or not.

ef	Logical; copy or not.
est	Logical; copy or not.
network	Logical; copy or not.
veh_rds	Logical; copy or not.
veh_csv	Logical; copy or not.
zip	Logical; zip or not.

**Value**

emission estimation g/h

**Note**

This function was created to copy and zip project without the emis.

**Examples**

```
## Not run:
# Do not run

## End(Not run)
```

---

inventory	<i>Inventory function.</i>
-----------	----------------------------

---

**Description**

inventory produces an structure of directories and scripts in order to run vein. It is required to know the vehicular composition of the fleet.

**Usage**

```
inventory(
  name,
  vehcomp = c(PC = 1, LCV = 1, HGV = 1, BUS = 1, MC = 1),
  show.main = FALSE,
  scripts = TRUE,
  show.dir = FALSE,
  show.scripts = FALSE,
  clear = TRUE,
  rush.hour = FALSE,
  showWarnings = FALSE
)
```

**Arguments**

name	Character, path to new main directory for running vein. NO BLANK SPACES
vehcomp	Vehicular composition of the fleet. It is required a named numerical vector with the names "PC", "LCV", "HGV", "BUS" and "MC". In the case that there are no vehicles for one category of the composition, the name should be included with the number zero, for example PC = 0. The maximum number allowed is 99 per category.
show.main	Logical; Do you want to see the new main.R file?
scripts	Logical Do you want to generate or no R scripts?
show.dir	Logical value for printing the created directories.
show.scripts	Logical value for printing the created scripts.
clear	Logical value for removing recursively the directory and create another one.
rush.hour	Logical, to create a template for morning rush hour.
showWarnings	Logical, showWarnings?

**Value**

Structure of directories and scripts for automating compilation of vehicular emissions inventory. The structure can be used with other type of sources of emissions. The structure of the directories is: daily, ef, emi, est, images, network and veh. This structure is a suggestion and the user can use another. ' ef: it is for storing the emission factors data-frame, similar to data(fe2015) but including one column for each of the categories of the vehicular composition. For instance, if PC = 5, there should be 5 columns with emission factors in this file. If LCV = 5, another 5 columns should be present, and so on.

emi: Directory for saving the estimates. It is suggested to use .rds extension instead of .rda.

est: Directory with subdirectories matching the vehicular composition for storing the scripts named input.R.

images: Directory for saving images.

network: Directory for saving the road network with the required attributes. This file will include the vehicular flow per street to be used by age\* functions.

veh: Directory for storing the distribution by age of use of each category of the vehicular composition. Those are data-frames with number of columns with the age distribution and number of rows as the number of streets. The class of these objects is "Vehicles". Future versions of vein will generate Vehicles objects with the explicit spatial component.

The name of the scripts and directories are based on the vehicular composition, however, there is included a file named main.R which is just an R script to estimate all the emissions. It is important to note that the user must add the emission factors for other pollutants. Also, this function creates the scripts input.R where the user must specify the inputs for the estimation of emissions of each category. Also, there is a file called traffic.R that generates objects of class "Vehicles". The user can rename these scripts.

**Examples**

```
## Not run:  
name = file.path(tempdir(), "YourCity")  
inventory(name = name)  
  
## End(Not run)
```

---

long_to_wide	<i>Transform data.frame from long to wide format</i>
--------------	--

---

**Description**

[long\\_to\\_wide](#) transform data.frame from long to wide format

**Usage**

```
long_to_wide(  
  df,  
  column_with_new_names = names(df)[1],  
  column_with_data = "emission",  
  column_fixed,  
  net  
)
```

**Arguments**

df	data.frame with three column.
column_with_new_names	Character, column that has new column names
column_with_data	Character column with data
column_fixed	Character, column that will remain fixed
net	To return a sf

**Value**

wide data.frame.

**See Also**

[emis\\_hot\\_td](#) [emis\\_cold\\_td](#) [wide\\_to\\_long](#)

**Examples**

```
## Not run:
df <- data.frame(pollutant = rep(c("CO", "propadiene", "NO2"), 10),
  emission = vein::Emissions(1:30),
  region = rep(letters[1:2], 15))
df
long_to_wide(df)
long_to_wide(df, column_fixed = "region")

## End(Not run)
```

---

make_grid	<i>Creates rectangular grid for emission allocation</i>
-----------	---

---

**Description**

make\_grid creates a sf grid of polygons. The spatial reference is taken from the spatial object.

**Usage**

```
make_grid(sproj, width, height = width, polygon, crs = 4326, ...)
```

**Arguments**

sproj	A spatial object of class sp or sf.
width	Width of grid cell. It is recommended to use projected values.
height	Height of grid cell.
polygon	Deprecated! <code>make_grid</code> returns only sf grid of polygons.
crs	coordinate reference system in numeric format from <a href="http://spatialreference.org/">http://spatialreference.org/</a> to transform/project spatial data using <code>sf::st_transform</code> . The default value is 4326
...	ignored

**Value**

A grid of polygons class 'sf'

**Examples**

```
## Not run:
data(net)
grid <- make_grid(net, width = 0.5/102.47) #500 mts
plot(grid, axes = TRUE) #class sf
# make grid now returns warnings for crs with form +init...
#grid <- make_grid(net, width = 0.5/102.47) #500 mts

## End(Not run)
```



---

my_age	<i>Returns amount of vehicles at each age</i>
--------	---

---

### Description

my\_age returns amount of vehicles at each age using a numeric vector.

### Usage

```
my_age(
  x,
  y,
  agemax,
  name = "vehicle",
  k = 1,
  pro_street,
  net,
  verbose = FALSE,
  namerows
)
```

### Arguments

x	Numeric; vehicles by street (or spatial feature).
y	Numeric or data.frame; when pro_street is not available, y must be 'numeric', else, a 'data.frame'. The names of the columns of this data.frame must be the same of the elements of pro_street and each column must have a profile of age of use of vehicle. When 'y' is 'numeric' the vehicles has the same age distribution to all street. When 'y' is a data.frame, the distribution by age of use varies the streets.
agemax	Integer; age of oldest vehicles for that category
name	Character; of vehicle assigned to columns of dataframe.
k	Integer; multiplication factor. If its length is > 1, it must match the length of x
pro_street	Character; each category of profile for each street. The length of this character vector must be equal to the length of 'x'. The names of the data.frame 'y' must be have the same content of 'pro_street'
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
verbose	Logical; message with average age and total number of vehicles.
namerows	Any vector to be change row.names. For instance, name of regions or streets.

### Value

dataframe of age distribution of vehicles.

**Note**

The functions `age*` produce distribution of the circulating fleet by age of use. The order of using these functions is:

1. If you know the distribution of the vehicles by age of use, use: `my_age`
2. If you know the sales of vehicles, or (the `regis`)\*better) the registry of new vehicles, use `age` to apply a survival function.
3. If you know the theoretical shape of the circulating fleet and you can use `age_ldv`, `age_hdv` or `age_moto`. For instance, you don't know the sales or registry of vehicles, but somehow you know the shape of this curve.
4. You can use/merge/transform/adapt any of these functions.

**Examples**

```
## Not run:
data(net)
dpc <- c(seq(1,20,3), 20:10)
PC_E25_1400 <- my_age(x = net$ldv, y = dpc, name = "PC_E25_1400")
class(PC_E25_1400)
plot(PC_E25_1400)
PC_E25_1400sf <- my_age(x = net$ldv, y = dpc, name = "PC_E25_1400", net = net)
class(PC_E25_1400sf)
plot(PC_E25_1400sf)
PC_E25_1400nsf <- sf::st_set_geometry(PC_E25_1400sf, NULL)
class(PC_E25_1400nsf)
yy <- data.frame(a = 1:5, b = 5:1) # perfiles por categoria de calle
pro_street <- c("a", "b", "a") # categorias de cada calle
x <- c(100,5000, 3) # vehiculos
my_age(x = x, y = yy, pro_street = pro_street)

## End(Not run)
```

---

net

*Road network of the west part of Sao Paulo city*


---

**Description**

This dataset is a `sf` class object with roads from a traffic simulations made by CET Sao Paulo, Brazil

**Usage**

```
data(net)
```

**Format**

A Spatial data.frame (`sf`) with 1796 rows and 1 variables:

**ldv** Light Duty Vehicles (veh/h)

**hdv** Heavy Duty Vehicles (veh/h)

**lkm** Length of the link (km)

**ps** Peak Speed (km/h)  
**ffs** Free Flow Speed (km/h)  
**tstreet** Type of street  
**lanes** Number of lanes per link  
**capacity** Capacity of vehicles in each link (1/h)  
**tmin** Time for travelling each link (min)  
**geometry** geometry

---

netspeed                      *Calculate speeds of traffic network*

---

### Description

netspeed Creates a dataframe of speeds for different hours and each link based on morning rush traffic data

### Usage

```
netspeed(q = 1, ps, ffs, cap, lkm, alpha = 0.15, beta = 4, net, scheme = FALSE)
```

### Arguments

q	Data-frame of traffic flow to each hour (veh/h)
ps	Peak speed (km/h)
ffs	Free flow speed (km/h)
cap	Capacity of link (veh/h)
lkm	Distance of link (km)
alpha	Parameter of BPR curves
beta	Parameter of BPR curves
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
scheme	Logical to create a Speed data-frame with 24 hours and a default profile. It needs ffs and ps:
	00:00-06:00    ffs
	06:00-07:00    average between ffs and ps
	07:00-10:00    ps
	10:00-17:00    average between ffs and ps
	17:00-20:00    ps
	20:00-22:00    average between ffs and ps
	22:00-00:00    ffs

**Value**

dataframe speeds with units or sf.

**Examples**

```
## Not run:
data(net)
data(pc_profile)
pc_week <- temp_fact(net$ldv+net$hdv, pc_profile)
df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm, alpha = 1)
class(df)
plot(df) #plot of the average speed at each hour, +- sd
df <- netspeed(ps = net$ps, ffs = net$ffs, scheme = TRUE)
class(df)
plot(df) #plot of the average speed at each hour, +- sd
dfsfs <- netspeed(ps = net$ps, ffs = net$ffs, scheme = TRUE, net = net)
class(dfsfs)
head(dfsfs)
plot(dfsfs) #plot of the average speed at each hour, +- sd

## End(Not run)
```

---

pc\_cold

*Profile of Vehicle start patterns*

---

**Description**

This dataset is a dataframe with percetage of hourly starts with a lapse of 6 hours with engine turned off. Data source is: Lents J., Davis N., Nikkila N., Osses M. 2004. Sao Paulo vehicle activity study. ISSRC. [www.issrc.org](http://www.issrc.org)

**Usage**

```
data(pc_cold)
```

**Format**

A data frame with 24 rows and 1 variables:

**V1** 24 hours profile vehicle starts for Monday

---

`pc_profile`*Profile of traffic data 24 hours 7 n days of the week*

---

**Description**

This dataset is a dataframe with traffic activity normalized monday 08:00-09:00. This data is normalized at 08:00-09:00. It comes from data of toll stations near Sao Paulo City. The source is ARTESP ([www.artesp.com.br](http://www.artesp.com.br))

**Usage**

```
data(pc_profile)
```

**Format**

A data frame with 24 rows and 7 variables:

**V1** 24 hours profile for Monday

**V2** 24 hours profile for Tuesday

**V3** 24 hours profile for Wednesday

**V4** 24 hours profile for Thursday

**V5** 24 hours profile for Friday

**V6** 24 hours profile for Saturday

**V7** 24 hours profile for Sunday

---

`pollutants`*Data.frame with pollutants names and molar mass used in VEIN*

---

**Description**

This dataset also includes MIR, MOIR and EBIR is Carter SAPRC07.xls <https://www.engr.ucr.edu/~carter/SAPRC/>

**Usage**

```
data(pollutants)
```

**Format**

A data frame with 148 rows and 10 variables:

**n** Number for each pollutant, from 1 to 132

**group1** classification for pollutants including "NMHC", "PAH", "METALS", "PM", "criteria" and "PCDD"

**group2** A sub classification for pollutants including "alkenes", "alkynes", "aromatics", "alkanes", "PAH", "aldehydes", "ketones", "METALS", "PM\_char", "criteria", "cycloalkanes", "NMHC", "PCDD", "PM10", "PM2.5"

**pollutant** 1 of the 132 pollutants covered

**CAS** CAS Registry Number

**g\_mol** molar mass

**MIR** Maximum incremental Reactivity (gm O3 / gm VOC)

**MOIR** Reactivity (gm O3 / gm VOC)

**EBIR** Reactivity (gm O3 / gm VOC)

**notes** Inform some assumption for molar mass

---

profiles

*Profile of traffic data 24 hours 7 n days of the week*

---

**Description**

This dataset is a list of data-frames with traffic activity normalized monday 08:00-09:00. It comes from data of toll stations near Sao Paulo City. The source is ARTESP ([www.artesp.com.br](http://www.artesp.com.br)) for months January and June and years 2012, 2013 and 2014. The type of vehicles covered are PC, MC, MC and HGV.

**Usage**

`data(pc_profile)`

**Format**

A list of data-frames with 24 rows and 7 variables:

**PC\_JUNE\_2012** 168 hours

**PC\_JUNE\_2013** 168 hours

**PC\_JUNE\_2014** 168 hours

**LCV\_JUNE\_2012** 168 hours

**LCV\_JUNE\_2013** 168 hours

**LCV\_JUNE\_2014** 168 hours

**MC\_JUNE\_2012** 168 hours

**MC\_JUNE\_2013** 168 hours  
**MC\_JUNE\_2014** 168 hours  
**HGV\_JUNE\_2012** 168 hours  
**HGV\_JUNE\_2013** 168 hours  
**HGV\_JUNE\_2014** 168 hours  
**PC\_JANUARY\_2012** 168 hours  
**PC\_JANUARY\_2013** 168 hours  
**PC\_JANUARY\_2014** 168 hours  
**LCV\_JANUARY\_2012** 168 hours  
**LCV\_JANUARY\_2013** 168 hours  
**LCV\_JANUARY\_2014** 168 hours  
**MC\_JANUARY\_2012** 168 hours  
**MC\_JANUARY\_2014** 168 hours  
**HGV\_JANUARY\_2012** 168 hours  
**HGV\_JANUARY\_2013** 168 hours  
**HGV\_JANUARY\_2014** 168 hours

---

remove_units	<i>Remove units</i>
--------------	---------------------

---

## Description

`remove_units` Remove units from sf, data.frames, matrix or units.

## Usage

```
remove_units(x)
```

## Arguments

x                    Object with class "sf", "data.frame", "matrix" or "units"

## Value

"sf", "data.frame", "matrix" or numeric

## Examples

```
## Not run:  
ef1 <- ef_cetesb(p = "C0", c("PC_G", "PC_FE"))  
class(ef1)  
sapply(ef1, class)  
a <- remove_units(ef1)  
  
## End(Not run)
```

---

speciate                      *Speciation of emissions*

---

## Description

speciate separates emissions in different compounds. It covers black carbon and organic matter from particulate matter. Soon it will be added more speciations

## Usage

```
speciate(x, spec = "bcom", veh, fuel, eu, show = FALSE, list = FALSE, pmpar)
```

## Arguments

x	Emissions estimation
spec	speciation: The speciations are: "bcom", "tyre" (or "tire"), "brake", "road", "iag", "iag-tunnel", "pmiag", "pmiag-tunnel", "nox", "nmhc". 'iag' now includes a speciation for use of industrial and building paintings. "bcom" stands for black carbon and organic matter. "pmiag" speciates PM2.5 and requires only argument x of PM2.5 emissions in g/h/km <sup>2</sup> as gridded emissions (flux). It also accepts one of the following pollutants: 'e_eth', 'e_hc3', 'e_hc5', 'e_hc8', 'e_ol2', 'e_olt', 'e_oli', 'e_iso', 'e_tol', 'e_xyl', 'e_c2h5oh', 'e_hcho', 'e_ch3oh', 'e_ket', 'e_so4i', 'e_so4j', 'e_no3i', 'e_no3j', 'e_pm2.5i', 'e_pm2.5j', 'e_orgi', 'e_orgj', 'e_eci', 'e_ecj' and these pollutants with tunnel, e.g. "e_eth-tunnel".
veh	Type of vehicle: When spec is "bcom" or "nox" veh can be "PC", "LCV", HDV" or "Motorcycle". When spec is "iag" veh can take two values depending: when the speciation is for vehicles veh accepts "veh", eu "Evaporative", "Liquid" or "Exhaust" and fuel "G", "E" or "D", when the speciation is for painting, veh is "paint" fuel or eu can be "industrial" or "building" when spec is "nmhc", veh can be "LDV" with fuel "G" or "D" and eu "PRE", "I", "II", "III", "IV", "V", or "VI". when spec is "nmhc", veh can be "HDV" with fuel "D" and eu "PRE", "I", "II", "III", "IV", "V", or "VI". when spec is "nmhc" and fuel is "LPG", veh and eu must be "ALL"
fuel	Fuel. When spec is "bcom" fuel can be "G" or "D". When spec is "iag" fuel can be "G", "E" or "D". When spec is "nox" fuel can be "G", "D", "LPG", "E85" or "CNG". Not required for "tyre", "brake" or "road". When spec is "nmhc" fuel can be G, D or LPG.
eu	Euro emission standard: "PRE", "ECE_1501", "ECE_1502", "ECE_1503", "I", "II", "III", "IV", "V", "III-CDFP", "IV-CDFP", "V-CDFP", "III-ADFP", "IV-ADFP", "V-ADFP" and "OPEN_LOOP". When spec is "iag" accept the values "Exhaust" "Evaporative" and "Liquid". When spec is "nox" eu can be "PRE", "I", "II", "III", "IV", "V", "VI", "VIc", "III-DPF" or "III+CRT". Not required for "tyre", "brake" or "road"
show	when TRUE shows row of table with respective speciation
list	when TRUE returns a list with number of elements of the list as the number species of pollutants



`pmpar` Numeric vector for PM speciation eg: `c(e_so4i = 0.0077, e_so4j = 0.0623, e_no3i = 0.00247, e_no3j = 0.01053, e_pm2.5i = 0.1, e_pm2.5j = 0.3, e_orgi = 0.0304, e_orgj = 0.1296, e_eci = 0.056, e_ecj = 0.024, h2o = 0.277)` These are default values. however, when this argument is present, new values are used.

### Value

dataframe of speciation in grams or mols

### Note

when `spec = "iag"`: `veh` is only "veh", `fuel` is "G" (blended with 25% ethanol), "D" (blended with 5% of biodiesel) or "E" (Ethanol 100%). `eu` is "Evaporative", "Liquid" or "Exhaust",

emissions of "pmiag" speciate pm2.5 into `e_so4i`, `e_so4j`, `e_no3i`, `e_no3j`, `e_mp2.5i`, `e_mp2.5j`, `e_orgi`, `e_orgj`, `e_eci`, `e_ecj` and `h2o`. Reference: Rafee, S.: Estudo numerico do impacto das emissoes veiculares e fixas da cidade de Manaus nas concentracoes de poluentes atmosfericos da regio amazonica, Master thesis, Londrina: Universidade Tecnologica Federal do Parana, 2015.

### References

"bcom": Ntziachristos and Zamaras. 2016. Passenger cars, light commercial trucks, heavy-duty vehicles including buses and motor cycles. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

"tyre", "brake" and "road": Ntziachristos and Boulter 2016. Automobile tyre and brake wear and road abrasion. In: EEA, EMEP. EEA air pollutant emission inventory guidebook-2009. European Environment Agency, Copenhagen, 2016

"iag": Ibarra-Espinosa S. Air pollution modeling in Sao Paulo using bottom-up vehicular emissions inventories. 2017. PhD thesis. Instituto de Astronomia, Geofisica e Ciencias Atmosfericas, Universidade de Sao Paulo, Sao Paulo, page 88. Speciate EPA: <https://cfpub.epa.gov/speciate/>. : K. Sexton, H. Westberg, "Ambient hydrocarbon and ozone measurements downwind of a large automotive painting plant" Environ. Sci. Technol. 14:329 (1980).P.A. Scheff, R.A. Schauer, James J., Kleeman, Mike J., Cass, Glen R., Characterization and Control of Organic Compounds Emitted from Air Pollution Sources, Final Report, Contract 93-329, prepared for California Air Resources Board Research Division, Sacramento, CA, April 1998. 2004 NPRI National Databases as of April 25, 2006, [http://www.ec.gc.ca/pdb/npri/npri\\_dat\\_rep\\_e.cfm](http://www.ec.gc.ca/pdb/npri/npri_dat_rep_e.cfm). Memorandum Proposed procedures for preparing composite speciation profiles using Environment Canada's National Pollutant Release Inventory (NPRI) for stationary sources, prepared by Ying Hsu and Randy Strait of E.H. Pechan Associates, Inc. for David Niemi, Marc Deslauriers, and Lisa Graham of Environment Canada, September 26, 2006.

### Examples

```
## Not run:
# Do not run
pm <- rnorm(n = 100, mean = 400, sd = 2)
df <- speciate(pm, veh = "PC", fuel = "G", eu = "I")
dfa <- speciate(pm, spec = "e_eth", veh = "veh", fuel = "G", eu = "Exhaust")
dfb <- speciate(pm, spec = "e_tol", veh = "veh", fuel = "G", eu = "Exhaust")
dfc <- speciate(pm, spec = "e_so4i")
```

```
## End(Not run)
```

---

Speed	<i>Construction function for class "Speed"</i>
-------	--

---

### Description

Speed returns a transformed object with class "Speed" and units km/h. This functions includes two arguments, distance and time. Therefore, it is posibel to change the units of the speed to "m" to "s" for example. This function returns a dataframe with units for speed. When this function is applied to numeric vectors it add class "units".

### Usage

```
Speed(x, ...)

## S3 method for class 'Speed'
print(x, ...)

## S3 method for class 'Speed'
summary(object, ...)

## S3 method for class 'Speed'
plot(x, ...)
```

### Arguments

x	Object with class "data.frame", "matrix" or "numeric"
...	ignored
object	Object with class "Speed"

### Value

Constructor for class "Speed" or "units"

### See Also

[units](#)

### Examples

```
## Not run:
data(net)
data(pc_profile)
speed <- Speed(net$ps)
class(speed)
plot(speed, type = "l")
```

```
pc_week <- temp_fact(net$ldv+net$hdv, pc_profile)
df <- netspeed(pc_week, net$ps, net$ffs, net$capacity, net$lkm)
summary(df)

## End(Not run)
```

---

split\_emis

*Split street emissions based on a grid*


---

## Description

`split_emis` split street emissions into a grid.

## Usage

```
split_emis(net, distance, add_column, verbose = TRUE)
```

## Arguments

net	A spatial dataframe of class "sp" or "sf". When class is "sp" it is transformed to "sf" with emissions.
distance	Numeric distance or a grid with class "sf".
add_column	Character indicating name of column of distance. For instance, if distance is an sf object, and you want to add one extra column to the resulting object.
verbose	Logical, to show more information.

## Examples

```
## Not run:
data(net)
g <- make_grid(net, 1/102.47/2) #500m in degrees
names(net)
dim(net)
netsf <- sf::st_as_sf(net)[, "ldv"]
x <- split_emis(net = netsf, distance = g)
dim(x)
g$A <- rep(letters, length = 20)[1:nrow(g)]
g$B <- rev(g$A)
netsf <- sf::st_as_sf(net)[, c("ldv", "hdv")]
xx <- split_emis(netsf, g, add_column = c("A", "B"))

## End(Not run)
```

---

temp_fact	<i>Expansion of hourly traffic data</i>
-----------	---

---

**Description**

temp\_fact is a matrix multiplication between traffic and hourly expansion data-frames to obtain a data-frame of traffic at each link to every hour

**Usage**

```
temp_fact(q, pro, net, time)
```

**Arguments**

q	Numeric; traffic data per each link
pro	Numeric; expansion factors data-frames
net	SpatialLinesDataFrame or Spatial Feature of "LINESTRING"
time	Character to be the time units as denominator, eg "1/h"

**Value**

data-frames of expanded traffic or sf.

**Examples**

```
## Not run:
# Do not run
data(net)
data(pc_profile)
pc_week <- temp_fact(net$ldv+net$hdv, pc_profile)
plot(pc_week)
pc_weeksf <- temp_fact(net$ldv+net$hdv, pc_profile, net = net)
plot(pc_weeksf)

## End(Not run)
```

---

to_latex	<i>creates a .tex a table from a data.frame</i>
----------	---

---

**Description**

[to\\_latex](#) reads a data.frame and generates a .tex table, aiming to replicate the method of [tablegenerator.com](#)

**Usage**

```
to_latex(df, file, caption = "My table", label = "tab:df")
```

**Arguments**

df	data.frame with three column.
file	Character, name of new .tex file
caption	Character caption of table
label	Character, label of table

**Value**

a text file with extension .tex.

**See Also**

[vein\\_notes long\\_to\\_wide](#)

**Examples**

```
## Not run:
df <- data.frame(pollutant = rep(c("CO", "propadiene", "NO2"), 10),
                 emission = vein::Emissions(1:30),
                 region = rep(letters[1:2], 15))

df
long_to_wide(df)
(df2 <- long_to_wide(df, column_fixed = "region"))
to_latex(df2)
to_latex(long_to_wide(df, column_fixed = "region"),
file = paste0(tempfile(), ".tex"))

## End(Not run)
```

---

Vehicles

*Construction function for class "Vehicles"*

---

**Description**

Vehicles returns a tranformed object with class "Vehicles" and units 'veh'. The type of objects supported are of classes "matrix", "data.frame", "numeric" and "array". If the object is a matrix it is converted to data.frame. If the object is "numeric" it is converted to class "units".

**Usage**

```
Vehicles(x, ..., time)

## S3 method for class 'Vehicles'
print(x, ...)

## S3 method for class 'Vehicles'
summary(object, ...)

## S3 method for class 'Vehicles'
plot(x, ..., message = TRUE)
```

**Arguments**

x	Object with class "Vehicles"
...	ignored
time	Character to be the time units as denominator, eg "1/h"
object	Object with class "Vehicles"
message	message with average age

**Value**

Objects of class "Vehicles" or "units"

**Examples**

```
## Not run:
lt <- rnorm(100, 300, 10)
class(lt)
vlt <- Vehicles(lt)
class(vlt)
plot(vlt)
LT_B5 <- age_hdv(x = lt, name = "LT_B5")
summary(LT_B5)
plot(LT_B5)

## End(Not run)
```

**Description**

[vein\\_notes](#) creates a text file '.txt' for writing technical notes about this emissions inventory

**Usage**

```

vein_notes(
  notes,
  file = "README",
  yourname = Sys.info()["login"],
  title = "Notes for this VEIN run",
  approach = "Top Down",
  traffic = "Your traffic information",
  composition = "Your traffic information",
  ef = "Your information about emission factors",
  cold_start = "Your information about cold starts",
  evaporative = "Your information about evaporative emission factors",
  standards = "Your information about standards",
  mileage = "Your information about mileage"
)

```

**Arguments**

notes	Character; vector of notes.
file	Character; Name of the file. The function will generate a file with an extension '.txt'.
yourname	Character; Name of the inventor compiler.
title	Character; Title of this file. For instance: "Vehicular Emissions Inventory of Region XX, Base year XX"
approach	Character; vector of notes.
traffic	Character; vector of notes.
composition	Character; vector of notes.
ef	Character; vector of notes.
cold_start	Character; vector of notes.
evaporative	Character; vector of notes.
standards	Character; vector of notes.
mileage	Character; vector of notes.

**Value**

Writes a text file.

**Examples**

```

## Not run:
#do not run
a <- "delete"
f <- vein_notes("notes", file = a)
file.remove(f)

## End(Not run)

```

vkm

*Estimation of VKM***Description**

vkm consists in the product of the number of vehicles and the distance driven by these vehicles in km. This function reads hourly vehicles and then extrapolates the vehicles

**Usage**

```
vkm(
  veh,
  lkm,
  profile,
  hour = nrow(profile),
  day = ncol(profile),
  array = TRUE,
  as_df = TRUE
)
```

**Arguments**

veh	Numeric vector with number of vehicles per street
lkm	Length of each link (km)
profile	Numerical or dataframe with nrow equal to 24 and ncol 7 day of the week
hour	Number of considered hours in estimation
day	Number of considered days in estimation
array	When FALSE produces a dataframe of the estimation. When TRUE expects a profile as a dataframe producing an array with dimensions (streets x hours x days)
as_df	Logical; when TRUE transform returning array in data.frame (streets x hour*days)

**Value**

emission estimation of vkm

**Examples**

```
## Not run:
# Do not run
pc <- lkm <- abs(rnorm(10,1,1))*100
pro <- matrix(abs(rnorm(24*7,0.5,1))), ncol=7, nrow=24)
vkms <- vkm(veh = pc, lkm = lkm, profile = pro)
class(vkms)
dim(vkms)
vkms2 <- vkm(veh = pc, lkm = lkm, profile = pro, as_df = FALSE)
```



```
class(vkms2)
dim(vkms2)

## End(Not run)
```

---

wide_to_long	<i>Transform data.frame from wide to long format</i>
--------------	--

---

## Description

[wide\\_to\\_long](#) transform data.frame from wide to long format

## Usage

```
wide_to_long(df, column_with_data = names(df), column_fixed, geometry)
```

## Arguments

df	data.frame with three column.
column_with_data	Character column with data
column_fixed	Character, column that will remain fixed
geometry	To return a sf

## Value

long data.frame.

## See Also

[emis\\_hot\\_td](#) [emis\\_cold\\_td](#) [long\\_to\\_wide](#)

## Examples

```
## Not run:
data(net)
net <- sf::st_set_geometry(net, NULL)
df <- wide_to_long(df = net)
head(df)

## End(Not run)
```

# Index

- \* **China**
    - ef\_china, 21
  - \* **age**
    - age, 6
    - age\_hdv, 8
    - age\_ldv, 10
    - age\_moto, 11
  - \* **cold**
    - cold\_mileage, 15
    - ef\_ldv\_cold, 35
    - ef\_ldv\_cold\_list, 36
  - \* **cumileage**
    - ef\_nitro, 45
  - \* **datasets**
    - fe2015, 85
    - fkm, 86
    - net, 98
    - pc\_cold, 100
    - pc\_profile, 101
    - pollutants, 101
    - profiles, 102
  - \* **deterioration**
    - emis\_det, 62
  - \* **ef\_china**
    - ef\_china, 21
  - \* **emission**
    - ef\_cetesb, 17
    - ef\_china, 21
    - ef\_hdv\_scaled, 28
    - ef\_hdv\_speed, 29
    - ef\_im, 32
    - ef\_ive, 33
    - ef\_ldv\_cold, 35
    - ef\_ldv\_cold\_list, 36
    - ef\_ldv\_scaled, 38
    - ef\_ldv\_speed, 39
    - ef\_local, 44
    - ef\_nitro, 45
    - ef\_whe, 47
    - emis\_det, 62
  - \* **emitters**
    - ef\_whe, 47
  - \* **factors**
    - ef\_cetesb, 17
    - ef\_china, 21
    - ef\_hdv\_scaled, 28
    - ef\_hdv\_speed, 29
    - ef\_im, 32
    - ef\_ive, 33
    - ef\_ldv\_cold, 35
    - ef\_ldv\_cold\_list, 36
    - ef\_ldv\_scaled, 38
    - ef\_ldv\_speed, 39
    - ef\_local, 44
    - ef\_nitro, 45
    - ef\_whe, 47
    - emis\_det, 62
  - \* **high**
    - ef\_whe, 47
  - \* **ive**
    - ef\_ive, 33
  - \* **mileage**
    - cold\_mileage, 15
    - ef\_im, 32
  - \* **speed**
    - ef\_hdv\_scaled, 28
    - ef\_hdv\_speed, 29
    - ef\_ive, 33
    - ef\_ldv\_scaled, 38
    - ef\_ldv\_speed, 39
  - \* **start**
    - ef\_ldv\_cold\_list, 36
  - \* **units**
    - remove\_units, 103
- add\_lkm, 3  
add\_polid, 4, 4, 83  
adt, 5, 5  
age, 6, 6, 7, 9, 11, 12, 98

- age\_hdv, [7](#), [8](#), [8](#), [9](#), [11](#), [12](#), [98](#)
- age\_ldv, [7](#), [9](#), [10](#), [10](#), [11](#), [12](#), [98](#)
- age\_moto, [7](#), [9](#), [11](#), [11](#), [12](#), [98](#)
- aw, [13](#), [13](#)
- celsius, [14](#)
- cold\_mileage, [15](#)
- colplot, [16](#), [16](#)
- ef\_cetesb, [17](#), [17](#), [44](#), [45](#)
- ef\_china, [21](#), [21](#), [71](#), [72](#)
- ef\_evap, [24](#), [24](#), [57](#), [66](#)
- ef\_fun, [27](#), [27](#)
- ef\_hdv\_scaled, [28](#), [28](#)
- ef\_hdv\_speed, [29](#), [56](#), [57](#)
- ef\_im, [32](#), [32](#)
- ef\_ive, [33](#), [33](#)
- ef\_ldv\_cold, [31](#), [35](#), [35](#), [41](#), [61](#)
- ef\_ldv\_cold\_list, [36](#)
- ef\_ldv\_scaled, [38](#)
- ef\_ldv\_speed, [23](#), [39](#), [39](#), [56](#), [57](#), [72](#)
- ef\_local, [44](#), [44](#)
- ef\_nitro, [45](#), [45](#)
- ef\_wear, [46](#), [46](#)
- ef\_whe, [47](#), [47](#)
- emis, [31](#), [41](#), [48](#), [48](#)
- emis\_chem, [56](#), [56](#)
- emis\_cold, [58](#), [59](#)
- emis\_cold\_td, [60](#), [60](#), [95](#), [113](#)
- emis\_det, [32](#), [62](#), [62](#)
- emis\_dist, [64](#), [64](#), [90](#)
- emis\_evap, [65](#), [65](#)
- emis\_evap2, [67](#)
- emis\_grid, [69](#), [70](#), [90](#)
- emis\_hot\_td, [23](#), [71](#), [71](#), [95](#), [113](#)
- emis\_merge, [75](#), [75](#)
- emis\_order, [76](#)
- emis\_paved, [78](#)
- emis\_post, [75](#), [80](#)
- emis\_source, [82](#), [82](#)
- emis\_to\_streets, [4](#), [83](#), [83](#)
- emis\_wear, [84](#)
- EmissionFactors, [52](#)
- EmissionFactorsList, [53](#)
- Emissions, [54](#)
- EmissionsArray, [55](#)
- fe2015, [85](#)
- fkm, [86](#)
- fuel\_corr, [30](#), [31](#), [36](#), [40](#), [41](#), [87](#)
- get\_project, [88](#), [88](#)
- grid\_emis, [90](#), [90](#)
- GriddedEmissionsArray, [77](#), [89](#)
- invcop, [92](#)
- inventory, [93](#)
- long\_to\_wide, [95](#), [95](#), [109](#), [113](#)
- make\_grid, [96](#), [96](#)
- my\_age, [7](#), [9](#), [11](#), [12](#), [97](#), [98](#)
- net, [98](#)
- netspeed, [99](#)
- par, [16](#), [17](#)
- pc\_cold, [100](#)
- pc\_profile, [101](#)
- plot.EmissionFactors (EmissionFactors), [52](#)
- plot.EmissionFactorsList (EmissionFactorsList), [53](#)
- plot.Emissions (Emissions), [54](#)
- plot.EmissionsArray (EmissionsArray), [55](#)
- plot.GriddedEmissionsArray (GriddedEmissionsArray), [89](#)
- plot.Speed (Speed), [106](#)
- plot.Vehicles (Vehicles), [109](#)
- pollutants, [101](#)
- print.EmissionFactors (EmissionFactors), [52](#)
- print.EmissionFactorsList (EmissionFactorsList), [53](#)
- print.Emissions (Emissions), [54](#)
- print.EmissionsArray (EmissionsArray), [55](#)
- print.GriddedEmissionsArray (GriddedEmissionsArray), [89](#)
- print.Speed (Speed), [106](#)
- print.Vehicles (Vehicles), [109](#)
- profiles, [102](#)
- remove\_units, [103](#), [103](#)
- speciate, [57](#), [104](#)
- Speed, [106](#)
- split\_emis, [107](#), [107](#)

summary.EmissionFactors  
    (EmissionFactors), [52](#)  
summary.EmissionFactorsList  
    (EmissionFactorsList), [53](#)  
summary.Emissions (Emissions), [54](#)  
summary.EmissionsArray  
    (EmissionsArray), [55](#)  
summary.GriddedEmissionsArray  
    (GriddedEmissionsArray), [89](#)  
summary.Speed (Speed), [106](#)  
summary.Vehicles (Vehicles), [109](#)

temp\_fact, [108](#)  
title, [16](#)  
to\_latex, [108](#), [108](#)

units, [106](#)

Vehicles, [109](#)  
vein\_notes, [109](#), [110](#), [110](#)  
vkm, [112](#)

weekly (emis\_order), [76](#)  
wide\_to\_long, [95](#), [113](#), [113](#)